

ASSIGNMENT - 02

Name : Aravind Reddy

Hall Ticket No : 2303a51027

Batch No. : 01

Course : AI Assistant Coding

Task 1: Statistical Summary for Survey Data

❖ Scenario:

You are a data analyst intern working with survey responses stored as numerical lists.

❖ Task:

Use Google Gemini in Colab to generate a Python function that reads a list of numbers and calculates the mean, minimum, and maximum values.

❖ Expected Output:

➤ Correct Python function

➤ Output shown in Colab

➤ Screenshot of Gemini prompt and result

The screenshot shows a Google Colab notebook titled "AI Assistant Coding.ipynb". A code cell contains the following Python function:

```
import statistics

def calculate_stats(numbers):
    if not numbers:
        return {}

    mean_value = statistics.mean(numbers)
    min_value = min(numbers)
    max_value = max(numbers)

    return {
        'mean': mean_value,
        'min': min_value,
        'max': max_value
    }

# Example usage:
my_list = [10, 20, 30, 40, 50]
stats = calculate_stats(my_list)
display(stats)

empty_list = []
empty_stats = calculate_stats(empty_list)
display(empty_stats)
```

Below the code cell, a Gemini AI interface is overlaid, showing a prompt and a generated response:

Prompt: Generate a Python function that takes a list of numbers and calculates mean, minimum, and maximum values.

Response: Sure, here's a Python function that takes a list of numbers and returns its mean, minimum, and maximum values.

Output: The generated Python code is displayed below the prompt.

Task 2: Armstrong Number – AI Comparison

❖ Scenario:

You are evaluating AI tools for numeric validation logic.

❖ Task:

Generate an Armstrong number checker using Gemini and GitHub Copilot.


Copilot.

Compare their outputs, logic style, and clarity.

❖ Expected Output:

➤ Side-by-side comparison table

➤ Screenshots of prompts and generated code



```
def is_armstrong_number(number):
    if not isinstance(number, int) or number < 0:
        raise ValueError("Input must be a non-negative integer.")


    num_str = str(number)
    num_digits = len(num_str)
    sum_of_powers = 0

    for digit_char in num_str:
        digit = int(digit_char)
        sum_of_powers += digit ** num_digits

    return sum_of_powers == number

# Example usage:
print("Is 1 an Armstrong number? ", is_armstrong_number(1))
print("Is 153 an Armstrong number? ", is_armstrong_number(153))
print("Is 370 an Armstrong number? ", is_armstrong_number(370))
print("Is 371 an Armstrong number? ", is_armstrong_number(371))
print("Is 407 an Armstrong number? ", is_armstrong_number(407))
print("Is 1634 an Armstrong number? ", is_armstrong_number(1634))
print("Is 1808 an Armstrong number? ", is_armstrong_number(1808))
```

Write a Python program to check whether a number is an Armstrong number.
Certainly! Here's a Python program to check if a number is an Armstrong number, along with an explanation of how it works.



```
# python program to check armstrong number
def is_armstrong_number(num):
    num_str = str(num)
    num_digits = len(num_str)

    total = sum(int(digit) ** num_digits for digit in num_str)

    # Check if the total equals the original number
    return total == num

# Test the function
test_number = 153
if is_armstrong_number(test_number):
    print(f"{test_number} is an Armstrong number.")
else:
    print(f"{test_number} is not an Armstrong number.")
```

```
/usr/local/bin/python3 "/Users/aravindreddy/Desktop/My-Information/College/AI Assisted Coding/Assignment - 01.py"
153 is an Armstrong number.
(base) => AI Assisted Coding
```

Task 3: Leap Year Validation Using Cursor AI

❖ Scenario:

You are validating a calendar module for a backend system.

❖ Task:

Use Cursor AI to generate a Python program that checks whether a given year is a leap year.


Use at least two different prompts and observe changes in code.

❖ Expected Output:

➤ Two versions of code

➤ Sample inputs/outputs

➤ Brief comparison



```
year = int(input("Enter year: "))

if year % 4 == 0:
    print("Leap Year")
else:
    print("Not a Leap Year")

# Improve leap year logic using proper conditions and readability.

year = int(input("Enter year: "))

if (year % 400 == 0) or (year % 4 == 0 and year % 100 != 0):
    print("Leap Year")
else:
    print("Not a Leap Year")
```

Task 4: Student Logic + AI Refactoring (Odd/Even Sum)

❖ Scenario:

Company policy requires developers to write logic before using AI.

❖ Task:

Write a Python program that calculates the sum of odd and even numbers in a tuple, then refactor it using any AI tool.

❖ Expected Output:

➤ Original code

➤ Refactored code

➤ Explanation of improvements

The screenshot shows a Google Colab notebook titled "AI Assistant Coding.ipynb". The notebook contains the following Python code:

```
numbers = [1, 2, 3, 4, 5, 6]
even_sum = 0
odd_sum = 0

for n in numbers:
    if n % 2 == 0:
        even_sum += n
    else:
        odd_sum += n

print("Even sum:", even_sum)
print("Odd sum:", odd_sum)
```

The output of the code is:

```
Even sum: 12
Odd sum: 9
```

A sidebar panel titled "Task 4: Student Logic + AI Refactoring (Odd/Even Sum)" shows the original code and its refactored version. The refactored code is:numbers = [1, 2, 3, 4, 5, 6]

even_sum = sum(n for n in numbers if n % 2 == 0)
odd_sum = sum(n for n in numbers if n % 2 != 0)

print("Even sum: (even_sum)")
print("Odd sum: (odd_sum)")

```
Even sum: 12
Odd sum: 9
```

A tooltip from Gemini 2.5 Flash provides feedback on improving leap year logic:

Improve leap year logic using proper conditions and readability.

You're right, the current logic only checks for divisibility by 4. I will improve the leap year logic in the code to correctly account for all conditions, including divisibility by 100 and 400, for proper leap year determination.

Provide the improved leap year Python code Explain the improved leap year logic Test

What can I help you build?

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)