

Product Batch - Task Submission - 02.09.2026

Task - 2

ROLL NO : 2303A51027

NAME : Aravind Reddy

1. Employee sequence by salary – ROW_NUMBER()

```
SELECT  
  
    emp_name,  
  
    department,  
  
    salary,  
  
    ROW_NUMBER() OVER (  
  
        ORDER BY salary DESC  
  
    ) AS row_num  
  
FROM employees;
```

2. Salary rank across the company – RANK()

```
SELECT  
  
    emp_name,  
  
    department,  
  
    salary,  
  
    RANK() OVER (  
  
        ORDER BY salary DESC  
  
    ) AS salary_rank  
  
FROM employees;
```

3. Salary rank without gaps – DENSE_RANK()

```
SELECT

    emp_name,

    department,

    salary,

    DENSE_RANK() OVER (

        ORDER BY salary DESC

    ) AS salary_rank

FROM employees;
```

4. Row number inside each department – ROW_NUMBER()

```
SELECT

    emp_name,

    department,

    salary,

    ROW_NUMBER() OVER (

        PARTITION BY department

        ORDER BY salary DESC

    ) AS dept_row_num

FROM employees;
```

5. Department-wise salary rank – RANK()

```
SELECT

    emp_name,

    department,

    salary,

    RANK() OVER (
```

```
    PARTITION BY department

    ORDER BY salary DESC

) AS dept_salary_rank

FROM employees;
```

6. Top 2 distinct salaries in each department – DENSE_RANK()

```
WITH ranked_employees AS (

    SELECT

        emp_name,

        department,

        salary,

        DENSE_RANK() OVER (

            PARTITION BY department

            ORDER BY salary DESC

        ) AS salary_rank

    FROM employees

)
```

```
SELECT

    emp_name,

    department,

    salary,

    salary_rank

FROM ranked_employees

WHERE salary_rank <= 2;
```

7. Highest-paid employee name per department – FIRST_VALUE()

```
SELECT  
  
    emp_name,  
  
    department,  
  
    salary,  
  
    FIRST_VALUE(emp_name) OVER (  
  
        PARTITION BY department  
  
        ORDER BY salary DESC  
  
    ) AS highest_paid_employee  
  
FROM employees;
```

8. Lowest-paid employee name per department – LAST_VALUE()

```
SELECT  
  
    emp_name,  
  
    department,  
  
    salary,  
  
    LAST_VALUE(emp_name) OVER (  
  
        PARTITION BY department  
  
        ORDER BY salary DESC  
  
        ROWS BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING  
  
    ) AS lowest_paid_employee  
  
FROM employees;
```

9. Compare first and last salary in each department

```
SELECT  
  
    emp_name,  
  
    department,
```

salary,

```
FIRST_VALUE(salary) OVER (  
    PARTITION BY department  
    ORDER BY salary DESC  
) AS highest_salary,
```

```
LAST_VALUE(salary) OVER (  
    PARTITION BY department  
    ORDER BY salary DESC  
    ROWS BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING  
) AS lowest_salary
```

FROM employees;

10. 2nd highest distinct salary employees – DENSE_RANK()

WITH ranked_employees AS (

```
SELECT  
    emp_name,  
    department,  
    salary,  
    DENSE_RANK() OVER (  
        ORDER BY salary DESC  
    ) AS salary_rank
```

FROM employees

)

```
SELECT  
  
    emp_name,  
  
    department,  
  
    salary  
  
FROM ranked_employees  
  
WHERE salary_rank = 2;
```