

Product Batch - Task Submission - 22.08.2026

ROLL NO : 2303A51027

NAME : Aravind Reddy

Question 1

DescriptionAccepted ×EditorialSolutionsSubmissions

740. Delete and Earn

Solved

MediumTopicsCompaniesHint

You are given an integer array `nums`. You want to maximize the number of points you get by performing the following operation any number of times:

- Pick any `nums[i]` and delete it to earn `nums[i]` points. Afterwards, you must delete **every** element equal to `nums[i] - 1` and **every** element equal to `nums[i] + 1`.

Return the **maximum number of points** you can earn by applying the above operation some number of times.

Example 1:

Input: `nums = [3,4,2]`

Output: 6

Explanation: You can perform the following operations:

- Delete 4 to earn 4 points. Consequently, 3 is also deleted. `nums = [2]`.

- Delete 2 to earn 2 points. `nums = []`.

You earn a total of 6 points.

Example 2:

Input: `nums = [2,2,3,3,3,4]`

Output: 9

Explanation: You can perform the following operations:

- Delete a 3 to earn 3 points. All 2's and 4's are also deleted. `nums = [3,3]`.

- Delete a 3 again to earn 3 points. `nums = [3]`.

- Delete a 3 once more to earn 3 points. `nums = []`.

You earn a total of 9 points.

Code

Python3Auto

```
1 class Solution:
2     def deleteAndEarn(self, nums: List[int]) -> int:
3         freq = Counter(nums)
4
5         max_num = max(nums)
6
7         dp = [0] * (max_num + 1)
8
9         for i in range(1, max_num + 1):
10             take = dp[i - 2] + i * freq[i] if i >= 2 else i * freq[i]
11             skip = dp[i - 1]
12
13             dp[i] = max(take, skip)
14
15         return dp[max_num]
```

Saved

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

nums =

[3,4,2]

Question 2

Problem List

416. Partition Equal Subset Sum

Medium

Topics

Companies

Given an integer array `nums`, return `true` if you can partition the array into two subsets such that the sum of the elements in both subsets is equal or `false` otherwise.

Example 1:

Input: `nums = [1,5,11,5]`
Output: `true`
Explanation: The array can be partitioned as [1, 5, 5] and [11].

Example 2:

Input: `nums = [1,2,3,5]`
Output: `false`
Explanation: The array cannot be partitioned into equal sum subsets.

Constraints:

- `1 <= nums.length <= 200`
- `1 <= nums[i] <= 100`

bluehost Build apps on your VPS

Seen this question in a real interview before? 1/6

14.1K 276 183 Online

Code

Python3 Auto

```
1 class Solution:
2     def canPartition(self, nums: List[int]) -> bool:
3         total = sum(nums)
4
5         if total % 2 != 0:
6             return False
7
8         target = total // 2
9
10        dp = [False] * (target + 1)
11        dp[0] = True
12
13        for num in nums:
14            for i in range(target, num - 1, -1):
15                dp[i] = dp[i] or dp[i - num]
16
17        return dp[target]
```

Saved

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

nums = [1,5,11,5]

Question 3

Problem List

494. Target Sum

Medium

Topics

Companies

You are given an integer array `nums` and an integer `target`.

You want to build an **expression** out of `nums` by adding one of the symbols `'+'` and `'-'` before each integer in `nums` and then concatenate all the integers.

- For example, if `nums = [2, 1]`, you can add a `'+'` before `2` and a `'-'` before `1` and concatenate them to build the expression `"+2-1"`.

Return the number of different **expressions** that you can build, which evaluates to `target`.

Example 1:

Input: `nums = [1,1,1,1,1]`, `target = 3`
Output: 5
Explanation: There are 5 ways to assign symbols to make the sum of `nums` be `target` 3.

`-1 + 1 + 1 + 1 + 1 = 3`
`+1 - 1 + 1 + 1 + 1 = 3`
`+1 + 1 - 1 + 1 + 1 = 3`
`+1 + 1 + 1 - 1 + 1 = 3`
`+1 + 1 + 1 + 1 - 1 = 3`

Example 2:

Input: `nums = [1]`, `target = 1`
Output: 1

Constraints:

Code

Python3 Auto

```
1 class Solution:
2     def findTargetSumWays(self, nums: List[int], target: int) -> int:
3         total = sum(nums)
4
5         if total + target < 0 or (total + target) % 2 != 0:
6             return 0
7
8         target_sum = (total + target) // 2
9
10        dp = [0] * (target_sum + 1)
11        dp[0] = 1
12
13        for num in nums:
14            for i in range(target_sum, num - 1, -1):
15                dp[i] += dp[i - num]
16
17        return dp[target_sum]
```

Saved

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

nums = [1,1,1,1,1]

Question 4

Problem List

DescriptionEditorialSolutionsSubmissions

Input: days = [1,4,6,7,8,20], costs = [2,7,15]
Output: 11
Explanation: For example, here is one way to buy passes that lets you travel your travel plan:
On day 1, you bought a 1-day pass for costs[0] = \$2, which covered day 1.
On day 3, you bought a 7-day pass for costs[1] = \$7, which covered days 3, 4, ..., 9.
On day 20, you bought a 1-day pass for costs[0] = \$2, which covered day 20.
In total, you spent \$11 and covered all the days of your travel.

Example 2:

Input: days = [1,2,3,4,5,6,7,8,9,10,30,31], costs = [2,7,15]
Output: 17
Explanation: For example, here is one way to buy passes that lets you travel your travel plan:
On day 1, you bought a 30-day pass for costs[2] = \$15 which covered days 1, 2, ..., 30.
On day 31, you bought a 1-day pass for costs[0] = \$2 which covered day 31.
In total, you spent \$17 and covered all the days of your travel.

Constraints:

- 1 <= days.length <= 365
- 1 <= days[i] <= 365
- days is in strictly increasing order.
- costs.length == 3
- 1 <= costs[i] <= 1000

8.9K29421 Online

Code

Python3Auto

```
1 class Solution:
2     def mincostTickets(self, days: List[int], costs: List[int]) -> int:
3         travel = set(days)
4
5         dp = [0] * 366
6
7         for day in range(1, 366):
8
9             if day not in travel:
10                 dp[day] = dp[day - 1]
11
12             else:
13                 one_day = dp[day - 1] + costs[0]
14
15                 seven_day = dp[max(0, day - 7)] + costs[1]
16
17                 thirty_day = dp[max(0, day - 30)] + costs[2]
18
19                 dp[day] = min(one_day, seven_day, thirty_day)
20
21         return dp[365]
```

Saved

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

days =
[1,4,6,7,8,20]

Question 5

Problem List

DescriptionEditorialSolutionsSubmissions

1049. Last Stone Weight II

MediumTopicsCompaniesHint

You are given an array of integers `stones` where `stones[i]` is the weight of the i^{th} stone.

We are playing a game with the stones. On each turn, we choose any two stones and smash them together. Suppose the stones have weights `x` and `y` with `x <= y`. The result of this smash is:

- If `x == y`, both stones are destroyed, and
- If `x != y`, the stone of weight `x` is destroyed, and the stone of weight `y` has new weight `y - x`.

At the end of the game, there is **at most one** stone left.

Return *the smallest possible weight of the left stone*. If there are no stones left, return `0`.

Example 1:

Input: stones = [2,7,4,1,8,1]
Output: 1
Explanation:
We can combine 2 and 4 to get 2, so the array converts to [2,7,1,8,1] then,
we can combine 7 and 8 to get 1, so the array converts to [2,1,1,1]
then,
we can combine 2 and 1 to get 1, so the array converts to [1,1,1] then,
we can combine 1 and 1 to get 0, so the array converts to [1], then
that's the optimal value.

Example 2:

Input: stones = [31,26,33,21,40]
Output: 5

3.5K8339 Online

Code

Python3Auto

```
1 class Solution:
2     def lastStoneWeightII(self, stones: List[int]) -> int:
3
4         total = sum(stones)
5         target = total // 2
6
7         dp = [False] * (target + 1)
8         dp[0] = True
9
10        for stone in stones:
11            for i in range(target, stone - 1, -1):
12                dp[i] = dp[i] or dp[i - stone]
13
14        for i in range(target, -1, -1):
15            if dp[i]:
16                return total - 2 * i
```

Saved

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

stones =
[31,26,33,21,40]

Question 6

Submit solution

Problem: Enter problem code, like 33A

Language:

Almost always, if you send a solution on PyPy, it works much faster

Source code:

```
1 n = int(input())
2 a = list(map(int, input().split()))
3
4 MAX = 100000
5
6 freq = [0] * (MAX + 1)
7
8 for x in a:
9     freq[x] += 1
10
11 dp = [0] * (MAX + 1)
12
13 dp[1] = freq[1]
14
15 for x in range(2, MAX + 1):
16     dp[x] = max(dp[x - 1], dp[x - 2] + x * freq[x])
17
18 print(dp[MAX])
```

☐ Switch off editor

Tab size: 4

Or choose file: No file chosen

→ Pay attention

Before contest
[Codeforces Round \(Div. 1\)](#)
3 days

Before contest
[Codeforces Round \(Div. 2\)](#)
3 days
[Register now >](#)
*has extra registration

→ Settings

☒ Show tags for unsolved problems
☐ Hide solved problems

→ Last unsolved

#	Name	Last submission
445A	DZY Loves Chessboard	390126223

Question 7

Submit solution

Problem: Enter problem code, like 33A

Language:

Almost always, if you send a solution on PyPy, it works much faster

Source code:

```
1 n = int(input())
2 a = list(map(int, input().split()))
3 b = list(map(int, input().split()))
4
5
6 dp = [[0] * n for _ in range(2)]
7
8 dp[0][0] = a[0]
9 dp[1][0] = b[0]
10
11 if n > 1:
12     dp[0][1] = max(a[1], b[0] + a[1])
13     dp[1][1] = max(b[1], a[0] + b[1])
14
15 for i in range(2, n):
16     dp[0][i] = a[i] + max(dp[1][i - 1], dp[1][i - 2])
17     dp[1][i] = b[i] + max(dp[0][i - 1], dp[0][i - 2])
18
19 print(max(dp[0][n - 1], dp[1][n - 1]))
```

☐ Switch off editor

Tab size: 4

Or choose file: No file chosen

→ Pay attention

Before contest
[Codeforces Round \(Div. 1\)](#)
3 days

Before contest
[Codeforces Round \(Div. 2\)](#)
3 days
[Register now >](#)
*has extra registration

→ Settings

☒ Show tags for unsolved problems
☐ Hide solved problems

→ Last unsolved

#	Name	Last submission
445A	DZY Loves Chessboard	390126223

Question 8

Submit solution

Problem: Enter problem code, like 33A

Language:

Almost always, if you send a solution on PyPy, it works much faster

Source code:

```
1 n = int(input())
2
3 a = []
4 for _ in range(n):
5     a.append(int(input()))
6
7
8 def solve(i, angle):
9     if i == n:
10         return angle % 360 == 0
11
12     return solve(i + 1, angle + a[i]) or solve(i + 1, angle - a[i])
13
14
15 if solve(0, 0):
16     print("YES")
17 else:
18     print("NO")
```

☐ Switch off editor

Tab size:

Or choose file: No file chosen

→ Pay attention

Before contest
[Codeforces Round \(Div. 1\)](#)
3 days

Before contest
[Codeforces Round \(Div. 2\)](#)
3 days
[Register now »](#)
*has extra registration

→ Settings

☒ Show tags for unsolved problems
☐ Hide solved problems

→ Last unsolved

#	Name	Last submission
445A	DZY Loves Chessboard	390126223

Question 9

Submit solution

Problem: Enter problem code, like 33A

Language:

Almost always, if you send a solution on PyPy, it works much faster

Source code:

```
1 n = int(input())
2 a = list(map(int, input().split()))
3
4 dp = [[0] * 3 for _ in range(n)]
5
6 # Day 0
7 dp[0][0] = 1
8
9 if a[0] == 1 or a[0] == 3:
10     dp[0][1] = 0
11 else:
12     dp[0][1] = 1000
13
14 if a[0] == 2 or a[0] == 3:
15     dp[0][2] = 0
16 else:
17     dp[0][2] = 1000
18
19
20 for i in range(1, n):
21
22     # Rest
23     dp[i][0] = min(dp[i-1][0],
```

☐ Switch off editor

Tab size:

Or choose file: No file chosen

→ Pay attention

Before contest
[Codeforces Round \(Div. 1\)](#)
3 days

Before contest
[Codeforces Round \(Div. 2\)](#)
3 days
[Register now »](#)
*has extra registration

→ Settings

☒ Show tags for unsolved problems
☐ Hide solved problems

→ Last unsolved

#	Name	Last submission
445A	DZY Loves Chessboard	390126223

Question 10

Submit solution

Problem: Enter problem code, like 33A

Language:

Almost always, if you send a solution on PyPy, it works much faster

Source code:

```

1  t = int(input())
2
3  for _ in range(t):
4      n = int(input())
5      a = list(map(int, input().split()))
6
7      INF = 10**9
8
9      # dp[i][0] -> minimum cost, friend kills next
10     # dp[i][1] -> minimum cost, you kill next
11     dp = [[INF] * 2 for _ in range(n + 1)]
12
13     dp[0][0] = 0
14
15     for i in range(n):
16
17         # Friend kills 1 boss
18         if i + 1 <= n:
19             dp[i + 1][1] = min(
20                 dp[i + 1][1],
21                 dp[i][0] + a[i]
22             )
23

```

☐ Switch off editor

Tab size:

Or choose file: No file chosen

→ **Pay attention**

Before contest
[Codeforces Round \(Div. 1\)](#)
3 days

Before contest
[Codeforces Round \(Div. 2\)](#)
3 days

[Register now »](#)
*has extra registration

→ **Settings**

- ☒ Show tags for unsolved problems
- ☐ Hide solved problems

→ **Last unsolved**

#	Name	Last submission
445A	DZY Loves Chessboard	390126223