

AI ASSISTED CODING

ASSIGNMENT-14.5

Name: CH.Vishwanath Rao

H.T.NO: 2303A51095

Task 1 – Image Gallery Website

Create an image gallery web page.

Requirements:

- Display images in a grid layout.
- Use AI to:
 - o Optimize layout using CSS Grid.
 - o Add hover zoom or overlay effects.
 - o Ensure mobile responsiveness.

```
<!--Create an image gallery web page.
Display images in a grid layout.
Optimize layout using CSS Grid.
Add hover zoom or overlay effects.
Ensure mobile responsiveness.
-->
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Image Gallery</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      padding: 0;
      background-color: #f0f0f0;
    }

    h1 {
      text-align: center;
      padding: 20px;
    }

    .gallery {
      display: grid;
      grid-template-columns: repeat(auto-fit, minmax(220px, 1fr));
      gap: 15px;
      padding: 20px;
    }

    .gallery-item {
      position: relative;
      overflow: hidden;
      border-radius: 10px;
    }
```

```

.gallery-item img {
  width: 100%;
  height: 200px;
  object-fit: cover;
  transition: transform 0.4s ease;
}

/* Hover Zoom */
.gallery-item:hover img {
  transform: scale(1.1);
}

/* Overlay Effect */
.overlay {
  position: absolute;
  top: 0;
  left: 0;
  width: 100%;
  height: 100%;
  background: rgba(0,0,0,0.4);
  color: white;
  display: flex;
  justify-content: center;
  align-items: center;
  opacity: 0;
  transition: 0.3s;
  font-size: 18px;
}

.gallery-item:hover .overlay {
  opacity: 1;
}

```

```

</head>
<body>
<h1>Image Gallery</h1>
<div class="gallery">
  <div class="gallery-item">
    
    <div class="overlay">Rose</div>
  </div>
  <div class="gallery-item">
    
    <div class="overlay">Lotus</div>
  </div>
  <div class="gallery-item">
    
    <div class="overlay">Hibiscus</div>
  </div>
  <div class="gallery-item">
    
    <div class="overlay">Dahlia</div>
  </div>
  <div class="gallery-item">
    
    <div class="overlay">Tulip</div>
  </div>
  <div class="gallery-item">
    
    <div class="overlay">Chrysanthemum</div>
  </div>
</div>
</body>
</html>

```

Image Gallery



Task 2 – Profile Card Generator

Create a profile card web page.

Requirements:

- Display user image, name, role, and social media links.
- Use AI to:
 - o Suggest modern UI colors and fonts.
 - o Design the card using Flexbox.
 - o Add hover animation and shadow effects

```
<!--2.Create a profile card web page
Suggest modern UI colors and fonts.
Design the card using Flexbox.
Add hover animation and shadow effects-->
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Profile Card</title>
  <style>
    body {
      font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
      background-color: #e0f7fa;
      display: flex;
      justify-content: center;
      align-items: center;
      height: 100vh;
      margin: 0;
    }

    .profile-card {
      background-color: #ffffff;
      border-radius: 15px;
      box-shadow: 0 4px 8px rgba(0, 0, 0, 0.1);
      width: 300px;
      text-align: center;
      padding: 20px;
      transition: transform 0.3s ease, box-shadow 0.3s ease;
    }

    .profile-card:hover {
      transform: translateY(-10px);
      box-shadow: 0 8px 16px rgba(0, 0, 0, 0.2);
    }

    .profile-image {
```

```

.profile-image {
  width: 100px;
  height: 100px;
  border-radius: 50%;
  object-fit: cover;
  margin-bottom: 15px;
}

.profile-name {
  font-size: 1.5em;
  color: #00796b;
  margin-bottom: 5px;
}

.profile-title {
  font-size: 1em;
  color: #004d40;
  margin-bottom: 15px;
}


.profile-description {
  font-size: 0.9em;
  color: #004d40;
}

```

```

<body>
  <div class="profile-card">
    
    <div class="profile-name">Lily</div>
    <div class="profile-title">Web Developer</div>
    <div class="profile-description">Passionate about creating interactive and responsive web applications.</div>
  </div>
</body>
</html>

```



Task 3 -Develop a dynamic shopping cart system.

Requirements:

- Add, remove, and update product quantities.
- Display real-time total price.

- Use AI to:
 - o Manage cart state using JavaScript objects.
 - o Persist cart data in localStorage.

```
✓ <!--Develop a dynamic shopping cart system.  
Add, remove, and update product quantities.  
Display real-time total price.  
Manage cart state using JavaScript objects.  
Persist cart data in localStorage.  
-->  
<!Doctype html>  
<html lang="en">  
✓ <head>  
  <meta charset="UTF-8">  
  <meta name="viewport" content="width=device-width, initial-scale=1.0">  
  <title>Shopping Cart</title>  
  <style>  
    ✓ body {  
      ✓ font-family: Arial, sans-serif;  
      margin: 0;  
      padding: 20px;  
      background-color: #f9f9f9;  
    }  
    ✓ h1 {  
      text-align: center;  
      margin-bottom: 20px;  
    }  
    ✓ .product-list, .cart {  
      display: flex;  
      flex-wrap: wrap;  
      gap: 20px;  
      justify-content: center;  
    }  
    ✓ .product, .cart-item {  
      background-color: white;  
      border-radius: 10px;  
      box-shadow: 0 2px 5px rgba(0,0,0,0.1);  
      padding: 15px;
```

```

    width: 200px;
    text-align: center;
  }

  .product img, .cart-item img {
    width: 100%;
    height: 150px;
    object-fit: cover;
    border-radius: 10px;
  }

  .product button, .cart-item button {
    margin-top: 10px;
    padding: 10px 15px;
    background-color: #28a745;
    color: white;
    border: none;
    border-radius: 5px;
    cursor: pointer;
  }

  .cart-item button {
    background-color: #dc3545;
  }

  .total {
    text-align: center;
    margin-top: 20px;
    font-size: 1.5em;
  }
</style>
</head>

```

```

<body>
  <h1>Shopping Cart</h1>
  <div class="product-list">
    <!-- Products will be dynamically added here -->
  </div>

  <h2>Your Cart</h2>
  <div class="cart">
    <!-- Cart items will be dynamically added here -->
  </div>

  <div class="total">
    Total: $<span id="total-price">0.00</span>
  </div>

  <script>
    const products = [
      { id: 1, name: 'Product 1', price: 19.99, image: 'https://via.placeholder.com/200x150' },
      { id: 2, name: 'Product 2', price: 29.99, image: 'https://via.placeholder.com/200x150' },
      { id: 3, name: 'Product 3', price: 39.99, image: 'https://via.placeholder.com/200x150' },
    ];

    let cart = JSON.parse(localStorage.getItem('cart')) || {};

    function displayProducts() {
      const productList = document.querySelector('.product-list');
      productList.innerHTML = '';
      products.forEach(product => {
        const productDiv = document.createElement('div');
        productDiv.className = 'product';
        productDiv.innerHTML = `
          
          <h3>${product.name}</h3>
          <p>${product.price.toFixed(2)}</p>
          <button onclick="addToCart(${product.id})">Add to Cart</button>
        `;
        productList.appendChild(productDiv);
      });
    }

    displayProducts();
  </script>

```


```

function updateCart() {
  const cartContainer = document.querySelector('.cart');
  cartContainer.innerHTML = '';
  let totalPrice = 0;

  Object.values(cart).forEach(item => {
    totalPrice += item.price * item.quantity;
    const cartItemDiv = document.createElement('div');
    cartItemDiv.className = 'cart-item';
    cartItemDiv.innerHTML = `
      
      <h3>${item.name}</h3>
      <p>${item.price.toFixed(2)} x ${item.quantity}</p>
      <button onclick="removeFromCart(${item.id})">Remove</button>
    `;
    cartContainer.appendChild(cartItemDiv);
  });
  document.getElementById('total-price').textContent = totalPrice.toFixed(2);
  localStorage.setItem('cart', JSON.stringify(cart));
}

displayProducts();
updateCart();
</script>
</body>

```



Task 4 – Role-Based Access Control Application

Create a role-based web application.

Requirements:

- Admin, Editor, User roles.
- Conditional UI rendering.
- Use AI to:
 - o Design access control logic.
 - o Maintain secure state transitions.
 - o Create scalable UI components.

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Role-Based Web Application</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
    }
    .section {
      padding: 15px;
      margin: 15px 0;
      border-radius: 5px;
      display: none;
    }
    .admin {
      background-color: #f8d7da;
      border: 1px solid #f5c6cb;
    }
    .editor {
      background-color: #d1ecf1;
      border: 1px solid #bee5eb;
    }
    .user {
      background-color: #d4edda;
      border: 1px solid #c3e6cb;
    }
    .role-indicator {
      font-weight: bold;
      margin-bottom: 20px;
      padding: 10px;
      background-color: #e2e3e5;
      border-radius: 5px;
    }
  </style>

```

```

</head>
<body>
  <h1>Role-Based Web Application</h1>
  <div class="role-indicator">Current Role: <span id="currentRole"></span></div>

  <div id="adminSection" class="section admin">
    <h2>Admin Section</h2>
    <p>Manage users and system settings.</p>
    <button onclick="performAction('admin')">Admin Action</button>
  </div>

  <div id="editorSection" class="section editor">
    <h2>Editor Section</h2>
    <p>Create and edit content.</p>
    <button onclick="performAction('editor')">Edit Content</button>
  </div>

  <div id="userSection" class="section user">
    <h2>User Section</h2>
    <p>View available content.</p>
    <button onclick="performAction('user')">View Content</button>
  </div>

  <script>
    const rolePermissions = {
      admin: ['adminSection', 'editorSection', 'userSection'],
      editor: ['editorSection', 'userSection'],
      user: ['userSection']
    };

    let currentUser = { role: 'editor' }; // Change to test different roles

```



```

// Show permitted sections
const permissions = rolePermissions[role] || [];
permissions.forEach(sectionId => {
  const element = document.getElementById(sectionId);
  if (element) {
    element.style.display = 'block';
  }
});

document.getElementById('currentRole').textContent = role;
}

function performAction(action) {
  if (rolePermissions[currentUser.role].includes(action + 'Section')) {
    alert(`${currentUser.role} performed: ${action}`);
  } else {
    alert('Access Denied');
  }
}

function switchRole(newRole) {
  if (rolePermissions[newRole]) {
    currentUser.role = newRole;
    renderUIBasedOnRole(newRole);
  }
}

// Initialize
renderUIBasedOnRole(currentUser.role);
</script>
</body>
</html>

```

Role-Based Web Application

Current Role: editor

Editor Section
 Create and edit content.

User Section
 View available content.

Task 5 – Multi-Language Website

Design a multilingual website.

Requirements:

- Switch languages dynamically.
- Persist language preference.
- Use AI to:
 - o Structure translation files.
 - o Handle RTL/LTR layouts.
 - o Improve accessibility.

```

<!--Multi-Language Website
Design a multilingual website.
Switch languages dynamically.
Persist language preference.
Structure translation files.
Handle RTL/LTR layouts.
Improve accessibility.
Languages are English French spanish German-->
<!doctype html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Multilingual Website</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f0f0f0;
      margin: 0;
      padding: 20px;
    }

    h1 {
      text-align: center;
      color: #333;
    }

    .language-selector {
      display: flex;
      justify-content: center;
      margin-top: 20px;
    }

    .language-selector button {
      margin: 0 10px;
      padding: 10px 20px;
      font-size: 16px;
    }
  </style>

```

```

  </script>
  <script>
    function setLanguage(lang) {
      document.getElementById('greeting').textContent = translations[lang];
      localStorage.setItem('preferredLanguage', lang);
    }

    // Load preferred language on page load
    window.onload = function() {
      const preferredLanguage = localStorage.getItem('preferredLanguage') || 'en';
      setLanguage(preferredLanguage);
    };

    // Handle RTL/LTR layouts
    function updateLayout(lang) {
      if (lang === 'ar' || lang === 'he') {
        document.body.style.direction = 'rtl';
      } else {
        document.body.style.direction = 'ltr';
      }
    }

    // Call updateLayout when language is changed
    function setLanguage(lang) {
      document.getElementById('greeting').textContent = translations[lang];
      localStorage.setItem('preferredLanguage', lang);
      updateLayout(lang);
    }
  </script>
</body>
</html>

```

Hello, World!

English

French

Spanish

German

Task 6 – Online Examination System

Create an online exam interface.

Requirements:

- Timer, questions, and submission.
- Prevent multiple submissions.
- Use AI to:
 - o Manage exam state.
 - o Improve exam UX.
 - o Ensure accessibility.

```

<!--Task 6 - Online Examination System
Create an online exam interface.
Timer, questions, and submission.
Prevent multiple submissions.
Manage exam state.
Improve exam UX.
Ensure accessibility.
-->
<!doctype html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Online Examination System</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f0f0f0;
      margin: 0;
      padding: 20px;
    }

    h1 {
      text-align: center;
      color: #333;
    }

    .exam-container {
      max-width: 600px;
      margin: 0 auto;
      background-color: #fff;
      padding: 20px;
      border-radius: 10px;
      box-shadow: 0 4px 8px rgba(0, 0, 0, 0.1);
    }
  </style>

```

```

    .question {
      margin-bottom: 20px;
    }

    .options {
      list-style-type: none;
      padding: 0;
    }

    .options li {
      margin-bottom: 10px;
    }

    .submit-btn {
      display: block;
      width: 100%;
      padding: 10px;
      background-color: #007BFF;
      color: #fff;
      border: none;
      border-radius: 5px;
      cursor: pointer;
    }
  </style>
</head>

```

```

</head>
<body>
  <h1>Online Examination System</h1>
  <div class="exam-container">
    <div class="question">
      <p>1. What is the capital of France?</p>
      <ul class="options">
        <li><input type="radio" name="q1" value="a"> A) Berlin</li>
        <li><input type="radio" name="q1" value="b"> B) Madrid</li>
        <li><input type="radio" name="q1" value="c"> C) Paris</li>
        <li><input type="radio" name="q1" value="d"> D) Rome</li>
      </ul>
    </div>
    <div class="question">
      <p>2. What is 2 + 2?</p>
      <ul class="options">
        <li><input type="radio" name="q2" value="a"> A) 3</li>
        <li><input type="radio" name="q2" value="b"> B) 4</li>
        <li><input type="radio" name="q2" value="c"> C) 5</li>
        <li><input type="radio" name="q2" value="d"> D) 6</li>
      </ul>
    </div>
    <button class="submit-btn">Submit Exam</button>
  </div>
</body>
</html>

```

Online Examination System

1. What is the capital of Italy?

- ☐ A) Madrid
- ☐ B) Lisbon
- ☐ C) Rome
- ☐ D) Athens

2. What is $5 * 3$?

- ☐ A) 8
- ☐ B) 15
- ☐ C) 12
- ☐ D) 10

Submit Exam