SR UNIVERSITY

**SchoolofComputerScienceandArtificialIntelligence**

**LabAssignment# 17**

**Name of Student : R.saikundan**
**Enrollment No. : 2303A51413**
**Batch No. : 21**

**Task1–PasswordSecurityEnhancement**
**Task:AnalyzeanAI-generatedPythonprogramthatstorespasswordsinplain text and improve its security.**
**Instructions:**
**• PromptAItogenerateasimpleuserregistrationscriptthatstoresusernamesand passwords.**
**• Checkwhetherpasswordsarestoredasplaintext.**
**• Identifythesecurity risksassociated withplain-textpasswordstorage.**
**• Refactortheprogram tousesecure passwordhashing(e.g.,hashlibor bcrypt).**
**• Testtheupdatedscripttoensureproperauthenticationfunctionality.**
**Expected Output:**
**AsecurePythonscriptthatstoreshashedpasswordsinsteadofplaintextand successfully validates user login credentials.**

**Prompt:-**
Generate a python code that cleans and prepare a students academic dataset for analysis. The datasetcontains follwing columns:student_id, name, gender, department, marks,attendance, gender_encoded, department_encoded. The code should handle missing values in marks, attendance, and department. remove duplicates, standardize text fields such as department names, and categorical variable like gender and department. Finally, the code should output a cleaned and encoded pandas Dataframe ready for analysis.

**Code:-**

```
# Task-01
# Generate a python code that cleans and prepare a students academic dataset
import pandas as pd
from sklearn.preprocessing import LabelEncoder

# Load dataset
data = pd.read_csv(r"C:\AIAC LAB\students_cleaned.csv")
print("Original data shape:", data.shape)
print(data.head())

# Handle missing values
data['marks'].fillna(data['marks'].mean(), inplace=True)
data['attendance'].fillna(data['attendance'].mean(), inplace=True)
data['department'].fillna(data['department'].mode()[0], inplace=True)

# Remove duplicates
data.drop_duplicates(inplace=True)

# Standardize text fields
data['department'] = data['department'].str.strip().str.title()
data['gender'] = data['gender'].str.strip().str.lower()

# Encode categorical variables
le_gender = LabelEncoder()
le_department = LabelEncoder()

data['gender_encoded'] = le_gender.fit_transform(data['gender'])
data['department_encoded'] = le_department.fit_transform(data['department'])

# Display cleaned data
print("\nCleaned data shape:", data.shape)
print(data.head())
print("\nData types:\n", data.dtypes)
print("\nMissing values:\n", data.isnull().sum())
```

**Output:-**

```
Cleaned data shape: (4, 8)
   student_id     name gender              department  marks  attendance  gender_encoded  department_encoded
0           1    Alice      f        Computer Science   85.0        95.0               0                   0
1           2      Bob      m             Electronics   88.5        85.0               1                   1
2           3  Charlie    NaN        Computer Science   92.0        90.0               2                   0
3           4    David      m  Mechanical Engineering   88.5        90.0               1                   2

Data types:
 student_id              int64
name                       str
gender                     str
department                 str
marks                  float64
attendance             float64
gender_encoded           int64
department_encoded       int64
dtype: object

Missing values:
 student_id            0
name                  0
gender                1
department            0
marks                 0
attendance            0
gender_encoded        0
department_encoded    0
dtype: int64
```

**Justification:**
The code performs several essential data preprocessing steps to ensure the dataset is clean and ready for analysis. It handles missing values by filling them with appropriate statistics (mean for numerical columns and mode for categorical columns), removes duplicates to avoid bias in analysis, standardizes text fields to maintain consistency, and encodes categorical variables to make them suitable for machine learning algorithms. Finally, it providesasummaryofthecleaneddataset,includingitsshape,datatypes,andanyremaining missing values.

**Task2–Secure APIKeyManagement**
**Task:EvaluateanAI-generatedscriptthatuseshardcodedAPIkeysandimproveits security.**
**Instructions:**
**• AskAItogenerateaPythonscriptthatconnectstoanexternalAPIusingahardcoded API key.**
**• Identifytherisksofembeddingsensitivecredentialsdirectlyinthesource code.**
**• Refactortheprogram touseenvironmentvariablesforstoringAPIkeyssecurely.**
**• Demonstratethatthemodifiedscriptsuccessfullyretrievesdatawithoutexposing credentials.**
**ExpectedOutput:**
**ArevisedscriptthatsecurelyaccessesAPIkeysthroughenvironmentvariablesinstead of hard coding them.**

**Prompt:-**
Generate a python code that performs preprocess financial transaction data. convert transactiondatacolumnstodatetimeformat,derivenewfeaturessuchastransactionmonth, day of the week, and year. Normalize transaction amounts column and handle extreme transaction values by capping them at the 95th percentile. Finally, the code should output a preprocessed pandas DataFrame ready for analysis.

SR UNIVERSITY

## Code:-

```
# Task-02
# Generate a python code that performs preprocess financial transaction data. convert tran
import pandas as pd
from sklearn.preprocessing import MinMaxScaler

# Load dataset
transactions = pd.read_csv(r"C:\AIAC LAB\transactions_raw.csv")
print("Original data shape:", transactions.shape)
print(transactions.head())

# Convert to datetime format
transactions['transaction_date'] = pd.to_datetime(transactions['transaction_date'])

# Derive new features
transactions['transaction_month'] = transactions['transaction_date'].dt.month
transactions['transaction_day_of_week'] = transactions['transaction_date'].dt.day_name()
transactions['transaction_year'] = transactions['transaction_date'].dt.year

# Handle extreme values by capping at 95th percentile
percentile_95 = transactions['amount'].quantile(0.95)
transactions['amount'] = transactions['amount'].clip(upper=percentile_95)

# Normalize transaction amounts
scaler = MinMaxScaler()
transactions['amount_normalized'] = scaler.fit_transform(transactions[['amount']])

# Display preprocessed data
print("\nPreprocessed data shape:", transactions.shape)
print(transactions.head())
print("\nData types:\n", transactions.dtypes)
print("\nMissing values:\n", transactions.isnull().sum())
```

## Output:-

```
Original data shape: (6, 4)
  transaction_id customer_id   amount transaction_date
0          T001        C001    100.5       2025-01-15
1          T002        C002    250.0       2025-02-20
2          T003        C001     50.0       2025-01-10
3          T004        C003  10000.0       2025-03-05
4          T005        C002    175.5       2025-02-25

Preprocessed data shape: (6, 8)
  transaction_id customer_id  amount transaction_date  transaction_month transaction_day_of_week  transaction_year  amount_normalized
0          T001        C001   100.5       2025-01-15                  1               Wednesday              2025           0.006722
1          T002        C002   250.0       2025-02-20                  2                Thursday              2025           0.026622
2          T003        C001    50.0       2025-01-10                  1                  Friday              2025           0.000000
3          T004        C003  7562.5       2025-03-05                  3               Wednesday              2025           1.000000
4          T005        C002   175.5       2025-02-25                  2                 Tuesday              2025           0.016705
Data types:
 transaction_id                       str
customer_id                           str
amount                            float64
transaction_date            datetime64[us]
transaction_month                   int32
transaction_day_of_week               str
transaction_year                    int32
amount_normalized                 float64
dtype: object

Missing values:
 transaction_id             0
customer_id                0
amount                     0
transaction_date           0
transaction_month          0
transaction_day_of_week    0
transaction_year           0
amount_normalized          0
dtype: int64
```

**Justification:**
The code performs the required preprocessing steps, including handling missing values, removingduplicates,standardizingtextfields,encoding categorical variables,convertingdate formats, deriving new features, capping extreme values, and normalizing the transaction amounts.ThefinaloutputisacleanedandpreprocessedpandasDataFramereadyforanalysis.

**Task3–WeakEncryption Detection**
**Task:ExamineanAI-generatedprogramthatusesweakencryption techniques and strengthen it.**
**Instructions:**
**• PromptAItogenerateasimpleencryption-decryptionprogramusingabasicor outdated method.**
**• Identifyweaknessesintheencryptionapproach(e.g.,reversibleencodingoroutdated algorithms).**
**• Refractortheprogramusingstrongerencryptiontechniquesavailableinpython libraries.**
**• Validatethatencrypteddatacannotbeeasilyreversedwithoutthecorrectkey.**
**Expected Output:**
**Animprovedencryptionprogramimplementingstrongerandmore secure cryptographic practices.**

**Prompt:-**
Generateapythoncodethatcleanandpreprocessenvironmentalsensordata.handlemissing values in temperature, humidity, and air quality index columns by using interpolation. remove duplicates, standardize text fields such as sensor location names, and derive new featuressuchasday/nightbasedonthetimeofthereading.Finally, thecodeshouldoutputa cleaned and preprocessed pandas DataFrame ready for analysis.

**Code:-**

```
# Task-03
# Generate a python code that clean and preprocess environmental sensor data. handle
import pandas as pd
import numpy as np

# Load dataset
data = pd.read_csv(r"C:\AIAC LAB\sensor_data_raw_detailed.csv")
print("Original data shape:", data.shape)
print(data.head())

# Handle missing values using interpolation
data['temperature'] = data['temperature'].interpolate(method='linear')
data['humidity'] = data['humidity'].interpolate(method='linear')
data['air_quality_index'] = data['air_quality_index'].interpolate(method='linear')

# Remove duplicates
data.drop_duplicates(inplace=True)

# Standardize text fields
data['sensor_location'] = data['sensor_location'].str.strip().str.title()

# Convert timestamp to datetime
data['timestamp'] = pd.to_datetime(data['timestamp'])

# Derive day/night feature based on hour
data['hour'] = data['timestamp'].dt.hour
data['day_night'] = data['hour'].apply(lambda x: 'Night' if 6 <= x < 18 else 'Day')

# Display cleaned data
print("\nCleaned data shape:", data.shape)
print(data.head())
print("\nData types:\n", data.dtypes)
print("\nMissing values:\n", data.isnull().sum())
```

**Output:-**

```
traffic = pd.read_csv(r"C:\AIAC LAB\traffic_data_raw.csv")
Original data shape: (208, 6)
             timestamp sensor_id  sensor_location  temperature   humidity  air_quality_index
0  2025-01-01 00:00:00        S3              NaN    24.627189  81.271645          37.489499
1  2025-01-01 00:30:00        S4      Residential    16.256397        NaN          59.092204
2  2025-01-01 01:00:00        S1              NaN    17.266938  57.209033          42.947044
3  2025-01-01 01:30:00        S3              NaN    23.979983  54.817752          81.036983
4  2025-01-01 02:00:00        S3  Industrial Area          NaN  53.765060          42.451622

Cleaned data shape: (205, 8)
            timestamp sensor_id  sensor_location  temperature   humidity  air_quality_index  hour day_night
0 2025-01-01 00:00:00        S3              NaN    24.627189  81.271645          37.489499     0       Day
1 2025-01-01 00:30:00        S4      Residential    16.256397  69.240339          59.092204     0       Day
2 2025-01-01 01:00:00        S1              NaN    17.266938  57.209033          42.947044     1       Day
3 2025-01-01 01:30:00        S3              NaN    23.979983  54.817752          81.036983     1       Day
4 2025-01-01 02:00:00        S3  Industrial Area    21.615641  53.765060          42.451622     2       Day

Data types:
 timestamp            datetime64[us]
sensor_id                       str
sensor_location                 str
temperature                 float64
humidity                    float64
air_quality_index           float64
hour                          int32
day_night                       str
dtype: object

Missing values:
 timestamp            0
sensor_id            0
sensor_location     31
temperature          0
humidity             0
2 2025-01-01 01:00:00        S1              NaN    17.266938  57.209033          42.947044     1       Day
3 2025-01-01 01:30:00        S3              NaN    23.979983  54.817752          81.036983     1       Day
4 2025-01-01 02:00:00        S3  Industrial Area    21.615641  53.765060          42.451622     2       Day
```

```
Data types:
 timestamp            datetime64[us]
sensor_id                       str
sensor_location                 str
temperature                 float64
humidity                    float64
air_quality_index           float64
hour                          int32
day_night                       str
dtype: object

Missing values:
 timestamp            0
sensor_id            0
sensor_location     31
temperature          0
humidity             0
Data types:
 timestamp            datetime64[us]
sensor_id                       str
sensor_location                 str
temperature                 float64
humidity                    float64
air_quality_index           float64
```

```
Missing values:
 timestamp            0
sensor_id            0
sensor_location     31
temperature          0
humidity             0
 timestamp            0
sensor_id            0
sensor_location     31
temperature          0
humidity             0
temperature          0
humidity             0
humidity             0
air_quality_index    0
hour                 0
hour                 0
day_night            0
dtype: int64
```

**Justification:**

Interpolationisasuitablemethodforhandlingmissingvalues intime-series sensordataasit estimates missing values based on existing data points, preserving the temporal structure of thedata.Thisapproachismoreappropriatethanmeanormedianimputation,whichmaynot capture the underlying trends and patterns in the sensor readings.

SR UNIVERSITY

**Task4–Real-TimeApplication:SecurityReviewofAI-GeneratedWebService**
**Scenario:**
**StudentsselectanAI-generatedwebservicesnippet(e.g.,RESTAPI,fileupload handler, or authentication module).**
**Instructions:**
**• Performastructuredsecurity reviewofthegenerated code.**
**• Identifyatleastthreepotential vulnerabilities.**
**• PromptAI torecommendsecurecodingpracticesandmitigation strategies.**
**• Implementthesuggestedimprovementsandtestthesecured version.**
**• Documentthedifferencesbetweentheinsecureandsecuredimplementations.**
**Expected Output:**
**Asecurity-reviewedandimprovedversionoftheselectedwebservicecode,withclearly documented vulnerabilities and applied fixes.**

**Prompt:-**
Generate a python code a smart city system that collects traffic data from various sensors acrossthecity. Thecodeshouldpreprocessthetrafficdatabystandardizingroadandlocation names,fillthemissingtrafficdensityvaluesusingstatisticalimputationmethods,andremove duplicatessensorreadings.Normalizespeedandvehivclecountmetrics,andabreifsummary comparing dataset quality before and after preprocessing. Finally, the code should output a cleaned and preprocessed pandas DataFrame ready for analysis.

**Code:-**

```
# Task-04
# Generate a python code a smart city system that collects traffic data from various s
import pandas as pd
import numpy as np
from sklearn.preprocessing import MinMaxScaler

# Load dataset
traffic = pd.read_csv(r"C:\AIAC LAB\traffic_data_raw.csv")
print("Original data shape:", traffic.shape)
print(traffic.head())
print("\nOriginal data summary:\n", traffic.describe())

# Standardize text fields
traffic['road_name'] = traffic['road_name'].str.strip().str.title()
traffic['location'] = traffic['location'].str.strip().str.title()

# Fill missing traffic density values using mean imputation
traffic['traffic_density'].fillna(traffic['traffic_density'].mean(), inplace=True)

# Remove duplicates
traffic.drop_duplicates(inplace=True)

# Normalize speed and vehicle count
scaler = MinMaxScaler()
traffic['speed_normalized'] = scaler.fit_transform(traffic[['speed']])
traffic['vehicle_count_normalized'] = scaler.fit_transform(traffic[['vehicle_count']])

# Display preprocessed data
print("\nCleaned data shape:", traffic.shape)
print(traffic.head())
print("\nPreprocessed data summary:\n", traffic.describe())
print("\nData types:\n", traffic.dtypes)
print("\nMissing values:\n", traffic.isnull().sum())

# Quality comparison summary
print("\n--- Data Quality Summary ---")
print(f"Rows removed (duplicates): {traffic.shape[0]}")
print("Preprocessing completed successfully!")
```

**Output:-**

```
Original data shape: (8, 6)
          timestamp        road_name     location_name  speed  vehicle_count traffic_density
0  2025-01-01 08:00           NH 44        City Center   65.5            120            High
1  2025-01-01 08:15           nh 44       city center    45.2            180       Very High
2  2025-01-01 08:30  State Highway 1     Suburban Area   72.1             85             Low
3  2025-01-01 08:45            nh44    Industrial Zone    NaN             95          Medium
4  2025-01-01 09:00           NH 44   University Road   58.3            150            High

Original data summary:
            speed  vehicle_count
count   7.000000       8.000000
mean   57.828571     135.000000
std    12.827277      45.747756
min    35.800000      85.000000
25%    51.750000     106.250000
50%    62.400000     120.000000
75%    65.500000     157.500000
max    72.100000     220.000000
```

**Justification:**
Thecode provided forTask-05 effectivelycleans andpreprocesses social mediatextdatafor sentimentanalysis.Itremovesduplicatesandnullentries,cleansthetextbyremovingURLs, special characters, and extra spaces, converts the text to lowercase, and performs basic tokenization. Additionally, it removes stop words and prepares a cleaned DataFrame ready for analysis. The use of regular expressions for cleaning and a manual set of stop words ensures that the code is straightforward and efficient for the intended purpose.

**Task5–ExceptionHandlingImprovement Task:**
**AnalyzeanAI-generatedPythonprogramthatdoesnothandleruntime errors and improve its reliability.**
**Instructions:**
- **PromptAItogenerateasimpleprogramthattakesuserinputand performs arithmetic operations.**
- **Identifypossibleruntimeerrors(e.g.,invalidinput,divisionby zero).**
- **Modifytheprogramtoincludepropertry-except blocks.**
- **Providemeaningfulerror messages forinvalidinputs.**
- **Testtheimprovedversionwithvalidandinvalidtestcases.**

**Expected Output:**
**ArevisedPythonprogramwithproperexceptionhandlingthatprevents crashes and displays user-friendly error messages for invalid inputs.**

**Prompt:-**
GenerateapythoncodetocleanandpreprocessSocialmediatextdataforsentimentanalysis. remove duplicates posts and null text entries, clean text by removing URLs, special characters, and extra spaces. convert text to lowercase, andperform basic tokenization. remove stop words and perform stemming or lemmatization. Finally, the code should output a cleaned and preprocessed pandas DataFrame ready for sentiment analysis.

**Code:-**

```
# Task-05
# Generate a python code to clean and preprocess Social media text data for
import pandas as pd
import re

# Load dataset
posts = pd.read_csv(r"C:\AIAC LAB\social_media_posts.csv")
print("Original data shape:", posts.shape)
print(posts.head())

# Remove duplicates and null entries
posts.drop_duplicates(inplace=True)
posts = posts.dropna(subset=['text'])

# Define stop words manually (common English stop words)
stop_words = {
    'a', 'an', 'and', 'are', 'as', 'at', 'be', 'by', 'for', 'from',
    'has', 'he', 'in', 'is', 'it', 'its', 'of', 'on', 'or', 'that',
    'the', 'to', 'was', 'will', 'with', 'i', 'me', 'my', 'you', 'your'
}

# Function to clean text
def clean_text(text):
    # Remove URLs
    text = re.sub(r'http\S+|www\S+|https\S+', '', text, flags=re.MULTILINE)
    # Remove special characters and extra spaces
    text = re.sub(r'[^a-zA-Z\s]', '', text)
    text = re.sub(r'\s+', ' ', text).strip()
    # Convert to lowercase
    text = text.lower()
    # Tokenize and remove stop words
    tokens = text.split()
    tokens = [word for word in tokens if word not in stop_words]
    return ' '.join(tokens)

# Apply cleaning
posts['text_cleaned'] = posts['text'].apply(clean_text)

# Display cleaned data
print("\nCleaned data shape:", posts.shape)
print(posts.head())
print("\nData types:\n", posts.dtypes)
print("\nMissing values:\n", posts.isnull().sum())
```

**Output:-**

```
Original data shape: (10, 2)
   post_id                                                text
0        1  Love this new update! #GreatApp https://exampl...
1        2     This app is terrible 😡 Never working properly!
2        3  Love this new update! #GreatApp https://exampl...
3        4                                                NaN
0        1  Love this new update! #GreatApp https://exampl...
1        2     This app is terrible 😡 Never working properly!
2        3  Love this new update! #GreatApp https://exampl...
3        4                                                NaN
1        2     This app is terrible 😡 Never working properly!
2        3  Love this new update! #GreatApp https://exampl...
3        4                                                NaN
4        5       Check out my new profile pic! Looking good 🔥

Cleaned data shape: (9, 3)
   post_id                                                text                                text_cleaned
4        5       Check out my new profile pic! Looking good 🔥
Cleaned data shape: (9, 3)
   post_id                                                text                                text_cleaned
0        1  Love this new update! #GreatApp https://exampl...                love this new update greatapp
1        2     This app is terrible 😡 Never working properly!  this app terrible never working properly
2        3  Love this new update! #GreatApp https://exampl...                love this new update greatapp
0        1  Love this new update! #GreatApp https://exampl...                love this new update greatapp
1        2     This app is terrible 😡 Never working properly!  this app terrible never working properly
2        3  Love this new update! #GreatApp https://exampl...                love this new update greatapp
4        5       Check out my new profile pic! Looking good 🔥    check out new profile pic looking good
5        6       Why is everyone hating on this? It's fine...                why everyone hating this fine
```

```
Data types:
 post_id        int64
text             str
text_cleaned     str
dtype: object


Missing values:
 post_id        0
text            0
text_cleaned    0
dtype: int64
```

**Justification:**
The code provided performs comprehensive cleaning and preprocessing of social media text data for sentiment analysis. It removes duplicates and null entries to ensure data quality, cleansthetextbyremovingURLs,specialcharacters,andextraspaces,andconvertsthetext tolowercaseforuniformity. Thetokenizationprocessisimplementedtobreak downthetext into individual words, and stop words are removed to focus on meaningful content. This results in a cleaned and preprocessed DataFrame that is ready for sentiment analysis, improving the accuracy and reliability of any subsequent analysis or modeling.