

SCHOOL OF COMPUTER SCIENCE AND ARTIFICIAL INTELLIGENCE		DEPARTMENT OF COMPUTER SCIENCE ENGINEERING	
Program Name: B. Tech		Assignment Type: Lab	Academic Year:2025-2026
Course Coordinator Name		Dr. Rishabh Mittal	
Instructor(s) Name			
		Mr. S Naresh Kumar	
		Ms. B. Swathi	
		Dr. Sasanko Shekhar Gantayat	
		Mr. Md Sallauddin	
		Dr. Mathivanan	
		Mr. Y Srikanth	
		Ms. N Shilpa	
		Dr. Rishabh Mittal (Coordinator)	
		Dr. R. Prashant Kumar	
		Mr. Ankushavali MD	
		Mr. B Viswanath	
		Ms. Sujitha Reddy	
		Ms. A. Anitha	
		Ms. M.Madhuri	
		Ms. Katherashala Swetha	
Ms. Velpula sumalatha			
Mr. Bingi Raju			
Course Code	23CS002PC304	Course Title	AI Assisted Coding
Year/Sem	III/II	Regulation	R23
Date and Day of Assignment	Week6 – Wednesday	Time(s)	23CSBTB01 To 23CSBTB52
Duration	2 Hours	Applicable to Batches	All batches
Assignment Number:11.3(Present assignment number)/24(Total number of assignments)			
Q.No.	Question		Expected Time to complete
1	Lab 11: Data Structures with AI Implementing Fundamental Data Structures using AI Assistance		Week6 -

	<p>Lab Objectives: By the end of this lab, students will be able to:</p> <ul style="list-style-type: none"> • Design and implement fundamental data structures in Python using AI assistance. • Effectively prompt AI tools (e.g., GitHub Copilot) for code generation, optimization, and documentation. • Understand and compare core data structures: Arrays, Linked Lists, Stacks, Queues, Priority Queues, Trees, and Graphs. • Improve code readability, efficiency, and maintainability using AI-generated suggestions. <p>Learning Outcomes After completing this lab, students will be able to:</p> <ul style="list-style-type: none"> • Apply appropriate data structures to solve real-world problems. • Analyze time and space complexity of different data structure operations. • Use AI tools responsibly to assist (not replace) logical thinking and problem-solving. • Validate, test, and refine AI-generated code. 	Wedne sday
	<p>Task 1: Smart Contact Manager (Arrays & Linked Lists) Scenario SR University's student club requires a simple Contact Manager Application to store members' names and phone numbers. The system should support efficient addition, searching, and deletion of contacts.</p> <p>Tasks</p> <ol style="list-style-type: none"> 1. Implement the contact manager using arrays (lists). 2. Implement the same functionality using a linked list for dynamic memory allocation. 3. Implement the following operations in both approaches: <ul style="list-style-type: none"> ○ Add a contact ○ Search for a contact ○ Delete a contact 4. Use GitHub Copilot to assist in generating search and delete methods. 5. Compare array vs. linked list approaches with respect to: <ul style="list-style-type: none"> ○ Insertion efficiency ○ Deletion efficiency <p>Expected Outcome</p> <ul style="list-style-type: none"> • Two working implementations (array-based and linked-list-based). • A brief comparison explaining performance differences. 	

```

Welcome AAC 11.4.py X
C:\Users> shash > Downloads > AAC 11.4.py > ArrayContactManager
1 class ArrayContactManager:
2     def __init__(self):
3         self.contacts = []
4     def add_contact(self, name, phone):
5         self.contacts.append({'name': name, 'phone': phone})
6     def search_contact(self, name):
7         for contact in self.contacts:
8             if contact['name'] == name:
9                 return contact['phone']
10        return None
11    def delete_contact(self, name):
12        for i, contact in enumerate(self.contacts):
13            if contact['name'] == name:
14                del self.contacts[i]
15            return True
16        return False
17
18 class Node:
19     def __init__(self, name, phone):
20         self.name = name
21         self.phone = phone
22         self.next = None
23
24 class LinkedListContactManager:

```

CHAT

CONTACT MANAGER IMPLEMENTATION WITH ARRAYS AND LINKED LI...

- o Add a contact
- o Search for a contact
- o Delete a contact

4. Use GitHub Copilot to assist in generating search and delete methods.

5. Compare array vs. linked list approaches with respect to:

- o Insertion efficiency
- o Deletion efficiency

Expected Outcome

- Two working implementations (array-based and linked-list-based).
- A brief comparison explaining performance differences.

give code in python without comments

✓ pwd

✓ Created array_contact_manager.py

✓ Created linked_list_contact_manager.py

✓ Created comparison.txt

I've created three files in your current directory (shash) with the implementations:

- array_contact_manager.py: Array-based contact manager
- linked_list_contact_manager.py: Linked list-based contact manager
- comparison.txt: Brief performance comparison

The code is provided without comments as requested. You can run these files directly in Python to test the functionality. For example, you could create a simple test script to instantiate the classes and call the methods.

AAC 11.4.py

Describe what to build next.

```

Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ArrayContactManager
18 class Node:
19     def __init__(self, name, phone):
20
21         self.phone = phone
22         self.next = None
23
24 class LinkedListContactManager:
25     def __init__(self):
26         self.head = None
27     def add_contact(self, name, phone):
28         new_node = Node(name, phone)
29         if not self.head:
30             self.head = new_node
31         else:
32             current = self.head
33             while current.next:
34                 current = current.next
35             current.next = new_node
36     def search_contact(self, name):
37         current = self.head
38         while current:
39             if current.name == name:
40                 return current.phone
41             current = current.next

```

```

Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ArrayContactManager
24 class LinkedListContactManager:
36     def search_contact(self, name):
37
38         return current.phone
39         current = current.next
40     return None
41
42 def delete_contact(self, name):
43     if not self.head:
44         return False
45     if self.head.name == name:
46         self.head = self.head.next
47         return True
48     current = self.head
49     while current.next:
50         if current.next.name == name:
51             current.next = current.next.next
52             return True
53         current = current.next
54     return False
55
56 array_cm = ArrayContactManager()
57 array_cm.add_contact("Alice", "123")
58 array_cm.add_contact("Bob", "456")
59 print("Array search Alice:", array_cm.search_contact("Alice"))
60

```

```

Welcome AAC 11.4.py X
C:\Users\shash\Downloads> AAC 11.4.py > ArrayContactManager
24 class LinkedListContactManager:
43     def delete_contact(self, name):
54         current = current.next
55         return False
56
57 array_cm = ArrayContactManager()
58 array_cm.add_contact("Alice", "123")
59 array_cm.add_contact("Bob", "456")
60 print("Array search Alice:", array_cm.search_contact("Alice"))
61 print("Array delete Bob:", array_cm.delete_contact("Bob"))
62 print("Array search Bob after delete:", array_cm.search_contact("Bob"))
63
64 linked_cm = LinkedListContactManager()
65 linked_cm.add_contact("Charlie", "789")
66 linked_cm.add_contact("Dave", "101")
67 print("Linked search Charlie:", linked_cm.search_contact("Charlie"))
68 print("Linked delete Dave:", linked_cm.delete_contact("Dave"))
69 print("Linked search Dave after delete:", linked_cm.search_contact("Dave"))

```

Task 2: Library Book Search System (Queues & Priority Queues)

Scenario

The SRU Library manages book borrow requests. Students and faculty submit requests, but **faculty requests must be prioritized** over student requests.

Tasks

1. Implement a **Queue (FIFO)** to manage book requests.
2. Extend the system to a **Priority Queue**, prioritizing faculty requests.
3. Use **GitHub Copilot** to assist in generating:
 - o enqueue() method
 - o dequeue() method
4. Test the system with a mix of student and faculty requests.

Expected Outcome

- Working queue and priority queue implementations.
- Correct prioritization of faculty requests.

```

Welcome AAC 11.4py CHAT
C:\Users\shash\Downloads> AAC 11.4py > ...
1 from collections import deque
2 import heapq
3 class BookRequest:
4     def __init__(self, requester_name, book title, role):
5         self.requester_name = requester_name
6         self.book_title = book_title
7         self.role = role
8     def __repr__(self):
9         return f'{self.role.upper()} | {self.requester_name} -> {self.book_title}'
10
11 class LibraryQueue:
12     def __init__(self):
13         self.queue = deque()
14     def enqueue(self, request):
15         self.queue.append(request)
16         print(f"[QUEUE] Added: {request}")
17     def dequeue(self):
18         if not self.queue:
19             print(f"[QUEUE] No requests in queue.")
20             return None
21         request = self.queue.popleft()
22         print(f"[QUEUE] Processing: {request}")
23         return request
24     def is_empty(self):

```

LIBRARY BOOK REQUEST SYSTEM IMPLEMENTATION

Library Book Search System (Queues & Priority Queues)

Scenario

The SRU Library manages book borrow requests. Students and faculty submit requests, but faculty requests must be prioritized over student requests.

Tasks

1. Implement a Queue (FIFO) to manage book requests.
2. Extend the system to a Priority Queue, prioritizing faculty requests.
3. Use GitHub Copilot to assist in generating:
 - o enqueue() method
 - o dequeue() method
4. Test the system with a mix of student and faculty requests.

Expected Outcome

- Working queue and priority queue implementations.
- Correct prioritization of faculty requests.

give code in python without comments just paste in the file

✓ Optimizing tool selection...

✓ Reviewed and created AAC 11.4py

```

Welcome AAC 11.4.py
C:\Users\shash\Downloads> AAC 11.4.py > ...
10 class LibraryQueue:
23     def is_empty(self):
24         return len(self._queue) == 0
25     def display(self):
26         if not self._queue:
27             print("[QUEUE] Queue is empty.")
28         else:
29             print("[QUEUE] Current requests:")
30             for req in self._queue:
31                 print(f"    {req}")
32 class PriorityLibraryQueue:
33     PRIORITY_MAP = {"faculty": 0, "student": 1}
34
35     def __init__(self):
36         self._heap = []
37         self._counter = 0
38     def enqueue(self, request):
39         priority = self.PRIORITY_MAP.get(request.role.lower(), 2)
40         heapq.heappush(self._heap, (priority, self._counter, request))
41         self._counter += 1
42         print(f"[PRIORITY QUEUE] Added: {request}")
43     def dequeue(self):
44         if not self._heap:

```

CHAT

LIBRARY BOOK REQUEST SYSTEM IMPLEMENTATION

Library Book Search System (Queues & Priority Queues)

Scenario

The SRU Library manages book borrow requests. Students and faculty submit requests, but faculty requests must be prioritized over student requests.

Tasks

1. Implement a Queue (FIFO) to manage book requests.
2. Extend the system to a Priority Queue, prioritizing faculty requests.
3. Use GitHub Copilot to assist in generating:
 - o enqueue() method
 - o dequeue() method
4. Test the system with a mix of student and faculty requests.

Expected Outcome

- Working queue and priority queue implementations.
- Correct prioritization of faculty requests.

give code in python without comments just paste in the file

✓ Optimizing tool selection...

✓ Reviewed and created AAC 11.4.py

✓ Created AAC 11.4.py

✓ Configured a Python environment

✓ Ran pylanceRunCodeSnippets - pylance mcp server (MCP Server)

✓ Reviewed code and provided a brief summary

AAC 11.4.py

Describe what to build next

Claude Sonnet 4.6

```

Welcome AAC 11.4.py
C: > Users > shash > Downloads > AAC 11.4.py > ...
32 class PriorityLibraryQueue:
43     def dequeue(self):
45         print("[PRIORITY QUEUE] No requests in queue.")
46         return None
47         _, _ , request = heapq.heappop(self._heap)
48         print(f"[PRIORITY QUEUE] Processing: {request}")
49         return request
50     def is_empty(self):
51         return len(self._heap) == 0
52     def display(self):
53         if not self._heap:
54             print("[PRIORITY QUEUE] Queue is empty.")
55         else:
56             sorted_requests = sorted(self._heap, key=lambda x: (x[0], x[1]))
57             print("[PRIORITY QUEUE] Current requests (by priority):")
58             for _, _, req in sorted_requests:
59                 print(f" {req}")
60 print("=" * 55)
61 print("          REGULAR QUEUE (FIFO) TEST")
62 print("=" * 55)
63 library_queue = LibraryQueue()
64 library_queue.enqueue(BookRequest("Alice", "Data Structures", "student"))
65 library_queue.enqueue(BookRequest("Dr. Smith", "Algorithms", "faculty"))

```

```

C: > Users > shash > Downloads > AAC 11.4.py > ...
65 library_queue.enqueue(BookRequest("Dr. Smith", "Algorithms", "faculty"))
66 library_queue.enqueue(BookRequest("Bob", "Operating Systems", "student"))
67 library_queue.enqueue(BookRequest("Dr. Lee", "Database Systems", "faculty"))
68 library_queue.enqueue(BookRequest("Carol", "Computer Networks", "student"))
69 print()
70 library_queue.display()
71 print()
72 print("--- Dequeuing all requests ---")
73 while not library_queue.is_empty():
74     library_queue.dequeue()
75 print()
76 print("=" * 55)
77 print("          PRIORITY QUEUE TEST (Faculty First)")
78 print("=" * 55)
79 priority_queue = PriorityLibraryQueue()
80 priority_queue.enqueue(BookRequest("Alice", "Data Structures", "student"))
81 priority_queue.enqueue(BookRequest("Dr. Smith", "Algorithms", "faculty"))
82 priority_queue.enqueue(BookRequest("Bob", "Operating Systems", "student"))
83 priority_queue.enqueue(BookRequest("Dr. Lee", "Database Systems", "faculty"))
84 priority_queue.enqueue(BookRequest("Carol", "Computer Networks", "student"))
85 print()
86 priority_queue.display()
87 print()

```

```
Welcome AAC 11.4.py
C: > Users > shash > Downloads > AAC 11.4.py > ...
76 print("=" * 55)
77 print("        PRIORITY QUEUE TEST (Faculty First)")
78 print("=" * 55)
79 priority_queue = PriorityLibraryQueue()
80 priority_queue.enqueue(BookRequest("Alice", "Data Structures", "student"))
81 priority_queue.enqueue(BookRequest("Dr. Smith", "Algorithms", "faculty"))
82 priority_queue.enqueue(BookRequest("Bob", "Operating Systems", "student"))
83 priority_queue.enqueue(BookRequest("Dr. Lee", "Database Systems", "faculty"))
84 priority_queue.enqueue(BookRequest("Carol", "Computer Networks", "student"))
85 print()
86 priority_queue.display()
87 print()
88 print("--- Dequeuing all requests ---")
89 while not priority_queue.is_empty():
90     priority_queue.dequeue()
91
```

Task 3: Emergency Help Desk (Stack Implementation)

Scenario

SR University's IT Help Desk receives technical support tickets from students and staff. While tickets are received sequentially, issue escalation follows a **Last-In, First-Out (LIFO)** approach.

Tasks

1. Implement a **Stack** to manage support tickets.
2. Provide the following operations:
 - o push(ticket)
 - o pop()
 - o peek()
3. Simulate at least **five tickets** being raised and resolved.
4. Use **GitHub Copilot** to suggest additional stack operations such as:
 - o Checking whether the stack is empty
 - o Checking whether the stack is full (if applicable)

Expected Outcome

- Functional stack-based ticket management system.
- Clear demonstration of LIFO behavior.


```

Welcome AAC 11.4.py X
C:\Users\shash\Downloads> AAC 11.4.py > ...
1 class SupportTicket:
2     def __init__(self, ticket_id, requester, issue, priority="normal"):
3         self.ticket_id = ticket_id
4         self.requester = requester
5         self.issue = issue
6         self.priority = priority
7
8     def __repr__(self):
9         return f"[#{self.ticket_id}] {self.requester} | {self.issue} ({self.priority.upper()})"
10
11
12 class HelpDeskStack:
13     MAX_SIZE = 10
14
15     def __init__(self):
16         self._stack = []
17
18     def push(self, ticket):
19         if self.is_full():
20             print(f"[STACK FULL] Cannot add: {ticket}")
21             return
22         self._stack.append(ticket)
23         print(f"[PUSHED] {ticket}")
24
25

```

CHAT

LIBRARY BOOK REQUEST SYSTEM IMPLEMENTATION

- o push(ticket)
- o pop()
- o peek()

3. Simulate at least five tickets being raised and resolved.

4. Use GitHub Copilot to suggest additional stack operations such as:

- o Checking whether the stack is empty
- o Checking whether the stack is full (if applicable)

Expected Outcome

- Functional stack-based ticket management system.
- Clear demonstration of LIFO behavior.

give code in python without comments

✓ Created AAC 11.5.py

✓ Created AAC 11.5.py

✓ Tried to run command but was blocked

✓ Ran pylanceRunCodeSnippet - pylance mcp server (MCP Server)

✓ Summarized results for the user

Code saved to [AAC 11.5.py](c:\Users\shash\Downloads\AAC 11.5.py) and verified working. Here's what it demonstrates:

Classes:

- SupportTicket — holds ticket ID, requester, issue description, and priority
- HelpDeskStack — list-based stack with MAX_SIZE = 10

+ AAC 11.4.py

Describe what to build next

Claude Sonnet 4.6

Welcome
AAC 11.4.py X
C:\> Users > shash > Downloads > AAC 11.4.py > ...
12 class HelpDeskStack:
13 def __init__(self):
14 self._stack = []
15 self._size = 0
16 self._max_size = 10
17
18 def push(self, ticket):
19 if self.is_full():
20 print("Stack is full. Cannot push ticket.")
21 return
22 self._stack.append(ticket)
23 print(f"[PUSHED] {ticket}")
24
25 def pop(self):
26 if self.is_empty():
27 print("[STACK EMPTY] No tickets to resolve.")
28 return None
29 ticket = self._stack.pop()
30 print(f"[RESOLVED] {ticket}")
31 return ticket
32
33 def peek(self):
34 if self.is_empty():
35 print("[STACK EMPTY] No tickets in stack.")
36 return None
37 ticket = self._stack[-1]
38 print(f"[PEEK] Next to resolve: {ticket}")
39 return ticket
40
41 def is_empty(self):
42 return len(self._stack) == 0
43
44 def is_full(self):

CHAT
+ - ⚙️ ... | 🔍 ✕
LIBRARY BOOK REQUEST SYSTEM IMPLEMENTATION
Created AAC 11.5.py
Tried to run command but was blocked
Ran pylanceRunCodeSnippet - pylance mcp server (MCP Server)
Summarized results for the user
Code saved to [AAC 11.5.py][c:\Users\shash\Downloads\AAC 11.5.py] and verified working. Here's what it demonstrates:
Classes:
SupportTicket — holds ticket ID, requester, issue description, and priority
HelpDeskStack — list-based stack with MAX_SIZE = 10
Operations implemented:
MethodDescription
push(ticket)Adds ticket to top of stack
pop()Removes and resolves ticket from top (LIFO)
peek()Views top ticket without removing it
is_empty()Returns True if no tickets
is_full()Returns True if at MAX_SIZE
size()Returns current ticket count
display()Shows all tickets top-to-bottom
AAC 11.4.py
Describe what to build next
Claude Sonnet 4.6

```

Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ...
12 class HelpDeskStack:
40
41     def is_empty(self):
42         return len(self._stack) == 0
43
44     def is_full(self):
45         return len(self._stack) >= self.MAX_SIZE
46
47     def size(self):
48         return len(self._stack)
49
50     def display(self):
51         if self.is_empty():
52             print("[STACK] Stack is empty.")
53         else:
54             print(f"[STACK] Current tickets (top = most recent, total={self.size}):")
55             for ticket in reversed(self._stack):
56                 print(f"    {ticket}")
57
58
59 print("=" * 60)
60 print("      SR UNIVERSITY IT HELP DESK - TICKET SYSTEM")
61 print("=" * 60)

```

```

Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ...
58
59 print("=" * 60)
60 print("      SR UNIVERSITY IT HELP DESK - TICKET SYSTEM")
61 print("=" * 60)
62
63 help_desk = HelpDeskStack()
64
65 print("\n--- Raising Support Tickets ---")
66 help_desk.push(SupportTicket(101, "Alice (Student)", "Cannot access Wi-Fi", "normal"))
67 help_desk.push(SupportTicket(102, "Bob (Staff)", "Projector not working in Lab3", "high"))
68 help_desk.push(SupportTicket(103, "Carol (Student)", "Email login failure", "normal"))
69 help_desk.push(SupportTicket(104, "Dr. Smith (Staff)", "VPN disconnecting repeatedly", "critical"))
70 help_desk.push(SupportTicket(105, "Eve (Student)", "Printer offline in Library", "normal"))
71
72 print()
73 help_desk.display()
74
75 print(f"\n[INFO] Stack empty? {help_desk.is_empty()}")
76 print(f"[INFO] Stack full? {help_desk.is_full()}")
77 print(f"[INFO] Total tickets in stack: {help_desk.size()}")
78
79 print("\n--- Peeking at top ticket ---")
80 help_desk.peek()
81

```

```
C: > Users > shash > Downloads > AAC 11.4.py > ...
72 print()
73 help_desk.display()
74
75 print(f"\n[INFO] Stack empty? {help_desk.is_empty()}")
76 print(f"[INFO] Stack full? {help_desk.is_full()}")
77 print(f"[INFO] Total tickets in stack: {help_desk.size()}")
78
79 print("\n--- Peeking at top ticket ---")
80 help_desk.peak()
81
82 print("\n--- Resolving Tickets (LIFO Order) ---")
83 while not help_desk.is_empty():
84     help_desk.pop()
85
86 print()
87 print(f"[INFO] Stack empty after resolving all? {help_desk.is_empty()}")
88 help_desk.pop()
89
```

Task 4: Hash Table

Objective

To implement a **Hash Table** and understand collision handling.

Task Description

Use AI to generate a hash table with:

- Insert
- Search
- Delete

Starter Code

```
class HashTable:
    pass
```

Expected Outcome

- Collision handling using chaining
- Well-commented methods

```
Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ...
1 class HashTable:
2     def __init__(self, capacity=16):
3         self.capacity = capacity
4         self.size = 0
5         self.buckets = [[] for _ in range(self.capacity)]
6
7     def _hash(self, key):
8         return hash(key) % self.capacity
9
10    def insert(self, key, value):
11        index = self._hash(key)
12        bucket = self.buckets[index]
13        for i, (k, v) in enumerate(bucket):
14            if k == key:
15                bucket[i] = (key, value)
16                return
17        bucket.append((key, value))
18        self.size += 1
19
20    def search(self, key):
21        index = self._hash(key)
22        bucket = self.buckets[index]
23        for k, v in bucket:
24            if k == key:
```

```
Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ...
1 class HashTable:
20    def search(self, key):
21        index = self._hash(key)
22        bucket = self.buckets[index]
23        for k, v in bucket:
24            if k == key:
25                return v
26        return None
27
28    def delete(self, key):
29        index = self._hash(key)
30        bucket = self.buckets[index]
31        for i, (k, v) in enumerate(bucket):
32            if k == key:
33                del bucket[i]
34                self.size -= 1
35                return True
36        return False
37
38    def load_factor(self):
39        return self.size / self.capacity
40
41    def display(self):
42        print(f"[HASH TABLE] capacity={self.capacity}, entries={self.size}, load_factor={self.load_factor()}")
43        for i, bucket in enumerate(self.buckets):
44            if bucket:
```

```
Welcome AAC 11.4.py X
C: > Users > shash > Downloads > AAC 11.4.py > ...
1 class HashTable:
41    def display(self):
42        print(f"[HASH TABLE] capacity={self.capacity}, entries={self.size}, load_factor={self.load_factor()}")
43        for i, bucket in enumerate(self.buckets):
44            if bucket:
45                chain = " -> ".join(f"{k}: {v}" for k, v in bucket)
46                print(f"Bucket[{i:2}]: {chain}")
47
48
49 print("=" * 55)
50 print("      HASH TABLE WITH CHAINING DEMO")
51 print("=" * 55)
52
53 ht = HashTable(capacity=7)
54
55 print("\n--- Inserting entries ---")
56 entries = [
57     ("alice", "alice@sru.edu"),
58     ("bob", "bob@sru.edu"),
59     ("carol", "carol@sru.edu"),
60     ("dave", "dave@sru.edu"),
61     ("eve", "eve@sru.edu"),
62     ("frank", "frank@sru.edu"),
63 ]
```

CHAT

+ v ⚙ ⋮ | [] x

← LIBRARY BOOK REQUEST SYSTEM IMPLEMENTATION []

✓ Ran `pylanceRunCodeSnippet` - pylance mcp server (MCP Server)

✓ Reviewed output for the user

Code saved to `[AAC 11.6.py](c:\Users\shash\Downloads\AAC 11.6.py)` and verified working. Here's a summary:

Methods implemented:

Method	Description
<code>insert(key, value)</code>	Inserts or updates a key-value pair
<code>search(key)</code>	Returns value for key, or <code>None</code> if missing
<code>delete(key)</code>	Removes entry, returns <code>True / False</code>
<code>load_factor()</code>	Returns <code>size / capacity</code> ratio
<code>display()</code>	Prints all non-empty buckets with chains

Collision handling — chaining: With capacity `7` and 10 entries, collisions are visible in the output:

- `Bucket[4]`: `alice` → `carol` → `grace` → `heidi` (4-way chain)
- `Bucket[5]`: `bob` → `frank` → `ivan` (3-way chain)
- `Bucket[3]`: `eve` → `judy` (2-way chain)

Each bucket holds a list of `(key, value)` pairs; on collision, new entries are simply appended to the chain. On search/delete, the chain is walked linearly until the key matches.

🔄 ↺ 📄 🔗

🔗 + AAC 11.4.py

🌐

Describe what to build next

🖥 v 🔍 v Claude Sonnet 4.6 v 🗨

➤

```
C: > Users > shash > Downloads > AAC 11.4.py > ...
58     ("bob", "bob@sru.edu"),
59     ("carol", "carol@sru.edu"),
60     ("dave", "dave@sru.edu"),
61     ("eve", "eve@sru.edu"),
62     ("frank", "frank@sru.edu"),
63     ("grace", "grace@sru.edu"),
64     ("heidi", "heidi@sru.edu"),
65     ("ivan", "ivan@sru.edu"),
66     ("judy", "judy@sru.edu"),
67 ]
68 for key, value in entries:
69     ht.insert(key, value)
70     print(f" [INSERT] key='{key}' -> '{value}'")
71
72 ht.display()
73
74 print("\n--- Searching entries ---")
75 for key in ["alice", "eve", "judy", "unknown"]:
76     result = ht.search(key)
77     if result:
78         print(f" [FOUND] key='{key}' -> '{result}'")
79     else:
80         print(f" [MISSING] key='{key}' not found")
81
```

```

C:\> Users > shash > Downloads > AAC 11.4.py > ...
74 print(f" [SEARCHING] key='{key}' -> '{result}'")
75 for key in ["alice", "eve", "judy", "unknown"]:
76     result = ht.search(key)
77     if result:
78         print(f" [FOUND] key='{key}' -> '{result}'")
79     else:
80         print(f" [MISSING] key='{key}' not found")
81
82 print("\n--- Updating an existing key ---")
83 ht.insert("alice", "alice.new@sru.edu")
84 print(f" [UPDATE] key='alice' -> '{ht.search('alice')}'")
85
86 print("\n--- Deleting entries ---")
87 for key in ["bob", "grace", "nonexistent"]:
88     success = ht.delete(key)
89     status = "DELETED" if success else "NOT FOUND"
90     print(f" [{status}] key='{key}'")
91
92 ht.display()
93

```

Task 5: Real-Time Application Challenge

Scenario

Design a **Campus Resource Management System** with the following features:

- Student Attendance Tracking
- Event Registration System
- Library Book Borrowing
- Bus Scheduling System
- Cafeteria Order Queue

Student Tasks

1. Choose the most appropriate data structure for each feature.
2. Justify your choice in **2–3 sentences**.
3. Implement **one selected feature** using AI-assisted code generation.


Expected Outcome

- Mapping table: Feature → Data Structure → Justification
- One fully working Python implementation

```

Welcome AAC 11.4.py AAC 11.7.py X
C:\> Users > shash > Downloads > AAC 11.7.py > ...
1 from collections import deque
2 import heapq
3 from datetime import datetime
4
5 print("MAPPING: Feature -> Data Structure -> Justification")
6 print("-" * 60)
7 print("Attendance -> Dictionary -> O(1) lookup by student ID")
8 print("Event Reg -> Set+Dictionary -> Deduplication + fast access")
9 print("Book Borrow -> Queue (FIFO) -> Serve requests in order")
10 print("Bus Schedule -> Priority Queue -> Earliest departure first")
11 print("Cafeteria -> Queue (FIFO) -> Orders prepared in sequence")
12
13 print("\n-- 1. Attendance (Dictionary) --")
14 attendance = {}
15 for sid, name, status in [("S001", "Alice", "present"), ("S002", "Bob", "absent"), ("S003", "Carol", "present"), ("S004", "David", "absent")]:
16     attendance.setdefault("2026-02-19", {})[sid] = (name, status)
17     print(f" {sid} {name} -> {status}")
18 print("Report:", [sid: s for sid, (n, s) in attendance["2026-02-19"].items()])
19
20 print("\n-- 2. Event Registration (Set + Dict) --")
21 events = {"Tech Fest 2026": {"attendees": set(), "capacity": 5}}
22 for sid in ["S001", "S002", "S003", "S004", "S005", "S006"]:
23     e = events["Tech Fest 2026"]
24     if sid in e["attendees"]: print(f" DUPLICATE: {sid}")

```



```
Welcome AAC 11.4.py AAC 11.7.py X
C: > Users > shash > Downloads > AAC 11.7.py > ...
17 print(f" {sid} {name} -> {status}")
18 print("Report:", {sid: s for sid, (n, s) in attendance["2026-02-19"].items()})
19
20 print("\n-- 2. Event Registration (Set + Dict) --")
21 events = {"Tech Fest 2026": {"attendees": set(), "capacity": 5}}
22 for sid in ["S001", "S002", "S003", "S002", "S004", "S005", "S006"]:
23     e = events["Tech Fest 2026"]
24     if sid in e["attendees"]: print(f" DUPLICATE: {sid}")
25     elif len(e["attendees"]) >= e["capacity"]: print(f" FULL: {sid} rejected")
26     else: e["attendees"].add(sid); print(f" Registered: {sid}")
27 print("Attendees:", sorted(events["Tech Fest 2026"]["attendees"]))
28
29 print("\n-- 3. Library Borrow (Queue) --")
30 bq = deque([("S001", "Data Structures"), ("S003", "Operating Systems"), ("S005", "Computer Networks"), ("S002", "Data
31 while bq:
32     sid, book = bq.popleft()
33     print(f" Issued '{book}' to {sid}")
34
35 print("\n-- 4. Bus Scheduling (Priority Queue) --")
36 buses, ctr = [], 0
37 for route, t in [("City", "07:30"), ("Airport", "09:00"), ("Mall", "08:15"), ("Station", "07:00"), ("Hospital", "10:30")
38     heapq.heappush(buses, (datetime.strptime(t, "%H:%M"), ctr, route)); ctr += 1
39 while buses:
40     (t, c, route) = heapq.heappop(buses)
```



```
Welcome AAC 11.4.py AAC 11.7.py X
C:\Users\shash>Downloads>AAC 11.7.py>...
33 print(f" Issued '{book}' to {sid}")
34
35 print("\n-- 4. Bus Scheduling (Priority Queue) --")
36 buses, ctr = [], 0
37 for route, t in [("City", "07:30"), ("Airport", "09:00"), ("Mall", "08:15"), ("Station", "07:00"), ("Hospital", "10:30")
38 | heapq.heappush(buses, (datetime.strptime(t, "%H:%M"), ctr, route)); ctr += 1
39 while buses:
40     dt, _, r = heapq.heappop(buses)
41     print(f" Dispatch: {r} at {dt.strftime('%H:%M')}")
42
43 print("\n-- 5. Cafeteria Orders (Queue) --")
44 oq = deque(enumerate(["Alice:Burger", "Bob:Pasta", "Carol:Sandwich", "Dave:Rice", "Eve:Noodles"], 1))
45 while oq:
46     num, entry = oq.popleft()
47     name, item = entry.split(":")
48     print(f" Order #{num} ready: {item} for {name}")
49
```

Note: Report should be submitted as a word document for all tasks in a single document with prompts, comments & code explanation, and output and if required, screenshots.