

ASSIGNMENT_2.3

2303A51512

Batch-26

Assignment Number:1.3(Present assignment number)/24(Total number of assignments)		
Q.No.	Question	Expected Time to complete
1	Lab 2: Exploring Additional AI Coding Tools beyond Copilot – Gemini (Colab) and Cursor AI Lab Objectives: ❖ To explore and evaluate the functionality of Google Gemini for AI-assisted coding within Google Colab. ❖ To understand and use Cursor AI for code generation, explanation, and refactoring. ❖ To compare outputs and usability between Gemini, GitHub Copilot, and Cursor AI. ❖ To perform code optimization and documentation using AI tools. Lab Outcomes (LOs): After completing this lab, students will be able to: ❖ Generate Python code using Google Gemini in Google Colab. ❖ Analyze the effectiveness of code explanations and suggestions by Gemini. ❖ Set up and use Cursor AI for AI-powered coding assistance. ❖ Evaluate and refactor code using Cursor AI features. ❖ Compare AI tool behavior and code quality across different platforms. Task 1: Word Frequency from Text File ❖ Scenario: You are analyzing log files for keyword frequency. ❖ Task: Use Gemini to generate Python code that reads a text file and counts word frequency, then explains the code. ❖ Expected Output: ➤ Working code ➤ Explanation ➤ Screenshot	Week1 - Monday

Prompt:

A by analyzing log files for keyword frequency ,generate python code that reads a text file and counts word frequency

Code:

```
[1]
✓ Os  import collections
import re

# Create a sample text file for demonstration
file_content = """
This is a sample text file.
It contains some words, and some words are repeated.
We will count the frequency of each word in this file.
"""

with open('sample_log.txt', 'w') as f:
    f.write(file_content)

print("Sample file 'sample_log.txt' created.")
```

... Sample file 'sample_log.txt' created.

```
[2]
✓ Os # Function to read a file and count word frequency
def count_word_frequency(filepath):
    try:
        with open(filepath, 'r', encoding='utf-8') as file:
            text = file.read()
```

```
    try:
        with open(filepath, 'r', encoding='utf-8') as file:
            text = file.read()

        # Convert text to lowercase and remove punctuation
        text = text.lower()
        words = re.findall(r'\b\w+\b', text) # Extracts words, ignoring punctuation

        # Count word frequency using collections.Counter
        word_counts = collections.Counter(words)

        return word_counts
    except FileNotFoundError:
        return f"Error: File not found at {filepath}"
    except Exception as e:
        return f"An error occurred: {e}"

# Specify the path to your log file
log_file_path = 'sample_log.txt'

# Get word frequencies
frequencies = count_word_frequency(log_file_path)

# Display the results
if isinstance(frequencies, dict):
    print("\nWord Frequencies:")
    for word, count in frequencies.most_common(10): # Display top 10 most common words
        print(f"{word}: {count}")
elif isinstance(frequencies, str):
    print(frequencies)
```

```
[2] ✓ 0s for word, count in frequencies.most_common(10): # Display top 10 most common words
        print(f'{word}: {count}')
    elif isinstance(frequencies, str):
        print(frequencies)

...
Word Frequencies:
'this': 2
'file': 2
'some': 2
'words': 2
'is': 1
'a': 1
'sample': 1
'text': 1
'it': 1
'contains': 1
```

Explanation:

This Python program first creates a sample text file and writes some text into it, then defines a function that reads the file, converts all text to lowercase, removes punctuation, and splits the text into individual words using regular expressions. It uses `collections.Counter` to count how many times each word appears in the file, ensuring that words with different cases are treated as the same. The program also includes error handling to manage cases where the file is missing or another error occurs. After reading the file, it displays the top 10 most frequently occurring words along with their counts, making it a simple and effective way to analyze word frequency in a text file.

Task 2: File Operations Using Cursor AI

❖ Scenario:

You are automating basic file operations.

❖ Task:

Use Cursor AI to generate a program that:

- Creates a text file
- Writes sample text
- Reads and displays the content

❖ Expected Output:

- Functional code
- Cursor AI screenshots

Prompt:

A Write a Python program that creates a text file, writes some sample text into it, then reads the file and prints its contents. The code should be simple and easy to understand.

Code:

```
[3]
✓ Os
# Define the filename and some sample text
file_name = "my_sample_file.txt"
sample_text = "Hello, this is a sample text file.\nIt contains two lines of text.\nThis is the third li

# Step 1: Create the file and write the sample text into it
with open(file_name, 'w') as file:
    file.write(sample_text)

print(f"File '{file_name}' created successfully with sample text.")

File 'my_sample_file.txt' created successfully with sample text.

[4]
✓ Os
# Step 2: Read the contents of the file
print(f"\nReading contents from '{file_name}':")
with open(file_name, 'r') as file:
    file_contents = file.read()

# Step 3: Print the contents
print(file_contents)

Reading contents from 'my_sample file.txt':
Hello, this is a sample text file.
It contains two lines of text.
This is the third line.
```

Explanation:

This Python code first defines a file name and sample text, then creates a text file and writes the sample text into it using write mode, automatically closing the file after writing. It prints a message to confirm that the file was created successfully. Next, the code opens the same file in read mode, reads all its contents, and finally prints the text to the screen, demonstrating simple file creation, writing, and reading operations in one program.

Task 3: CSV Data Analysis

❖ Scenario:

You are processing structured data from a CSV file.

❖ Task:

Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

❖ Expected Output:

- Correct output
- Screenshot

Prompt:

A write Python code that reads a CSV file using the pandas library, displays the first few rows of the dataset, and calculates the mean, minimum, and maximum values for all numerical columns. Assume that the CSV file is already uploaded to Colab with the name data.csv. The code should clearly print the calculated statistics with proper labels. After executing the code, ensure that both the code and the correct output showing the mean, min, and max values are visible, and take a screenshot of the Colab notebook displaying these results.

Code:

```
import pandas as pd
import numpy as np
import os

# 1. Create a dummy CSV file for demonstration
csv_file_name = 'sample_data.csv'

data = {
    'Name': ['Alice', 'Bob', 'Charlie', 'David', 'Eve'],
    'Age': [24, 27, 22, 32, 29],
    'Score': [85, 91, 78, 95, 88],
    'City': ['NY', 'LA', 'CHI', 'NY', 'LA']
}
df_dummy = pd.DataFrame(data)
df_dummy.to_csv(csv_file_name, index=False)

print(f"Created '{csv_file_name}' with sample data:")
print(df_dummy.head())
```

*** Created 'sample_data.csv' with sample data:

	Name	Age	Score	City
0	Alice	24	85	NY
1	Bob	27	91	LA
2	Charlie	22	78	CHI
3	David	32	95	NY
4	Eve	29	88	LA

```
import pandas as pd

# 2. Read the CSV file
csv_file_name = 'sample_data.csv' # Make sure this matches the file you created or have
try:
    df = pd.read_csv(csv_file_name)
    print(f"\nSuccessfully read '{csv_file_name}'. First 5 rows:\n")
    display(df.head())

    # 3. Pick a numeric column for calculations (e.g., 'Score')
    numeric_column_name = 'Score' # You can change this to 'Age' or another numeric column

    if numeric_column_name in df.columns and pd.api.types.is_numeric_dtype(df[numeric_column_name]):
        # 4. Calculate mean, minimum, and maximum
        mean_value = df[numeric_column_name].mean()
        min_value = df[numeric_column_name].min()
        max_value = df[numeric_column_name].max()

        # 5. Print the results clearly
        print(f"\nStatistics for column '{numeric_column_name}':")
        print(f"  Mean: {mean_value:.2f}")
        print(f"  Minimum: {min_value}")
        print(f"  Maximum: {max_value}")

    else:
        print(f"Error: Column '{numeric_column_name}' not found or is not numeric.")

except FileNotFoundError:
    print(f"Error: The file '{csv_file_name}' was not found. Please make sure it exists.")
except Exception as e:
    print(f"An error occurred: {e}")
```

```
***  
Successfully read 'sample_data.csv'. First 5 rows:
```

	Name	Age	Score	City
0	Alice	24	85	NY
1	Bob	27	91	LA
2	Charlie	22	78	CHI
3	David	32	95	NY
4	Eve	29	88	LA

```
Statistics for column 'Score':  
Mean: 87.40  
Minimum: 78  
Maximum: 95
```

Explanation :

This code reads a CSV file, shows the first few rows, then checks if a chosen column (like “Score”) is numeric. If it is, it calculates the mean, minimum, and maximum values and prints them. If the file is missing or the column isn’t valid, it shows an error message instead.

Task 4: Sorting Lists – Manual vs Built-in

❖ Scenario:

You are reviewing algorithm choices for efficiency.

❖ Task:

Use **Gemini** to generate:

- Bubble sort
- Python’s built-in sort()
- Compare both implementations.

❖ Expected Output:

- Two versions of code
- Short comparison

Prompt:

Write Python code to implement bubble sort and also use the built-in sort() function, then compare their efficiency

Great! I've put together a plan to implement both bubble sort and Python's

Code:

```

def bubble_sort(arr):
    """
    Implements the Bubble Sort algorithm to sort a list in ascending order.
    The list is sorted in-place.
    """
    n = len(arr)
    # Traverse through all array elements
    for i in range(n - 1):
        # Last i elements are already in place
        for j in range(n - 1 - i):
            # Traverse the array from 0 to n-i-1
            # Swap if the element found is greater than the next element
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
    return arr

# Example usage:
my_list = [64, 34, 25, 12, 22, 11, 90]
print(f"Original list: {my_list}")

sorted_list = bubble_sort(my_list)
print(f"Sorted list: {sorted_list}")

my_list_2 = [5, 1, 4, 2, 8]
print(f"Original list 2: {my_list_2}")
sorted_list_2 = bubble_sort(my_list_2)
print(f"Sorted list 2: {sorted_list_2}")

```

Original list: [64, 34, 25, 12, 22, 11, 90]
 Sorted list: [11, 12, 22, 25, 34, 64, 90]
 Original list 2: [5, 1, 4, 2, 8]
 Sorted list 2: [1, 2, 4, 5, 8]

```

def bubble_sort(arr):
    """
    Implements the Bubble Sort algorithm to sort a list in ascending order.
    The list is sorted in-place.
    """
    n = len(arr)
    # Outer loop: iterate from n-1 down to 1
    # 'i' represents the last index of the unsorted portion
    for i in range(n - 1, 0, -1):
        # Inner loop: iterate from 0 up to i-1
        # 'j' goes through the unsorted part, comparing adjacent elements
        for j in range(i):
            # Swap if the element found is greater than the next element
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
    return arr

# Example usage:
my_list = [64, 34, 25, 12, 22, 11, 90]
print(f"Original list: {my_list}")

sorted_list = bubble_sort(my_list)
print(f"Sorted list: {sorted_list}")

my_list_2 = [5, 1, 4, 2, 8]
print(f"Original list 2: {my_list_2}")
sorted_list_2 = bubble_sort(my_list_2)
print(f"Sorted list 2: {sorted_list_2}")

... Original list: [64, 34, 25, 12, 22, 11, 90]
Sorted list: [11, 12, 22, 25, 34, 64, 90]
Original list 2: [5, 1, 4, 2, 8]
Sorted list 2: [1, 2, 4, 5, 8]

```



```

import random

# 1. Create a sample list of unsorted numbers
original_list = [random.randint(1, 100) for _ in range(10)]
print(f"Original list: {original_list}")

# 2. Create a copy of this list, as list.sort() sorts in-place
sorted_list = original_list.copy()

# 3. Apply the sort() method directly to the copied list to sort it in ascending order
sorted_list.sort()

# 4. Print both the original and the sorted list to demonstrate the effect of the built-in sort
print(f"Sorted list (using list.sort()): {sorted_list}")

--- Original list: [42, 67, 2, 8, 38, 3, 40, 70, 98, 44]
    Sorted list (using list.sort()): [2, 3, 8, 38, 40, 42, 44, 67, 70, 98]

```

```

import random

# 1. Define the desired number of elements for the test list
list_size = 5000 # You can change this to 1000, 5000, 10000, etc.

# 2. Populate 'test_data' with 'list_size' random integers
# Using random.randint(1, 10000) to generate numbers within a reasonable range
test_data = [random.randint(1, 10000) for _ in range(list_size)]

# 3. Print the first few elements and the length of the generated list to verify
print(f"Generated a list of {len(test_data)} random integers.")
print(f"First 10 elements: {test_data[:10]}...")

--- Generated a list of 5000 random integers.
    First 10 elements: [617, 9925, 7006, 1656, 8090, 6684, 3950, 3242, 111, 2825]...

import time

# 1. Create a copy of the test_data list for bubble sort
bubble_sort_data = test_data.copy()

# 2. Measure execution time for Bubble Sort
start_time_bubble = time.time()
bubble_sort(bubble_sort_data)
end_time_bubble = time.time()
time_taken_bubble = end_time_bubble - start_time_bubble

# 3. Create another copy of the test_data list for built-in sort
builtin_sort_data = test_data.copy()

# 4. Measure execution time for built-in list.sort()
start_time_builtin = time.time()
builtin_sort_data.sort()
end_time_builtin = time.time()
time_taken_builtin = end_time_builtin - start_time_builtin

# 5. Print the comparison results
print(f"Comparison of Sorting Algorithms Performance (List Size: {list_size})")
print("-----")
print(f"Bubble Sort execution time: {time_taken_bubble:.6f} seconds")
print(f"Built-in sort() execution time: {time_taken_builtin:.6f} seconds")
print("-----")

if time_taken_bubble > time_taken_builtin:
    print(f"The built-in sort() was approximately {time_taken_bubble / time_taken_builtin:.2f} times faster than Bubble Sort.")
elif time_taken_builtin > time_taken_bubble:
    print(f"Bubble Sort was approximately {time_taken_builtin / time_taken_bubble:.2f} times faster than the built-in sort() (Highly unlikely for large lists).")
else:
    print("Both algorithms took approximately the same amount of time.")

```

Explanation :

This code measures how long Bubble Sort and Python's built-in sort() take on the same list, then prints the times and shows which method was faster. Bubble Sort is usually much slower because it's $O(n^2)$, while the built-in sort is optimized at $O(n \log n)$.