

ASSIGNMENT-3.4

Name: k.manjula

H NO:2303A51857

BATCH-13

Task 1: Zero-shot Prompt – Fibonacci Series Generator

Task Description #1

- Without giving an example, write a single comment prompt asking GitHub Copilot to generate a Python function to print the first N Fibonacci numbers.

Expected Output #1

- A complete Python function generated by Copilot without any example provided.
- Correct output for sample input N = 7 → 0 1 1 2 3 5 8
- Observation on how Copilot understood the instruction with zero context.

PROMPT:

#Generate a Python function that takes an integer N as input and prints the first N Fibonacci numbers in order.

CODE:

```
#generate a Python function that takes a.py / fibonacci
1 #Generate a Python function that takes an integer N as input and prints the first N Fibonacci numbers in order.
2 def fibonacci():
3     n = int(input("Enter N: "))
4     a, b = 0, 1
5     for _ in range(n):
6         print(a, end=" ")
7         a, b = b, a + b
8     fibonacci()
9
10
```

OUTPUT:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#generate a Python function tha
t takes a.py"
Enter N: 10
0 1 1 2 3 5 8 13 21 34
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#generate a Python function tha
t takes a.py"
Enter N: 12
0 1 1 2 3 5 8 13 21 34 55 89
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#generate a Python function tha
t takes a.py"
Enter N: 7
0 1 1 2 3 5 8
PS C:\Users\neera\OneDrive\Desktop\assignments>
```

JUSTIFICATION:

Observation :

Copilot correctly understood the instruction without any examples by:

- Recognizing the term *Fibonacci series*
- Identifying that the function should generate values iteratively
- Printing the sequence starting from 0
- Handling the input N as the number of terms

This shows that Copilot can infer logic and structure accurately even with minimal context, which is the essence of zero-shot prompting.

Task 2: One-shot Prompt – List Reversal Function

Task Description #2

- Write a comment prompt to reverse a list and provide one example below the comment to guide Copilot.

Expected Output #2

- Copilot-generated function to reverse a list using slicing or loop.
- Output: [3, 2, 1] for input [1, 2, 3]
- Observation on how adding a single example improved Copilot's accuracy.

PROMPT:

Write a Python function that reverses a given list.

Example: input [1, 2, 3] → output [3, 2, 1]

CODE:

```
# Write a Python function that reverses a given list.
# Example: input [1, 2, 3] → output [3, 2, 1]
def reverse_list(input_list):
    reversed_list = []
    for item in input_list:
        reversed_list.insert(0, item)
    return reversed_list
# Example usage:
print(reverse_list([1, 2, 3])) # Output: [3, 2, 1]
```

OUTPUT:

```
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#generate a Python function tha
t takes a.py"
[3, 2, 1]
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#generate a Python function tha
t takes a.py"
```

JUSTIFICATION:

Providing a single example helped Copilot clearly understand:

- The expected input and output format
- That the list order must be fully reversed
- The most efficient approach using slicing

The one-shot example reduced ambiguity and improved accuracy compared to zero-shot prompting.

Task 3: Few-shot Prompt – String Pattern Matching

Task Description #3

- Write a comment with 2–3 examples to help Copilot understand how to check if a string starts with a capital letter and ends with a period.

Expected Output #3

- A function `is_valid()` that checks the pattern.
- Output: True or False based on input.
- Students reflect on how multiple examples guide Copilot to generate more accurate code.

PROMPT:


```
# Write a Python function is_valid(text) that returns True if a string
# starts with a capital letter and ends with a period, otherwise False.

# Example: "Hello." → True
# Example: "hello." → False
# Example: "Hello" → False
```

CODE:

```
# Write a Python function is_valid(text).py > ...
1 # Write a Python function is_valid(text) that returns True if a string
2 # starts with a capital letter and ends with a period, otherwise False.
3 # Example: "Hello." → True
4 # Example: "hello." → False
5 # Example: "Hello" → False
6 def is_valid(text):
7     if len(text) == 0:
8         return False
9     return text[0].isupper() and text[-1] == '.'
10
11 # Example usages:
12 print(is_valid("Hello.")) # True
13 print(is_valid("hello.")) # False
14 print(is_valid("Hello")) # False
15
```

OUTPUT:



JUSTIFICATION:

Providing multiple examples helped Copilot clearly identify:

- The importance of the first character being uppercase
- The requirement of a period at the end
- The exact conditions for True and False outputs

Few-shot prompting reduces misunderstanding and leads to more precise and reliable code generation.

Task 4: Zero-shot vs Few-shot – Email Validator

Task Description #4

- First, prompt Copilot to write an email validation function using zero-shot (just the task in comment).
- Then, rewrite the prompt using few-shot examples.

Expected Output #4

- Compare both outputs:

Zero-shot may result in basic or generic validation.

Few-shot gives detailed and specific logic (e.g., @ and domain checking).

- Submit both code versions and note how few-shot improves reliability.

Zero-shot

PROMPT:

Write a Python function that checks whether an email address is valid and returns True or False.

CODE:

```
# Write a Python function that checks whether an email address is valid and returns True or False.
def is_valid_email(email):
    if "@" not in email:
        return False
    username, domain = email.split("@", 1)
    if username == "":
        return False
    if "." not in domain or domain.startswith("."):
        return False
    return True
email = input("Enter email address: ")
print(is_valid_email(email))
```

OUTPUT:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS

Enter email address: reddy@gmail.com
True
PS C:\Users\neera\OneDrive\Desktop\assignments>
```

Few-shot

PROMPT

Write a Python function that checks whether an email address is valid and returns True or False.

Example: "user@gmail.com" → True

Example: "user@gmail" → False

Example: "user@.com" → False

CODE

```
# Write a Python function that checks whether an email address is valid and returns True or False.
# Example: "user@gmail.com" → True
# Example: "user@gmail" → False
# Example: "user@.com" → False

def is_valid_email(email):
    if "@" not in email:
        return False
    username, domain = email.split("@", 1)
    if username == "":
        return False
    if "." not in domain or domain.startswith("."):
        return False
    return True

# Example usages:
print(is_valid_email("user@gmail.com"))
print(is_valid_email("user@gmail"))
print(is_valid_email("user@.com"))
```

OUTPUT

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS

+ FullyQualifiedErrorId : CommandNotFoundException

PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/# Write a Python function that checks wh.py"
True
False
False
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/# Write a Python function that
```

JUSTIFICATION:

Zero-shot prompting provides only the task description, so Copilot generates a simple and generic email validation logic. This approach may miss several invalid cases. In few-shot prompting, example inputs and outputs are given along with the task. These examples help

Copilot understand the validation rules more clearly. As a result, few-shot prompting produces more accurate and reliable code than zero-shot prompting.

Task 5: Prompt Tuning – Summing Digits of a Number

Task Description #5

- Experiment with 2 different prompt styles to generate a function that returns the sum of digits of a number.

Style 1: Generic task prompt

Style 2: Task + Input/Output example

Expected Output #5

- Two versions of the `sum_of_digits()` function.
- Example Output: `sum_of_digits(123) → 6`
- Short analysis: which prompt produced cleaner or more optimized code and why?

#Style 1: Generic task prompt

PROMPT

#Write a Python function that returns the sum of digits of a number.

CODE

```
#Write a Python function to check whether a number is prime or not.
1  ## Write a Python function that returns the sum of digits of a number.
2  def sum_of_digits(n):
3      if n < 0:
4          n = -n # Make sure to handle negative numbers
5          total = 0
6          while n > 0:
7              digit = n % 10
8              total += digit
9              n //= 10
10         return total
11 n=int(input("Enter a number: "))
12 print("Sum of digits:", sum_of_digits(n))
13
```

OUTPUT

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS
Enter a number: 123
Sum of digits: 6
PS C:\Users\neera\OneDrive\Desktop\assignments>
```

Style 2: Task + Input/Output example

PROMPT


Write a Python function that returns the sum of digits of a number.

Example: `sum_of_digits(123) → 6`

CODE

```
# Write a Python function that returns the sum of digits of a number.
# Example: sum_of_digits(123) → 6
def sum_of_digits(n):
    if n < 0:
        n = -n # Make sure to handle negative numbers
    total = 0
    while n > 0:
        digit = n % 10
        total += digit
        n //= 10
    return total
# Example usages:
print(sum_of_digits(123)) # Output: 6
print(sum_of_digits(-456)) # Output: 15
print(sum_of_digits(0)) # Output: 0
print(sum_of_digits(7890)) # Output: 24
```

OUTPUT



```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#Write a Python function to che
ck whe the.py"
6
15
0
24
PS C:\Users\neera\OneDrive\Desktop\assignments> & C:/Users/neera/anaconda3/python.exe "c:/Users/neera/OneDrive/Desktop/assignments/#Write a Python function to che
```

JUSTIFICATION

The generic prompt produced a correct but longer solution using a loop.

The prompt with an example guided Copilot to generate a cleaner and more optimized one-line solution.

Providing input/output examples helps the model infer intent more clearly and produce concise, efficient code.