

Name: B. Srikar

Batch: 02

Course: AI ASSISTED CODING

Semester: Even

Task 1:

Employee Data: Create Python code that defines a class named `Employee` with the following attributes: `empid`, `empname`, `designation`, `basic_salary`, and `exp`. Implement a method `display_details()` to print all employee details. Implement another method `calculate_allowance()` to determine additional allowance based on experience:

- If `exp > 10 years` → allowance = 20% of `basic_salary`
- If `5 ≤ exp ≤ 10 years` → allowance = 10% of `basic_salary`
- If `exp < 5 years` → allowance = 5% of `basic_salary`

Finally, create at least one instance of the `Employee` class, call the `display_details()` method, and print the calculated allowance.

CODE AND OUTPUT:

```
class Employee:
    def __init__(self, empID, empName, designation, basicSalary, exp):
        self.empID = empID
        self.empName = empName
        self.designation = designation
        self.basicSalary = basicSalary
        self.exp = exp
    def display_details(self):
        print(f"Employee ID: {self.empID}")
        print(f"Employee Name: {self.empName}")
        print(f"Designation: {self.designation}")
        print(f"Basic Salary: {self.basicSalary}")
        print(f"Experience: {self.exp} years")
    def calculate_salary(self):
        if self.exp > 10:
            allowance = 0.2 * self.basicSalary
```

```
17         elif self.exp >=5:
18             allowance = 0.1 * self.basicSalary
19         else:
20             allowance = 0.05 * self.basicSalary
21         total_salary = self.basicSalary + allowance
22         print(f"Allowance: {total_salary}")
23 emp=Employee(101, "John Doe", "Software Engineer", 60000, 7)
24 emp.display_details()
25 emp.calculate_salary()
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS pwsh

Employee Name: John Doe
Designation: Software Engineer
Basic Salary: 60000
Experience: 7 years
Allowance: 66000.0

Task 2:

Electricity Bill Calculation- Create Python code that defines a class named `ElectricityBill` with attributes: `customer_id`, `name`, and `units_consumed`. Implement a method `display_details()` to print customer details, and a method `calculate_bill()` where:

- Units \leq 100 \rightarrow ₹5 per unit
- 101 to 300 units \rightarrow ₹7 per unit
- More than 300 units \rightarrow ₹10 per unit

Create a bill object, display details, and print the total bill amount.

CODE AND OUTPUT:

```
class ElectricityBill:
    def __init__(self, customer_id, name, units_consumed):
        self.customer_id = customer_id
        self.name = name
        self.units_consumed = units_consumed
    def display_details(self):
        print(f"Customer ID: {self.customer_id}")
        print(f"Customer Name: {self.name}")
        print(f"Units Consumed: {self.units_consumed}")
    def calculate_bill(self):
        if self.units_consumed <= 100:
            rate = 5
        elif self.units_consumed <= 300:
            rate = 7
        else:
            rate = 10
        total_bill = self.units_consumed * rate
        print(f"Total Bill Amount: {total_bill}")

46 bill=ElectricityBill(201, "Alice Smith", 250)
47 bill.display_details()
48 bill.calculate_bill()
49 bill2=ElectricityBill(202, "Bob Johnson", 350)
50 bill2.display_details()
51 bill2.calculate_bill()
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

```
Customer ID: 201
Customer Name: Alice Smith
Units Consumed: 250
Total Bill Amount: 1750
Customer ID: 202
Customer Name: Bob Johnson
Units Consumed: 350
Total Bill Amount: 3500
```

Task 3:

Product Discount Calculation- Create Python code that defines a class named `Product` with attributes: `product_id`, `product_name`, `price`, and `category`. Implement a method `display_details()` to print product details. Implement another method `calculate_discount()` where:

- Electronics → 10% discount
- Clothing → 15% discount
- Grocery → 5% discount

Create at least one product object, display details, and print the final price after discount.

CODE AND OUTPUT:

```
class Product:
    def __init__(self, product_id, product_name, price, category):
        self.product_id = product_id
        self.product_name = product_name
        self.price = price
        self.category = category
    def display_details(self):
        print(f"Product ID: {self.product_id}")
        print(f"Product Name: {self.product_name}")
        print(f"Price: {self.price}")
        print(f"Category: {self.category}")
    def calculate_discount(self):
        if self.category == "Electronics":
            discount = 0.1 * self.price
        elif self.category == "Clothing":
            discount = 0.15 * self.price
        elif self.category == "Groceries":
            discount = 0.05 * self.price
```

```
71         else:
72             discount = 0
73             print(f"final amount after discount: {self.price - discount}")
74 product=Product(301, "Smartphone", 50000, "Electronics")
75 product.display_details()
76 product.calculate_discount()
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS pwsh - Microsoft V

Product ID: 301
Product Name: Smartphone
Price: 50000
Category: Electronics
final amount after discount: 45000.0

Task 4:

Book Late Fee Calculation- Create Python code that defines a class named `LibraryBook` with attributes: `book_id`, `title`, `author`, `borrower`, and `days_late`. Implement a method `display_details()` to print book details, and a method `calculate_late_fee()` where:

- Days late $\leq 5 \rightarrow$ ₹5 per day
- 6 to 10 days late \rightarrow ₹7 per day
- More than 10 days late \rightarrow ₹10 per day

Create a book object, display details, and print the late fee.

CODE AND OUTPUT:

```
class LibraryBook:
    def __init__(self,book_id,title,author,borrower,days_late):
        self.book_id = book_id
        self.title = title
        self.author = author
        self.borrower = borrower
        self.days_late = days_late
    def display_details(self):
        print(f"Book ID: {self.book_id}")
        print(f"Title: {self.title}")
        print(f"Author: {self.author}")
        print(f"Borrower: {self.borrower}")
        print(f"Days Late: {self.days_late}")
    def calculate_fine(self):
        fine=0
        if self.days_late <=5:
            fine = self.days_late * 5
            elif self.days_late <=10:
                fine = (5 * 5) + (self.days_late - 5) * 7
            else:
                fine = (5 * 5) + (5 * 7) + (self.days_late - 10) * 10
        print(f"Total Fine: {fine}")
book=LibraryBook(401, "The Great Gatsby", "F. Scott Fitzgerald",
book.display_details()
book.calculate_fine()
```

PROBLEMS OUTPUT TERMINAL ... pwsh - Microsoft VS Code

Book ID: 401
Title: The Great Gatsby
Author: F. Scott Fitzgerald
Borrower: Charlie Brown
Days Late: 12
Total Fine: 80

Task 5:

Student Performance Report - Define a function

`student_report(student_data)` that accepts a dictionary containing

student names and their marks. The function should:

- Calculate the average score for each student
- Determine pass/fail status (pass ≥ 40)
- Return a summary report as a list of dictionaries

Use Copilot suggestions as you build the function and format the output.

CODE AND OUTPUT:

```
def student_report(student_data):  
    report = []  
    for student, marks in student_data.items():  
        average_score = sum(marks) / len(marks)  
        status = "Pass" if average_score >= 40 else "Fail"  
        report.append({  
            "Student": student,  
            "Average Score": average_score,  
            "Status": status  
        })  
    return report  
  
student_data = {  
    "Alice": [45, 78, 89],  
    "Bob": [23, 34, 45],  
    "Charlie": [67, 56, 78]  
}  
  
report = student_report(student_data)  
for entry in report:  
    print(entry)
```

```
{'Student': 'Alice', 'Average Score': 70.66666666666667, 'Status': 'Pass'}  
{'Student': 'Bob', 'Average Score': 34.0, 'Status': 'Fail'}  
{'Student': 'Charlie', 'Average Score': 67.0, 'Status': 'Pass'}
```

Task 6:

Taxi Fare Calculation-Create Python code that defines a class named

`TaxiRide` with attributes: `ride_id`, `driver_name`, `distance_km`, and `waiting_time_min`. Implement a method `display_details()` to print ride details, and a method `calculate_fare()` where:

- ₹15 per km for the first 10 km
- ₹12 per km for the next 20 km
- ₹10 per km above 30 km
- Waiting charge: ₹2 per minute

Create a ride object, display details, and print the total fare.

CODE AND OUTPUT:

```
class TaxiRide:
    def __init__(self,ride_id,driver_name,distance_km,waiting_time):
        self.ride_id = ride_id
        self.driver_name = driver_name
        self.distance_km = distance_km
        self.waiting_time = waiting_time
    def display_details(self):
        print(f"Ride ID: {self.ride_id}")
        print(f"Customer Name: {self.driver_name}")
        print(f"Distance (km): {self.distance_km}")
        print(f"Waiting Time (minutes): {self.waiting_time}")
    def calculate_fare(self):
        if self.distance_km <=10:
            fare = self.distance_km * 15
        elif self.distance_km <=30:
            fare = (10 * 15) + (self.distance_km - 10) * 12
        else:
            fare = (10 * 15) + (20 * 12) + (self.distance_km - 30) * 10
```

```
149         fare += self.waiting_time * 2
150         print(f"Total Fare: {fare}")
151     ride=TaxiRide(501, "David Lee", 25, 10)
152     ride.display_details()
153     ride.calculate_fare()
154     ride.print_details()

PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL    PORTS

Ride ID: 501
Customer Name: David Lee
Distance (km): 25
Waiting Time (minutes): 10
Total Fare: 350
```

Task 7:

Statistics Subject Performance - Create a Python function `statistics_subject(scores_list)` that accepts a list of 60 student scores and computes key performance statistics. The function should return the following:

- Highest score in the class
- Lowest score in the class
- Class average score
- Number of students passed (score ≥ 40)
- Number of students failed (score < 40)

Allow Copilot to assist with aggregations and logic

CODE AND OUTPUT:

```
def statistics_subject(score_list):
    if not score_list:
        return None
    average_score = sum(score_list) / len(score_list)
    highest_score = max(score_list)
    lowest_score = min(score_list)
    pass_count = sum(1 for score in score_list if score >= 40)
    fail_count = len(score_list) - pass_count
    return {
        "Average Score": average_score,
        "Highest Score": highest_score,
        "Lowest Score": lowest_score,
        "Pass Count": pass_count,
        "Fail Count": fail_count
    }

scores = [45, 78, 89, 23, 34, 67, 56, 78, 90, 12]
stats = statistics_subject(scores)
print(stats)
```

```
{'Average Score': 57.2, 'Highest Score': 90, 'Lowest Score': 12, 'Pass Count': 7, 'Fail Count': 3}
```

Task Description #8 (Transparency in Algorithm Optimization)

Task: Use AI to generate two solutions for checking prime numbers:

- Naive approach(basic)
- Optimized approach

Prompt:

“Generate Python code for two prime-checking methods and explain how the optimized version improves performance.”

Code and Output:

```
import time
def is_prime_basic(n):
    if n <= 1:
        return False
    for i in range(2, n):
        if n % i == 0:
            return False
    return True
def is_prime_optimized(n):
    if n <= 1:
        return False
    if n <= 3:
        return True
    if n % 2 == 0 or n % 3 == 0:
        return False
    i = 5
    while i * i <= n:
```

```

194     while i * i <= n:
195         if n % i == 0 or n % (i + 2) == 0:
196             return False
197         i += 6
198     return True
199 st = time.time()
200 print(is_prime_basic(29))           # True
201 et = time.time()
202 print(f"Basic method took {et - st} seconds")
203 st = time.time()
204 print(is_prime_optimized(29))      # True
205 et = time.time()
206 print(f"Optimized method took {et - st} seconds")
207

```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

True

Basic method took 0.0002682209014892578 seconds

True

Optimized method took 0.0012965202331542969 seconds

Explanation:

The basic method checks for factors from 2 to $n-1$, which can be slow for large n .

The optimized method reduces the number of checks by:

1. Eliminating even numbers and multiples of 3 right away.
2. Only checking up to the square root of n , since a larger factor of n must be a multiple of a smaller factor that has already been checked.
3. Checking only numbers of the form $6k \pm 1$, as all primes greater than 3 can be expressed in this form. This significantly reduces the number of iterations needed to determine primality.

Task Description #9 (Transparency in Recursive Algorithms)

Objective: Use AI to generate a recursive function to calculate Fibonacci numbers.

Prompt:

1. Ask AI to add clear comments explaining recursion.
2. Ask AI to explain base cases and recursive calls.

Code and Output:

```
224 def fibonacci(n):
225     # Base case: if n is 0 or 1, return n
226     if n <= 0:
227         return 0
228     elif n == 1:
229         return 1
230     # Recursive case: return the sum of the two preceding Fibonacci numbers
231     else:
232         return fibonacci(n - 1) + fibonacci(n - 2)
233 print(fibonacci(6)) # Output: 8
234 print(fibonacci(10)) # Output: 55
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS pwsh - Microsoft VS

8
55

Explanation:

In this recursive function, we define two base cases:

1. If n is 0, we return 0.
2. If n is 1, we return 1.

For any other value of n , we make two recursive calls:

1. $\text{fibonacci}(n - 1)$: This call computes the $(n-1)$ th Fibonacci number.
2. $\text{fibonacci}(n - 2)$: This call computes the $(n-2)$ th Fibonacci number.

The function then returns the sum of these two calls, effectively building up the Fibonacci sequence from the base cases upward.

Task Description #10 (Transparency in Error Handling)


Task: Use AI to generate a Python program that reads a file and processes data.

Prompt:

“Generate code with proper error handling and clear explanations for each

exception.”

Code and Output:



The screenshot shows a VS Code editor window with a Python script in the editor and a terminal window at the bottom. The script attempts to read a file named 'non_existent_file.txt', which does not exist, resulting in a `FileNotFoundError`. The terminal output shows the error message: `Error: The file was not found. Details: [Errno 2] No such file or directory: 'non_existent_file.txt'`.

```
252 try:
253     with open('non_existent_file.txt', 'r') as file:
254         content = file.read()
255         print(content)
256 except FileNotFoundError as e:
257     print(f"Error: The file was not found. Details: {e}")
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS pwsh - Microsoft VS Code + - □ 🗑 ...

Error: The file was not found. Details: [Errno 2] No such file or directory: 'non_existent_file.txt'