

REG NO: 230701020

NAME : Akilesh Prasad I k

DEPT : CSE - A

# TIME COMPLEXITY

## QUESTION 2.A

AIM:

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;

    int s =1;

    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**For example:**

Input	Result
9	12

AIM:

Step 1: Start

Step 2: Input the integer **n**

Step 3: Initialize **c** to **0** to count operations

Step 4: Initialize **i** to **1**

Step 5: Increment **c** by **1**

Step 6: Initialize **s** to **1**

Step 7: Increment **c** by **1**

Step 8: While **s** is less than or equal to **n**, do Steps 8.1 to 8.5

Step 8.1: Increment **c** by **1**

Step 8.2: Increment **i** by **1**

Step 8.3: Increment **c** by **1**

Step 8.4: Add **i** to **s** (**s += i**)

Step 8.5: Increment **c** by **1**

Step 9: Increment **c** by **1**

Step 10: Print the value of `c`

Step 11: Stop

#### PROGRAM:

```
#include<stdio.h>
void function(int n)
{
    int c=0;
    int i=1;
    c++;
    int s=1;
    c++;
    while(s<=n)
    {
        c++;
        i++;
        c++;
        s+=i;
        c++;
    }
    c++;
    printf("%d",c);
}
int main()
{
    int n;
    scanf("%d",&n);
    function(n);
    return 0;
}
```

#### OUTPUT :

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

Passed all tests! ✓

#### RESULT:

## AIM:

The above code is executed successfully and gives expected output.

## QUESTION 2.b

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
```

```
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

## ALGORITHM:

Step 1: Start

Step 2: Input the integer n

Step 3: Initialize c to 0 to count operations

Step 4: If n is equal to 1, go to Step 5, else go to Step 7

Step 5: Increment c by 1

Step 6: Print "\*" and go to Step 12

Step 7: Increment c by 1

Step 8: For each integer i from 1 to n, do Steps 9 to 11

Step 9: Increment c by 1

Step 10: For each integer j from 1 to n, do Steps 10.1 to 10.4

Step 10.1: Increment c by 1

Step 10.2: Increment c by 1

Step 10.3: Increment c by 1

Step 10.4: Break out of the inner loop

Step 11: Increment c by 1

Step 12: Increment `c` by 1  
Step 13: Print the value of `c`  
Step 14: Stop

#### PROGRAM:

```
#include<stdio.h>
void func(int n)
{   int c=0;
    if(n==1)
    { c++;
      printf("*");
    }
    else
    {
        c++;
        for(int i=1; i<=n; i++)
        {
            c++;
            for(int j=1; j<=n; j++)
            {
                c++;
                //printf("*");
                c++;
                //printf("*");
                c++;
                break;
            }
            c++;
        }
        c++;
    }
    printf("%d",c);
}

int main()
{
    int n;
    scanf("%d",&n);
    func(n);
}
```

#### OUTPUT:

**AIM:**

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

**RESULT:**

The above code is executed successfully and gives expected output.

### QUESTION 2.C

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {  
    {  
        for (i = 1; i <= num; ++i)  
        {  
            if (num % i == 0)  
            {  
                printf("%d ", i);  
            }  
        }  
    }  
}
```

**Note:** No need of counter increment for declarations and scanf() and counter variable printf() statement.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**ALGORITHM:**

Step 1: Start

Step 2: Input the integer n

Step 3: Initialize c to 0 to count operations

Step 4: For each integer i from 1 to n, do Steps 5 to 7

Step 5: Increment c by 1

Step 6: If n is divisible by i ( $n \% i == 0$ ), increment c by 1

Step 7: Increment c by 1

Step 8: Increment c by 1

Step 9: Print the value of c

Step 10: Stop

#### PROGRAM:

```
#include <stdio.h>

void Factor(int num) {
    int c = 0;
    for (int i = 1; i <= num; ++i)
    {
        c++;
        if (num % i == 0)
        {
            c++;
        }
        c++;
    }
    c++;
    printf("%d", c);
}

int main() {
    int n;
    scanf("%d", &n);
    Factor(n);
    return 0;
}
```

#### OUTPUT:

**AIM:**

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

Passed all tests! ✓

**RESULT:**

The above code is executed successfully and gives expected output.

## QUESTION 2.D

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c = 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**ALGORITHM:**

Step 1: Start

Step 2: Input the integer n

Step 3: Initialize **count** to **0** to count operations

Step 4: Initialize **c** to **0**

Step 5: Increment **count** by 1  
Step 6: For each integer **i** from  $n/2$  to  $n - 1$ , do Steps 7 to 9  
Step 7: Increment **count** by 1  
Step 8: Initialize **j** to 1 and while **j** is less than **n**, do Steps 8.1 to 8.5  
Step 8.1: Increment **count** by 1  
Step 8.2: Initialize **k** to 1 and while **k** is less than **n**, do Steps 8.2.1 to 8.2.4  
Step 8.2.1: Increment **count** by 1  
Step 8.2.2: Increment **c** by 1  
Step 8.2.3: Increment **count** by 1  
Step 8.2.4: Multiply **k** by 2 ( $k = k * 2$ )  
Step 8.3: Increment **count** by 1  
Step 8.4: Multiply **j** by 2 ( $j = j * 2$ )  
Step 9: Increment **count** by 1  
Step 10: Increment **count** by 1  
Step 11: Print the value of **count**  
Step 12: Stop

**PROGRAM:**



AIM:

```
#include<stdio.h>
void function(int n)
{
    int count=0;
    int c= 0;
    count++;
    for(int i=n/2; i<n; i++){
        count++;
        for(int j=1; j<n; j = 2 * j){
            count++;
            for(int k=1; k<n; k = k * 2){
                count++;
                c++;
                count++;
            }
            count++;
        }
        count++;
    }
    count++;
    printf("%d",count);
}
int main(){
    int n;
    scanf("%d",&n);
    function(n);
}
```

OUTPUT:

	Input	Expected	Got	
✓	4	30	30	✓
✓	10	212	212	✓

Passed all tests! ✓

RESULT:

The above code is executed successfully and gives expected output.

## QUESTION 2.E

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n /= 10;
    }
    print(rev);
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

## ALGORITHM:

- Step 1: Start
- Step 2: Input the integer n
- Step 3: Initialize counter to 0 to count operations
- Step 4: Initialize rev to 0 and remainder as unassigned
- Step 5: Increment counter by 1
- Step 6: While n is not equal to 0, do Steps 6.1 to 6.7
- Step 6.1: Increment counter by 1
- Step 6.2: Calculate remainder as  $n \% 10$
- Step 6.3: Increment counter by 1
- Step 6.4: Update rev to  $rev * 10 + remainder$
- Step 6.5: Increment counter by 1
- Step 6.6: Divide n by 10 ( $n /= 10$ )
- Step 6.7: Increment counter by 1
- Step 7: Increment counter by 1
- Step 8: Increment counter by 1
- Step 9: Print the value of counter
- Step 10: Stop

AIM:

PROGRAM:

```
#include <stdio.h>
void reverse(int n)
{
    int counter=0;
    int rev = 0, remainder;
    counter++;
    while (n != 0)
    {
        counter++;
        remainder = n % 10;
        counter++;
        rev = rev * 10 + remainder;
        counter++;
        n/= 10;
        counter++;
    }
    counter++;
    counter++;
    //print(rev);
    printf("%d",counter);
}
int main(){
    int n;
    scanf("%d",&n);
    reverse(n);
}
```

OUTPUT:

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

Passed all tests! ✓

RESULT:

The above code is executed successfully and gives expected output.