

EXPERIMENT - 8

Privilege Escalation Using TryHackMe

Step 1: Login to Platform

Open TryHackMe and log in

Step 2: Open Room

Search for **Linux Privilege Escalation** and join the room.

Step 3: Start AttackBox

Launch the AttackBox and open the terminal.

Step 4: Perform Enumeration

Check user details, system information, and permissions to identify possible vulnerabilities.

Step 5: Identify Vulnerabilities

Look for misconfigurations such as sudo permissions, SUID files, weak file access, or cron jobs.


Step 6: Escalate Privileges

Exploit the identified vulnerability to gain higher privileges (root access).

Step 7: Verify and Complete Tasks

Confirm root access and capture required flags to complete the exercise.

Output:



The screenshot displays a CTF challenge interface for "Linux Privilege Escalation". The left panel shows the challenge title, a brief description, and a "Task 1: Introduction" section. The right panel shows a terminal window with the following commands and outputs:

```
root@ip-10-48-154-46:~# ^C
root@ip-10-48-154-46:~# ^C
root@ip-10-48-154-46:~# ^C
root@ip-10-48-154-46:~# ^C
root@ip-10-48-154-46:~# ssh user@TARGET_IP
ssh: Could not resolve hostname target_ip: Name or service not known
root@ip-10-48-154-46:~# ssh tryhackne@10.10.45.123
ssh: connect to host 10.10.45.123 port 22: Connection timed out
root@ip-10-48-154-46:~# ip
Usage: ip [ OPTIONS ] OBJECT { COMMAND | help }
       ip [-force] [-batch filename]
where  OBJECT := { link | address | addrlabel | route | rule | neigh | ntable |
              tunnel | tuntap | maddress | mroute | mrule | monitor | xfrm |
              netns | lztp | fou | macsec | tcp_metrics | token | netconf | lla |
              vrf | sr | nexthop }
       *
       OPTIONS := { -V[ersion] | -s[tatistics] | -d[etails] | -r[esolve] |
                  -h[uman-readable] | -l[ec] | -j[son] | -p[retty] |
                  -f[amily] { inet | inet6 | mpls | bridge | link } |
                  -d | -D | -1 | -O | -M | -B | -S |
                  -l[oops] { maximum-addr-flush-attempts } | -b[r[ief] |
                  -o[neline] | -t[imestamp] | -ts[hort] | -b[atch] [filename] |
                  -rc[vbuf] [size] | -n[etns] name | -N[umeric] | -a[ll] |
                  -c[olor] }
root@ip-10-48-154-46:~# id
uid=0(root) gid=0(root) groups=0(root),998(docker),1001(rvm)
root@ip-10-48-154-46:~# uname -a
Linux ip-10-48-154-46 5.15.0-124-generic #134-20.04.1-Ubuntu SMP Tue Oct 1 15:27:33 UTC 2024
x86_64 x86_64 x86_64 GNU/Linux
root@ip-10-48-154-46:~# sudo -l
sudo: unable to resolve host ip-10-48-154-46: Name or service not known
Matching Defaults entries for root on ip-10-48-154-46:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/snap/bin

User root may run the following commands on ip-10-48-154-46:
    (ALL : ALL) ALL
root@ip-10-48-154-46:~#
```

Result:

Privilege escalation was successfully performed, demonstrating how system misconfigurations can lead to unauthorized access and highlighting the importance of secure system practices.