

RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR, THANDALAM – 602 105



**RAJALAKSHMI
ENGINEERING COLLEGE**

**CS23221
PYTHON PROGRAMMING LAB**

Laboratory Observation Note Book

NAME: NITHIESH S

YEAR/BRANCH/SECTION: I/CSE/D

REGISTER NO: 230701215

SEMESTER: II

ACADEMIC YEAR: 2023-24



REG No: 230701215

Name: NITHIESH S

Year: 1st

Branch: CSE

Sec: D

S. No.	Date	Title	Page No.	Teacher's Signature / Remarks
Introduction to python-Variables-Datatypes-Input/Output-Formatting				
1.1		Converting Input Strings		
1.2		Gross salary		
1.3		Square Root		
1.4		Gain percent		
1.5		Deposits		
1.6		Carpenter		
Operators in Python				
2.1		Widgets and Gizmos		
2.2		Doll Sings		
2.3		Birthday party		
2.4		Hamming Weight		
2.5		Compound Interest		
2.6		Eligible to donate blood		
2.7		C or D		
2.8		Troy Battle		
2.9		Tax and Tip		
2.10		Return last digit of the given number		
Selection Structures in Python				
3.1		Admission eligibility		
3.2		Classifying triangles		
3.3		Electricity Bill		
3.4		IN/OUT		
3.5		Vowel or Constant		



3.6		Leap Year		
3.7		Month name to Days		
3.8		Pythagorean triple		
3.9		Second Last Digit		
3.10		Chinese Zodiac		
Algorithmic Approach: Iteration Control Structures				
4.1		Factors of a Number		
4.2		Non-Repeated Digits Count		
4.3		Prime Checking		
4.4		Next Perfect Square		
4.5		Nth Fibonacci		
4.6		Disarium Number		
4.7		Sum of Series		
4.8		Unique Digits Count		
4.9		Product of single digits		
4.10		Perfect Square After adding One		
Strings in Python				
5.1		Count chars		
5.2		Decompress the String		
5.3		First N Common Characters		
5.4		Remove Characters		
5.5		Remove Palindrome Words		
5.6		Return Second Word in Uppercase		
5.7		Reverse String		
5.8		String characters balance Test		
5.9		Unique Names		
5.10		Username Domain Extension		
List in Python				
6.1		Monotonic array		
6.2		Check pair with difference k .		
6.3		Count Elements		



6.4		Distinct Elements in an Array		
6.5		Element Insertion		
6.6		Find the Factor		
6.7		Merge list		
6.8		Merge Two Sorted Arrays Without Duplication		
6.9		Print Element Location		
6.10		Strictly increasing		
Tuples & Set				
7.1		Binary String		
7.2		Check Pair		
7.3		DNA Sequence		
7.4		Print repeated no		
7.5		Remove repeated		
7.6		malfunctioning keyboard		
7.7		American keyboard		
Dictionary				
8.1		Uncommon Words		
8.2		Sort Dictionary By Values Summation		
8.3		Winner Of Election		
8.4		Student Record		
8.5		Scramble Score		
Functions				
9.1		Abundant Number		
9.2		Automorphic number or not		
9.3		Check Product of Digits		
9.4		Christmas Discount		
9.5		Coin Change		
9.6		Difference Sum		



9.7		Ugly number		
Searching & Sorting				
10.1		Merge Sort		
10.2		Bubble Sort		
10.3		Peak Element		
10.4		Binary Search		
10.5		Frequency of Numbers		



01 - Introduction to Python-Variables-Datatypes

Input/Output-Formatting



Sample Output:

10,<class 'int'>

10.9,<class 'float'>

For example:

Input	Result
10	10,<class 'int'>
10.9	10.9,<class 'float'>



Ex. No. : 1.1

Date:

Register No: 230701215

Name: Nithiesh S

Converting Input Strings

Write a program to convert strings to an integer and float and display its type.

Sample Input:

10

10.9

```
a=int(input())
```

```
b=float(input())
```

```
print(a,",",type(a),sep="")
```

```
print(round(b,1),",",type(b),sep="")
```

Sample Input:

10000



Sample Output:

16000

For example:

Input	Result
10000	16000



Ex. No. : 1.2

Date:

Register No: 230701215

Name: Nithiesh S

Gross Salary

Ramesh's basic salary is input through the keyboard. His dearness allowance is 40% of his basic salary, and his house rent allowance is 20% of his basic salary. Write a program to calculate his gross salary.

```
b_s=int(input(""))
d_a=(b_s//20)*2
h_r=(b_s//10)*5
g_s= b_s+d_a+h_r
print(g_s)
```



Sample Input:

8.00

Sample Output:

2.828

For example:

Input	Result
14.00	3.742



Ex. No. : 1.3

Date:

Register No: 230701215

Name: Nithiesh S

Square Root

Write a simple python program to find the square root of a given floating point number. The output should be displayed with 3 decimal places.

```
import math  
  
a=float(input())  
  
b=math.sqrt(a)  
  
print("{:.3f}".format(b))
```



Input Format:

The first line contains the Rs X

The second line contains Rs Y

The third line contains Rs Z

Sample Input:

10000

250

15000

Sample Output:

46.34 is the gain percent.

For example:

Input	Result
45500 500 60000	30.43 is the gain percent.



Ex. No. : 1.4

Date:

Register No: 230701215

Name: Nithiesh S

Gain percent

Alfred buys an old scooter for Rs. X and spends Rs. Y on its repairs. If he sells the scooter for Rs. Z ($Z > X + Y$). Write a program to help Alfred to find his gain percent. Get all the above-mentioned values through the keyboard and find the gain percent.

```
x=int(input())
y=int(input())
c=x+y
z=int(input())
g=z-c
s=g/c*100
print(format(s,".2f"),"is the gain percent.")
```



Sample Input

10

20

Sample Output

Your total refund will be \$6.00.

For example:

Input	Result
20 20	Your total refund will be \$7.00.



Ex. No. : 1.5

Date:

Register No: 230701215

Name: Nithiesh S

Deposits

In many jurisdictions, a small deposit is added to drink containers to encourage people to recycle them. In one particular jurisdiction, drink containers holding one liter or less have a \$0.10 deposit and drink containers holding more than one liter have a \$0.25 deposit. Write a program that reads the number of containers of each size (less and more) from the user. Your program should continue by computing and displaying the refund that will be received for returning those containers. Format the output so that it includes a dollar sign and always displays exactly two decimal places.

```
a=int(input())
```

```
b=int(input())
```

```
c=a*0.1
```

```
d=b*0.25
```

```
e=c+d
```

```
print("Your total refund will be $%.2f"%e)
```



Sample Input:

450

Sample Output:

weekdays 10.38

weekend 0.38

For example:

Input	Result
450	weekdays 10.38 weekend 0.38



Ex. No. : 1.6

Date:

Register No: 230701215

Name: Nithiesh S

Carpenter

Justin is a carpenter who works on an hourly basis. He works in a company where he is paid Rs 50 for an hour on weekdays and Rs 80 for an hour on weekends. He works 10 hrs more on weekdays than weekends. If the salary paid for him is given, write a program to find the number of hours he has worked on weekdays and weekends.

Hint:

If the final result(hrs) are in -ve convert that to +ve using abs() function

The abs() function returns the absolute value of the given number.

```
number = -20
absolute_number = abs(number)
print(absolute_number)
# Output: 20
```



```
sal=int(input())
b=(sal-500)/130
absolute=abs(b)
print("weekdays",format(10+absolute,".2f"))
print("weekend",format(absolute,".2f"))
```



02- Operators in Python



Sample Input

10

20

Sample Output

The total weight of all these widgets and gizmos is 2990 grams.

For example:

Input	Result
10 20	The total weight of all these widgets and gizmos is 2990 grams.



Ex. No. : 2.1

Date:

Register No: 230701215

Name: Nithiesh S

Widgets and Gizmos

An online retailer sells two products: widgets and gizmos. Each widget weighs 75 grams. Each gizmo weighs 112 grams. Write a program that reads the number of widgets and the number of gizmos from the user. Then your program should compute and display the total weight of the parts.

```
a=int(input())
```

```
b=int(input())
```

```
print("The total weight of all these widgets and gizmos is", (a*75+b*112), "grams.")
```



Sample Input

10

Sample Output

True

Explanation:

Since 10 is an even number and a number between 0 and 100, True is printed



Ex. No. : 2.2

Date:

Register No: 230701215

Name: Nithiesh S

Doll Sings

In London, every year during Dasara there will be a very grand doll show. People try to invent new dolls of different varieties. The best-sold doll's creator will be awarded with a cash prize. So people broke their heads to create dolls innovatively. Knowing this competition, Mr.Lokpaul tried to create a doll that sings only when an even number is pressed and the number should not be zero and greater than 100.

IF Lokpaul wins print true, otherwise false.

```
a=int(input())
```

```
print(a%2==0 and 0<=a<=100)
```



Input Given:

N-No of friends

P1,P2,P3 AND P4-No of chocolates

OUTPUT:

"True" if he can buy that packet and "False" if he can't buy that packet.

SAMPLE INPUT AND OUTPUT:

5

25

12

10

9

OUTPUT

True False True False



Ex. No. : 2.3

Date:

Register No: 230701215

Name: Nithiesh S

Birthday Party

Mr. X's birthday is in next month. This time he is planning to invite N of his friends. He wants to distribute some chocolates to all of his friends after the party. He went to a shop to buy a packet of chocolates. At the chocolate shop, 4 packets are there with different numbers of chocolates. He wants to buy such a packet which contains a number of chocolates, which can be distributed equally among all of his friends. Help Mr. X to buy such a packet.

```
a=int(input())
b=int(input())
c=int(input())
d=int(input())
e=int(input())
print(b%a==0,c%a==0,d%a==0,e%a==0)
```



Sample Input

3

Sample Output:

2

Explanation:

The binary representation of 3 is 011, hence there are 2 ones in it. so the output is 2.



Ex. No. : 2.4

Date:

Register No: 230701215

Name: Nithiesh S

Hamming Weight

Write a python program that takes a integer between 0 and 15 as input and displays the number of '1' s in its binary form.(Hint:use python bitwise operator.

```
a=bin(int(input()))  
print(a.count("1"))
```



Sample Input:

10000

Sample Output:

Balance as of end of Year 1: \$10400.00.

Balance as of end of Year 2: \$10816.00.

Balance as of end of Year 3: \$11248.64



Ex. No. : 2.5

Date:

Register No: 230701215

Name: Nithiesh S

Compound Interest

Pretend that you have just opened a new savings account that earns 4 percent interest per year. The interest that you earn is paid at the end of the year, and is added to the balance of the savings account. Write a program that begins by reading the amount of money deposited into the account from the user. Then your program should compute and display the amount in the savings account after 1, 2, and 3 years. Display each amount so that it is rounded to 2 decimal places.

```
a=float(input())
```

```
b1=a*1.04
```

```
b2=b1*1.04
```

```
b3=b2*1.04
```

```
print("Balance as of end of Year 1: ${:.2f}".format(b1))
```

```
print("Balance as of end of Year 2: ${:.2f}".format(b2))
```

```
print("Balance as of end of Year 3: ${:.2f}".format(b3))
```



Input Format:

Input consists of two integers that correspond to the age and weight of a person respectively.

Output Format:

Display True(IF ELIGIBLE)

Display False (if not eligible)

Sample Input

19

45

Sample Output

True



Ex. No. : 2.6

Date:

Register No: 230701215

Name: Nithiesh S

Eligible to donate blood

A team from the Rotract club had planned to conduct a rally to create awareness among the Coimbatore people to donate blood. They conducted the rally successfully. Many of the Coimbatore people realized it and came forward to donate their blood to nearby blood banks. The eligibility criteria for donating blood are people should be above or equal to 18 and his/ her weight should be above 40. There was a huge crowd and staff in the blood bank found it difficult to manage the crowd. So they decided to keep a system and ask the people to enter their age and weight in the system. If a person is eligible he/she will be allowed inside.

Write a program and feed it to the system to find whether a person is eligible or not.

```
a=int(input())
```

```
b=int(input())
```

```
print(a>=18 and b>40)
```



Input Format:

An integer x, $0 \leq x \leq 1$.

Output Format:

output a single character "C" or "D" depending on the value of x.

Input 1:

0

Output 1:

C

Input 2:

1

Output 1:

D



Ex. No. : 2.7

Date:

Register No: 230701215

Name: Nithiesh S

C or D

Mr. Ram has been given a problem kindly help him to solve it. The input of the program is either 0 or 1. IF 0 is the input he should display "C" if 1 is the input it should display "D". There is a constraint that Mr. Ram should use either logical operators or arithmetic operators to solve the problem, not anything else.

Hint:

Use ASCII values of C and D.

```
a=int(input())
```

```
print(chr(a+67))
```



Input format:

Line 1 has the total number of weapons

Line 2 has the total number of Soldiers.

Output Format:

If the battle can be won print True otherwise print False.

Sample Input:

32

43

Sample Output:'

False



Ex. No. : 2.8

Date:

Register No: 230701215

Name: Nithiesh S

Troy Battle

In the 1800s, the battle of Troy was led by Hercules. He was a superstitious person. He believed that his crew can win the battle only if the total count of the weapons in hand is in multiple of 3 and the soldiers are in an even number of count. Given the total number of weapons and the soldier's count, Find whether the battle can be won or not according to Hercules's belief. If the battle can be won print True otherwise print False.

```
a=int(input())
```

```
b=int(input())
```

```
print(a%3==0 and b%2==0)
```



Sample Input

100

Sample Output

The tax is 5.00 and the tip is 18.00, making the total 123.00



Ex. No. : 2.9

Date:

Register No: 230701215

Name: Nithiesh S

Tax and Tip

The program that you create for this exercise will begin by reading the cost of a meal ordered at a restaurant from the user. Then your program will compute the tax and tip for the meal. Use your local tax rate (5 percent) when computing the amount of tax owing. Compute the tip as 18 percent of the meal amount (without the tax). The output from your program should include the tax amount, the tip amount, and the grand total for the meal including both the tax and the tip. Format the output so that all of the values are displayed using two decimal places.

```
a=int(input())
tax=a*(5/100)
tip=a*(18/100)
total=tax+tip+a
```

```
print("The tax is {:.2f} and the tip is {:.2f}, making the total {:.2f}".format(tax, tip, total))
```



For example:

Input	Result
123	3



Ex. No. : 2.10

Date:

Register No: 230701215

Name: Nithiesh S

Return last digit of the given number

Write a program that returns the last digit of the given number. Last digit is being referred to the least significant digit i.e. the digit in the ones (units) place in the given number.

The last digit should be returned as a positive number.

For example,

if the given number is 197, the last digit is 7

if the given number is -197, the last digit is 7

```
a=abs(int(input()))
```

```
b=a%10
```

```
print((b))
```



03 - Selection Structures in Python



Sample Test Cases

Test Case 1

Input

70

60

80

Output

The candidate is eligible

Test Case 2

Input

50

80

80

Output

The candidate is eligible

Test Case 3

Input

50

60

40

Output

The candidate is not eligible

For example:

Input	Result
50 80 80	The candidate is eligible



Ex. No. : 3.1

Date:

Register No: 230701215

Name: Nithiesh S

Admission Eligibility

Write a program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths ≥ 65

Marks in Physics ≥ 55

Marks in Chemistry ≥ 50

Or

Total in all three subjects ≥ 180

```
a=int(input())
```

```
b=int(input())
```

```
c=int(input())
```

```
total=a+b+c
```

```
if(a>=65 and b>=55 and c>=50):
```

```
    print("The candidate is eligible")
```

```
elif(total>=180):
```

```
    print("The candidate is eligible")
```

```
else:
```

```
    print("The candidate is not eligible")
```



Sample Input 1

60

60

60

Sample Output 1

That's a equilateral triangle

For example:

Input	Result
40 40 80	That's a isosceles triangle



Ex. No. : 3.2

Date:

Register No: 230701215

Name: Nithiesh S

Classifying Triangles

A triangle can be classified based on the lengths of its sides as equilateral, isosceles or scalene. All three sides of an equilateral triangle have the same length. An isosceles triangle has two sides that are the same length, and a third side that is a different length. If all of the sides have different lengths then the triangle is scalene.

Write a program that reads the lengths of the three sides of a triangle from the user. Then display a message that states the triangle's type.

```
a=int(input())
b=int(input())
c=int(input())
if(a==b==c):
    print("That's a equilateral triangle")
elif(a==b):
    print("That's a isosceles triangle")
else:
    print("That's a scalene triangle")
```



Sample Test Cases

Test Case 1

Input

50

Output

100.00

Test Case 2

Input

300

Output

517.50

For example:

Input	Result
500	1035.00



Ex. No. : 3.3

Date:

Register No: 230701215

Name: Nithiesh S

Electricity Bill

Write a program to calculate and print the Electricity bill where the unit consumed by the user is given from test case. It prints the total amount the customer has to pay. The charge are as follows:

Unit	Charge / Unit
Upto 199	@1.20
200 and above but less than 400	@1.50
400 and above but less than 600	@1.80
600 and above	@2.00

If bill exceeds Rs.400 then a surcharge of 15% will be charged and the minimum bill should be of Rs.100/-

```
a= float(input())
```

```
if a<=199:
```

```
    bill=a*1.20
```

```
if 200<=a<400:
```

```
    bill=a*1.50
```

```
if 400<=a<600:
```

```
    bill=(a*1.80)
```

```
if a>600:
```

```
    bill=(a*2.00)
```

```
if bill>400:
```

```
    bill+=bill*0.15
```

```
if bill<100:
```

```
    bill=100.00
```



```
print("{:.2f}".format(bill))
```

Input Format:

Input consists of 2 integers.

The first integer corresponds to the number of problems given and the second integer corresponds to the number of problems solved.

Output Format:

Output consists of the string “IN” or “OUT”.

Sample Input and Output:

Input

8

3

Output

OUT

For example:

Input	Result
8 3	OUT



Ex. No. : 3.4

Date:

Register No: 230701215

Name: Nithiesh S

IN/OUT

Ms. Sita, the faculty handling programming lab for you is very strict. Your seniors have told you that she will not allow you to enter the week's lab if you have not completed atleast half the number of problems given last week. Many of you didn't understand this statement and so they requested the good programmers from your batch to write a program to find whether a student will be allowed into a week's lab given the number of problems given last week and the number of problems solved by the student in that week.

```
a=int(input())
```

```
b=int(input())
```

```
c=a/2
```

```
if(c<b):
```

```
    print('IN')
```

```
else:
```

```
    print("OUT")
```



Sample Input 1

i

Sample Output 1

It's a vowel.

Sample Input 2

y

Sample Output 2

Sometimes it's a vowel... Sometimes it's a consonant.

Sample Input3

c

Sample Output 3

It's a consonant.

For example:

Input	Result
y	Sometimes it's a vowel... Sometimes it's a consonant.
u	It's a vowel.
p	It's a consonant.



Ex. No. : 3.5

Date:

Register No: 230701215

Name: Nithiesh S

Vowel or Consonant

In this exercise you will create a program that reads a letter of the alphabet from the user. If the user enters a, e, i, o or u then your program should display a message indicating that the entered letter is a vowel. If the user enters 'y' then your program should display a message indicating that sometimes y is a vowel, and sometimes y is a consonant. Otherwise your program should display a message indicating that the letter is a consonant.

```
ai=input()

if ai=='a':

    print("It's a vowel.")

elif ai=='e':

    print("It's a vowel.")

elif ai=='i':

    print("It's a vowel.")

elif ai=='o':

    print("It's a vowel.")

elif ai=='u':

    print("It's a vowel.")

elif ai=='y':

    print("Sometimes it's a vowel... Sometimes it's a consonant.")

else:

    print("It's a consonant.")
```



Sample Input 1

1900

Sample Output 1

1900 is not a leap year.

Sample Input 2

2000

Sample Output 2

2000 is a leap year.



Ex. No. : 3.6

Date:

Register No: 230701215

Name: Nithiesh S

Leap Year

Most years have 365 days. However, the time required for the Earth to orbit the Sun is actually slightly more than that. As a result, an extra day, February 29, is included in some years to correct for this difference. Such years are referred to as leap years. The rules for determining whether or not a year is a leap year follow:

- Any year that is divisible by 400 is a leap year.
- Of the remaining years, any year that is divisible by 100 is not a leap year.
- Of the remaining years, any year that is divisible by 4 is a leap year.
- All other years are not leap years.

Write a program that reads a year from the user and displays a message indicating whether or not it is a leap year.

```
a=int(input())

if(a%400==0):

    print(a, "is a leap year.")

elif(a%100==0):

    print(a, "is not a leap year.")

else:

    print(a, "is a leap year.")
```



Sample Input 1

February

Sample Output 1

February has 28 or 29 days in it.

Sample Input 2

March

Sample Output 2

March has 31 days in it.

Sample Input 3

April

Sample Output 3

April has 30 days in it.

For example:

Input	Result
February	February has 28 or 29 days in it.
March	March has 31 days in it.



Ex. No. : 3.7

Date:

Register No: 230701215

Name: Nithiesh S

Month name to days

The length of a month varies from 28 to 31 days. In this exercise you will create a program that reads the name of a month from the user as a string. Then your program should display the number of days in that month. Display “28 or 29 days” for February so that leap years are addressed.

```
a=input()
if a=="January":
    print("January has 31 days in it.")
elif a=="February":
    print("February has 28 or 29 days in it.")
elif a=="March":
    print("March has 31 days in it.")
elif a=="April":
    print("April has 30 days in it.")
elif a=="May":
    print("May has 31 days in it.")
elif a=="June":
    print("June has 30 days in it.")
elif a=="July":
    print("July has 31 days in it.")
elif a=="August":
    print("August has 31 days in it.")
elif a=="September":
    print("September has 30 days in it.")
elif a=="October":
    print("October has 31 days in it.")
elif a=="November":
    print("November has 30 days in it.")
else:
    print("December has 31 days in it.")
```



Sample Input

3

5

4

Sample Output

Yes

For example:

Input	Result
3	Yes
4	
5	



Ex. No. : 3.8

Date:

Register No: 230701215

Name: Nithiesh S

Pythagorean triple

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third.

For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "Yes", otherwise, print "No".

```
a=int(input())
b=int(input())
c=int(input())
if(a*a+b*b==c*c):
    print('yes')
elif(b*b+c*c==a*a):
    print('yes')
elif(c*c+a*a==b*b):
    print('yes')
else:
    print('no')
```



For example:

Input	Result
197	9



Ex. No. : 3.9

Date:

Register No: 230701215

Name: Nithiesh S

Second last digit

Write a program that returns the second last digit of the given number. Second last digit is being referred to the digit in the tens place in the given number.

For example, if the given number is 197, the second last digit is 9.

Note1 - The second last digit should be returned as a positive number. i.e. if the given number is -197, the second last digit is 9.

Note2 - If the given number is a single digit number, then the second last digit does not exist. In such cases, the program should return -1. i.e. if the given number is 5, the second last digit should be returned as -1.

```
a=(int(input()))
```

```
a=abs(a)
```

```
if(0<=a<=9):
```

```
    print("-1")
```

```
else:
```

```
    rem=(a/10)%10
```

```
    print(int(rem))
```



Sample Input 1

2010

Sample Output 1

2010 is the year of the Tiger.

Sample Input 2

2020

Sample Output 2

2020 is the year of the Rat.



Ex. No. : 3.10

Date:

Register No: 230701215

Name: Nithiesh S

Chinese Zodiac

The Chinese zodiac assigns animals to years in a 12 year cycle. One 12 year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the dragon, and 1999 being another year of the hare.

Year Animal

2000 Dragon

2001 Snake

2002 Horse

2003 Sheep

2004 Monkey

2005 Rooster

2006 Dog

2007 Pig

2008 Rat

2009 Ox

2010 Tiger

2011 Hare

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.



```
a=int(input())
r=a%12
if r==0:
    print(a,"is the year of the Monkey.")
elif r==1:
    print(a,"is the year of the Rooster.")
elif r==2:
    print(a,"is the year of the Dog.")
elif r==3:
    print(a,"is the year of the Pig.")
elif r==4:
    print(a,"is the year of the Rat.")
elif r==5:
    print(a,"is the year of the Ox.")
elif r==6:
    print(a,"is the year of the Tiger.")
elif r==7:
    print(a,"is the year of the Hare.")
```



04 - Iteration Control Structures



For example:

Inpu t	Result
20	1 2 4 5 10 20



Ex. No. : 4.1

Date:

Register No: 230701215

Name: Nithiesh S

Factors of a number

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number).

```
n=int(input())
```

```
for i in range(1,n+1):
```

```
    if(n%i)==0:
```

```
        print(i,end=' ')
```



For example:

Input	Result
292	1
1015	2
108	3
22	0



Ex. No. : 4.2

Date:

Register No: 230701215

Name: Nithiesh S

Non Repeated Digit Count

Write a program to find the count of non-repeated digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

Some examples are as below.

If the given number is 292, the program should return 1 because there is only 1 non-repeated digit '9' in this number

If the given number is 1015, the program should return 2 because there are 2 non-repeated digits in this number, '0', and '5'.

If the given number is 108, the program should return 3 because there are 3 non-repeated digits in this number, '1', '0', and '8'.

If the given number is 22, the function should return 0 because there are NO non-repeated digits in this number.

```
number=int(input())  
num_str=str(number)  
unique_digits=set()  
  
for digit in num_str:  
    unique_digits.add(digit)  
unique_digit_count=len(unique_digits)  
  
print(unique_digit_count)
```



Example1: if the given number N is 7, the method must return 2

Example2: if the given number N is 10, the method must return 1

For example:

Input	Result
7	2
10	1



Ex. No. : 4.3

Date:

Register No: 230701215

Name: Nithiesh S

Prime Checking

Write a program that finds whether the given number N is Prime or not. If the number is prime, the program should return 2 else it must return 1.

Assumption: $2 \leq N \leq 5000$, where N is the given number.

```
n=int(input())
flag=0
for i in range(2,n):
    if(n%i==0):
        flag=1
        break
    if(n%i==0):
        flag=1
        break
if flag:
    print("1")
else:
    print("2")
```



Input Format:

Integer input from stdin.

Output Format:

Perfect square greater than N.

Example Input:

10

Output:

16



Ex. No. : 4.4

Date:

Register No: 230701215

Name: Nithiesh S

Next Perfect Square

Given a number N, find the next perfect square greater than N.

```
num=int(input())
while 1:
    num=num+1
    root=(num**0.5)
    if root==int(root):
        print(num)
        break
```



NOTE: Fibonacci series looks like –

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, . . . and so on.

i.e. Fibonacci series starts with 0 and 1, and continues generating the next number as the sum of the previous two numbers.

- first Fibonacci number is 0,
- second Fibonacci number is 1,
- third Fibonacci number is 1,
- fourth Fibonacci number is 2,
- fifth Fibonacci number is 3,
- sixth Fibonacci number is 5,
- seventh Fibonacci number is 8, and so on.

For example:

Input:

7

Output

8



Ex. No. : 4.5

Date:

Register No: 230701215

Name: Nithiesh S

Nth Fibonacci

Write a program to return the nth number in the fibonacci series. The value of N will be passed to the program as input.

```
n=int(input())  
a,b=0,1
```

```
for I in range(1,n):  
    a,b=b,a+b
```



Input Format:

Single Integer Input from stdin.

Output Format:

Yes or No.

Example Input:

175

Output:

Yes

Explanation

$$1^1 + 7^2 + 5^3 = 175$$

Example Input:

123

Output:

No

For example:

Input	Result
175	Yes
123	No



Ex. No. : 4.6

Date:

Register No: 230701215

Name: Nithiesh S

Disarium Number

A Number is said to be Disarium number when the sum of its digit raised to the power of their respective positions becomes equal to the number itself. Write a program to print number is Disarium or not.

```
number=int(input())
num_str=str(number)
length=len(num_str)
total=0
for i in range(length):
    total+=int(num_str[i])**i+1
if total==number:
    print("Yes")
else:
    print("No")
```



Sample Test Cases

Test Case 1

Input

4

Output

1234

Explanation:

as input is 4, have to take 4 terms.

$1 + 11 + 111 + 1111$

Test Case 2

Input

6

Output

123456

For example:

Input	Result
3	123



Ex. No. : 4.7

Date:

Register No: 230701215

Name: Nithiesh S

Sum of Series

Write a program to find the sum of the series $1 + 11 + 111 + 1111 + \dots + n$ terms (n will be given as input from the user and sum will be the output)

```
n=int(input())
total=0
term=0

for i in range(1,n+1):
    term=(term*10)+1
    total=total+term

print(total)
```



For example:

Input	Result
292	2
1015	3



Ex. No. : 4.8

Date:

Register No: 230701215

Name: Nithiesh S

Unique Digit Count

Write a program to find the count of unique digits in a given number N. The number will be passed to the program as an input of type int.

Assumption: The input number will be a positive integer number ≥ 1 and ≤ 25000 .

For e.g.

If the given number is 292, the program should return 2 because there are only 2 unique digits '2' and '9' in this number

If the given number is 1015, the program should return 3 because there are 3 unique digits in this number, '1', '0', and '5'.

```
number=int(input())
num_str=str(number)
unique_digits=set()

for digit in num_str:
    unique_digits.add(digit)
unique_digit_count=len(unique_digits)

print(unique_digit_count)
```



Input Format:

Single Integer input.

Output Format:

Output displays Yes if condition satisfies else prints No.

Example Input:

14

Output:

Yes

Example Input:

13

Output:

No



Ex. No. : 4.9

Date:

Register No: 230701215

Name: Nithiesh S

Product of single digit

Given a positive integer N, check whether it can be represented as a product of single digit numbers.

```
number=int(input())

if number<10:
    print("Yes")
else:
    for factor in range (2,10):
        if number % factor == 0 and 1 <= number // factor <= 9:
            print ("Yes")
            break
    else:
        print("No")
```



Input Format:

Single integer input.

Output Format:

Yes or No.

Example Input:

24

Output:

Yes

Example Input:

26

Output:

No

For example:

Input	Result
24	Yes



Ex. No. : 4.10

Date:

Register No: 230701215

Name: Nithiesh S

Perfect Square After adding One

Given an integer N, check whether N the given number can be made a perfect square after adding 1 to it.

```
num=int(input())
num=num+1
a=int(num**0.5)
if a**2==num:
    print("Yes")
else:
    print("No")
```



05 - List in Python



Sample Case 0

Sample Input 0

4

1

2

3

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, $\text{arr}[2]=3$ is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

3

1

2

1

Sample Output 1

1

Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, $\text{arr}[1]=2$ is the pivot between the two subarrays.
- The index of the pivot is 1.

For example:

Input	Result
4 1 2 3 3	2
3 1 2 1	1



Ex. No. : 5.1

Date:

Register No: 230701215

Name: Nithiesh S

Balanced Array

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq \text{arr}[i] \leq 2 \times 10^4$, where $0 \leq i < n$
- It is guaranteed that a solution always exists.

The first line contains an integer n, the size of the array arr.

Each of the next n lines contains an integer, arr[i], where $0 \leq i < n$.

a=int(input())

l=[]

for i in range(a):

l.append(int(input()))

c=sum(l)//2

q=0

for j in l:

q+=j

if q >=c:

q=j

break;

print(l.index(q))



Input

1

3

1

3

5

4

Output:

1

Input

1

3

1

3

5

99

Output

0

For example:

Input	Result
1 3 1 3 5 4	1
1 3 1 3 5 99	0



Ex. No. : 5.2

Date:

Register No: 230701215

Name: Nithiesh S

Check pair with difference k

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

def find pair with difference k(arr, k):

n = len(arr)

i, j = 0, 1

while i < n and j < n:

if i != j and arr[j] - arr[i] == k:

return 1

elif arr[j] - arr[i] < k:

j += 1

else:

i += 1

return 0



Read input

T = int(input())

for _ in range(T):

 N = int(input())

 arr = list(map(int, input().split()))

 k = int(input())

 # Sort the array (if it's not already sorted)

 arr.sort()

 # Find if such a pair exists

 result = find_pair_with_difference_k(arr, k)

 print(result)



Sample Test Cases

Test Case 1

Input

7

23

45

23

56

45

23

40

Output

23 occurs 3 times

45 occurs 2 times

56 occurs 1 times

40 occurs 1 times



Ex. No. : 5.3

Date:

Register No: 230701215

Name: Nithiesh S

Count Elements

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

```
a=int(input())
dic={}
for i in range(a):
    k=int(input())
    if k not in dic:
        dic[k]=1
    else:
        dic[k]+=1
for i in dic:
    print(f'{i} occurs {dic[i]} times')
```



Example Input:

5

1

2

2

3

4

Output:

1 2 3 4

Example Input:

6

1

1

2

2

3

3

Output:

1 2 3

For example:

Input Result

5

1

2

2

3

4

1 2 3 4

6

1

1

2

2

3

3

1 2 3



Ex. No. : 5.4

Date:

Register No: 230701215

Name: Nithiesh S

Distinct Elements in an Array

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

```
a=set()
b=int(input())
for i in range(b):
    a.add(int(input()))
b=sorted(list(a))
for i in b:
    print(i,end=' ')
```



Sample Test Cases

Test Case 1

Input

1
3
4
5
6
7
8
9
10
11
2

Output

ITEM to be inserted:2
After insertion array is:

1
2
3
4
5
6
7
8
9
10
11

Test Case 2

Input

11
22
33
55
66
77
88
99
110
120
44

Output

ITEM to be inserted:44
After insertion array is:

11
22
33
44
55
66
77
88
99
110
120



Ex. No. : 5.5

Date:

Register No: 230701215

Name: Nithiesh S

Element Insertion

Consider a program to insert an element / item in the sorted array. Complete the logic by filling up required code in editable section. Consider an array of size 10. The eleventh item is the data is to be inserted.

```
l=[]
for i in range(10):
    l.append(int(input()))
c=int(input())
l.append(c)
l=sorted(l)
print(f"ITEM to be inserted:{c}\nAfter insertion array is:")
for i in l:
    print(i)
```



Sample Case 0**Sample Input 0**

10

3

Sample Output 0

5

Explanation 0

Factoring $n = 10$ results in $\{1, 2, 5, 10\}$. Return the $p = 3^{\text{rd}}$ factor, 5, as the answer.

Sample Case 1**Sample Input 1**

10

5

Sample Output 1

0

Explanation 1

Factoring $n = 10$ results in $\{1, 2, 5, 10\}$. There are only 4 factors and $p = 5$, therefore 0 is returned as the answer.

Sample Case 2**Sample Input 2**

1

1

Sample Output 2

1

Explanation 2

Factoring $n = 1$ results in $\{1\}$. The $p = 1^{\text{st}}$ factor of 1 is returned as the answer.

For example:

Input	Result
10 3	5
10 5	0
1 1	1



Ex. No. : 5.6

Date:

Register No: 230701215

Name: Nithiesh S

Find the Factor

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the [list](#), sorted ascending. If there is no p^{th} element, return 0.

Constraints

$$1 \leq n \leq 10^{15}$$

$$1 \leq p \leq 10^9$$

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

```
def find_pth_factor(n, p):
    factors = []
    for i in range(1, int(n**0.5) + 1):
        if n % i == 0:
            factors.append(i)
            if i != n // i:
                factors.append(n // i)
    factors.sort()
    if p > len(factors):
        return 0
    else:
        return factors[p-1]

n=int(input(""))
p=int(input(""))

print(find_pth_factor(n,p))
```



Sample test case

Sample input

2
2
1
3
5
7
2
4
6
8

Sample Output

[[1, 3, 2, 4], [5, 7, 6, 8]]



Ex. No. : 5.7

Date:

Register No: 230701215

Name: Nithiesh S

Merge List

Write a Python program to Zip two given lists of lists.

Input:

m : row size

n: column size

list1 and list 2 : Two lists

Output

Zippped List : List which combined both list1 and list2

```
m=int(input())
n=int(input())
l1=[]
l2=[]
l=[]
for i in range(m):
    temp=[]
    for i in range(n):
        temp.append(int(input()))
    l1.append(temp)
for i in range(m):
    temp=[]
    for i in range(n):
        temp.append(int(input()))
    l2.append(temp)
for i in range(m):
    l.append(l1[i]+l2[i])
print(l)
```



Sample Input 1

5
1
2
3
6
9
4
2
4
5
10

Sample Output 1

1 2 3 4 5 6 9 10



Ex. No. : 5.8

Date:

Register No: 230701215

Name: Nithiesh S

Merge Two Sorted Arrays Without Duplication

Output is a merged array without duplicates.

Input Format

N1 - no of elements in array 1

Array elements for array 1

N2 - no of elements in array 2

Array elements for array2

Output Format

Display the merged array

```
l1=set()
l2=set()
a=int(input())
for i in range(a):
    l1.add(int(input()))
b=int(input())
for i in range(b):
    l2.add(int(input()))
l1.update(l2)
m=sorted(list(l1))
for i in m:
    print(i,end=' ')
```



For example, if there are 4 elements in the array:

5
6
5
7

If the element to search is 5 then the output will be:

5 is present at location 1

5 is present at location 3

5 is present 2 times in the array.

Sample Test Cases

Test Case 1

Input

4
5
6
5
7
5

Output

5 is present at location 1.

5 is present at location 3.

5 is present 2 times in the array.

Test Case 2

Input

5
67
80
45
97
100
50

Output

50 is not present in the array.



Ex. No. : 5.9

Date:

Register No: 230701215

Name: Nithiesh S

Print Element Location

Write a program to print all the locations at which a particular element (taken as input) is found in a list and also print the total number of times it occurs in the list. The location starts from 1.

```
a=[]
n=int(input())
for i in range(n):
    a.append(int(input()))
f=int(input())
l=1
t=False
c=0
for i in a:
    if i==f:
        print("%d is present at location %d."%(f,l))
        c+=1
        l+=1
if c!=0:
    print("%d is present %d times in the array."%(f,c))
else:
    print("%d is not present in the array."%f)
```



Sample Test Case

Input

7

1

2

3

0

4

5

6

Output

True



Ex. No. : 5.10

Date:

Register No: 230701215

Name: Nithiesh S

Strictly increasing

Write a Python program to check if a given list is strictly increasing or not. Moreover, If removing only one element from the list results in a strictly increasing list, we still consider the list true

Input:

n : Number of elements

List1: List of values

Output

Print "True" if list is strictly increasing or decreasing else print "False"

```
def is_strictly_increasing(lst):
    increasing = True
    for i in range(1, len(lst)):
        if lst[i] <= lst[i - 1]:
            increasing = False
            break
    if increasing:
        return True
    else:
        for i in range(len(lst)):
            temp_lst = lst[:i] + lst[i+1:]
            increasing_after_removal = True
            for j in range(1, len(temp_lst)):
                if temp_lst[j] <= temp_lst[j - 1]:
                    increasing_after_removal = False
                    break
            if increasing_after_removal:
                return True
    return False

n = int(input())
List1 = []
for _ in range(n):
    List1.append(int(input()))

result = is_strictly_increasing(List1)

if result:
```



```
    print("True")  
else:  
    print("False")
```



06 - Strings in Python



For example:

Input	Result
-------	--------

rec@123	
---------	--

3	
---	--

3	
---	--

1	
---	--



Ex. No. : 6.1

Date:

Register No: 230701215

Name: Nithiesh S

Count Chars

Write a python program to count all letters, digits, and special symbols respectively from a given string

```
str1=input()
a=0
n=0
s=0
for i in range(len(str1)):
    if (str1[i].isalpha()):
        a+=1
    elif (str1[i].isdigit()):
        n+=1
    else:
        s+=1
print(a)
print(n)
print(s)
```



Sample Input 1
a2b4c6

Sample Output 1
aabbbbcccccc



Ex. No. : 6.2

Date:

Register No: 230701215

Name: Nithiesh S

Decompress the String

Assume that the given string has enough memory. Don't use any extra space(IN-PLACE)

```
str1=input()
```

```
l = [i for i in str1]
```

```
i=0
```

```
while i<len(l):
```

```
    char = l[i]
```

```
    count =0
```

```
    i =i+1
```

```
    while i<len(l) and l[i].isdigit():
```

```
        count =count*10+int(l[i])
```

```
        i +=1
```

```
    print(char*count,end='')
```



Input Format:

The first line contains S1.

The second line contains S2.

The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$

$2 \leq \text{Length of S1, S2} \leq 1000$

Example Input/Output 1:

Input:

```
abcbde  
cdefghbb  
3
```

Output:

```
bcd
```

Note:

b occurs twice in common but must be printed only once.



Ex. No. : 6.3

Date:

Register No: 230701215

Name: Nithiesh S

First N Common Chars

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

```
s1=input()
s2=input()
n=int(input())
char=set()
count=0
for c in s1:
    if c in s2 and c not in char:
        print(c,end="")
        char.add(c)
        count+=1
    if count == n:
        break
```



Sample Input 1
experience
enc

Sample Output 1
xpri



Ex. No. : 6.4

Date:

Register No: 230701215

Name: Nithiesh S

Remove Characters

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

```
s1=input()
s2=input()
s1="".join(i for i in s1 if i not in s2)
print(s1)
```



For example:

Input	Expected
Malayalam is my mother tongue	is my mother tongue
He did a good deed	he good



Ex. No. : 6.5

Date:

Register No: 230701215

Name: Nithiesh S

Remove Palindrome Words

String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

```
l=input().lower()
s1=l.split()
for i in s1:
    if(i[::-1]!=i):
        print(i,end=' ')
```



For example:

Input	Result
Wipro Technologies Bangalore	TECHNOLOGIES
Hello World	WORLD
Hello	LESS



Ex. No. : 6.6

Date:

Register No: 230701215

Name: Nithiesh S

Return Second World in Uppercase

Write a program that takes as input a string (sentence), and returns its second word in uppercase.

For example:

If input is "Wipro Technologies Bangalore" the function should return "TECHNOLOGIES"

If input is "Hello World" the function should return "WORLD"

If input is "Hello" the program should return "LESS"

NOTE 1: If input is a sentence with less than 2 words, the program should return the word "LESS".

NOTE 2: The result should have no leading or trailing spaces.

```
s=input().split()
if(len(s)>=2):
    print(s[1].upper())
else:
    print("LESS")
```



Input:

A&B

Output:

B&A

Explanation: As we ignore '&' and

As we ignore '&' and then reverse, so answer is "B&A".

For example:

Input	Result
-------	--------

A&x#	
------	--

x&A#	
------	--



Ex. No. : 6.7

Date:

Register No: 230701215

Name: Nithiesh S

Revers String

Reverse a string without affecting special characters. Given a string S, containing special characters and all the alphabets, reverse the string without affecting the positions of the special characters.

```
seq =input()
```

```
chars = ['$','%','*','#','^']
```

```
nums = []
```

```
for i in range(len(seq)):
```

```
    if seq[i] not in chars:
```

```
        nums.append(seq[i])
```

```
nums.reverse()
```

```
for j in seq:
```

```
    if j in chars:
```

```
        idx = seq.index(j)
```

```
        nums.insert(idx,j)
```

```
reverse = ''.join(nums)
```

```
print(reverse)
```



For example:

Input	Result
Yn	
PYnative	
True	



Ex. No. : 6.8

Date:

Register No: 230701215

Name: Nithiesh S

String characters balance Test

Write a program to check if two strings are balanced. For example, strings s1 and s2 are balanced if all the characters in the s1 are present in s2. The character's position doesn't matter. If balanced display as "true", otherwise "false".

```
def balance(s1,s2):  
    flag=True  
    for i in s1:  
        if i in s2:  
            pass  
        else:  
            flag=False  
    return flag  
s1=input()  
s2=input()  
if balance(s1,s2)==True:  
    print("True")  
else:  
    print("False")
```



Input:

first
second
first
third
second

then your program should display:

Output:

first
second
third



Ex. No. : 6.9

Date:

Register No: 230701215

Name: Nithiesh S

Unique Names

In this exercise, you will create a program that reads words from the user until the user enters a blank line. After the user enters a blank line your program should display each word entered by the user exactly once. The words should be displayed in the same order that they were first entered. For example, if the user enters:

```
l=[]
try:
    while True:
        s=input()
        if s not in l:
            l.append(s)
except EOFError:
    print('\n'.join(l))
```



Example Input/Output 1:

Input:

vijayakumar.r@rajalakshmi.edu.in

Output:

edu.in
rajalakshmi
vijayakumar.r



Ex. No. : 6.10

Date:

Register No: 230701215

Name: Nithiesh S

Username Domain Extension

Given a string S which is of the format USERNAME@DOMAIN.EXTENSION, the program must print the EXTENSION, DOMAIN, USERNAME in the reverse order.

Input Format:

The first line contains S.

Output Format:

The first line contains EXTENSION.

The second line contains DOMAIN.

The third line contains USERNAME.

Boundary Condition:

1 <= Length of S <= 100

```
s=input()
parts=s.split('@')
username, domain_extension = parts[0], parts[1]
domain, extension = domain_extension.split('.', 1)

print(extension)
print(domain)
print(username)
```





07 - Functions



Example input:

12

Output:

Yes

Explanation

The proper divisors of 12 are: 1, 2, 3, 4, 6, whose sum is $1 + 2 + 3 + 4 + 6 = 16$. Since sum of proper divisors is greater than the given number, 12 is an abundant number.

Example input:

13

Output:

No

Explanation

The proper divisors of 13 is: 1, whose sum is 1. Since sum of proper divisors is not greater than the given number, 13 is not an abundant number.

For example:

Test	Result
<code>print(abundant(12))</code>	Yes
<code>print(abundant(13))</code>	No



Ex. No. : 7.1

Date:

Register No: 230701215

Name: Nithiesh S

Abundant Number

An abundant number is a number for which the sum of its proper divisors is greater than the number itself. Proper divisors of the number are those that are strictly lesser than the number.

Input Format:

Take input an integer from stdin

Output Format:

Return Yes if given number is Abundant. Otherwise, print No

```
def abundant(n):
```

```
    sum1=0
```

```
    for i in range(1,(n//2)+1):
```

```
        if(n%i==0):
```

```
            sum1+=i
```

```
    if(sum1>n):
```

```
        return "Yes"
```

```
    else:
```

```
        return "No"
```



Input Format:

Take a Integer from Stdin

Output Format:

Print Automorphic if given number is Automorphic number, otherwise Not Automorphic

Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic

Example input: 7 Output: Not Automorphic

For example:

Test

Result

print(automorphic(5))

Automorphic



Ex. No. : 7.2

Date:

Register No: 230701215

Name: Nithiesh S

Automorphic number or not

An automorphic number is a number whose square ends with the number itself. For example, 5 is an automorphic number because $5*5=25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display “Invalid input”.

If it is an automorphic number display “Automorphic” else display “Not Automorphic”.

```
def automorphic(n):
```

```
    if n <= 0:
```

```
        return "Invalid input" # Only positive integers are  
valid
```

```
    square = n * n
```

```
    if str(square).endswith(str(n)):
```

```
        return "Automorphic"
```

```
    else:
```

```
        return "Not Automorphic"
```



Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

Test	Result
print(productDigits(1256))	True
print(productDigits(1595))	False



Ex. No. : 7.3

Date:

Register No: 230701215

Name: Nithiesh S

Check Product of Digits

Write a code to check whether product of digits at even places is divisible by sum of digits at odd place of a positive integer.

```
def productDigits(n):
    pro=1
    s1=0
    for i in range(len(str(n))):
        t=n%10
        if((i)%2==0):

            pro*=t
        else:
            s1+=t
        n//=10
    if((pro%s1)==0):
        return "True"

    else:
        return "False"
```



Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

Test	Result
print(christmasDiscount(578))	12



Ex. No. : 7.4

Date:

Register No: 230701215

Name: Nithiesh S

Christmas Discount

An e-commerce company plans to give their customers a special discount for Christmas. They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an python code to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10^{100000}$

```
def christmasDiscount(total_bill):
```

```
    prime_digits = {'2', '3', '5', '7'}
```

```
    total_bill_str = str(total_bill)
```

```
    discount_value = 0
```

```
    for digit in total_bill_str:
```

```
        if digit in prime_digits:
```

```
            discount_value += int(digit)
```

```
    return discount_value
```

```
total_bill = 75320
```

```
discount = christmasDiscount(total_bill)
```



Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value



Ex. No. : 7.5

Date:

Register No: 230701215

Name: Nithiesh S

Coin Change

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

```
def coinChange(n):
```

```
    count=0
```

```
    while n>0:
```

```
        if(n>=4):
```

```
            n-=4
```

```
        elif(n==3):
```

```
            n-=3
```

```
        elif(n==2):
```

```
            n-=2
```

```
        elif(n==1):
```

```
            n-=1
```

```
        count+=1
```

```
    return count
```



Input Format:

Take a number in the form of String from stdin.

Output Format:

Print the difference between sum of even and odd digits

Example input:

1453

Output:

1

Explanation:

Here, sum of even digits is $4 + 3 = 7$

sum of odd digits is $1 + 5 = 6$.

Difference is 1.

Note that we are always taking absolute difference



Ex. No. : 7.6

Date:

Register No: 230701215

Name: Nithiesh S

Difference Sum

Given a number with maximum of 100 digits as input, find the difference between the sum of odd and even position digits.

```
def differenceSum(n):  
    s1=str(n)  
    s_e=0  
    s_o=0  
    for i, digit in enumerate(s1):  
        if(i+1)%2==0:  
            s_e+=int(digit)  
        else:  
            s_o+=int(digit)  
    return abs(s_e - s_o)
```

```
n=1234567890
```

```
d=differenceSum(n)
```



For example:

Test	Result
print(checkUgly(6))	ugly
print(checkUgly(21))	not ugly



Ex. No. : 7.7

Date:

Register No: 230701215

Name: Nithiesh S

Ugly number

A number is considered to be ugly if its only prime factors are 2, 3 or 5.

[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

```
def checkUgly(n):
```

```
    if n <= 0:
```

```
        return "not ugly"
```

```
    while n % 2 == 0:
```

```
        n //= 2
```

```
    while n % 3 == 0:
```

```
        n //= 3
```

```
    while n % 5 == 0:
```

```
        n //= 5
```

```
    if n == 1:
```

```
        return "ugly"
```

```
    else:
```

```
        return "not ugly"
```



08 – Tuple/Set



Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No



Ex. No. : 8.1

Date:

Register No: 230701215

Name: Nithiesh S

Binary String

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

```
a=input()  
c=0  
for i in range(len(a)):  
    if (a[i]!='0' or a[i]!='1'):  
        c=c+1  
  
if c==len(a):  
    print("Yes")  
else:  
    print("No")
```



Examples:

Input: t = (5, 6, 5, 7, 7, 8), K = 13

Output: 2

Explanation:

Pairs with sum K(= 13) are {(5, 8), (6, 7), (6, 7)}.

Therefore, distinct pairs with sum K(= 13) are { (5, 8), (6, 7) }.

Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0



Ex. No. : 8.2

Date:

Register No: 230701215

Name: Nithiesh S

Check Pair

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to **K**.

```
tuple_str = input()
t = tuple(map(int, tuple_str.split(",")))
K = int(input())

distinct_pairs = set()
for i in range(len(t)):
    for j in range(i + 1, len(t)):
        if t[i] + t[j] == K:
            distinct_pairs.add((min(t[i], t[j]), max(t[i], t[j])))

print(len(distinct_pairs))
```



Example 1:

Input: s = "AAAAACCCCCAAAAACCCCCAAAAAGGGTTT"

Output: ["AAAAACCCCC","CCCCCAAAA"]

Example 2:

Input: s = "AAAAAAAAAAAA"

Output: ["AAAAAAAAAA"]

For example:

Input	Result
AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAA



Ex. No. : 8.3

Date:

Register No: 230701215

Name: Nithiesh S

DNA Sequence

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string **s** that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

```
s=input()
if len(s)<=10:
    print()
else:
    sequences={}
    result=[]
    for i in range(len(s)-9):
        sequence=s[i:i+10]
        if sequence in sequences and sequence not in result:
            result.append(sequence)
        else:
            sequences[sequence]=True
    for seq in result:
        print(seq)
```



Example 1:**Input:** nums = [1,3,4,2,2]**Output:** 2**Example 2:****Input:** nums = [3,1,3,4,2]**Output:** 3**For example:**

Input	Result
1 3 4 4 2	4



Ex. No. : 8.4

Date:

Register No: 230701215

Name: Nithiesh S

Print repeated no

Given an array of integers `nums` containing `n + 1` integers where each integer is in the range `[1, n]` inclusive. There is only **one repeated number** in `nums`, return *this repeated number*. Solve the problem using [set](#).

a = input()

b = a.split() # Call split as a function

seen = set()

for num in b:

if num in seen:

print(num)

else:

seen.add(num)



Sample Input:

5 4

1 2 8 6 5

2 6 8 10

Sample Output:

1 5 10

3

Sample Input:

5 5

1 2 3 4 5

1 2 3 4 5

Sample Output:

NO SUCH ELEMENTS

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3



Ex. No. : 8.5

Date:

Register No: 230701215

Name: Nithiesh S

Remove repeated

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

```
a = input().split()
```

```
n1 = input().split()
```

```
n2 = input().split()
```

```
c = set()
```

```
for num in n1:
```

```
    if num not in n2:
```

```
        c.add(num)
```

```
for num1 in n2:
```

```
    if num1 not in n1:
```

```
        c.add(num1)
```

```
c = sorted(map(int, c))
```

```
if c:
```



```
print(" ".join(map(str, c)))  
  
print(len(c))  
  
else:  
  
print("NO SUCH ELEMENTS")
```



Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1



Ex. No. : 8.6

Date:

Register No: 230701215

Name: Nithiesh S

Malfunctioning Keyboard

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.







Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

```
def can_type_word(word, broken_letters):  
    for letter in word:  
        if letter in broken_letters:  
            return False  
    return True  
  
def fully_typed_words(text, broken_letters):  
    words = text.split()  
    fully_typed_count = 0  
  
    for word in words:  
        if can_type_word(word, broken_letters):  
            fully_typed_count += 1
```



```
return fully_typed_count
```



~ 1	! 2	@ 3	# 4	\$ 5	% 6	^ 7	& 8	* 9	(0) -	+ =	 Backspace	
Tab 	Q	W	E	R	T	Y	U	I	O	P	{ [}]	 \ _
Caps Lock 	A	S	D	F	G	H	J	K	L	: ;	" '	Enter 	
Shift 	Z	X	C	V	B	N	M	< ,	> .	? /	Shift 		
Ctrl	Win Key	Alt								Alt	Win Key	Menu	Ctrl

Example 1:

Input: words = ["Hello","Alaska","Dad","Peace"]

Output: ["Alaska","Dad"]

Example 2:

Input: words = ["omk"]

Output: []

Example 3:

Input: words = ["ad sdf","sfd"]

Output: ["ad sdf","sfd"]

For example:

Input	Result
4 Hello Alaska Dad Peace	Alaska Dad



Ex. No. : 8.7

Date:

Register No: 230701215

Name: Nithiesh S

American keyboard

Given an array of strings words, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".

```
rows=["qwertyuiop","asdfghjkl","zxcvbnm"]
```

```
n=int(input())
```

```
words=[]
```

```
for i in range(n):
```

```
    word=input()
```

```
    words.append(word)
```

```
l=[]
```

```
for word in words:
```

```
    flag=False
```

```
    for row in rows:
```

```
        if all(char in row for char in word.lower()):
```

```
            flag=True
```

```
            break
```

```
    if flag:
```

```
        l.append(word)
```




```
if l:  
    for i in range(len(l)):  
        print(l[i])  
else:  
    print("No words")
```



09 – Dictionary



Example 1:

Input: s1 = "this apple is sweet", s2 = "this apple is sour"

Output: ["sweet","sour"]

Example 2:

Input: s1 = "apple apple", s2 = "banana"

Output: ["banana"]

Constraints:

1 <= s1.length, s2.length <= 200

s1 and s2 consist of lowercase English letters and spaces.

s1 and s2 do not have leading or trailing spaces.

All the words in s1 and s2 are separated by a single space.

Note:

Use dictionary to solve the problem

For example:

Input	Result
this apple is sweet this apple is sour	sweet sour



Ex. No. : 9.1

Date:

Register No: 230701215

Name: Nithiesh S

Uncommon words

A sentence is a string of single-space separated words where each word consists only of lowercase letters. A word is uncommon if it appears exactly once in one of the sentences, and does not appear in the other sentence.

Given two sentences s1 and s2, return a list of all the uncommon words. You may return the answer in any order.

```
s1=input().split()
```

```
s2=input().split()
```

```
cow={}
```

```
for i in s1:
```

```
    if i in cow:
```

```
        cow[i]+=1
```

```
    else:
```

```
        cow[i]=1
```

```
for i in s2:
```

```
    if i in cow:
```

```
        cow[i]+=1
```

```
    else:
```



```
cow[i]=1
result=[j for j in cow if cow[j]==1]
for x in result:
    print(x,end=' ')
```



Input : test_dict = {'Gfg' : [6, 7, 4], 'best' : [7, 6, 5]}

Output : {'Gfg': 17, 'best': 18}

Explanation : Sorted by sum, and replaced.

Input : test_dict = {'Gfg' : [8,8], 'best' : [5,5]}

Output : {'best': 10, 'Gfg': 16}

Explanation : Sorted by sum, and replaced.

Sample Input:

2

Gfg 6 7 4

Best 7 6 5

Sample Output

Gfg 17

Best 18

For example:

Input	Result
2 Gfg 6 7 4 Best 7 6 5	Gfg 17 Best 18



Ex. No. : 9.2

Date:

Register No: 230701215

Name: Nithiesh S

Sort Dictionary by Values Summation

Give a dictionary with value lists, sort the keys by summation of values in value list.

```
n=int(input())
d={}
for _ in range(n):
    data=input().split()
    key=data[0]
    values=list(map(int, data[1:]))
    d[key]=values
sum_d={}
for key, values in d.items():
    sum_d[key]=sum(values)
sort=dict(sorted(sum_d.items(),key=lambda item:item[1]))
for key, total in sort.items():
    print(f'{key} {total}')
```



Examples:

```
Input : votes[] = {"john", "johnny", "jackie",  
                  "johnny", "john", "jackie",  
                  "jamie", "jamie", "john",  
                  "johnny", "jamie", "johnny",  
                  "john"};
```

Output : John

We have four Candidates with name as 'John', 'Johnny', 'jamie', 'jackie'. The candidates John and Johnny get maximum votes. Since John is alphabetically smaller, we print it. Use dictionary to solve the above problem

Sample Input:

```
10  
John  
John  
Johnny  
Jamie  
Jamie  
Johnny  
Jack  
Johnny  
Johnny  
Jackie
```

Sample Output:

```
Johnny
```

For example:

Input	Result
10 John John Johnny Jamie Jamie Johnny Jack Johnny Johnny Jackie	Johnny



Ex. No. : 9.3

Date:

Register No: 230701215

Name: Nithiesh S

Winner of Election

Given an array of names of candidates in an election. A candidate name in the array represents a vote cast to the candidate. Print the name of candidates received Max vote. If there is tie, print a lexicographically smaller name.

```
n=int(input())

votes={}

for i in range(n):

    c=input().strip()

    if c in votes:

        votes[c]+=1

    else:

        votes[c]=1

max_v=-1

winner=""

for c,j in votes.items():

    if j>max_v:

        max_v=j

        winner=c
```



```
elif j==max_v and c<winner:  
    winner=c  
print(winner)
```



Sample input:

4

James 67 89 56

Lalith 89 45 45

Ram 89 89 89

Sita 70 70 70

Sample Output:

Ram

James Ram

Lalith

Lalith



Ex. No. : 9.4

Date:

Register No: 230701215

Name: Nithiesh S

Student Record

Create a student dictionary for n students with the student name as key and their test mark assignment mark and lab mark as values. Do the following computations and display the result.

1. Identify the student with the highest average score
2. Identify the student who has the highest Assignment marks
3. Identify the student with the Lowest lab marks
4. Identify the student with the lowest average score

Note:

If more than one student has the same score display all the student names

```
n = int(input())
highest_avg_score = -1
highest_avg_students = []
highest_assignment_score = -1
highest_assignment_students = []
lowest_lab_score = float('inf')
lowest_lab_students = []
lowest_avg_score = float('inf')
lowest_avg_students = []
for _ in range(n):
    name, test_mark, assignment_mark, lab_mark = input().split()
    test_mark = int(test_mark)
    assignment_mark = int(assignment_mark)
    lab_mark = int(lab_mark)
    avg_score = (test_mark + assignment_mark)/3
    if avg_score > highest_avg_score:
        highest_avg_score = avg_score
        highest_avg_students = [name]
```



```
elif avg_score == highest_avg_score:
    highest_avg_students.append(name)
if assignment_mark > highest_assignment_score:
    highest_assignment_score = assignment_mark
    highest_assignment_students = [name]
elif assignment_mark == highest_assignment_score:
    highest_assignment_students.append(name)
if lab_mark < lowest_lab_score:
    lowest_lab_score = lab_mark
    lowest_lab_students = [name]
elif lab_mark == lowest_lab_score:
    lowest_lab_students.append(name)
if avg_score < lowest_avg_score:
    lowest_avg_score = avg_score
    lowest_avg_students = [name]
elif avg_score == lowest_avg_score:
    lowest_avg_students.append(name)

print(' '.join(highest_avg_students))
print(' '.join(highest_assignment_students))
print(' '.join(sorted(lowest_lab_students)))
print(' '.join(lowest_avg_students))
```



The points associated with each letter are shown below:

Points Letters

1 A, E, I, L, N, O, R, S, T and U

2 D and G

3 B, C, M and P

4 F, H, V, W and Y

5 K

8 J and X

10 Q and Z

Sample Input

REC

Sample Output

REC is worth 5 points.



Ex. No. : 9.5

Date:

Register No: 230701215

Name: Nithiesh S

Scramble Score

In the game of Scrabble™, each letter has points associated with it. The total score of a word is the sum of the scores of its letters. More common letters are worth fewer points while less common letters are worth more points.

Write a program that computes and displays the Scrabble™ score for a word. Create a dictionary that maps from letters to point values. Then use the dictionary to compute the score.

A Scrabble™ board includes some squares that multiply the value of a letter or the value of an entire word. We will ignore these squares in this exercise.

```
scrabble={'A':1, 'E':1, 'T':1, 'L':1,'N':1,'O':1,'R':1,'S':1,'U':1,
        'D':2,'G':2,
        'B':3, 'C':3, 'M':3, 'P':3,
        'F':4, 'H':4,'V':4, 'W':4,'Y':4,
        'K':5,
        'J':8,'X':8,
        'Q':10, 'Z':10}
s=input().upper()
points=0
for i in s:
    if i in scrabble:
        points+=scrabble[i]
    else:
        print("Letter not found.....")
print("%s is worth %d points"%(s,points))
```



10 - Searching & Sorting



For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8



Ex. No. : 10.1

Date:

Register No: 230701215

Name: Nithiesh S

Merge Sort

Write a Python program to sort a list of elements using the merge sort algorithm.

```
def bubble_sort(arr):  
    n = len(arr)  
    for i in range(n):  
        for j in range(0, n-i-1):  
            if arr[j] > arr[j+1]:  
                arr[j], arr[j+1] = arr[j+1], arr[j]  
    return arr  
  
num_elements = int(input().strip())  
array = list(map(int, input().strip().split()))  
  
sorted_array = bubble_sort(array)  
  
print(" ".join(map(str, sorted_array)))
```



Input Format

The first line contains an integer, n , the size of the [list](#) a .
The second line contains n , space-separated integers $a[i]$.

Constraints

- $2 \leq n \leq 600$
- $1 \leq a[i] \leq 2 \times 10^6$.

Output Format

You must print the following three lines of output:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

Sample Input 0

3
1 2 3

Sample Output 0

[List](#) is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9



Ex. No. : 10.2

Date:

Register No: 230701215

Name: Nithiesh S

Bubble Sort

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

```
def bubble_sort(arr):
```

```
    n = len(arr)
```

```
    num_swaps = 0
```

```
    for i in range(n):
```

```
        for j in range(0, n-i-1):
```

```
            if arr[j] > arr[j+1]:
```

```
                arr[j], arr[j+1] = arr[j+1], arr[j]
```

```
                num_swaps += 1
```

```
    return arr, num_swaps
```

```
num_elements = int(input().strip())
```

```
array = list(map(int, input().strip().split()))
```

```
sorted_array, num_swaps = bubble_sort(array)
```



```
print(f'List is sorted in {num_swaps} swaps.')
```

```
print(f'First Element: {sorted_array[0]}')
```

```
print(f'Last Element: {sorted_array[-1]}')
```



Input Format

The first line contains a single integer n , the length of A .
The second line contains n space-separated integers,A[i].

Output Format

Print peak numbers separated by space.

Sample Input

5
8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4 12 3 6 8	12 8



Ex. No. : 10.3

Date:

Register No: 230701215

Name: Nithiesh S

Peak Element

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

```
a=int(input())
```

```
lst1=[str(x) for x in input().split(" ")
```

```
lst2=[]
```

```
lst=[]
```

```
g=0
```

```
for i in lst1:
```

```
    if i.isdigit():
```

```
        g=int(i)
```

```
        lst.append(g)
```

```
for i in range(0,a):
```

```
    if(i==0):
```

```
        if(lst[i]>=lst[i+1]):
```

```
            lst2.append(lst[i])
```

```
    elif(i>0 and i<a-2):
```

```
        if(lst[i]>=lst[i-1] and lst[i]>=lst[i+1]):
```

```
            lst2.append(lst[i])
```

```
    elif(i==a-1):
```

```
        if(lst[i]>=lst[i-1]):
```

```
            lst2.append(lst[i])
```

```
for i in lst2:
```

```
    print(i,end=" ")
```



For example:

Input	Result
1 2 3 5 8 6	False
3 5 9 45 42 42	True



Ex. No. : 10.4

Date:

Register No: 230701215

Name: Nithiesh S

Binary Search

Write a Python program for binary search.

```
def binary_search(arr, target):
```

```
    left, right = 0, len(arr) - 1
```

```
    while left <= right:
```

```
        mid = (left + right) // 2
```

```
        if arr[mid] == target:
```

```
            return True
```

```
        elif arr[mid] < target:
```

```
            left = mid + 1
```

```
        else:
```

```
            right = mid - 1
```

```
    return False
```

```
sorted_list = list(map(int, input().split(',')))
```

```
target = int(input())
```

```
sorted_list.sort()
```



```
result = binary_search(sorted_list, target)  
print(result)
```



Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2



Ex. No. : 10.5

Date:

Register No: 230701215

Name: Nithiesh S

Frequency of Elements

To find the frequency of numbers in a list and display in sorted order.

Constraints:

$1 \leq n$, $\text{arr}[i] \leq 100$

```
def count_frequencies(arr):
```

```
    frequency_dict = {}
```

```
    for num in arr:
```

```
        if num in frequency_dict:
```

```
            frequency_dict[num] += 1
```

```
        else:
```

```
            frequency_dict[num] = 1
```

```
sorted_keys = sorted(frequency_dict.keys())
```

```
for key in sorted_keys:
```

```
    print(key, frequency_dict[key])
```

```
# Read input from the user
```

```
input_list = list(map(int, input().split()))
```

```
# Count frequencies and display the result
```

```
count_frequencies(input_list)
```

