

**Ex. No. : 10.1**

**Date: 01.06.24**

**Register No.: 230701245**

**Name Praveen S**

### **Bubble Sort**

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

**Input Format:** The first line reads the number of elements in the array. The second line reads the array elements one by one.

**Output Format:** The output should be a sorted list.

**For example:**

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

**Program:**

```
n=int(input())
k=[int(x) for x in input().split()]
k.sort()
for i in k:
    print(i,end=' ')
```



**Ex. No. : 10.2**

**Date: 01.06.24**

**Register No.: 230701245**

**Name Praveen S**

### **Peak Element**

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element  $a[i]$  is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$  for middle elements.  $[0 < i < n-1]$

$A[i-1] \leq A[i]$  for last element  $[i=n-1]$

$A[i] \geq A[i+1]$  for first element  $[i=0]$

#### **Input Format**

The first line contains a single integer  $n$ , the length of  $A$ .

The second line contains  $n$  space-separated integers,  $A[i]$ .

#### **Output Format**

**Print** peak numbers separated by space.

#### **Sample Input**

5

8 9 10 2 6

#### **Sample Output**

10 6

**For example:**

Input	Result
4 12 3 6 8	12 8



**Program:**

```
a=int(input())

lst1=[str(x) for x in input().split(" ")]

lst2=[]

lst=[]

g=0

for i in lst1:

    if i.isdigit():

        g=int(i)

        lst.append(g)

for i in range(0,a):

    if(i==0):

        if(lst[i]>=lst[i+1]):

            lst2.append(lst[i])

    elif(i>0 and i<a-2):

        if(lst[i]>=lst[i-1] and lst[i]>=lst[i+1]):

            lst2.append(lst[i])

    elif(i==a-1):

        if(lst[i]>=lst[i-1]):

            lst2.append(lst[i])

for i in lst2:

    print(i,end=" ")
```



Ex. No. : 10.3

Date: 01.06.24

Register No.: 230701245

Name: Praveen S

### Merge Sort

Write a Python program to sort a list of elements using the merge sort algorithm.

**For example:**

Input	Result
5 6 5 4 3 8	3 4 5 6 8

**Program:**

```
def merge_sort(arr):  
    if len(arr) > 1:  
        mid = len(arr) // 2  
        left_half = arr[:mid]  
        right_half = arr[mid:]  
        merge_sort(left_half)  
        merge_sort(right_half)  
        i = j = k = 0  
        while i < len(left_half) and j < len(right_half):  
            if left_half[i] < right_half[j]:  
                arr[k] = left_half[i]  
                i += 1  
            else:
```



```

        arr[k] = right_half[j]

        j += 1

        k += 1

while i < len(left_half):

    arr[k] = left_half[i]

    i += 1

    k += 1

while j < len(right_half):

    arr[k] = right_half[j]

    j += 1

    k += 1

def main():

    n = int(input())

    arr = list(map(int, input().split()))

    merge_sort(arr)

    for num in arr:

        print(num, end=" ")

if __name__ == "__main__":

    main()

```



Ex. No. : 10.4

Date: 01.06.24

Register No.: 230701245

Name: Praveen S

## Sum of Two numbers

An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

### Input Format

The first line contains a single integer n , the length of list

The second line contains n space-separated integers, list[i].

The third line contains integer k.

### Output Format

Print Yes or No.

### Sample Input

7

0 1 2 4 6 5 3

1

### Sample Output

Yes

For example:

Input	Result
5 8 9 12 15 3 11	Yes
6 2 9 21 32 43 43 1 4	No



**Program:**

```
n=int(input())  
a=[int(x) for x in input().split()]  
k=int(input())  
flag=0  
if len(a)!=n:  
    print("No")  
    flag=1  
for i in a:  
    for j in a:  
        if i+j==k and flag==0:  
            flag=1  
            print("Yes")  
            break  
if flag==0:  
    print("No")
```



Ex. No. : 10.5

Date: 01.06.24

Register No.: 230701245

Name: Praveen S

### **Frequency of Elements**

To find the frequency of numbers in a list and display in sorted order.

**Constraints:**

$1 \leq n$ ,  $\text{arr}[i] \leq 100$

**Input:**

1 68 79 4 90 68 1 4 5

**output:**

1 2

4 2

5 1

68 2

79 1

90 1

**For example:**

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2





**Program:**

```
lst5=[int(x) for x in input().split(" ")]  
lst=sorted(list(set(lst5)))  
c=0  
for i in lst:  
    c=0  
    for j in lst5:  
        if(i==j):  
            c=c+1  
    print("%d %d"%(i,c))
```

