

CS23532-COMPUTER NETWORKS-LAB MANUAL

Practical -9

Name:Ramya sreevarshini B
RegNo:230701262

AIM:-Implementation of SUBNETTING in CISCO PACKET TRACER simulator.

Classless IP subnetting is a technique that allows for more efficient use of IP addresses by allowing for subnet masks that are not just the default masks for each IP class. This means that we can divide our IP address space into smaller subnets, which can be useful when we have a limited number of IP addresses but need to create multiple networks.

CREATING A NETWORK TOPOLOGY:


The first step in implementing classless IP subnetting is to create a network topology in Packet Tracer. To create a network topology in Packet Tracer, select the "New" button in the top left corner, then select "Network" and "Generic". This will create a blank network topology that we can use to add devices.

ADDING THE DEVICES:

Once we have created our network topology, we can add devices to it. Here, we will be adding routers, switches, and PCs. To add a device, select the device from the bottom left corner and drag it onto the network topology. Then, connect the devices by dragging a cable from one device's port to another device's port.

SUBNETTING:

To subnet the network address of 192.168.1.0/24 to provide enough space for at least 5 addresses for end devices, the switch, and the router, we can use a /27 subnet mask. This will give us 8 subnets with 30 host addresses each.



The IP addressing for the network shown in the topology can be as follows:

- Router R1:
- GigabitEthernet0/0: 192.168.1.1
- GigabitEthernet0/1: 192.168.2.1
- Switch S1:
- FastEthernet0/1: 192.168.1.0/27
- PC1: 192.168.1.11
- PC2: 192.168.1.12
- PC3: 192.168.1.13
- PC4: 192.168.1.14
- PC5: 192.168.1.15
- FastEthernet0/2: 192.168.2.0/27
- PC1: 192.168.2.11
- PC2: 192.168.2.12
- PC3: 192.168.2.13
- PC4: 192.168.2.14
- PC5: 192.168.2.15
- Router R2:
- FastEthernet0/0: 192.168.3.1
- FastEthernet0/1: 192.168.4.1
- Switch S2:
- FastEthernet0/1: 192.168.3.0/27

- PC1: 192.168.3.11
- PC2: 192.168.3.12
- PC3: 192.168.3.13
- PC4: 192.168.3.14
- PC5: 192.168.3.15
- FastEthernet0/2: 192.168.4.0/27
- PC1: 192.168.4.11
- PC2: 192.168.4.12
- PC3: 192.168.4.13
- PC4: 192.168.4.14
- PC5: 192.168.4.15

CONFIGURING THE DEVICES:

Now that we have added our devices and connected them, we can start configuring them. We will start by configuring the router. Right-click on the router and select "CLI". This will open the command-line interface (CLI) for the router. In the CLI, enter the following commands: #enable

```
#confi
```

```
gure
```

```
termin
```

```
al
```

```
#interf
```

```
ace
```

```
FastEt
```

```
hernet
```

```
0/0
```

```
#ip address {IP
```

```
address} {subnet
```

```
mask} #no
```

```
shutdown
```

```
#exit
```

```
interface FastEthernet0/1
```

```
ip address {IP address} {subnet mask}
```

```
n
```

```
o
```

```
s
```

```
h
```

```
u
```

```
t
```

```
d
```

```
o
```

```
w
```

```
n
```

```
e
```

```
x
```

```
i
```

```
t
```

Replace "{IP address}" and "{subnet mask}" with your desired IP address and subnet mask. The first interface, FastEthernet0/0, will be connected to the switch, while the second interface, FastEthernet0/1, will be connected to one of the PCs. These commands configure the router's interfaces with IP addresses and subnet masks.

Next, we will configure the switch. Right-click on the switch and select "CLI". In the CLI, enter the following commands:

```
enable
configure terminal
interface
FastEthernet
0/1
switch
port
mode
access
exit
```

```
interface
FastEthernet
0/2
switch
port
mode
access
exit
```

These commands configure the switch to operate in access mode on its two ports, which are connected to the two PCs.

Finally, we will configure the PCs. Right-click on each PC and select "Config". In the configuration window, enter the IP address, subnet mask, default gateway, and DNS server information. The IP address and subnet mask should be within the same subnet as the router's FastEthernet0/1 interface.







To configure the GigabitEthernet interface on the router, you can follow these steps:

1. Right-click on the router and select "CLI".
2. Enter the

```
following
commands: enable
configure terminal
interface GigabitEthernet0/0
ip address {IP
```

TESTING THE NETWORK:

Now that our network topology is configured, we can test the network. Open a command prompt on each PC and try to ping the other PC. If the ping is successful, then the network is functioning properly. We can also use the "ping" command to test connectivity between the router and the PCs.

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num
	Successful	PC4(2)	Router2	ICMP		0.000	N	12
	Successful	PC4(2)	PC2(1)(1)	ICMP		0.000	N	13
	Successful	PC0	Router0	ICMP		0.000	N	14

Student observation:

1. Write down your understanding of subnetting.

Subnetting is the process of dividing a large network into smaller sub-networks (subnets). It helps in efficient IP address utilization and improves network management.

2. What is the advantage of implementing subnetting within a Network?

Subnetting enhances network performance, security, and organization. It also reduces network congestion by limiting broadcast traffic within each subnet.

3. Find out whether subnetting is implemented in your college. If yes, draw and list down the subnets used with IP addresses.

Yes, colleges often implement subnetting to separate departments (e.g., Admin, Labs, Library).

Example:

- Subnet 1 (Admin): 192.168.1.0/26
- Subnet 2 (Labs): 192.168.1.64/26
- Subnet 3 (Library): 192.168.1.128/26

(Draw a diagram in your notebook showing a main router connected to three subnet networks labeled with these IP ranges.)

RESULT:

Thus the implementation of SUBNETTING in CISCO PACKET TRACER simulator has been studied successfully.

