

04 - Divide and Conquer

Ex. No. : 4.1

Date: 03.09.24

Register No.: 230701336

Name: SRI AKASH U G

Problem Statement:

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

ALGORITHM:

Step 1: Start

Step 2: Read the value of n from the user and initialize an array arr of size n. Read n values into the array.

Step 3: Check if the first element of arr is 0. If true, print n and exit the program.

Step 4: Call the divide function with arr, 0, and n-1 to find the index of the first occurrence of 0.

Step 5: If the index is not 0, print the value of n - index, which represents the count of 0s in the array. Otherwise, print the index.

Step 6: End

PROGRAM:

```
#include <stdio.h> int divide(int  
[],int,int); int divide(int a[],int left,int  
right)  
{  
    int mid=0; mid=left+(right-left)/2;  
    if  
    (a[0]==0) return 0; else if  
    (a[right-1]==1) return right; if  
    ((a[mid]==0) && (a[mid-1]==0))  
    return divide(a,0,mid); else if  
    (a[mid]==0) return mid; else return  
    divide(a,mid+1,right);  
}  
int main()  
{  
    int n; scanf("%d",&n);  
    int  arr[n]; for (int  
    i=0;i<n;i++)
```

```
{  
    scanf("%d",&arr[i]);  
}  
int zero=divide(arr,0,n); printf("%d",nzero);  
}
```

OUTPUT:

	Input	Expected	Got	
✓	5 1 1 1 1 0 0	2	2	✓
✓	10 1 1 1 1 1 1 1 1 1 1 1 1	0	0	✓
✓	8 0 0 0 0 0 0 0 0 0	8	8	✓
✓	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

RESULT :

Hence the above program has been executed successfully.

Ex. No. : 4.2

Date: 03.09.24

Register No.: 230701336

Name: SRI AKASH U G

AIM:

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\frac{n}{2}$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: 3

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: 2

For example:

Input	RESULT
3 3 2 3	3


```

{
    int mid=left+(right-left)/2; if
    (a[mid]!=key)
    {
        Count(a,left,mid,key);
        Count(a,mid+1,right,key);
    }
    else
    {
        c++;
    }
    return c;
}

```

```

int main()
{
    int n; scanf("%d",&n); int
    arr[n]; for (int
    i=0;i<n;i++)

```

```

scanf("%d",&arr[i]); int
k=arr[0]; if
(Count(arr,0,n,k)>n/2)
printf("%d",k); else
{
    for (int i=0;i<n/2;i++) if
        (arr[i]!=k)
        {
            printf("%d",k); break;
        }
}
}

```

OUTPUT:

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

RESULT :

Hence the above program has been executed successfully.

Ex. No. : 4.3

Date: 03.09.24

Register No.: 230701336

Name: SRI AKASH U G

AIM:

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

ALGORITHM:

Step 1: Start

Step 2: Read the value of n from the user and initialize an array arr of size n. Read n values into the array.

Step 3: Read the integer x from the user, which will be used to find the floor value.

Step 4: Call the search function with arr, x, 0, and n-1 to find the largest element in arr that is less than or equal to x.

Step 5: Print the floor value returned by the search function.

Step 6: End

PROGRAM:

```
#include<stdio.h> int
search(int[],int,int,int); int search(int
arr[],int x,int left,int right)
{
    int mid=left+(right-left)/2;
    if(arr[mid]<=x)
    {
        int max = arr[mid];
        for(int i=0;i<mid;i++){
            if(arr[i]>=max) max=arr[i];
        }
    }
}
```

```

        return max;
    }
    else if(arr[mid]>x)
    {
        return search(arr,x,left,mid);
    }
    else
        return search(arr,x,mid+1,right);
}

int main()
{
    int n,x,floor;
    scanf("%d",&n); int
    arr[n]; for(int i=0;i<n;i++){
        scanf("%d",&arr[i]);
    }

    scanf("%d",&x); floor =
    search(arr,x,0,n-1); printf("%d",floor);
    return
    0;
}

```

OUTPUT:

	Input	Expected	Got	
✓	6 1 2 8 10 12 19 5	2	2	✓
✓	5 10 22 85 108 129 100	85	85	✓
✓	7 3 5 7 9 11 13 15 10	9	9	✓

Passed all tests! ✓

RESULT :

Hence the above program has been executed successfully.

Ex. No. : 4.4

Date: 03.09.24

Register No.: 230701336

Name: SRI AKASH
U G

AIM:

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as “No”.

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value “x”)

ALGORITHM:

Step 1: Start

Step 2: Read the value of n from the user and initialize an array arr of size n. Read n values into the array.

Step 3: Read the integer x from the user, which represents the target sum.

Step 4: Call the twosum function with arr, 0, n-1, and x to find two numbers in the array that add up to x.

Step 5: If a pair is found, print the two numbers; otherwise, print "No" to indicate that no such pair exists.

Step 6: End

PROGRAM:

```
#include<stdio.h> void twosum(int arr[],int
left,int right,int x){ if (left >= right){ printf("No");
return;} int sum=arr[left]+arr[right]; if
(sum==x){ printf("%d\n",arr[left]);
printf("%d\n",arr[right]);

}

else if(sum<x){ twosum(arr,left+1,right,x);
}

else{ twosum(arr,left,right-
1,x);
```

```
    }  
}  
  
int main(){ int n,x;  
    scanf("%d",&n); int arr[n];  
    for (int i=0;i<n;i++){  
        scanf("%d",&arr[i]);  
    }  
    scanf("%d",&x);  
    twosum(arr,0,n-1,x); return  
    0;  
}
```

OUTPUT:

	Input	Expected	Got	
✓	4 2 4 8 10 14	4 10	4 10	✓
✓	5 2 4 6 8 10 100	No	No	✓

Passed all tests! ✓

RESULT :

Hence the above program has been executed successfully..

Ex. No. : 4.5

Date: 03.09.24

Register No.: 230701336

Name: SRI AKASH U G

AIM:

Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n The next n lines contain the elements.

Output:

Sorted list of elements For
example:

Input	RESULT
5 67 34 12 98 78	12 34 67 78 98

ALGORITHM:

Step 1: Start

Step 2: Read the value of n from the user and dynamically allocate an array arr of size n. Read n values into the array.

Step 3: Call the q_sort function with arr, 0, and n-1 to sort the array using the Quick Sort algorithm.

Step 4: In the q_sort function, select a pivot and partition the array into two halves. Recursively apply the same sorting process to both halves.

Step 5: Once sorted, iterate through the array and print the sorted values.

Step 6: End

PROGRAM:

```
#include<stdio.h> void quicksort(int  
arr[],int left,int right){ if(left<right){ int  
j=right; int i=left; int pivot=left;  
while(i<j){ while(arr[i]<=arr[pivot]){ i++;}  
while(arr[j]>arr[pivot]){ j--; } if(i<j){  
    int temp=arr[i];  
    arr[i]=arr[j]; arr[j]=temp;  
}  
}
```

OUTPUT:

	Input	Expected	Got	
✓	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✓
✓	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✓
✓	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✓

Passed all tests! ✓

Correct
Marks for this submission: 1.00/1.00.

RESULT :

Hence the above program has been executed successfully..