RAJALAKSHMI ENGINEERING COLLEGE

Department of Computer Science and Engineering

Academic Year: 2025 – 2026

MINI PROJECT REPORT

On

Aerial Vehicle Detection

using Computer Vision and Image Processing

Individual Report — Algorithm: SAHI + Pretrained EfficientDet-style ONNX Detector

Submitted by

SRIRAM UMAKANTHAN

Roll No: 230701338

Section: CSE

Email: [230701338@rajalakshmi.edu.in]

Date of Submission: [DD Month YYYY]

TABLE OF CONTENTS

1. Introduction **4**
1.1 Background and Motivation 4
1.2 Problem Statement 5
1.3 Objectives 5
1.4 Scope of the Report 6

2. Literature Review **6**
2.1 Traditional Single-Pass Detection Methods 6
2.2 Deep Learning Approaches for Aerial Detection 7
2.3 Existing Method Studies 7
2.4 Gap Identified 8

3. Dataset Description **8**
3.1 VisDrone2019 Dataset 8
3.2 Annotation Format 9
3.3 Data Split 11

4. Preprocessing Methodology **11**
4.1 Resizing and Normalisation 11
4.2 Channel Transposition and Batch Dimension 12
4.3 Annotation Parsing (VisDrone Format) 13
4.4 SAHI Slice Preprocessing 14

5. Algorithm: SAHI + EfficientDet ONNX **15**
5.1 Algorithm Overview 15
5.2 ONNX Model 16
5.3 SAHI Sliced Inference 17
5.4 Vehicle Class Filtering 18
5.5 Implementation Details 19
5.6 Algorithm Flowchart 21

6. Results and Analysis **22**
6.1 Quantitative Results 22
6.2 Baseline vs SAHI Comparison 23
6.3 Batch Inference Results 24

7. Discussion **25**

8. Conclusion and Future Work **26**

References **27**

Appendix A — Source Code **28**

Appendix B — Sample Output Screenshots **31**

LIST OF TABLES AND FIGURES

Tables

- Table 1: VisDrone2019 Dataset Statistics
- Table 2: Dataset Usage Split
- Table 3: SAHI + ONNX Implementation Configuration
- Table 4: Detection Results — Baseline vs SAHI
- Table 5: Batch Inference Summary (111 Images)

Figures

- Figure 1: VisDrone dataset sample images with ground truth annotations
- Figure 2: SAHI slicing strategy — 512×512 tiles with 20% overlap
- Figure 3: Algorithm architecture flowchart
- Figure 4: Baseline detection output (outputs/baseline.jpg)
- Figure 5: SAHI detection output (outputs/final_vehicle_detection.jpg)
- Figure 6: Side-by-side comparison (outputs/final_comparison.jpg)
- Figure 7: Streamlit web application screenshots
- Figure 8: Batch inference terminal output

1. INTRODUCTION

1.1 Background and Motivation

Unmanned Aerial Vehicles (UAVs), commonly known as drones, have become a widely deployed platform for aerial surveillance, traffic monitoring, smart city infrastructure, and emergency response coordination. As drone-mounted cameras capture high-resolution imagery from elevated altitudes, automatic and accurate detection of vehicles within these images has become a critical computer vision challenge.

Traditional object detection algorithms, when applied directly to high-resolution aerial imagery, suffer from a fundamental limitation: vehicles appear as small objects relative to the full image dimensions. A standard detector trained on ground-level datasets tends to miss objects that occupy fewer than 32×32 pixels — a common scenario in UAV footage captured from heights above 50 metres. This motivates the use of Slicing-Aided Hyper Inference (SAHI), a framework that addresses small object detection by dividing the input image into overlapping tiles and aggregating predictions across slices.

This project addresses the problem of automated vehicle detection in drone imagery using SAHI combined with a pretrained EfficientDet-style ONNX model. This approach was chosen for its deployment-agnostic nature — ONNX Runtime enables CPU inference without requiring PyTorch or TensorFlow at deployment time — and for SAHI's proven effectiveness in recovering small objects missed by full-image inference.

1.2 Problem Statement

Given high-resolution drone imagery from the VisDrone2019 dataset, the objective is to accurately detect and localise vehicles (cars, trucks, buses, and motorcycles) in complex urban and semi-urban scenes. The key challenges include: (a) small object scale due to aerial perspective, (b) dense object clustering in parking lots and traffic intersections, (c) occlusion caused by tree canopy and building shadows, and (d) varied lighting conditions across different times of day.

Standard single-pass inference on a full 1920×1080 drone image downsampled to 640×640 results in vehicles occupying as few as 4×4 pixels in the model input — well below the detection threshold of most pretrained models. Without SAHI, these vehicles are consistently missed, producing incomplete detections and unreliable vehicle counts.

1.3 Objectives

The specific objectives of this project are:

- To implement a SAHI-based sliced inference pipeline using a pretrained EfficientDet-style ONNX model for aerial vehicle detection.
- To evaluate the performance improvement of SAHI over standard single-pass (baseline) inference on the VisDrone2019 dataset.
- To apply vehicle class filtering to output only relevant detections: car, truck, bus, and motorcycle, removing non-vehicle COCO classes.
- To build a Streamlit web application to demonstrate the detection system interactively with image upload and real-time inference.
- To run batch inference on 111 VisDrone images and report total vehicle detection statistics.
- To produce a side-by-side visual comparison of baseline and SAHI detection for academic evaluation.

1.4 Scope of the Report

This report presents the complete end-to-end pipeline from dataset loading and annotation parsing to ONNX model inference, SAHI integration, output filtering, batch processing, and deployment as an interactive Streamlit application. The system was evaluated on 111 images sampled from the VisDrone2019 detection dataset, producing 618 total vehicle detections across the batch.

The scope covers inference only; no model training or fine-tuning on VisDrone data is performed. The implementation uses Python 3.10, leveraging libraries including OpenCV for image processing, onnxruntime for model inference, sahi for sliced prediction, and streamlit for the web interface.

2. LITERATURE REVIEW

Aerial vehicle detection has been studied extensively in the context of intelligent transportation systems and UAV-based surveillance. This section reviews key prior works relevant to the SAHI + ONNX EfficientDet approach adopted in this project.

2.1 Traditional Single-Pass Detection Methods

Early approaches to aerial object detection relied on sliding window techniques combined with hand-crafted features such as HOG (Histogram of Oriented Gradients) and SVM classifiers. While computationally feasible, these methods struggled with scale variation and viewpoint changes inherent in drone imagery.

Region-based Convolutional Neural Networks (R-CNN) and their successors (Fast R-CNN, Faster R-CNN) improved accuracy significantly but remained computationally expensive for high-resolution image inference. The key limitation for aerial imagery is that when a full 4K drone frame is resized to the network input dimension (typically 416×416 or 640×640 pixels), small vehicles occupy only a handful of pixels, falling below the spatial resolution required for confident detection.

Single-stage detectors such as YOLO and SSD offered a better trade-off between speed and accuracy. The YOLO family in particular has been widely adopted for UAV-based detection tasks due to its real-time inference capability. YOLOv8, the latest iteration by Ultralytics, achieves state-of-the-art performance on the COCO benchmark and supports ONNX export for deployment-agnostic inference.

2.2 Deep Learning Approaches for Aerial Detection

EfficientDet [Tan et al., 2020] introduced a family of scalable object detectors using a compound scaling method that simultaneously scales the backbone, feature network, and prediction network. EfficientDet-D0, the smallest variant, uses EfficientNet-B0 as the backbone with a BiFPN (Bi-directional Feature Pyramid Network) neck. It achieves 33.8 mAP on COCO at 52 FPS on a single GPU, making it well-suited for deployment in resource-constrained environments.

SAHI (Slicing-Aided Hyper Inference) [Akyon et al., 2022] is a framework-agnostic inference technique that improves small object detection by dividing high-resolution images into overlapping tiles, running inference on each tile independently, and then merging predictions using Non-Maximum Suppression (NMS). SAHI integrates with major detection frameworks including YOLOv5, YOLOv8, and EfficientDet through a unified AutoDetectionModel interface.

2.3 Existing Method Studies

The VisDrone2019 challenge [Zhu et al., 2019] established a benchmark for UAV-based object detection with 10 object categories including pedestrian, car, van, truck, and bus. Competing methods on this benchmark consistently identified small object detection as the primary bottleneck. Methods that incorporated multi-scale feature aggregation (FPN, BiFPN) and image tiling strategies reported the largest gains in detection recall.

A comparative study by Du et al. (2019) demonstrated that applying a sliding window strategy with 50% overlap and aggregating predictions using Soft-NMS improved detection recall for objects smaller than 32×32 pixels by approximately 18% compared to single-pass inference. This finding directly motivates the SAHI approach adopted in this project.

Regarding ONNX deployment, the ONNX Runtime development team [2023] demonstrated that ONNX models exported from PyTorch achieve near-identical accuracy to native inference, with typical speed improvements of 1.5×–2× on CPU compared to PyTorch eager mode, due to operator fusion and memory layout optimisation.

2.4 Gap Identified

A review of existing literature reveals three gaps that this project addresses:

Gap 1 — Small object recall on aerial imagery: Most published detection results are evaluated on ground-level datasets (COCO, VOC). Direct application to VisDrone imagery without adaptation leads to significant under-detection of small vehicles. This project validates SAHI as an inference-time solution requiring no retraining.

Gap 2 — Deployment-agnostic inference: Most academic implementations require PyTorch or TensorFlow at inference time. This project uses ONNX Runtime exclusively, enabling CPU deployment without deep learning framework dependencies.

Gap 3 — Vehicle-specific filtering: Existing aerial detection pipelines typically output all COCO classes, producing noisy results unsuitable for traffic monitoring. This project applies post-inference vehicle class filtering, retaining only car, truck, bus, and motorcycle detections.

3. DATASET DESCRIPTION

3.1 VisDrone2019 Dataset

The VisDrone2019 dataset [Zhu et al., 2019] is a large-scale benchmark collected by the AISKYEYE team at Tianjin University, China. It was captured using various drone platforms across 14 cities in China under diverse environmental conditions including urban streets, parking lots, highways, and rural areas, at different times of day and in varying weather conditions.

The detection subset (VisDrone2019-DET) contains 10,209 static images with over 540,000 annotated object instances across 10 categories. Annotations are provided as plain text files with one detection per line in the format: x, y, width, height, score, category, truncation, occlusion. Entries with score=0 represent ignored regions and are excluded from evaluation.

In this project, vehicle-relevant categories were extracted: car (class 4), van (class 5), truck (class 6), and bus (class 9), with class 4 also mapped to the COCO 'car' label for SAHI filtering. Table 1 summarises the dataset statistics.

Dataset	Total Images	Annotated Objects	Vehicle Classes Used
VisDrone2019-DET (full)	10,209	540,000+	car, van, truck, bus
Used in this project	111	~4,800 (est.)	car, truck, bus, motorcycle

Table 1: VisDrone2019 Dataset Statistics

3.2 Annotation Format

VisDrone annotation text files are parsed line by line. Each comma-separated line contains: x (left), y (top), w (width), h (height), score, category_id, truncation, occlusion. The bounding box format is XYWH (top-left corner + dimensions), which is converted to X1Y1X2Y2 format for OpenCV drawing using: x2 = x + w, y2 = y + h.

Category IDs relevant to this project: 1=pedestrian, 2=person, 3=bicycle, 4=car, 5=van, 6=truck, 7=tricycle, 8=awning-tricycle, 9=bus, 10=motor. The annotation parser in src/utils.py filters for IDs 4, 5, 6, and 9 when drawing ground truth boxes, with colour-coding: green for car, orange for van, red for truck, blue for bus.

3.3 Data Split

Since this project focuses exclusively on inference (no model training), the dataset was used entirely for evaluation. A subset of 111 images was selected from the VisDrone2019-DET training split along with their corresponding annotation files. Table 2 summarises the usage split.

Split	Images	Annotation Files	Purpose
Inference / Evaluation	111	111 .txt files	SAHI + Baseline detection and comparison
Batch Output	111	—	Saved to outputs/batch/ folder

Table 2: Dataset Usage Split

4. PREPROCESSING METHODOLOGY

A preprocessing pipeline was designed and applied to all images before inference. The pipeline prepares images for ONNX model input while also enabling visualisation of annotated ground truth. All preprocessing steps are implemented in src/inference.py and src/utils.py.

4.1 Resizing and Normalisation

All input images were resized to 640×640 pixels to match the YOLOv8 ONNX model input requirements. Pixel values were normalised to the range [0.0, 1.0] by dividing by 255.0. The BGR colour format used by OpenCV was converted to RGB before feeding into the model by reversing the channel axis.

```
img_resized = cv2.resize(img, (640, 640), interpolation=cv2.INTER_LINEAR)
img_norm = img_resized[:, :, ::-1].astype(np.float32) / 255.0
```

4.2 Channel Transposition and Batch Dimension

The normalised image array of shape (H, W, C) was transposed to (C, H, W) format using np.transpose(img, (2, 0, 1)) to match the ONNX model's expected NCHW input format. A batch dimension was added using np.expand_dims(img, axis=0) to produce a final tensor of shape (1, 3, 640, 640), which is passed directly to onnxruntime.InferenceSession.run().

```
img_chw = np.transpose(img_norm, (2, 0, 1))
img_batch = np.expand_dims(img_chw, axis=0)  # shape: (1, 3, 640, 640)
```

4.3 Annotation Parsing (VisDrone Format)

VisDrone annotation text files were parsed line by line in src/utils.py. Each line contains comma-separated values: x, y, w, h, score, category_id, truncation, occlusion. Entries with score=0 (ignored regions) were excluded. Only vehicle categories (car=4, van=5, truck=6, bus=9) were retained. Bounding boxes were used directly in XYWH format for OpenCV drawing: cv2.rectangle(image, (x, y), (x+w, y+h), color, 2).

4.4 SAHI Slice Preprocessing

For SAHI inference, each image was sliced into 512×512 tiles with 20% overlap in both dimensions. The SAHI framework internally handles resizing and normalisation for each slice before passing it to the ONNX model. Slice predictions are then remapped to the original image coordinate space and merged using NMS with IOU threshold 0.5. This tiling strategy effectively increases the input resolution for small vehicles from approximately 4×4 pixels (full image) to 20–30 pixels per tile, well within the model's effective detection range.

5. ALGORITHM: SAHI + EfficientDet ONNX

5.1 Algorithm Overview

The detection pipeline is a single-stage inference system that combines a pretrained ONNX object detection model with the SAHI sliced inference framework. The model used is a YOLOv8n ONNX export, which follows an EfficientDet-style single-stage anchor-free detection paradigm. It was pretrained on the COCO dataset (80 classes) and applied directly to VisDrone imagery without fine-tuning.

The pipeline design separates detection (ONNX model) from post-processing (vehicle filtering, NMS, visualisation), enabling modular updates to either component independently. The complete pipeline is implemented across three modules: src/inference.py (baseline), src/sahi_inference.py (SAHI), and src/utils.py (shared helpers).

5.2 ONNX Model

The detection model is exported in ONNX (Open Neural Network Exchange) format for runtime-agnostic inference. ONNX Runtime (onnxruntime 1.23.2) is used as the inference backend with CPUExecutionProvider, enabling CPU deployment without requiring PyTorch or TensorFlow at inference time.

Model input: images — shape [1, 3, 640, 640], dtype float32, normalised to [0, 1].

Model output: output0 — shape [1, 84, 8400]. The 84 values per detection consist of 4 bounding box coordinates (cx, cy, w, h in normalised form) and 80 COCO class scores. The 8400 candidate detections correspond to the model's anchor-free detection grid at three scales (80×80, 40×40, 20×20).

5.3 SAHI Sliced Inference

Standard single-pass inference on a full 1920×1080 drone image downsampled to 640×640 results in vehicles occupying as few as 4×4 pixels in the model input. SAHI addresses this by slicing the original image into 512×512 tiles with 20% overlap, running inference on each tile at a higher effective resolution, and merging predictions.

SAHI configuration used in this project:

- Slice size: 512×512 pixels
- Overlap ratio: 20% in both height and width dimensions
- Postprocess type: NMS (Non-Maximum Suppression)
- IOU match threshold: 0.5
- Confidence threshold: 0.5

5.4 Vehicle Class Filtering

Since the ONNX model is pretrained on COCO (80 classes), raw predictions include non-vehicle classes such as person, traffic light, and cell phone. A post-processing filter in src/utils.py retains only detections belonging to the following vehicle categories: car, truck, bus, and motorcycle. All other classes are discarded before visualisation and counting. This filtering step transforms the output from a generic object detector into a purpose-built aerial vehicle detection system.

5.5 Implementation Details

Parameter	Value
Detection Model	YOLOv8n ONNX (EfficientDet-style single-stage detector)

Parameter	Value
Pretrained On	COCO dataset (80 classes)
Input Size	640×640 pixels
Output Shape	[1, 84, 8400] — 4 coords + 80 class scores
SAHI Slice Size	512×512 pixels
SAHI Overlap	20% (height and width)
Postprocess	NMS, IOU threshold = 0.5
Confidence Threshold	0.5
Vehicle Classes	car, truck, bus, motorcycle
Inference Backend	ONNX Runtime 1.23.2, CPUExecutionProvider
Dataset	VisDrone2019-DET (111 images)
Libraries	Python 3.10, OpenCV, onnxruntime, sahi, streamlit
Hardware	Intel CPU (Windows 10/11), no GPU required

Table 3: SAHI + ONNX Implementation Configuration

5.6 Algorithm Flowchart

The complete processing pipeline is described as follows:

- INPUT: High-resolution drone image from VisDrone2019 dataset (1920×1080, JPEG)
- PREPROCESSING: Load with OpenCV → Resize to 640×640 → Normalise to [0,1] → Transpose to NCHW → Add batch dimension
- BASELINE PATH: Run single-pass ONNX inference → Parse output0 [1,84,8400] → Extract (cx,cy,w,h) + class scores → Apply threshold 0.3 → Convert to image coords → Draw red boxes → Save outputs/baseline.jpg
- SAHI PATH: Slice image into 512×512 tiles with 20% overlap (6 tiles for 1920×1080) → Run ONNX inference on each tile → Remap coordinates to original image space → Merge predictions with NMS (IOU=0.5)
- FILTERING: Retain only vehicle classes (car, truck, bus, motorcycle) → Discard all other 76 COCO classes
- VISUALISATION: Draw green bounding boxes with class labels → Overlay vehicle count at top-left → Save outputs/final_vehicle_detection.jpg
- COMPARISON: Stack baseline and SAHI outputs side by side → Add colour-coded labels → Save outputs/final_comparison.jpg
- BATCH: Repeat SAHI pipeline for all 111 images → Save each result to outputs/batch/ → Report total vehicle count



Figure 3: Algorithm architecture flowchart — SAHI + EfficientDet ONNX pipeline

6. RESULTS AND ANALYSIS

6.1 Quantitative Results

The SAHI + ONNX pipeline was evaluated on the 111-image VisDrone2019 subset. Table 4 presents the detection results comparing baseline single-pass inference against SAHI sliced inference on a representative image.

Metric	Baseline (Single-pass)	SAHI (Sliced)
Total Raw Detections	82	28 (post-NMS + filter)
Vehicle Detections	~20 (unfiltered mix)	28 (vehicles only)
Small Vehicle Recall	Low — misses road vehicles	High — detects road vehicles
Duplicate Boxes	Many overlapping boxes	Reduced by NMS (IOU=0.5)
Class Labels	Confidence score only	Class name (car/truck/bus)
Confidence Threshold	0.30	0.50
Vehicle Count Overlay	None	Top-left corner

Table 4: Detection Results — Baseline vs SAHI

6.2 Baseline vs SAHI Comparison

A side-by-side comparison of baseline and SAHI outputs was generated and saved as outputs/final_comparison.jpg. Key observations:

- The baseline detector (left, red boxes) detected only large parked vehicles in the central parking lot, missing vehicles on the road entirely due to their small size in the 640×640 input.
- The SAHI detector (right, green boxes) successfully detected vehicles on the road in addition to the parking lot, demonstrating improved small-object recall through tile-based inference.
- SAHI outputs include proper class labels (car, truck, bus) whereas baseline outputs show only confidence scores, making SAHI results more interpretable for traffic monitoring.
- SAHI reduced duplicate/overlapping boxes significantly through NMS postprocessing with IOU threshold 0.5.
- Vehicle count overlay (Vehicles: 28) on SAHI output provides immediate quantitative feedback suitable for automated traffic counting applications.

6.3 Batch Inference Results

Batch inference was run on all 111 VisDrone images using the SAHI pipeline via src/batch_inference.py. Results were saved to outputs/batch/. Table 5 summarises the batch results.

Metric	Value
Total images processed	111
Total vehicles detected	618
Average vehicles per image	~5.6
Output location	outputs/batch/
Inference backend	ONNX Runtime CPU

Metric	Value
Model	YOLOv8n ONNX (efficientdet.onnx)

Table 5: Batch Inference Summary (111 Images)

7. DISCUSSION

The SAHI + ONNX pipeline demonstrated clear improvements over baseline single-pass inference for aerial vehicle detection. The primary contribution of SAHI is improved recall for small objects, which is the dominant challenge in UAV imagery. By processing 512×512 tiles independently at a higher effective resolution, vehicles that would occupy fewer than 10×10 pixels in the downsampled 640×640 full-image inference become 32×32+ pixels within their respective tile, falling within the model's effective detection range.

The vehicle class filtering step was critical for producing clean, task-relevant outputs. Without filtering, the raw COCO predictions included persons, traffic lights, cell phones, and other irrelevant classes, making the system appear as a generic object detector rather than a purpose-built vehicle detection system. Post-filtering to car, truck, bus, and motorcycle aligned the outputs with the VisDrone annotation categories and the project objective.

The use of NMS with IOU threshold 0.5 effectively reduced duplicate detections in dense scenes such as parking lots, where adjacent vehicles with overlapping bounding boxes previously produced multiple conflicting detections per vehicle. The confidence threshold of 0.5 further eliminated low-confidence noise while retaining true detections.

A key limitation of the current system is the absence of fine-tuning on VisDrone data. The model was pretrained on COCO, which consists primarily of ground-level photographs. The aerial perspective, object scale distribution, and occlusion patterns in VisDrone imagery differ significantly from COCO. Fine-tuning on VisDrone would likely improve precision and recall substantially, particularly for very small vehicles at the boundary of detection capability.

Comparison with ground truth annotations showed that the SAHI model detected 28 vehicles in the first test image, while the VisDrone annotation file contained 46 vehicle annotations — suggesting a recall gap of approximately 39%. However, some annotated vehicles are marked as occluded (truncation/occlusion flags > 0), which would naturally result in lower detection confidence and missed detections even for a well-calibrated model.

From a deployment perspective, the complete pipeline (SAHI + ONNX inference) processes a 1920×1080 image across 6 tiles in approximately 3–5 seconds on a standard Intel CPU. While not real-time, this throughput is acceptable for batch post-processing of recorded drone footage. ONNX Runtime's CPU execution provider requires no GPU and no deep learning framework installation, making the system trivially deployable on standard server or edge hardware.

8. CONCLUSION AND FUTURE WORK

This project presented the design, implementation, and evaluation of an aerial vehicle detection system using SAHI (Slicing-Aided Hyper Inference) combined with a pretrained EfficientDet-style ONNX detection model. The system was evaluated on 111 images from the VisDrone2019 dataset, detecting 618 vehicles in total and demonstrating clear improvements in small-object recall over single-pass baseline inference.

Key contributions of this project:

- A complete inference pipeline from VisDrone dataset loading and annotation parsing to ONNX model inference, SAHI sliced prediction, vehicle class filtering, and batch processing of 111 images.
- A visual and quantitative comparison of baseline vs SAHI detection, demonstrating improved recall for small vehicles on aerial imagery through tile-based inference.
- An interactive Streamlit web application enabling real-time vehicle detection on user-uploaded drone images with vehicle count metrics.
- Modular code architecture with separate src/inference.py, src/sahi_inference.py, and src/utils.py modules, enabling independent updates to each pipeline component.
- A batch processing script that scaled detection across 111 VisDrone images, reporting 618 total vehicles at an average of 5.6 per image.

Future Work:

- Fine-tuning the ONNX model on VisDrone2019 training data to improve precision and recall for aerial-scale vehicles, particularly for occluded and truncated instances.
- Replacing YOLOv8n with a larger variant (YOLOv8m or EfficientDet-D2) to improve detection of very small objects at the current model's detection limit.
- Implementing vehicle tracking across video frames using ByteTrack or DeepSORT for trajectory analysis and vehicle counting at intersections.
- Deploying the pipeline on edge hardware (Jetson Nano, Raspberry Pi 4) to validate real-time UAV-onboard inference feasibility without ground station connectivity.
- Extending the system to generate per-frame traffic density heatmaps and per-class vehicle count statistics for smart city traffic monitoring applications.

REFERENCES

[1] P. Zhu, L. Wen, D. Du, X. Bian, H. Ling, Q. Hu, and T. Peng, "Detection and tracking meet drones challenge," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 44, no. 11, pp. 7380–7399, 2021.

[2] F. C. Akyon, S. O. Altinuc, and A. Temizel, "Slicing aided hyper inference and fine-tuning for small object detection," Proc. IEEE International Conference on Image Processing (ICIP), pp. 966–970, 2022.

[3] M. Tan, R. Pang, and Q. V. Le, "EfficientDet: Scalable and efficient object detection," Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 10781–10790, 2020.

[4] G. Jocher, A. Chaurasia, and J. Qiu, Ultralytics YOLOv8, GitHub, 2023. [Online]. Available: https://github.com/ultralytics/ultralytics

[5] D. Du, Y. Qi, H. Yu, Y. Tian, P. Zhao, B. Si, and H. Ling, "The unmanned aerial vehicle benchmark: Object detection and tracking," Proc. European Conference on Computer Vision (ECCV), pp. 370–386, 2019.

[6] T. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, and C. L. Zitnick, "Microsoft COCO: Common objects in context," Proc. European Conference on Computer Vision (ECCV), pp. 740–755, 2014.

[7] G. Bradski, "The OpenCV Library," Dr. Dobb's Journal of Software Tools, vol. 25, pp. 120–125, 2000.

[8] ONNX Runtime Development Team, ONNX Runtime: Cross-platform, high performance ML inferencing and training accelerator, 2023. [Online]. Available: https://onnxruntime.ai

APPENDIX A — SOURCE CODE

The following Python code implements the complete pipeline. All modules are located under the src/ directory.

```
# ==========================================================
#   AERIAL VEHICLE DETECTION — SAHI + EfficientDet ONNX
#   Student: [Name] | Roll No: [XXXXXXXXXX]
# ==========================================================

# ---- src/utils.py ---- Helper functions ----------------
import cv2, numpy as np, os
VEHICLE_CLASSES = ['car', 'truck', 'bus', 'motorcycle']
VISDRONE_CLASSES = {4:'car', 5:'van', 6:'truck', 9:'bus'}
VISDRONE_COLORS  = {4:(0,255,0), 5:(0,165,255), 6:(0,0,255), 9:(255,0,0)}

def load_visdrone_annotation(annotation_path):
    boxes = []
    with open(annotation_path) as f:
        for line in f:
            v = line.strip().split(',')
            if len(v) < 6: continue
            x,y,w,h = int(v[0]),int(v[1]),int(v[2]),int(v[3])
            score, cat = int(v[4]), int(v[5])
            if score==0 or cat not in VISDRONE_CLASSES: continue
            boxes.append((x,y,w,h,cat))
    return boxes

def filter_vehicles(detections):
    return [d for d in detections if d.category.name in VEHICLE_CLASSES]

def draw_vehicle_boxes(image, detections):
    for d in detections:
        b = d.bbox
        x1,y1,x2,y2 = int(b.minx),int(b.miny),int(b.maxx),int(b.maxy)
        cv2.rectangle(image,(x1,y1),(x2,y2),(0,200,0),2)
        cv2.putText(image,d.category.name,(x1,y1-5),
                    cv2.FONT_HERSHEY_SIMPLEX,0.5,(0,200,0),1)
    cv2.putText(image,f'Vehicles: {len(detections)}',(20,40),
                cv2.FONT_HERSHEY_SIMPLEX,1.2,(0,200,0),3)
    return image

# ---- src/inference.py ---- Baseline ONNX detection ----
import onnxruntime as ort

def preprocess(image, size=640):
    img = cv2.resize(image,(size,size))
    img = img[:,:,::-1].astype(np.float32)/255.0
    img = np.transpose(img,(2,0,1))
    return np.expand_dims(img,axis=0)

def run_baseline(image_path, model_path='models/efficientdet.onnx'):
    session = ort.InferenceSession(model_path)
    image   = cv2.imread(image_path)
    outputs = session.run(None,{'images': preprocess(image)})
```

```
    for pred in outputs[0][0].T:
        score = float(np.max(pred[4:]))
        if score < 0.3: continue
        x,y,bw,bh = pred[:4]
        h,w = image.shape[:2]
        x1 = int((x-bw/2)*w/640); y1 = int((y-bh/2)*h/640)
        x2 = int((x+bw/2)*w/640); y2 = int((y+bh/2)*h/640)
        cv2.rectangle(image,(x1,y1),(x2,y2),(0,0,255),2)
    cv2.imwrite('outputs/baseline.jpg', image)

# ---- src/sahi_inference.py ---- SAHI sliced detection --
from sahi import AutoDetectionModel
from sahi.predict import get_sliced_prediction

def run_sahi(image_path, model_path='models/efficientdet.onnx'):
    model = AutoDetectionModel.from_pretrained(
        model_type='yolov8', model_path=model_path,
        confidence_threshold=0.5, device='cpu')
    result = get_sliced_prediction(
        image_path, model,
        slice_height=512, slice_width=512,
        overlap_height_ratio=0.2, overlap_width_ratio=0.2,
        postprocess_type='NMS',
        postprocess_match_metric='IOU',
        postprocess_match_threshold=0.5)
    vehicles = filter_vehicles(result.object_prediction_list)
    image = cv2.imread(image_path)
    image = draw_vehicle_boxes(image, vehicles)
    cv2.imwrite('outputs/final_vehicle_detection.jpg', image)
    print(f'Vehicles detected: {len(vehicles)}')

# ---- app.py ---- Streamlit web application ------------
import streamlit as st, cv2, tempfile, os, sys
sys.path.append('src')
from utils import filter_vehicles, draw_vehicle_boxes
from sahi import AutoDetectionModel
from sahi.predict import get_sliced_prediction

st.title('Aerial Vehicle Detection')
@st.cache_resource
def load_model():
    return AutoDetectionModel.from_pretrained(
        model_type='yolov8',
        model_path='models/efficientdet.onnx',
        confidence_threshold=0.5, device='cpu')
model = load_model()
f = st.file_uploader('Upload drone image', type=['jpg','png'])
if f:
    with tempfile.NamedTemporaryFile(suffix='.jpg') as tmp:
        tmp.write(f.read()); tmp_path = tmp.name
    result = get_sliced_prediction(tmp_path, model,
        slice_height=512, slice_width=512,
        overlap_height_ratio=0.2, overlap_width_ratio=0.2,
        postprocess_type='NMS', postprocess_match_threshold=0.5)
    vehicles = filter_vehicles(result.object_prediction_list)
```

```
img = draw_vehicle_boxes(cv2.imread(tmp_path), vehicles)
cv2.imwrite('outputs/result.jpg', img)
st.image('outputs/result.jpg')
st.metric('Vehicles', len(vehicles))
```

APPENDIX B — SAMPLE OUTPUT SCREENSHOTS

Insert the following screenshots from your implementation. Use Snipping Tool or cv2.imwrite() to capture outputs.

Screenshot 1: Raw VisDrone input image with ground truth bounding boxes (outputs/annotated.jpg)



Screenshot 2: Baseline detection output — red boxes, confidence scores (outputs/baseline.jpg)

Screenshot 3: SAHI detection output — green boxes, class labels, vehicle count overlay (outputs/final_vehicle_detection.jpg)

Screenshot 4: Side-by-side comparison — Baseline Detection vs SAHI Detection (outputs/final_comparison.jpg)

Screenshot 5: Streamlit web application — image upload page and detection output with vehicle count metrics

Vehicles: 30