NAME: srijan Shankar s REG NO: 230701341

EX NO 10: IMPLEMENTATION OF AVL TREE

```
#include <stdio.h>
#include <stdlib.h>
struct AVLNode {
  int key; struct
  AVLNode *left; struct
  AVLNode *right; int
  height;
};
int max(int a, int b) {
  return (a > b) ? a : b;
}
int height(struct AVLNode *node) {
  if (node == NULL)
     return 0;
  return node->height;
}
struct AVLNode *newNode(int key) {
  struct AVLNode *node = (struct AVLNode *)malloc(sizeof(struct AVLNode));
  node->key = key; node->left = NULL; node->right = NULL; node->height =
  1; return node;
}
struct AVLNode *rotateRight(struct AVLNode *y) {
  struct AVLNode *x = y->left;
  struct AVLNode *T2 = x->right;
  x->right = y; y-
  >left = T2;
```

```
y->height = max(height(y->left), height(y->right)) + 1; x-
  >height = max(height(x->left), height(x->right)) + 1; return
  х;
}
struct AVLNode *rotateLeft(struct AVLNode *x) {
  struct AVLNode *y = x->right;
  struct AVLNode *T2 = y->left;
  y->left = x; x-
  >right = T2;
  x->height = max(height(x->left), height(x->right)) + 1; y-
  >height = max(height(y->left), height(y->right)) + 1;
  return y;
}
int getBalance(struct AVLNode *node) {
  if (node == NULL)
     return 0;
  return height(node->left) - height(node->right);
}
struct AVLNode *insert(struct AVLNode *node, int key) {
  if (node == NULL)
     return newNode(key);
  if (key < node->key)
     node->left = insert(node->left, key);
  else if (key > node->key)
     node->right = insert(node->right, key);
  else
     return node; node->height = 1 + max(height(node->left),
  height(node->right)); int balance = getBalance(node);
  if (balance > 1 && key < node->left->key)
     return rotateRight(node);
```

```
if (balance < -1 && key > node->right->key)
     return rotateLeft(node);
  if (balance > 1 && key > node->left->key) {
     node->left = rotateLeft(node->left);
     return rotateRight(node);
  }
  if (balance < -1 && key < node->right->key) {
     node->right = rotateRight(node->right);
     return rotateLeft(node);
  }
  return node;
}
void inorder(struct AVLNode *node) {
  if (node != NULL) {
     inorder(node->left);
     printf("%d", node->key);
     inorder(node->right);
  }
}
int main() {
  struct AVLNode *root = NULL;
  root = insert(root, 10); root =
  insert(root, 20); root =
  insert(root, 30); root =
  insert(root, 40); root =
  insert(root, 50); root =
  insert(root, 25);
  printf("Inorder traversal of the AVL tree:\n");
  inorder(root); printf("\n");
  return 0;
}
```