

# **RAJALAKSHMI ENGINEERING COLLEGE**

**RAJALAKSHMI NAGAR, THANDALAM – 602 105**



**RAJALAKSHMI  
ENGINEERING COLLEGE**

**CS23221  
PYTHON PROGRAMMING LAB**

**Laboratory Observation Note Book**

**Name: SRIWANTH SATHISH**

**Year/Branch/Section: 1-year/CSE/F**

**Register No: 2116230701344**

**Semester: 2<sup>nd</sup> Semester**

**Academic Year: 2023 - 2024**

## 07 – Tuple/Set

**Ex. No. : 7.1**

**Date: 18.05.24**

**Register No.: 230701344**

**Name: Sriwanth sathish**

## **Binary String**

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

**For example:**

Input	Result
01010101010	Yes
010101 10101	No

### **Program:**

```
a = input() try:
```

```
    c = int(a)
```

```
print("Yes") except:
```

```
    print("No")
```

	Input	Expected	Got	
✓	01010101010	Yes	Yes	✓
✓	REC123	No	No	✓
✓	010101 10101	No	No	✓

## DNA Sequence

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string **s** that represents a **DNA sequence**, return all the **10-letterlong** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

### Example 1:

**Input:** s = "AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT"

**Output:** ["AAAAACCCCC","CCCCCAAAAA"] **Example 2:**

**Input:** s = "AAAAAAAAAAAA"

**Output:** ["AAAAAAAAAAAA"]

### For example:

Input	Result
AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA

**Program:** def

findRepeatedSequences(s):

```
    sequences = {}    result
= []    for i in range(len(s)
- 9):
```

```
    seq = s[i:i+10]
```

```
    sequences[seq] = sequences.get(seq, 0) + 1
```

```
if sequences[seq] == 2:
```

```
    result.append(seq)    return result s1 = input()
```

```
for i in findRepeatedSequences(s1):
```

```
    print(i)
```

	Input	Expected	Got	
✓	AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAA	AAAAACCCCC CCCCCAAAA	✓
✓	AAAAAAAAAAAAA	AAAAAAAAA	AAAAAAAAA	✓

**Ex. No. : 7.3**

**Date: 18.05.24**

**Register No.:230701344**

**Name: Sriwanth sathish**







---

## American keyboard

Given an array of strings words, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".

~ 1	! 2	@ 3	# 4	\$ 5	% 6	^ 7	& 8	* 9	( 0	) -	+ =	 Backspace	
Tab 	Q	W	E	R	T	Y	U	I	O	P	{ [	} ]	 \ _
Caps Lock 	A	S	D	F	G	H	J	K	L	: ;	" '	Enter 	
Shift 	Z	X	C	V	B	N	M	< ,	> .	? /	Shift 		
Ctrl	Win Key	Alt								Alt	Win Key	Menu	Ctrl

- 
- 
- **Example 1:**
- **Input:** words = ["Hello","Alaska","Dad","Peace"] • **Output:** ["Alaska","Dad"]
- **Example 2:**
- **Input:** words = ["omk"] • **Output:** []
- **Example 3:**
- **Input:** words = ["adsdf","sfd"]
- **Output:** ["adsdf","sfd"]
- 

- **For example:**

Input	Result
4 Hello Alaska Dad Peace	Alaska Dad

**Program:**

```
def findWords(words):  
  
    row1 = set('qwertyuiop')  
  
    row2 = set('asdfghjkl')  
  
    row3 = set('zxcvbnm')  
  
    result = []  
    for  
word in words:  
  
        w = set(word.lower())        if w.issubset(row1) or  
w.issubset(row2) or w.issubset(row3):  
  
            result.append(word)  
  
    if len(result) == 0:  
        print("No words")    else:  
        for i in result:  
            print(i)  
  
a = int(input()) arr = [input()  
for i in range(a)]  
  
findWords(arr)
```



	Input	Expected	Got	
✓	4 Hello Alaska Dad Peace	Alaska Dad	Alaska Dad	✓
✓	1 omk	No words	No words	✓
✓	2 adsfd afd	adsfd afd	adsfd afd	✓

Ex. No. : 7.4

Date: 18.05.24

Register No.: 230701344

Name Sriwanth sathish

## Print repeated no

Given an array of integers **nums** containing **n + 1** integers where each integer is in the range **[1, n]** inclusive. There is only **one repeated number** in **nums**, return *this repeated number*. Solve the problem using [set](#).

### Example 1:

**Input:** nums = [1,3,4,2,2]

**Output:** 2

### Example 2:

**Input:** nums = [3,1,3,4,2]

**Output:** 3

### For example:

Input	Result
1 3 4 4 2	4

### Program:

```
n=input().split(" ") n
= list(n) for i in
range(len(n)):
    for j in range(i+1,len(n)):
        if n[i] == n[j]:
            print(n[i])      exit(0)
```



	Input	Expected	Got	
✓	1 3 4 4 2	4	4	✓
✓	1 2 2 3 4 5 6 7	2	2	✓

Ex. No. : 7.5

Date: 18.05.24

Register No.:230701344

Name: Sriwanth sathish

## Check Pair

Given a tuple and a positive integer  $k$ , the task is to find the count of distinct pairs in the tuple whose sum is equal to  $K$ .

### Examples:

**Input:**  $t = (5, 6, 5, 7, 7, 8)$ ,  $K = 13$

**Output:** 2

Explanation:

Pairs with sum  $K (= 13)$  are  $\{(5, 8), (6, 7), (6, 7)\}$ .

Therefore, distinct pairs with sum  $K (= 13)$  are  $\{(5, 8), (6, 7)\}$ . Therefore, the required output is 2.

### For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0

### Program: def

```
count_distinct_pairs(t, K):
```

```
    distinct_pairs = set()
```

```
    for i in range(len(t)):
```

```
        for j in range(i + 1, len(t)):
```

```
            if t[i] + t[j] == K:
```

```
                distinct_pairs.add((min(t[i], t[j]),
```

```

max(t[i], t[j]))    return
len(distinct_pairs) t_input =
input() t = tuple(map(int,
t_input.split(','))) K = int(input())
print(count_distinct_pairs(t, K))

```

	Input	Expected	Got	
✓	5,6,5,7,7,8 13	2	2	✓
✓	1,2,1,2,5 3	1	1	✓
✓	1,2 0	0	0	✓