

Ex. No: 2

Date: 20.08.24

Register No.: 230701356

Name: Swathi Saravanan

Finding Time Complexity of Algorithms

2.a. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;    int s =1;

    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
void function(int n){
    set count = 0

    set i = 1

    increment count by 1
```

set s = 1

increment count by 1

while (s <=n){

 increment count by 1

 increment i by 1

 increment count by 1

 set s = s + i

 increment count by 1

}

increment count by 1

print count

}

Program:

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int n;
```

```
    int c=0;
```

```
    int i=1;
```

```
    c++;
```

```
    int s=1;
```

```
    c++;
```

```
    scanf("%d",&n);
```

```
    while(s <=n)
```

```
    {
```

```
        c++;
```

```
    i++;  
    c++;  
    s += i;  
    c++;  
}c++;  
printf("%d",c);  
}
```

Output:

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

Passed all tests! ✓

2.b. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
void func(int n){
    initialize count to 0
    if n = 1{
        increment count by 1
        print "*"
    }
    else{
        increment count by 1
```

```

// outer loop from 1 to n
for each i from 1 to n{
    increment count by 1

    // inner loop from 1 to n
    for each j from 1 to n{
        increment count by 1

        // simulate print statements with count increments
        increment count by 1 // first simulated printf("*")
        increment count by 1 // second simulated printf("*")

        // exit inner loop immediately
        increment count by 1 // break statement
    }
    increment count by 1
}
increment count by 1
}
print count
}

```

Program:

```

#include<stdio.h>

int main()
{
    int n,c=0;

    scanf("%d",&n);

```

```

if(n==1)
{
    c++;
    //printf("*");
}
else
{
    c++;
    for(int i=1; i<=n; i++)
    {
        c++;
        for(int j=1; j<=n; j++)
        {
            c++;
            //printf("*");

            c++;
            //printf("*");

            c++;
            break;
        }c++;
    }c++;
}
printf("%d",c);
}

```

Output:

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

2.c. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {  
  {  
    for (i = 1; i <= num; ++i)  
    {  
      if (num % i == 0)  
      {  
        printf("%d ", i);  
      }  
    }  
  }  
}
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
function Factor(num) {  
  initialize count to 0  
  
  // loop from 1 to num  
  for each i from 1 to num {  
    increment count by 1  
  
    // check if i is a factor of num  
    if num modulo i equals 0 {  
      increment count by 1  
      // simulate printing i (e.g., printf("%d ", i);)  
    }  
  }  
}
```



```
        increment count by 1 // end of inner if-statement
    }

    increment count by 1 // after loop completion

    print count
}
```

Program:

```
#include<stdio.h>

int main()
{
    int n,c=0;
    scanf("%d",&n);
    for(int i=1;i<=n;++i)
    {
        c++;
        if(n%i==0)
        {
            c++;
            //printf("%d",i);
        }
        c++;
    }
    printf("%d",c);
}
```

Output:

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

2.d. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c = 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
function(n) {
    initialize count to 0
    initialize c to 0

    increment count by 1

    // outer loop: i goes from n/2 to n-1
    for each i from n/2 to n-1 {
        increment count by 1

        // middle loop: j starts at 1 and doubles each iteration until j < n
        for each j starting from 1 and doubling each time (j = 2 * j) until j < n {
            increment count by 1
        }
    }
}
```

```

        // inner loop: k starts at 1 and doubles each iteration until k < n
        for each k starting from 1 and doubling each time (k = k * 2) until k < n {
            increment count by 1
            increment c by 1
            increment count by 1
        }

        increment count by 1 // after inner loop ends
    }

    increment count by 1 // after middle loop ends
}

increment count by 1 // after outer loop ends

print count
}

```

Program:

```

#include<stdio.h>

int main()
{
    int cr=0,n;
    int c=0;
    scanf("%d",&n);
    cr++;
    for(int i=n/2;i<n;i++)

```

```

{
    cr++;
    for(int j=1;j<n;j=2*j)
    {
        cr++;
        for(int k=1;k<n;k=k*2)
        {
            cr++;
            c++;
            cr++;
        }cr++;
    }cr++;
}cr++;
printf("%d",cr);
}

```

Output:

	Input	Expected	Got	
✓	4	30	30	✓
✓	10	212	212	✓

2.e. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n /= 10;
    }
    print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
function reverse(n) {
    initialize count to 0

    initialize rev to 0

    initialize remainder

    increment count by 1 // for initialization

    // loop until n is not equal to 0
    while n is not equal to 0 {
        increment count by 1 // start of loop

        remainder = n modulo 10
```

increment count by 1 // after calculating remainder

rev = rev * 10 + remainder

increment count by 1 // after updating rev

n = n divided by 10

increment count by 1 // after updating n

}

increment count by 1 // after loop ends

// simulate printing rev (e.g., print(rev))

increment count by 1 // for print statement

print count

}

Program:

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int n,c=0;
```

```
    scanf("%d",&n);
```

```
    int rev = 0, remainder;
```

```
    c++;
```

```
    while (n != 0)
```

```
    {
```

```
        c++;
```

```

    remainder = n % 10;

    c++;

    rev = rev * 10 + remainder;

    c++;

    n/= 10;

    c++;

}c++;

c++;

printf("%d",c);

}

```

Output:

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓