

09- Functions

Ex. No. : 9.1

Date: 01.06.24

Register No.: 230701373

Name: SP VARUN

Christmas Discount

An e-commerce company plans to give their customers a special discount for Christmas. They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an python code to find the discount value for the given total bill amount.

Constraints

$1 \leq \text{orderValue} < 10e^{100000}$

Input

The input consists of an integer orderValue, representing the total bill amount.

Output



Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

| Test | Result |
|-------------------------------|--------|
| print(christmasDiscount(578)) | 12 |

Program:

```
def is_prime_digit(digit):  
    return digit in [2,3,5,7]  
  
def christmasDiscount(n):  
    s=discount=0  
    prime_digits=[2,3,5,7]  
    for digit in str(n):  
        digit=int(digit)    if  
        is_prime_digit(digit):  
            discount+=digit  
    return discount
```

| | Test | Expected | Got | |
|---|-------------------------------|----------|-----|---|
| ✓ | print(christmasDiscount(578)) | 12 | 12 | ✓ |

Ex. No. : 9.2

Date: 01.06.24

Register No.: 230701373

Name: SP VARUN

Check Product of Digits

Write a code to check whether product of digits at even places is divisible by sum of digits at odd place of a positive integer.

Input Format:

Take an input integer from stdin.

Output Format:

Print TRUE or FALSE.

Example Input:

1256

Output:

TRUE

Example Input:

1595

Output:

FALSE

For example:

| Test | Result |
|---|--------|
| <code>print(productDigits(1256))</code> | True |



| | |
|----------------------------|-------|
| print(productDigits(1595)) | False |
|----------------------------|-------|

Program:

```
def productDigits(n):    a=n
```

```
    temp=[]    list1=[]
```

```
    list2=[]    rem=0    while
```

```
    a!=0:        rem=a%10
```

```
    temp.append(rem)
```

```
    a=a//10    for i in
```

```
    range(len(temp)):
```

```
    if(i+1)%2==0:
```

```
    list1.append(temp[i])
```

```
    else:
```

```
        list2.append(temp[i])
```

```
    pro=1    sum=0
```

```
        for i in list1:
```

```
        sum+=i    for i
```

```
        in list2:
```

```
        pro*=i
```

```
        if pro%sum==0:
```

```
            return True
```

```
    else:
```

```
        return False
```

| | Test | Expected | Got | |
|---|----------------------------|----------|-------|---|
| ✓ | print(productDigits(1256)) | True | True | ✓ |
| ✓ | print(productDigits(1595)) | False | False | ✓ |

Ex. No. : 9.3

Date: 01.06.24

Register No.: 230701373

Name: SP VARUN

Abundant Number

An abundant number is a number for which the sum of its proper divisors is greater than the number itself. Proper divisors of the number are those that are strictly lesser than the number.

Input Format:

Take input an integer from stdin **Output**

Format:

Return Yes if given number is Abundant. Otherwise, print No **Example**

input:

12

Output:

Yes

Explanation

The proper divisors of 12 are: 1, 2, 3, 4, 6, whose sum is $1 + 2 + 3 + 4 + 6 = 16$. Since sum of proper divisors is greater than the given number, 12 is an abundant number. **Example**

input:

13

Output:

No

Explanation

The proper divisors of 13 is: 1, whose sum is 1. Since sum of proper divisors is not greater than the given number, 13 is not an abundant number.

For example:

| Test | Result |
|---------------------|--------|
| print(abundant(12)) | Yes |
| print(abundant(13)) | No |

Program:

```
def abundant(number):
```

```
    d_s=sum([divisor for divisor in range(1,number) if number % divisor == 0])
```

```
    if d_s>number:    return"Yes"
```

```
    else:
```

```
        return "No"
```

| | Test | Expected | Got | |
|---|---------------------|----------|-----|---|
| ✓ | print(abundant(12)) | Yes | Yes | ✓ |
| ✓ | print(abundant(13)) | No | No | ✓ |

Ex. No. : 9.4
No.: 230701373

Date: 01.06.24 Register
Name SP VARUN

Ugly number

A number is considered to be ugly if its only prime factors are 2, 3 or 5. [1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number. return ugly if it is ugly, else return not ugly Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers. **For example:**

| Test | Result |
|---------------------|--------|
| print(checkUgly(6)) | ugly |



| | |
|----------------------|----------|
| print(checkUgly(21)) | not ugly |
|----------------------|----------|

Program:

```
def checkUgly(n):
```

```
    if n <= 0:
```

```
        return "not ugly"
```

```
    while n % 2 == 0:
```

```
        n //= 2
```

```
    while n % 3 == 0:
```

```
        n //= 3
```

```
    while n % 5 == 0:
```

```
        n //= 5
```

```
    return "ugly" if n == 1 else "not ugly"
```

| | Test | Expected | Got | |
|---|----------------------|----------|----------|---|
| ✓ | print(checkUgly(6)) | ugly | ugly | ✓ |
| ✓ | print(checkUgly(21)) | not ugly | not ugly | ✓ |

Ex. No. : 9.5

Date: 01.06.24

Register No.: 230701373

Name SP VARUN

Automorphic number or not

An automorphic number is a number whose square ends with the number itself. For example, 5 is an automorphic number because $5*5=25$. The last digit is 5 which same as the given number.

If the number is not valid, it should display "Invalid input".

If it is an automorphic number display "Automorphic" else display "Not Automorphic".

Input Format:

Take a Integer from Stdin Output

Format:

Print Automorphic if given number is Automorphic number, otherwise Not Automorphic

Example input: 5 Output: Automorphic Example input: 25 Output: Automorphic Example

input: 7 Output: Not Automorphic **For example:**

Test

Result

print(automorphic(5)) Automorphic **Program:**

```
def automorphic(n):
```

```
    if(n<0):
```

```
        return "Invalid input"
```

```
    square = n * n    n_s=str(n)
```

```
    s_s=str(square)    if
```

```
s_s.endswith(n_s):
```

```
return "Automorphic"
```

```
else:
```

```
    return "Not Automorphic"
```

| | Test | Expected | Got | |
|---|-----------------------|-----------------|-----------------|---|
| ✓ | print(automorphic(5)) | Automorphic | Automorphic | ✓ |
| ✓ | print(automorphic(7)) | Not Automorphic | Not Automorphic | ✓ |