

Ex. No.: 10a)

Date: 11.04.25

### BEST FIT

**Aim:**

To implement Best Fit memory allocation technique using Python.

**Algorithm:**

1. Input memory blocks and processes with sizes
2. Initialize all memory blocks as free.
3. Start by picking each process and find the minimum block size that can be assigned to current process
4. If found then assign it to the current process.
5. If not found then leave that process and keep checking the further processes.

**Program Code:**

```
#include <stdio.h>
#include <stdlib.h>
int main()
{
    int n, m;
    printf("Enter the no. of processes & blocks");
    scanf("%d %d", &n, &m);
    int p[n], b[m];
    printf("Enter the sizes of processes:\n");
    for (int i = 0; i < n; i++)
    {
        scanf("%d", &p[i]);
    }
    printf("Enter the sizes of memory blocks:\n");
    for (int i = 0; i < m; i++)
    {
        scanf("%d", &b[i]);
    }
    int f[n], f2[m];
```

```
for (int i=0; i<n; i++) {
```

```
    f[i] = -1;
```

```
}
```

```
for (int i=0; i<m; i++) {
```

```
    f2[i] = 0;
```

```
}
```

```
for (int i=0; i<n; i++) {
```

```
    int k = -1;
```

```
    for (int j=0; j<m; j++) {
```

```
        if (b[i] >= p[j] && f2[j] == 0) {
```

```
            if (k == -1 || b[k] < b[j]) {
```

```
                k = j;
```

```
            }
```

```
        }
```

```
    }
```

```
    if (k != -1) {
```

```
        f[i] = k;
```

```
        f[k] = 1;
```

```
    }
```

```
}
```

```
printf("Process no    Process size    Block no.\n");
```

```
for (int i=0; i<n; i++) {
```

```
    if (f[i] != -1)
```

```
        printf("%d    %d    %d\n",
```

```
            i+1, p[i], f[i]+1);
```

```
    else
```

```
        printf("%d    %d    %s\n",
```

```
            i+1, p[i], "Not Allocated");
```

```
    }
```

```
}
```

### Sample Output:

Process No.	Process Size	Block no.
1	212	4
2	417	2
3	112	3
4	426	5

Enter the no. of processes & blocks : 3 3

Enter the sizes of the processes

100 200 300

Enter the sizes of memory blocks

250 100 150

Process No	Process size	Block no
1	100	2
2	200	1
3	300	Not Allocated

### Result:

Thus using C program we have executed the code for best fit memory allocation algorithm is implemented

Ex. No.: 10b)

Date: 11.04.25

### FIRST FIT

Aim:

To write a C program for implementation memory allocation methods for fixed partition using first fit.

Algorithm:

1. Define the max as 25.
2. Declare the variable frag[max], b[max], f[max], i, j, nb, nf, temp, highest=0, bf[max], ff[max].
- 3: Get the number of blocks, files, size of the blocks using for loop.
- 4: In for loop check bf[j]!=1, if so temp=b[j]-f[i]
- 5: Check highest

Program Code:

```
#include <stdio.h>
#include <stdbool.h>
int main()
{
    int n, m;
    printf("Enter the no. of processes & blocks");
    scanf("%d %d", &n, &m);
    int p[n], b[m];
    printf("Enter the sizes of the processes \n");
    for(int i=0; i<n; i++)
    {
        scanf("%d", &p[i]);
    }
    printf("Enter the sizes of memory blocks \n");
    for(int i=0; i<m; i++)
    {
        scanf("%d", &b[i]);
    }
}
```

```
int f[n], f2[m];
```

```
for (int i = 0; i < n; i++) {
```

```
    f[i] = -1;
```

```
}
```

```
for (int i = 0; i < m; i++) {
```

```
    f2[i] = 0;
```

```
}
```

```
for (int i = 0; i < n; i++) {
```

```
    for (int j = 0; j < m; j++) {
```

```
        if (b[j] > p[i] && f2[j] == 0) {
```

```
            f[i] = 1;
```

```
            f2[j] = 1;
```

```
            break;
```

```
        }
```

```
    }
```

```
}
```

```
printf("Process No    Process Size    Block no  
        Block size      Fragment);
```

```
for (int i = 0; i < n; i++) {
```

```
    if (f[i] != -1)
```

```
    {
```

```
        printf("%d %.d %.d\n", i+1,
```

```
                p[i], f[i]+1
```

```
    }
```

```
    else
```

```
    {
```

```
        printf("%d %.d %.s\n", i+1, p[i], "Not allocated")
```

```
    }
```

```
}
```



## Sample Output:

```

Enter the number of blocks:4
Enter the number of files:3

Enter the size of the blocks:-
Block 1:5
Block 2:8
Block 3:4
Block 4:10
Enter the size of the files:-
File 1:1
File 2:4
File 3:7

```

File_no:	File_size :	Block_no:	Block_size:	Fragment
1	1	1	5	4
2	4	2	8	4
3	7	4	10	3

Enter the number of processes & blocks: 4 5

Enter the sizes of the processes :

212 417 112 426

Enter the sizes of the memory blocks

100 500 200 300 600

Process No.	Process Size	Block No.	Block Size	Fragment
1	212	2	500	288
2	417	5	600	183
3	112	3	200	88
4	426			

Not Allocated

## Result:

Thus using C program we have executed the code for first fit memory allocation algorithm.