

Ex. No.: 11a)  
Date: 12/4/25.

### FIFO PAGE REPLACEMENT

#### Aim:

To find out the number of page faults that occur using First-in First-out (FIFO) page replacement technique.

#### Algorithm:

1. Declare the size with respect to page length
2. Check the need of replacement from the page to memory
3. Check the need of replacement from old page to new page in memory 4.
- Form a queue to hold all pages
5. Insert the page require memory into the queue
6. Check for bad replacement and page fault
7. Get the number of processes to be inserted
8. Display the values

#### Program Code:

```
#include <stdio.h>
#define Max 100
int main () {
    int ref str [max], frames [max];
    int n, frame size, i, j, k;
    int page fault = 0, pointer = 0, bound;
    printf ("Enter the size of reference string: ");
    scanf ("%d", &n);
    for (i=0; i<n; i++) {
        printf ("Enter [%d]: ", i+1);
        scanf ("%d", &ref str[i]);
    }
    printf ("Enter page frame size: ");
    scanf ("%d", &frame size);
    for (i=0; i<frame size; i++) {
        scanf ("%d", &frames[i]);
        for (j=0; j<frame size; j++) {
            if (frames[j] == ref str[i]) {
                pointer = j;
                break;
            }
        }
        if (pointer == -1) {
            page fault++;
            frames[pointer] = ref str[i];
            pointer++;
        }
    }
    printf ("Total page faults: %d", page fault);
}
```

```

frames[i] = -1;
for (i = 0; i < n; i++) {

```

```

    found = 0;

```

```

    for (j = 0; j < framesize; j++) {

```

```

        if (frames[j] == refstr[i]) {

```

```

            found = 1;

```

```

            break;

```

```

        }

```

```

    }

```

```

    if (!found) {

```

```

        frames[pointer] = refstr[i];

```

```

        pointer = (pointer + 1) % framesize;

```

```

        page_fault++;

```

```

        printf("%d -> ", refstr[i]);

```

```

        for (k = 0; k < framesize; k++) {

```

```

            if (frames[k] != -1)

```

```

                printf("%d ", frames[k]);

```

```

            else

```

```

                printf("- ");

```

```

        }

```

```

        printf("\n");

```

```

    }

```

```

    else

```

```

    }

```

```

    printf("%d -> No page Fault \n", refstr[i]);

```

```

}

```

```

printf("\n total page faults : %d \n", page_fault);

```

```

return 0;

```

```

}

```

### Sample Output:

```
[root@localhost student]# python fifo.py
```

```
Enter the size of reference string: 20
```

```
Enter [ 1 ] : 7
```

```
Enter [ 2 ] : 0
```

```
Enter [ 3 ] : 1
```

```
Enter [ 4 ] : 2
```

```
Enter [ 5 ] : 0
```

```
Enter [ 6 ] : 3
```

```
Enter [ 7 ] : 0
```

```
Enter [ 8 ] : 4
```

```
Enter [ 9 ] : 2
```

```
Enter [10] : 3
```

```
Enter [11] : 0
```

```
Enter [12] : 3
```

```
Enter [13] : 2
```

```
Enter [14] : 1
```

```
Enter [15] : 2
```

```
Enter [16] : 0
```

```
Enter [17] : 1
```

```
Enter [18] : 7
```

```
Enter [19] : 0
```

```
Enter [20] : 1
```

```
Enter page frame size : 3
```

```
7 -> 7 - -
```

```
0 -> 7 0 -
```

```
1 -> 7 0 1
```

```
2 -> 2 0 1
```

```
0 -> No Page Fault
```

```
3 -> 2 3 1
```

```
0 -> 2 3 0
```

```
4 -> 4 3 0
```

```
2 -> 4 2 0
```

```
3 -> 4 2 3
```

```
0 -> 0 2 3
```

```
3 -> No Page Fault
```

```
2 -> No Page Fault
```

```
1 -> 0 1 3
```

```
2 -> 0 1 2
```

```
0 -> No Page Fault
```

```
1 -> No Page Fault
```

```
7 -> 7 1 2
```

```
0 -> 7 0 2
```

1 -> 7 0 1

Total page faults: 15.

[root@localhost student]#

gll

Result :

The FIFO page replacement algorithm has been  
successfully implemented.