

**Ex. No: 4**

**Date: 03.09.24**

**Register No.: 230701386**

**Name: R YASHVINTHINI**

---

## **Divide and Conquer**

### **4.a. Number of Zeros in a Given Array**

**Aim:** Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

**Algorithm:**

1. Initialize Count
2. Create a function findCount that takes an array a, and two integers l and r representing the left and right indices of the array segment to be processed.
3. check if the element at index l is 0. If true, increment count by the number of elements in the segment (r - l + 1).
4. If the element at index l is not 0 and l is less than r, calculate the middle index m as  $(l + r) / 2$ . Recursively call findCount for the left segment (l to m) and the right segment (m + 1 to r).
5. read the size of the array n from the user.
6. Read Array Elements
7. Call the findCount function with the array a, and the indices 0 and n - 1.
8. Print count.

**Program:**

```
#include<stdio.h>
```

```
int count=0;
```

```
void findCount(int a[],int l,int r){
```

```

if(a[l]==0){
    count+=(r-l+1);
}else{
    if(l<r){
        int m=(l+r)/2;
        findCount(a,l,m);
        findCount(a,m+1,r);
    }
}
}

int main(){
    int n;
    scanf("%d",&n);
    int a[n];
    for(int i=0;i<n;i++){
        scanf("%d",&a[i]);
    }
    findCount(a,0,n-1);
    printf("%d",count);
}

```

**Output:**

	Input	Expected	Got	
✓	5 1 1 1 0 0	2	2	✓
✓	10 1 1 1 1 1 1 1 1 1 1 1	0	0	✓
✓	8 0 0 0 0 0 0 0 0 0	8	8	✓

## 4.b. Majority Element

**Aim:** Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than  $\lfloor n / 2 \rfloor$  times. You may assume that the majority element always exists in the array.

Example 1:

**Input:** `nums = [3,2,3]`

**Output:** 3

Example 2:

**Input:** nums = [2,2,1,1,1,2,2]

**Output:** 2

Constraints:

- $n == \text{nums.length}$
- $1 \leq n \leq 5 * 10^4$
- $-2^{31} \leq \text{nums}[i] \leq 2^{31} - 1$

**Algorithm:**

function Count(a[], l, r, key):

    mid = l + (r - l) / 2

    if a[mid] == key:

        increment count

    if l < mid:

        Count(a, l, mid, key)

    if mid + 1 < r:

        Count(a, mid + 1, r, key)

    return count

function main():

    n = input() // Read the size of the array

    arr[] = input() // Read the array of size n

    k = arr[0] // Set the first element as the key

    if Count(arr, 0, n, k) > n / 2:

        print(k) // If the count of k exceeds n/2, print it as the majority element

    else:

        for i = 0 to n / 2 - 1:

```
    if arr[i] != k:
        print(k) // If the first half contains an element different from k, print k
    break
```

### **Program:**

```
#include <stdio.h>

int count=0;

int Count(int a[],int l,int r,int key)
{
    int mid=l+(r-l)/2;
    if (a[mid]==key)
        count++;
    else
    {
        Count(a,l,mid,key);
        Count(a,mid+1,r,key);
    }
    return count;
}

int main()
{
    int n;
    scanf("%d",&n);
    int arr[n];
    for (int i=0;i<n;i++)
        scanf("%d",&arr[i]);
    int k=arr[0];
```

```

if (Count(arr,0,n,k)>n/2)
    printf("%d",k);
else
{
    for (int i=0;i<n/2;i++)
        if (arr[i]!=k)
        {
            printf("%d",k);
            break;
        }
}
}

```

**Output:**

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

## 4.c. Finding Floor Value

**Aim:** Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x. Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

### Algorithm:

```
function find(a[], l, r, key):
```

```
    if l <= r:
```

```
        if a[l] <= key:
```

```
            print a[l] // Print elements less than or equal to the key
```

```
        // Recursive case: divide the array into two parts and continue searching
```

```
        mid = (l + r) / 2
```

```
        find(a, l, mid, key) // Search left half
```

```
        find(a, mid + 1, r, key) // Search right half
```

```
function main():
```

```
    n = input() // Read the size of the array
```

```
    a[] = input() // Read the array of size n
```

```
    k = input() // Read the key
```

```
    find(a, 0, n-1, k) // Call the recursive function to print values <= key
```

### Program:

```
#include<stdio.h>
```

```
void find(int a[],int l,int r,int key)
```

```
{
```

```

    if(a[l] <= key)
    {
        printf("%d",a[l]);
    }
    else
    {
        if(l > r){
            int mid=(l+r)/2;
            find(a,l,mid+1,key);
            find(a,mid,r,key);
        }
    }
}

int main()
{
    int n;
    scanf("%d",&n);
    int a[n];

    for(int i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }

    int k;
    scanf("%d",&k);
    find(a,n-1,0,k);

```



}

Output:

	Input	Expected	Got	
✓	6 1 2 8 10 12 19 5	2	2	✓
✓	5 10 22 85 108 129 100	85	85	✓
✓	7 3 5 7 9 11 13 15 10	9	9	✓

## 4.d. Two Elements Sum to X

**Aim:** Given a sorted array of integers say `arr[]` and a number `x`. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = `x`. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer `n` – Size of array

Next `n` lines Contains `n` numbers – Elements of an array

Last Line Contains Integer `x` – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

**Algorithm:**

```
function sum(a[], l, r, s):
```

```
    if l < r:
```

```
        mid = (l + r) / 2 // Find the middle index
```

```
        if a[mid] + a[r] == s: // Check if the sum of a[mid] and a[r] equals s
```

```
            s1 = a[mid]
```

```
            s2 = a[r]
```

```
            return 1 // Pair found
```

```
        else:
```

```
            return sum(a, l, r - 1, s) // Continue searching in the subarray
```

```
function main():
```

```
    n = input() // Read the size of the array
```

```
    a[] = input() // Read the array of size n
```

```
    x = input() // Read the target sum x
```

```

result = sum(a, 0, n - 1, x) // Call the sum function

if result == 0:

    print("No") // If no pair is found, print "No"

else:

    print(s1)

    print(s2) // Print the two numbers found that add up to x

```

**Program:**

```

#include<stdio.h>

int s1=0,s2=0;

int sum(int a[],int l,int r,int s)
{
    if(l<r)
    {
        int mid=(l+r)/2;

        if(a[mid]+a[r]==s)
        {
            s1=a[mid];

            s2=a[r];

            return 1;
        }

        sum(a,l,r-1,s);
    }

    return 0;
}

```

```

}

int main()
{
    int n;

    scanf("%d",&n);

    int a[n];

    for(int i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }

    int x;

    scanf("%d",&x);

    int y=sum(a,0,n-1,x);

    if (y==0)

        printf("%s","No");

    else

    {

        printf("%d\n%d",s1,s2);

    }

}

```

**Output:**

	Input	Expected	Got	
✓	4 2 4 8 10 14	4 10	4 10	✓
✓	5 2 4 6 8 10 100	No	No	✓

## 4.e. Implementation of Quick Sort

**Aim:** Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n The next n lines contain the elements.

Output:

Sorted list of elements **Algorithm:**

```
function quickSort(a[], l, r):
```

```
    if l < r:
```

```
        pivotIndex = partition(a, l, r) // Partition the array and get the pivot index
```

```
        quickSort(a, l, pivotIndex - 1) // Recursively sort the left subarray
```

```
        quickSort(a, pivotIndex + 1, r) // Recursively sort the right subarray
```

```
function partition(a[], l, r):
```

```
    pivot = a[r] // Select the pivot (using the last element)
```

```

i = l - 1 // Pointer for the smaller element
for j = l to r - 1: // Iterate through the array
    if a[j] <= pivot: // If current element is smaller than or equal to the pivot
        i = i + 1
        swap(a[i], a[j]) // Swap elements
swap(a[i + 1], a[r]) // Move the pivot to the correct position
return i + 1 // Return the pivot index

```

function main():

```

n = input() // Read the size of the array
a[] = input() // Read the array of size n
quickSort(a, 0, n - 1) // Call the quickSort function to sort the array
print(a[]) // Print the sorted array

```

### **Program:**

```

#include<stdio.h>

void quick(int a[],int l,int r)
{
    if(l<r)
    {

        int p=(l+r)/2;

        int i=l;

        int j=r;

        while(i<j)
        {

```

```
while(a[p]>=a[i] )
```

```
{
```

```
    i++;
```

```
}
```

```
while(a[p]<a[j] )
```

```
{
```

```
    j--;
```

```
}
```

```
if(i<=j)
```

```
{
```

```
    int temp=a[i];
```

```
    a[i]=a[j];
```

```
    a[j]=temp;
```

```
}int temp=a[j];
```

```
a[j]=a[p];
```

```
a[p]=temp;
```

```
quick(a,l+1,r);
```

```
}
```

```
}
```

```

int main()

{

    int n;

    scanf("%d",&n);

    int a[n];

    for(int i=0;i<n;i++)

    {

        scanf("%d",&a[i]);

    }

    quick(a,0,n-1);

    for(int i=0;i<n;i++)

    {

        printf("%d ",a[i]);

    }

}

}

```

### Output:

	Input	Expected	Got	
✓	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✓
✓	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✓
✓	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✓



