

--	--	--

**Ex. No: 2**

**Date: 20.08.24**

**Register No.: 230701502**

**Name: Guru Raja T**

---

## **Finding Time Complexity of Algorithms**

### **2.a. Finding Complexity using Counter Method**

**Aim:** Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;    int s =1;

    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Algorithm:**

```
void function(int n){
    set count = 0
```

--	--	--

--	--	--

set i = 1

increment count by 1

set s = 1

increment count by 1

while (s <=n){

    increment count by 1

    increment i by 1

    increment count by 1

    set s = s + i

    increment count by 1

}

increment count by 1

print count

}

**Program:**

#include<stdio.h>

void function(int n){

    int count=0;

    int i=1;

    count++;

    int s=1;

    count++;

    while(s<=n){

        count++;

        i++;

--	--	--

--	--	--

```

    count++;

    s+=i;

    count++;

}

count++;

printf("%d",count);

}

int main(){

    int n;

    scanf("%d",&n);

    function(n);

}

```

Output:

	Input	Expected	Got	
✓	9	12	12	✓
✓	4	9	9	✓

Passed all tests! ✓

--	--	--

--	--	--

## 2.b. Finding Complexity using Counter Method

**Aim:** Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
        printf("*");
    }
    else
    {
        for(int i=1; i<=n; i++)
        {
            for(int j=1; j<=n; j++)
            {
                printf("*");
                printf("*");
                break;
            }
        }
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Algorithm:**

```
void func(int n){
    initialize count to 0

    if n = 1{
        increment count by 1
        print "*"
    }

    else{
        increment count by 1
```

--	--	--

--	--	--

```

// outer loop from 1 to n
for each i from 1 to n{
    increment count by 1

    // inner loop from 1 to n
    for each j from 1 to n{
        increment count by 1

        // simulate print statements with count increments
        increment count by 1 // first simulated printf("*")
        increment count by 1 // second simulated printf("*")

        // exit inner loop immediately
        increment count by 1 // break statement
    }
    increment count by 1
}
increment count by 1
}
print count
}

```

**Program:**

```

#include<stdio.h>

void func(int n)
{
    int count=0;
    if(n==1)

```

--	--	--

--	--	--

```

    { count++;
      printf("*");
    }
    else
    {count++;
      for(int i=1; i<=n; i++)
      { count++;
        for(int j=1; j<=n; j++)
        { count++;
          //printf("*");
          count++;
          //printf("*");
          count++;
          break;
        }
        count++;
      }
      count++;
    }
    printf("%d",count);
}

```

```

int main(){
    int n;
    scanf("%d",&n);
    func(n);
}

```

--	--	--

--	--	--

Output:

	Input	Expected	Got	
✓	2	12	12	✓
✓	1000	5002	5002	✓
✓	143	717	717	✓

--	--	--

--	--	--

## 2.c. Finding Complexity using Counter Method

**Aim:** Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
    for (i = 1; i <= num;++i)
    {
        if (num % i== 0)
        {
            printf("%d ", i);
        }
    }
}
```

**Note:** No need of counter increment for declarations and scanf() and counter variable printf() statement.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Algorithm:**

```
function Factor(num) {
    initialize count to 0

    // loop from 1 to num
    for each i from 1 to num {
        increment count by 1

        // check if i is a factor of num
        if num modulo i equals 0 {
            increment count by 1
            // simulate printing i (e.g., printf("%d ", i);)
        }
    }
```

--	--	--



--	--	--

```
    increment count by 1 // end of inner if-statement  
}
```

```
increment count by 1 // after loop completion
```

```
print count  
}
```

#### **Program:**

```
#include<stdio.h>  
  
void Factor(int num)  
{ int count=0;  
  for (int i = 1; i <= num;++i)  
  {  
    count++;  
    if (num % i== 0)  
    {  
      count++;  
      //printf("%d ", i);  
    }  
    count++;  
  }  
  count++;  
  printf("%d",count);  
}
```

```
int main(){
```

--	--	--

--	--	--

```
int n;  
scanf("%d",&n);  
Factor(n);  
}
```

Output:

	Input	Expected	Got	
✓	12	31	31	✓
✓	25	54	54	✓
✓	4	12	12	✓

--	--	--

--	--	--

## 2.d. Finding Complexity using Counter Method

**Aim:** Convert the following algorithm into a program and find its timecomplexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Algorithm:**

```
function(n) {
    initialize count to 0

    initialize c to 0

    increment count by 1

    // outer loop: i goes from n/2 to n-1
    for each i from n/2 to n-1 {
        increment count by 1

        // middle loop: j starts at 1 and doubles each iteration until j < n
        for each j starting from 1 and doubling each time (j = 2 * j) until j < n {
            increment count by 1
        }
    }
}
```

--	--	--

--	--	--

```

// inner loop: k starts at 1 and doubles each iteration until k < n
for each k starting from 1 and doubling each time (k = k * 2) until k < n {
    increment count by 1
    increment c by 1
    increment count by 1
}

increment count by 1 // after inner loop ends
}

increment count by 1 // after middle loop ends
}

increment count by 1 // after outer loop ends

print count
}

```

**Program:**

```

#include<stdio.h>

void function(int n)
{
    int count=0;
    int c= 0;
    count++;
    for(int i=n/2; i<n; i++){
        count++;
    }
}

```

--	--	--

--	--	--

```

for(int j=1; j<n; j = 2 * j){
    count++;
    for(int k=1; k<n; k = k * 2){
        count++;
        c++;
        count++;
    }
    count++;
}
count++;
}
count++;
printf("%d",count);
}

int main(){
    int n;
    scanf("%d",&n);
    function(n);
}

```

Output:

	Input	Expected	Got	
✓	4	30	30	✓
✓	10	212	212	✓

--	--	--

--	--	--

## 2.e. Finding Complexity using Counter Method

**Aim:** Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n /= 10;
    }
    print(rev);
}
```

**Note:** No need of counter increment for declarations and scanf() and count variable printf() statements.

**Input:**

A positive Integer n

**Output:**

Print the value of the counter variable

**Algorithm:**

```
function reverse(n) {
    initialize count to 0

    initialize rev to 0

    initialize remainder

    increment count by 1 // for initialization

    // loop until n is not equal to 0
    while n is not equal to 0 {
        increment count by 1 // start of loop

        remainder = n modulo 10
```

--	--	--

--	--	--

increment count by 1 // after calculating remainder

rev = rev \* 10 + remainder

increment count by 1 // after updating rev

n = n divided by 10

increment count by 1 // after updating n

}

increment count by 1 // after loop ends

// simulate printing rev (e.g., print(rev))

increment count by 1 // for print statement

print count

}

### Program:

```
#include<stdio.h>
```

```
void reverse(int n)
```

```
{
```

```
    int count=0;
```

```
    int rev = 0, remainder;
```

```
    count++;
```

```
    while (n != 0)
```

```
    {
```

```
        count++;
```

```
        remainder = n % 10;
```

--	--	--

--	--	--

```

        count++;

        rev = rev * 10 + remainder;

        count++;

        n/= 10;

        count++;

    }

    count++;

    //print(rev);

    count++;

    printf("%d",count);

}

```

```

int main(){

    int n;

    scanf("%d",&n);

    reverse(n);

}

```

Output:

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓

--	--	--