

EXP NO : 08

Nmap using tryhackme platform

DATE: 10.09.2024

Nmap Live Host Discovery

AIM:

To use Nmap to discovery live hosts using ARP Scan ,ICMP scan , and TCP/UDP Ping Scan in the tryhackme platform.

TASK : 2 - SUBNETWORKS:

Send a packet with following

Send Packet

From:

computer1



To:

computer1



Packet Type:

arp_request



Data:

computer6

Send Packet

- 1.From computer1
- 2.To computer1 (to indicate it is broadcast)
- 3.Packet Type: " ARP Request"

4.Data : computer6 (because we are asking for computer6 MAC address using ARP Request)

How many devices can see the ARP Request?

Ans : 4

Did computer6 receive the ARP Request ? (Y / N)

Ans : N

Send a packet with the following:

Send Packet

From:

computer4



To:

computer4



Packet Type:

arp_request



Data:

computer6

Send Packet

- 1.From computer4
- 2.To computer4 (to indicate it is broadcast)
- 3.Packet Type: “ ARP Request”
- 4.Data : computer6 (because we are asking for computer6 MAC address using ARP Request)

How many devices can see the ARP Request ?

Ans : 4

Did computer6 reply to the ARP Request ? (Y / N)

Ans : Y

TASK - 3 : Enumerating Targets

What is the first IP address Nmap would scan if you provided 10.10.12.13/29 as your target ?

Ans : 10.10.12.8

How many IP addresses will Nmap scan if you provide the following range 10.10.0-255.101-125 ?

Ans : 6400

TASK - 4 : Discovering Live Hosts

Send a packet with following :

- 1.From computer1
- 2.To computer3
- 3.Packet Type : “Ping Request”

What is the type of packet that computer1 sent before the ping ?

Ans : ARP Request

How many computers responded to the ping request?

Ans : 1

Send a packet with following:

- 1.From computer2

2.To computer5

3.Packet Type: "Ping Request"

What is the name of the first device that responded to the first ARP Request?

Ans : router

What is the name of the first device that responded to the second ARP Request?

Computer5

Send another Ping request.Did it required new ARP Requests? (Y / N)

Ans : N

TASK - 5 : Nmap Host Discovery Using ARP

We will be sending broadcast ARP Requests packets with the following options:

- From computer1
- To computer1 (to indicate it is broadcast)
- Packet Type: "ARP Request"
- Data: try all the possible eight devices (other than computer1) in the network: computer2, computer3, computer4, computer5, computer6, switch1, switch2, and router.

How many devices are you able to discover using ARP requests?

Ans : 3

TASK - 6 : Nmap Host Discovery Using ICMP

Nmap Host Discovery Using ICMP :

What is the option required to tell Nmap to use ICMP Timestamp to discover live hosts?

Ans : -PP

What is the option required to tell Nmap to use ICMP Address Mask to discover live hosts?

Ans : -PM

What is the option required to tell Nmap to use ICMP Echo to discover live hosts?

Ans : -PE

TASK - 7 : Nmap Host Discovery Using TCP and UDP

Which TCP ping scan does not require a privileged account?

Ans : TCP SYN Ping

Which TCP ping scan requires a privileged account?

Ans : TCP ACK Ping

What option do you need to add to Nmap to run a TCP SYN ping scan on the telnet port?

Ans : -PS23

TASK - 8 : Using Reverse - DNS Lookup

We want Nmap to issue a reverse DNS lookup for all the possible hosts on a subnet, hoping to get some insights from the names. What option should we add?

Ans : -R

RESULT :

Nmap to discover live host using ARP scan, ICMP scan and TCP/UDP ping scan in the tryhackme platform.