

EX NO:11D

Date:28.10.24

E.MONIKA

231901032

REMOTE PROCEDURE CALL FOR SORTING AN ARRAY -XMLRPC

AIM:

To Implement an XML RPC code for sorting array

Algorithm:

Algorithm

Server Program

1. **Import Required Library:** Import the xmlrpc.server library, which provides functionalities for setting up an XML-RPC server.
2. **Define sort_array Function:**
 - Define a function called sort_array that takes a list (arr) as input. ○ Inside this function, return the sorted version of arr.
3. **Set Up Server:**
 - Create an instance of SimpleXMLRPCServer, specifying localhost as the host and 8000 as the port.
 - Print a message indicating the server is running.
4. **Register Function:**
 - Register the sort_array function with the XML-RPC server under the name "sort_array". This makes it available for remote calls.
5. **Run the Server:**
 - Call server.serve_forever() to start the server and keep it running indefinitely, waiting for client requests.

Client Program

1. **Import Required Library:** Import the xmlrpc.client library to enable communication with the XML-RPC server.
2. **Connect to Server:**
 - Create a ServerProxy object to connect to the server running on http://localhost:8000.

3. Prepare Input Array:

- Define an array `arr` with some integer values that will be sent to the server for sorting.

4. Call `sort_array` Method:

- Use the `server.sort_array()` function to send `arr` to the server for sorting.
- Store the result (sorted array) in a variable `sorted_arr`.

5. Display Results:

- Print the original `arr` and the `sorted_arr` to verify the sorting operation was successful.

Program:

SERVER PROGRAM: import
xmlrpc.server

Function to sort the array

```
def sort_array(arr): return  
sorted(arr)
```

*# Setting up the server with xmlrpc.server.SimpleXMLRPCServer(('localhost',
8000)) as server:*

```
print("Server is running...")
```

Registering the sort_array function as an XML-RPC method

```
server.register_function(sort_array, 'sort_array')  
server.serve_forever()
```

CLIENT PROGRAM:

```
import xmlrpc.client
```

Connect to the server server =

```
xmlrpc.client.ServerProxy('http://localhost:8000')
```

Input array to be sorted arr

```
= [12, 4, 5, 3, 7, 2]
```

```
# Calling the sort_array method on the server sorted_arr  
= server.sort_array(arr)  
  
# Displaying the result print("Original  
Array:", arr) print("Sorted Array:",  
sorted_arr)
```

Output

SERVER OUTPUT

```
Server is running...
```

CLIENT OUTPUT

```
Original Array: [12, 4, 5, 3, 7, 2]  
Sorted Array: [2, 3, 4, 5, 7, 12]
```

```
Process finished with exit code 0
```

RESULT:

Procedure call for sorting an array - XMLRPC remoted.