

# 03-Python列表

## 列表介绍

- 列表由一系列特定顺序(sequence)排列的元素组成。
- 在Python中，用方括号[] 表示列表，用逗号分隔其中的元素。
- 最后一个元素后面的逗号会被忽略。

```
In [6]: bicycles = ['trek', 'cannondale', 'redline', 'specialized',]  
print(bicycles)
```

```
['trek', 'cannondale', 'redline', 'specialized']
```

python列表没有类型限制，列表中可以存放任意类型的元素

```
In [3]: elements = [3, 'hello', 2.5, True, 'world', ]  
print(elements)
```

```
[3, 'hello', 2.5, True, 'world']
```

利用索引访问列表元素

```
In [5]: numbers = [1, 2, 3, 4, 5]  
print(numbers[0])  
print(numbers[4])  
  
# 可以使用符号数作为索引，-1表示最后一个元素  
print(numbers[-1])  
print(numbers[-5])
```

```
1  
5  
5  
1
```

通过索引查找或者修改元素

```
In [1]: motorcycles = ['honda', 'yamaha', 'suzuki', ]  
motorcycles[0] = 'ducati'  
print(motorcycles)
```

```
['ducati', 'yamaha', 'suzuki']
```

在末尾附加元素：append方法

```
In [2]: motorcycles = ['honda', 'yamaha', 'suzuki', ]
motorcycles.append('ducati')
print(motorcycles)
```

```
['honda', 'yamaha', 'suzuki', 'ducati']
```

在列表中插入元素：insert方法

```
In [3]: motorcycles = ['honda', 'yamaha', 'suzuki', ]
motorcycles.insert(0, 'ducati')
print(motorcycles)
```

```
['ducati', 'honda', 'yamaha', 'suzuki']
```

使用del语句删除元素

```
In [4]: motorcycles = ['honda', 'yamaha', 'suzuki', ]
del motorcycles[0]
print(motorcycles)
```

```
['yamaha', 'suzuki']
```

del语句也可以用来删除其他简单变量

```
In [1]: message = 'Hello'
print(message)
del message
print(message)
```

```
Hello
```

```
-----
NameError                                Traceback (most recent call last)
Cell In[1], line 4
      2 print(message)
      3 del message
----> 4 print(message)
```

```
NameError: name 'message' is not defined
```

pop语句删除列表末尾的元素并返回元素值

```
In [2]: motorcycles = ['honda', 'yamaha', 'suzuki', ]
print(motorcycles)

popped_motorcycle = motorcycles.pop()
print(motorcycles)
print(popped_motorcycle)
```

```
['honda', 'yamaha', 'suzuki']
['honda', 'yamaha']
suzuki
```

pop语句删除列表任意位置的元素

```
In [4]: motorcycles = ['honda', 'yamaha', 'suzuki', ]
first_owned = motorcycles.pop(0)
print(f'The first motorcycle I owned was a {first_owned.title()}')
print(motorcycles)
```

The first motorcycle I owned was a Honda.  
['yamaha', 'suzuki']

`remove`方法根据值删除列表中的元素

```
In [5]: motorcycles = ['honda', 'yamaha', 'suzuki', 'ducati']
print(motorcycles)
motorcycles.remove('ducati')
print(motorcycles)
```

['honda', 'yamaha', 'suzuki', 'ducati']  
['honda', 'yamaha', 'suzuki']

如果列表中有相同的值，`remove`方法删除第一个匹配的值

```
In [7]: motorcycles = ['honda', 'yamaha', 'suzuki', 'honda']
motorcycles.remove('honda')
print(motorcycles)
```

['yamaha', 'suzuki', 'honda']

使用`sort()`方法对列表进行永久性(in place)排序

```
In [8]: cars = ['bmw', 'audi', 'toyota', 'subaru', ]
cars.sort()
print(cars)
```

['audi', 'bmw', 'subaru', 'toyota']

```
In [9]: cars.sort(reverse=True)
print(cars)
```

['toyota', 'subaru', 'bmw', 'audi']

使用`sorted()`函数对列表进行临时排序

```
In [13]: cars = ['bmw', 'audi', 'toyota', 'subaru', ]
print(f"The original list:\n {cars}\n")
print(f"The sorted list:\n {sorted(cars)}\n")
print(f"The original list:\n {cars}\n")
```

The original list:  
['bmw', 'audi', 'toyota', 'subaru']

The sorted list:  
['audi', 'bmw', 'subaru', 'toyota']

The original list:  
['bmw', 'audi', 'toyota', 'subaru']

倒着打印列表：使用`reverse()`方法

```
In [14]: cars = ['bmw', 'audi', 'toyota', 'subaru', ]
print(cars)
cars.reverse()
print(cars)
```

['bmw', 'audi', 'toyota', 'subaru']  
['subaru', 'toyota', 'audi', 'bmw']

确定列表的长度： 使用`len()`函数

```
In [15]: len(cars)
```

Out[15]: 4

很多其他数据类型和数据结构都可以使用`len()`函数

```
In [16]: len('hello world')
```

Out[16]: 11

## 操作列表

遍历整个列表

```
In [17]: magicians = ['alice', 'david', 'carolina', ]
for magician in magicians:
    print(magician)
```

alice  
david  
carolina

在Python语言中，使用 `:` 表示代码块的开始，使用缩进来表示代码块

```
In [18]: magicians = ['alice', 'david', 'carolina',]
for magician in magicians:
    print(f"{magician.title()}, that was a great trick!")
    print(f"I can't wait to see your next trick, {magician.title()}. \n")

print("Thank you, everyone. That was a great magic show!")
```

Alice, that was a great trick!  
I can't wait to see your next trick, Alice.

David, that was a great trick!  
I can't wait to see your next trick, David.

Carolina, that was a great trick!  
I can't wait to see your next trick, Carolina.

Thank you, everyone. That was a great magic show!

使用 `range()` 函数创建数值列表

```
In [19]: for value in range(1, 5):
        print(value)
```

1  
2  
3  
4

使用 `range()` 函数产生1到10的偶数, `range()` 函数的第三个参数表示步长

```
In [21]: for value in range(2, 11, 2):
        print(value)
```

2  
4  
6  
8  
10

`range()` 函数的步长可以是负数

```
In [29]: for value in range(5, 0, -1):
        print(value, end=' ')
```

5 4 3 2 1

使用 `range()` 函数创建数字列表

```
In [30]: numbers = list(range(1, 6))
print(numbers)
```

[1, 2, 3, 4, 5]

对数字列表进行统计计算

```
In [31]: digits = [1, 2, 3, 4, 5, 6, 7, 8, 9, 0, ]  
min(digits)
```

Out[31]: 0

```
In [35]: max(digits)
```

Out[35]: 9

```
In [34]: sum(digits)
```

Out[34]: 45

## 列表解析 (List Comprehension)

```
In [36]: #列表解析格式: [ 变量表达式 for 变量 in 列表 ]  
squares = [ value**2 for value in range(1, 11)]  
print(squares)
```

[1, 4, 9, 16, 25, 36, 49, 64, 81, 100]

## 列表切片 (Slice)

```
In [37]: players = ['charles', 'martina', 'michael', 'florence', 'eli', ]  
print(players[0:3]) # 切片的长度等于3-0=3
```

['charles', 'martina', 'michael']

```
In [38]: print(players[1:4])
```

['martina', 'michael', 'florence']

```
In [39]: print(players[:4])
```

['charles', 'martina', 'michael', 'florence']

```
In [40]: print(players[2:])
```

['michael', 'florence', 'eli']

```
In [41]: print(players[-3:])
```

['michael', 'florence', 'eli']

## 切片的步长

```
In [47]: numbers = list(range(1, 11))
         print(numbers[1:10:2])
```

[2, 4, 6, 8, 10]

### 步长可以为负数

```
In [44]: print(numbers[9:0:-2])
```

[10, 8, 6, 4, 2]

```
In [48]: print(numbers[-1:-10:-2])
```

[10, 8, 6, 4, 2]

### 复制列表

```
In [58]: my_food = ['pizza', 'falafel', 'carrot cake', ]
         # 不可以这样复制列表
         # friend_food = my_food

         friend_food = my_food[:]
         friend_food.append('cannoli')
         my_food.append('ice cream')

         print(my_food)
         print(friend_food)
         print(id(my_food))
         print(id(friend_food))
```

['pizza', 'falafel', 'carrot cake', 'ice cream']  
['pizza', 'falafel', 'carrot cake', 'cannoli']  
2887549032640  
2887549033920

### 使用extend方法扩展列表

```
In [50]: numbers = list(range(1, 11))
         numbers.extend([11, 12, 13])
         print(numbers)
```

[1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13]

### 使用双端队列deque

```
In [54]: from collections import deque
dq = deque(range(10))
dq.append(11)
dq.appendleft(-1) # appendleft效率比insert(0, -1)高
print(dq)

dq.pop()
dq.popleft()
print(dq)
```

```
deque([-1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 11])
deque([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

```
In [72]: dq.index(5)
```

```
Out[72]: 6
```

```
In [55]: dq.extend([11, 12, 13])
dq.extendleft([-1, -2, -3])
print(dq)
```

```
deque([-3, -2, -1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12, 13])
```

```
In [57]: dq.rotate(1) # 向右旋转1位
print(dq)

dq.rotate(-4) # 向左旋转1位
print(dq)
```

```
deque([12, 13, -3, -2, -1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 11])
deque([-1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12, 13, -3, -2])
```

## 元组 (Tuple)

```
In [59]: dimensions = (200, 50)
print(dimensions[0])
print(dimensions[1])
```

```
200
50
```

## 遍历元组

```
In [64]: for dimension in dimensions:
print(dimension)
```

```
200
50
```

元组中数据是不可以修改的



```
In [60]: dimensions[0] = 250
```

```
-----  
TypeError                                Traceback (most recent call last)  
Cell In[60], line 1  
----> 1 dimensions[0] = 250  
  
TypeError: 'tuple' object does not support item assignment
```

只包含一个元素的元组，必须在元素后面加上逗号

```
In [67]: m_t = (3, )  
m_t
```

```
Out[67]: (3,)
```