

Alarm Clock

Embedded Systems Project Report

Monday 10:00 lab

Jakub Pawlak	Artur Pietrzak
234767@edu.p.lodz.pl	234768@edu.p.lodz.pl
Juliusz Szymajda	
234769@edu.p.lodz.pl	

April 3, 2022

Devices used:

Eduboard LPC2148 v1.0

Interfaces used:

GPIO, I²C, SPI

Devices used:

1. LCD display
2. RTC
3. Button
4. Joystick
5. Buzzer
6. Timer
7. EEPROM

Contents

1	Project Description	4
1.1	General description	4
1.2	Setting the alarm	4
1.3	Changing the current time	4
1.4	Turning off the alarm	4
2	Peripherals and interface configuration	5
2.1	LCD Display	5
2.2	GPIO	6
2.3	I ² C	6
2.4	SPI	6
2.5	Debounce Timer	6
3	Failure Mode and Effect Analysis	6
	References	6
	Code Listings	
1	LCD setup function	5

1 Project Description

1.1 General description

The project is an digital clock with the ability to set an alarm for a given hour. The device displays current time on the LCD display. Using button and joystick it is possible to set the current time, or set an alarm. If the alarm is set and the alarm time is the current time, the buzzer emits a sound until the alarm is turned off.

1.2 Setting the alarm

The alarm setting mode it entered by pressing down the joystick center push-down switch. When in alarm setting mode, the user can change the alarm time by selecting the digit with left/right movement, and selecting the value with up/down movement. After the correct time is selected, alarm is set by pressing the button.

When alarm is turned on, it can be turned off by short press of the button.

1.3 Changing the current time

The time setting mode is entered by holding down the button. Then, the time is set with the joystick in the similar way, the alarm is set. After setting the time it is set by short press of the button.

1.4 Turning off the alarm

When the alarm clock starts emmiting sound, the user can turn it off by pressing the button.

2 Peripherals and interface configuration

2.1 LCD Display

```
62 void DisplayInit(void) {
63     IODIR1 |= (LCD_DATA | LCD_E | LCD_RS);
64     IOCLR1  = (LCD_DATA | LCD_E | LCD_RS);
65
66     IODIRO |= LCD_RW;
67     IOCLRO  = LCD_RW;
68
69     IODIRO |= LCD_BACKLIGHT;
70     IOCLRO  = LCD_BACKLIGHT;
71
72     LcdCommand(0x30);
73     delay2ms();
74     LcdCommand(0x30);
75     delay37us();
76     LcdCommand(0x30);
77     delay37us();
78
79     LcdCommand(0x38); // set 8-bit, 2 line mode
80     delay37us();
81
82     LcdCommand(0x08); // display off
83     delay37us();
84
85     clearDisplay();
86
87     LcdCommand(0x06); // cursor direction - increment, no shift
88     delay2ms();
89
90     LcdCommand(0x0c); // display on, cursor off
91     delay2ms();
92
93     LcdCommand(0x02); // cursor to home position
94     delay2ms();
95 }
```

Listing 1: LCD setup function

2.2 GPIO

2.3 I²C

2.4 SPI

2.5 Debounce Timer

3 Failure Mode and Effect Analysis

Component	Severity
Microcontroller	Critical
Power Supply	Critical ¹
RTC	Critical
LCD Display	High
Speaker	High
Button	High
Joystick	High

Table 1: Severity of component's failure

References

- [1] Embedded Artists. *LPC2148 Education Board User's Guide*, 2006. EA2-USG-0601 v1.2 Rev B.
- [2] Hitachi. *HD44780U (LCD-II) (Dot Matrix Liquid Crystal Display Controller/Driver)*. ADE-207-272(Z) '99.9 Rev. 0.0.

¹Long-term power supply failures are of critical severity, but in case of short pause in power delivery, the system is able to recover using the RTC and the data stored in EEPROM