pynvme: test NVMe devices in Python

https://github.com/cranechu/pynvme

pynvme

The pynvme is a python extension module.

Users can operate NVMe SSD intuitively in

Python scripts. It is designed for NVMe SSD

testing with performance considered.

Integrated with third-party tools, vscode and pytest, pynvme provides a convenient and professional solution to test NVMe devices.






First Example

```
cranechu@localhost: ~/pynyme
Host Read Commands:
                             203987588
                                                                           ~/pvnvme▶ sudo pvthon3
Host Write Commands:
                             25207644
                                                                          Python 3.7.2 (default, Jan 16 2019, 19:49:22)
Controller Busy Time:
                             1542 minutes
                                                                          [GCC 8.2.1 20181215 (Red Hat 8.2.1-6)] on linux
Power Cycles:
                             45
                                                                          Type "help", "copyright", "credits" or "license" for more information.
Power On Hours:
                             42 hours
                                                                          >>> import nyme
Unsafe Shutdowns:
                                                                          Starting SPDK v19.01-pre / DPDK 18.08.0 initialization...
                             19
Unrecoverable Media Errors: 28
                                                                           [ DPDK EAL parameters: pynyme driver -c 0x2 -m 5892 --base-virtaddr=0x20
Lifetime Error Log Entries: 1563
                                                                          000000000 -- file-prefix=spdk0 --proc-type=auto 1
Warning Temperature Time:
                                                                          EAL: Detected 4 lcore(s)
                             0 minutes
                                                                          EAL: Detected 1 NUMA nodes
Critical Temperature Time:
                            0 minutes
Temperature Sensor 1:
                             318 Kelvin (45 Celsius)
                                                                          EAL: Auto-detected process type: PRIMARY
                                                                          EAL: Multi-process socket /var/run/dpdk/spdk0/mp socket
Number of Oueues
                                                                          EAL: Probing VFIO support...
 .========
                                                                          EAL: no supported IOMMU extensions found!
Number of I/O Submission Oueues:
                                                                          EAL: VFIO support could not be initialized
Number of I/O Completion Oueues:
                                                                          >>> nvme0 = nvme.Controller(b'01:00.0')
                                                                          EAL: PCI device 0000:01:00.0 on NUMA socket 0
Namespace ID:1
                                                                          EAL: probe driver: 1179:113 spdk nyme
Deallocate:
                                                                          nvme pcie.c: 992:nvme pcie qpair construct: *INFO*: max completions cap
                             Supported
Deallocated/Unwritten Error: Not Supported
                                                                           32 num trackers = 96
Deallocated Read Value:
                                                                          driver.c: 449:attach cb: *INFO*: attached device 0000:01:00.0: KBG30ZMS2
                             Unknown
Deallocate in Write Zeroes:
                            Not Supported
                                                                          . 1 namespaces, pid 3001
                                                                                                         ADDA0102
Deallocated Guard Field:
                             0xFFFF
                                                                          >>> nyme0n1 = nyme.Namespace(nyme0)
                                                                          driver.c: 76:memzone reserve shared memory: *INFO*: create token table,
                             Supported
                                                                          size: 2000472768
Reservation:
                             Not Supported
                                                                          >>> eui64 = nvme0n1.id data(127, 120)
Namespace Sharing Capabilities: Private
Size (in LBAs):
                             500118192 (476M)
                                                                          >>> eui64
 Capacity (in LBAs):
                             500118192 (476M)
                                                                          1604155579155941376
Utilization (in LBAs):
                             500118192 (476M)
                                                                          >>> eui64.to bytes(8, byte order='little'
                                                                           ...).hex()
Thin Provisioning:
                             Not Supported
                                                                          Traceback (most recent call last):
Per-NS Atomic Units:
                                                                            File "<stdin>". line 1. in <module>
NGUID/EUI64 Never Reused:
                             No
                                                                          TypeError: to bytes() missing required argument 'byteorder' (pos 2)
Number of LBA Formats:
                                                                          >>> eui64.to bytes(8, byteorder='little').hex()
Current LBA Format:
                             LBA Format #01
                                                                           '00080d04001b4316'
LBA Format #00: Data Size: 4096 Metadata Size:
                                                                          >>> # the EUI64 got by pynvme is just the same as the spdk example. Good
LBA Format #01: Data Size: 512 Metadata Size:
                                                                          >>> exit()
                                                                           ~/pynvme▶
```

SPDK

pynvme


Pynvme is based on SPDK



Pynvme Architecture

Build python library with Cython:


- setup.py
- driver.c
- driver.h
- cdriver.pxd
- driver wrap.pyx
- Makefile



Pynvme Architecture

Organize test cases in pytest:

- mvme.so
- pytest.ini
- conftest.py
- driver_test.py




Why Python?

- $\sqrt{}$ Many beautiful mature libraries
 - pytest
 - logging
 - multiprocessing
 - numpy
 - matplotlib
 - pydoc
 - os, io, time, pytemperature, statistics, yaml, json, struct, ...
- √ Friendly IDEs for developing, debugging, and testing
 - VSCode, emacs, Pycharm
- $\sqrt{}$ CI: develop firmware softly










Pynvme CI Status



Config and Compile

- git clone https://github.com/cranechu/pynvme
- 2. cd pynvme
- 3. ./install.sh
- 4. now, ready to run test scripts with pytest
- Fedora29 is recommended.
- find test script examples in driver test.py.
- find more => https://github.com/cranechu/pynvme

Pytest Execution



- "The pytest framework makes it easy to write small tests, yet scales to support complex functional testing for applications and libraries."
- "pytest fixtures offer dramatic improvements over the classic xUnit style of setup/teardown functions"
- pytest test_mod.py # run tests in a module
- pytest testing/ # run tests in a directory
- pytest test_mod.py::test_func # run a specific test case
- pytest test_mod.py -s # run tests without log capturing
- https://media.readthedocs.org/pdf/pytest/latest/pytest.pdf

Test Script Files

```
emacs
import pytest
                             34 # -*- coding: utf-8 -*-
                             35
                             36
                             37 import os
                                import time
                                                                                        pytest collects test
                                import pytest
import nyme
                                                                                      files and cases before
                             40 import logging
                             41 import warnings
                                                                                             execution
                                import nyme as d
test functions
                                def test create device(nvme0, nvme0n1):
                             46
                                    assert nyme0 is not None
                             47
                                def test create device invalid():
test file name
                                    with pytest.raises(d.NvmeEnumerateError):
                                        nvme1 = d.Controller(b"00:00.0")
                           55k 35: 0 UU-x-~/pynvme/driver test.py
                                                                            3% -master Python
```

An Example

pytest fixtures

pytest cases are started with test

create qpair and buffer for write commands

write data, and then read in the callback

```
_ _ ×
                                 emacs
  def test write identify and verify with callback(nvme0, nvme0n1):
        id buf = d.Buffer(4096)
249
250
        nvme0.identifv(id buf).waitdone()
251
252
        q = d.Qpair(nvme0, 20)
253
        n = nvme0n1
        read buf = d.Buffer(4096, "read buffer")
255
256
        def read cb(cdw0, status):
257
             assert id buf[:40] == read buf[:40]
258
259
        def write cb(cdw0, status):
            n.read(g, read buf, 5, 8, cb=read cb)
260
261
        n.write(q, id buf, 5, 8, cb=write cb).waitdo.
 ZUZ
263
264
        id buf[0] += 1
        n.write(q, id buf, 5, 8, cb=write cb).waitdone(2)
        id buf[9] = (id buf[9] >> 1)
266
267
        n.write(q, id buf, 5, 8, cb=write cb).waitdone(2)
268
55k 249: 0 UU- -~/pynvme/driver test.py 15% -master Python [test
In: test write identify and verify with callback()
```

fill buffer with identify data

callback functions are called when cmds are completed

the status of the callback function also includes the **Phase Tag** bit

IOWorker

```
emacs
                                                                                           define IO patterns in
                                                                                           ioworker's parameter
1066 @pytest.mark.parametrize("qcount", [1, 2, 4, 8, 15])
1067 def test ioworker iops multiple queue(nvme0n1, qcount):
                                                                                                     list
1068
         1 = [1]
         io total = 0
1069
1070
         for i in range(gcount):
             a = nvme0n1.ioworker(io size=8, lba align=8,
1071
1072
                                  region start=0, region end=256*1024*8, # 1GB space
                                                                                                send IO in a
1073
                                  lba random=False, gdepth=16,
                                                                                             separated process
1074
                                  read percentage=100, time=10).start()
1075
             l.append(a)
1076
1077
         for a in 1:
1078
             r = a.close()
                                                                                             wait ioworkers till
1079
             io total += (r.io count read+r.io count write)
                                                                                             finish, and collect
1080
1081
                                                                                                 result data
         logging.info("Q %d IOPS: %dK" % (gcount, io total/10000))
1082
55k 1068: 0 UU- -~/pynvme/driver test.py
                                                 60% -master Python [test ioworker iop
In: test ioworker iops multiple queue()
```


Fixtures of Pynvme

- create/delete test objects. in conftest.py:
 - nvme0
 - nvme0n1
 - pcie
 - ...
- parametrize of tests
 - @pytest.mark.parametrize("qcount", [1, 2, 4, 8, 15])
 - @pytest.mark.parametrize("repeat", range(10))
- test control
 - @pytest.mark.skip("nvme over tcp")
- doc: https://docs.pytest.org/en/latest/fixture.html


Visual Studio Code

X

- VSCode is the most popular IDE.
 - root user is not recommended by vscode, so users need to run sudo without a password: sudo visudo
- Pynvme also providers an extension to monitor device status and cmdlog in every qpair. To install the extension:
 - code --install-extension pynvme-console-0.1.2.vsix
- Add DUT pci address to .vscode/settings.json
 - get the BDF address with Ispci
- make setup; code . # launch the vscode



Welcome to use and contribute



https://github.com/cranechu/pynvme