

Discovering Frequent Patterns in Big Data Using FFIMiner Algorithm

In this tutorial, we will discuss two approaches to find frequent patterns in big data using FFIMiner algorithm.

1. **Basic approach:** Here, we present the steps to discover frequent patterns using a single minimum support value
 2. **Advanced approach:** Here, we generalize the basic approach by presenting the steps to discover frequent patterns using multiple minimum support values.
-

Basic approach: Executing FFIMiner on a single dataset at a particular minimum support value

Step 1: Import the FFIMiner algorithm

```
In [1]: from PAMI.fuzzyFrequentPatterns.basic import FFIMiner as alg
```

Step 2: Specify the following input parameters

```
In [2]: inputFile = 'T10_utility.txt'

minimumSupportCount=1000 #Users can also specify this constraint between 0 to 1.

separator=' '
```

Step 3: Execute the FFIMiner algorithm

```
In [3]: obj = alg.FFIMiner(iFile=inputFile, minSup=minimumSupportCount, sep=separator) #
obj.startMine() #Start the mining process
```

Step 4: Storing the generated patterns

Step 4.1: Storing the generated patterns in a file

```
In [4]: obj.savePatterns(outFile='frequentPatternsMinSupCount1000.txt')
```

Step 4.2. Storing the generated patterns in a data frame

```
In [5]: frequentPatternsDF= obj.getPatternsAsDataFrame()
```

Step 5: Getting the statistics

Step 5.1: Total number of discovered patterns

```
In [6]: print('Total No of patterns: ' + str(len(frequentPatternsDF)))
```

Total No of patterns: 383

Step 5.2: Runtime consumed by the mining algorithm

```
In [7]: print('Runtime: ' + str(obj.getRuntime()))
```

Runtime: 331.8520133495331

```
In [8]: ##### Step 5.3: Total Memory consumed by the mining algorithm
```

```
In [9]: print('Memory (RSS): ' + str(obj.getMemoryRSS()))  
print('Memory (USS): ' + str(obj.getMemoryUSS()))
```

Memory (RSS): 425664512

Memory (USS): 386793472