

ECLAT

July 1, 2022

1 Discovering Frequent Patterns in Big Data Using ECLAT Algorithm

In this tutorial, we will discuss two approaches to find frequent patterns in big data using ECLAT algorithm.

1. Basic approach: Here, we present the steps to discover frequent patterns using a single minimum support value
 2. Advanced approach: Here, we generalize the basic approach by presenting the steps to discover frequent patterns using multiple minimum support values.
-

1.1 Basic approach: Executing ECLAT on a single dataset at a particular minimum support value

Step 1: Import the ECLAT algorithm

```
[1]: from PAMI.frequentPattern.basic import ECLAT as alg
```


Step 2: Specify the following input parameters

```
[2]: inputFile = 'transactional_T10I4D100K.csv'

minimumSupportCount=100 #Users can also specify this constraint between 0 to 1.

seperator='\t'
```

Step 3: Execute the ECLAT algorithm

```
[3]: obj = alg.ECLAT(iFile=inputFile, minSup=minimumSupportCount, sep=seperator)  
      ↪ #initialize
      obj.startMine() #Start the mining process
```

Frequent patterns were generated successfully using ECLAT algorithm

Step 4: Storing the generated patterns

Step 4.1: Storing the generated patterns in a file

```
[4]: obj.savePatterns(outFile='frequentPatternsMinSupCount100.txt')
```

Step 4.2. Storing the generated patterns in a data frame

```
[6]: frequentPatternsDF= obj.getPatternsAsDataFrame()
```

Step 5: Getting the statistics

Step 5.1: Total number of discovered patterns

```
[7]: print('Total No of patterns: ' + str(len(frequentPatternsDF)))
```

Total No of patterns: 27532

Step 5.2: Runtime consumed by the mining algorithm

```
[8]: print('Runtime: ' + str(obj.getRuntime()))
```

Runtime: 8.184143304824829

```
[8]: ##### Step 5.3: Total Memory consumed by the mining algorithm
```

```
[9]: print('Memory (RSS): ' + str(obj.getMemoryRSS()))  
print('Memory (USS): ' + str(obj.getMemoryUSS()))
```

Memory (RSS): 580968448

Memory (USS): 542699520

1.2 Advanced approach: Executing ECLAT on a single dataset at multiple minimum support values

Step 1: Import the ECLAT algorithm

```
[10]: from PAMI.frequentPattern.basic import ECLAT as alg
```

Step 2: Specify the following input parameters

```
[11]: inputFile = 'transactional_T10I4D100K.csv'  
  
minimumSupportCountList = [100, 150, 200, 250, 300]  
#Users can also specify this constraint between 0 to 1. E.g., minSupList = [0.  
↪ 0.005, 0.006, 0.007, 0.008, 0.009]  
  
seperator='\t'
```

Step 3: Initialize Data Frame to save values

```
[12]: import pandas as pd
result = pd.DataFrame(columns=['algorithm', 'minSup', 'patterns', 'runtime', 'memory'])
```

Step 4: Execute the ECLAT algorithm using a for loop

```
[13]: algorithm = 'ECLAT'
for minSupCount in minimumSupportCountList:
    obj = alg.ECLAT('transactional_T10I4D100K.csv', minSup=minSupCount, sep=separator)
    obj.startMine()
    df = pd.DataFrame([algorithm, minSupCount, len(obj.getPatterns()), obj.getRuntime(), obj.getMemoryRSS()], index=result.columns).T
    result = result.append(df, ignore_index=True)
```

Frequent patterns were generated successfully using ECLAT algorithm

/tmp/ipykernel_110903/3559891175.py:6: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a future version. Use pandas.concat instead.

```
result = result.append(df, ignore_index=True)
```

Frequent patterns were generated successfully using ECLAT algorithm

Frequent patterns were generated successfully using ECLAT algorithm

Frequent patterns were generated successfully using ECLAT algorithm

Frequent patterns were generated successfully using ECLAT algorithm

Step 5: Plotting the graphs

Step 5.1 Importing the plot library


```
[14]: from PAMI.extras.graph import plotLineGraphsFromDataFrame as plt
```

Step 5.2. Plotting the number of patterns


```
[15]: ab = plt.plotGraphsFromDataFrame(result)
ab.plotGraphsFromDataFrame()
```

/home/jupyterHub/anaconda3/envs/jupyterHub/lib/python3.10/site-packages/pandas/core/indexes/base.py:6982: FutureWarning: In a future version, the Index constructor will not infer numeric dtypes when passed object-dtype sequences (matching Series behavior)


```
return Index(sequences[0], name=names)
```



Graph for No Of Patterns is successfully generated!



Graph for Runtime taken is successfully generated!



Graph for memory consumption is successfully generated!

1.2.1 Step 6: Saving the results in a latex file

```
[16]: from PAMI.extras.graph import generateLatexFileFromDataFrame as gdf
      gdf.generateLatexCode(result)
```

Latex files generated successfully