Advanced Composites Studio Limited

FireCoat-X™ ThermaClear™

Therma Clear

Transparent Fireproof Material / Product Summary

FireCoat-X™ ThermaClear™ brings a transparent finish and fire protection together, preserving the colour and texture of the substrate. On exposure to fire, the coating rapidly expands to form an insulating char layer.

Transparent by design

A colourless, transparent protective layer that preserves the material's original colour and natural texture.

Protection through expansion

An intumescent system that forms an insulating char layer to separate the substrate from heat and oxygen.

Water-based application

Suitable for spraying or brushing, dilutable with water and able to form a film at room temperature.

Property	Reported value	Material or context
Light transmittance	>65%	Transparent coating
Maximum expansion ratio	120x	Expansion and char formation on fire exposure
Surface hardness	6H	Coating surface
Adhesion	>1.25 MPa	Adhesion stated in the product material
Fire and thermal protection for wood	>2 h	5 mm wood
Fire and thermal protection for cardboard	>1 h	1 mm cardboard

Substrates: Wood / Glass / Cardboard / FRP composites
Application areas: Architecture & heritage / Packaging & logistics / Rail transit interiors

Figures reflect the product materials and updated product specifications. Protection times refer to the substrates and thicknesses stated in those materials.
Figures reflect product images 3 and 4 and updated product specifications. This summary is not an independent test report.