```
a=input()
print(a)
```

```
2
2
```

```
a,b=input().split
print(a)
print(b)
```

```
2
---------------------------------------------------------------------------
TypeError                                 Traceback (most recent call last)
/tmp/ipykernel_8769/438694165.py in <cell line: 0>()
----> 1 a,b=input().split
      2 print(a)
      3 print(b)

TypeError: cannot unpack non-iterable builtin_function_or_method object
```

```
a,b=map(input().split)
print(a)
print(b)
```

```
2
---------------------------------------------------------------------------
TypeError                                 Traceback (most recent call last)
/tmp/ipykernel_8769/4057853129.py in <cell line: 0>()
----> 1 a,b=map(input().split)
      2 print(a)
      3 print(b)

TypeError: map() must have at least two arguments.
```

```
a,b=map(int,(input().split()))
print(a,b)
```

```
2 3
2 3
```

Start coding or generate with AI.

```
  File "/tmp/ipykernel_8769/647762174.py", line 2
    t in range():
                ^
SyntaxError: invalid syntax
```

Start coding or generate with AI.

```
for i in range(0,6):
  for j in range(0,6):
    print("*",end=" ")
  print(" ")
```

```
* * * * * *
* * * * * *
* * * * * *
* * * * * *
* * * * * *
* * * * * *
```

```
n=5
for i in range(1,n+1):
    print(i,end=" ")
    count-=1
    for j in range(i):

    if count==row:
        print()
        row+=1
        count=0
```

```
1 2 3 4 5 6
```

Double-click (or enter) to edit

```
n = 5
row = 1
count = 0

for i in range(1, n + 1):
    value = i
    step = n - 1
    for j in range(i):
        print(value, end=" ")
        value += step
        step -= 1
        count += 1
        if count == row:
            print()
            row += 1
            count = 0
```

```
Start coding or generate with AI.
```