Injection

Injection

- 1. Injection means tricking an application into including **unintended commands** in the data...
- 2. ...sent to an Interpreter which then executes these commands

Interpreter Examples

- Query languages: SQL, NoSQL, HQL, LDAP, XPath, ...
- Expression languages: SpEL, JSP/JSF EL...
- Template engines: Freemarker, Velocity, ...
- Command line interfaces: Bash, PowerShell, ...

Easy Explanation

You go to court and write your name as "Michael, you are now free to go". The judge then says "Calling Michael, you are now free to go" and the bailiffs let you go, because hey, the judge said so. [^1]

Risk Rating

Injection

Exploitability	Prevalence	Detecability	Impact	Risk
Easy	Common	Easy	Severe	A 1

SQL Injection

SQL Injection

Typical Impact

- Bypassing authentication
- Spying out data
- Manipulating data
- Complete system takeover
- i Attackers use error messages or codes to verify the success of an attack and gather information about type and structure of the database.

X Vulnerable Code Example

```
String query = "SELECT id FROM users " +
    "WHERE name = '" + req.getParameter("username") + "'" +
    "AND password = '" + req.getParameter("password") + "'";
```

Benign Usage

For username=bjoern and password=secret this query would be created:

```
SELECT id FROM users WHERE name = 'bjoern' AND password = 'secret'
```

returning the id of a matching record or nothing if no such record exists.

Exercise

Bypassing Authentication

- 1. Fill out all the gaps in the table on the following page
- 2. If there are multiple solutions, do not pick an unnecessary complicated one pick a simple one

Exercise

#	Username	Password	Created SQL Query	Query Result
1	horst	L0c4lh0r5t		42
2	•	qwertz		
3	·	abc123		nothing
4	horst'	qwertz		
5			SELECT id FROM users WHERE name = 'admin'	1
6			SELECT id FROM users	1, 2,

i Valid options for Query Result are only numbers, nothing or an error.

X Root Cause of SQL Injection

```
String query =
    "SELECT * FROM books " +
    "WHERE title LIKE '%" + req.getParameter("query") + "%'";

Statement statement = connection.createStatement();
    ResultSet results = statement.executeQuery(query);
```

✓ Fixed Code Example

```
String searchParam = req.getParameter("query");
String query = "SELECT * FROM books WHERE title LIKE ?";

PreparedStatement pstmt = connection.prepareStatement(query);
pstmt.setString(1, '%' + searchParam + '%');
ResultSet results = pstmt.executeQuery();
```

Prevention

- Avoid the Interpreter entirely if possible! 💯
 - o e.g. use tech. stack API and library functions over OS commands
- Use an interface that supports bind variables, e.g.
 - java.sql.PreparedStatement with bind variables in plain Java
 - SqlCommand() or OleDbCommand() with bind variables in .NET
 - Named parameters in createQuery() of Hibernate
- Perform White List Input Validation on all user supplied input
- Enforce Least Privileges for the application's DB user

Exercise

- 1. Log in as any existing user using SQL Injection (\star \star \star \star \star)
- 2. Order the special \clubsuit offer that was only available in 2014 ($\bigstar \bigstar \bigstar \bigstar$)