Authentication Flaws

X Typical Flaws in Authentication

- Permits brute force or other automated attacks
- Permits default, weak, or well-known passwords
- Uses weak or ineffective credential recovery and forgot-password processes (e.g. "knowledge-based answers")
- Uses plain text, encrypted, or weakly hashed passwords
- Has missing or ineffective multi-factor authentication
- Exposes Session IDs in the URL
- Does not rotate Session IDs after successful login
- Does not properly invalidate Session IDs

Risk Rating

Broken Authentication


Exploitability	Prevalence	Detecability	Impact	Risk
Easy	Common	Average	Severe	A2
(3	+ 2	+ 2)/3	* 3	= 7.0

Exercise

- 1. Watch How To Keep Your Passwords Safe 📺
- 2. Log in with MC SafeSearch's user account (\(\dagger \dagger \))

Exercise

- 1. Pick one Security Question and explain how 6 it is against attacks.
- 2. What would you recommend to pick as an answer? Assume that the risk of compromise is full takeover of your user account.



Password Strength Controls

- Enforce minimum password length of at least 10 characters
- Maximum length should allow 64 characters or more
- No periodic password resets as users rely on predictable patterns
- Avoid password complexity rules as all of them are predictable
- Ban bad passwords or ones which have appeared in data breaches
 - e.g. Troy Hunt's 10GB+ list or Daniel Miesler's various lists
- Allow convenience features on password fields
 - Offer Show Password while typing option
 - Allow pasting from clipboard into password fields

Other Authentication Controls

- Transmit passwords only over TLS
 - The "login landing page" must be served over TLS as well
- Prevent Brute-Force Attacks (e.g. throttling or periodic lockout)
- Require re-authentication for sensitive features
- Offer optional 2FA / MFA
 - Consider strong transaction authentication

Enterprise Controls

Use centralized corporate authentication system (if in place)

Two-Factor Authentication

Two-factor authentication adds a second level of authentication to an account log-in. When you have to enter only your username and one password, that's considered a single-factor authentication. 2FA requires the user to have two out of three types of credentials before being able to access an account. The three types are:

- Something you know, such as a personal identification number (PIN), password or a pattern
- Something you have, such as an ATM card, phone, or fob
- Something you are, such as a biometric like a fingerprint or voice print [^1]

2FA Method Comparison

Method	Security	Privacy	Access
SMS	<i>></i>	•	
Authenticator App	٩٩		
Hardware Key	عرعرع		

Hardware keys win from a security perspective, they are private and unaffected by a dying or out of range phone. However, only a few services (Google, Dropbox, Facebook, Github and a few others) support the standard so far. Unless you trust your phone provider (and few providers are trustworthy), **an authenticator app is the best option**.

Password Managers

Password managers are programs, browser plugins or web services that automate management of large number of different credentials, including memorizing and fillingin, generating random passwords on different sites etc. [^2]

KeePass	LastPass ••••	1Password
Open Source (GPLv2)	Proprietary / Freemium	Proprietary
Local installation, optional file or cloud sync	Cloud-based	Local installation with Cloud sync

Exercise

- 1. Log in with the admin's user account (\star
- 2. Reset Jim's password by answering his secret question ($\uparrow \uparrow \uparrow \uparrow \uparrow$)
- 3. Log in with Bjoern's user account ($\uparrow \uparrow \uparrow \uparrow \uparrow \uparrow$)