

COMPUTER NETWORKS (BCSC 0008)

Copyright content, use only with the written permission of presenter mentioned

Lecture 21

Text and Reference Books


Text Books:

1. Fourouzan B. A. (2004), "Data Communication and Networking", 4th Edition, McGraw-Hill.

References:

- 1. Kurose, J. F. and Ross K. W. (2005), "Computer Networking: A Top-Down Approach Featuring the Internet", 3rd Edition, Addison-Wesley.
- 2. A. S. Tanenbaum (2006), "Computer Networks", 2nd Edition, Prentice Hall India.


Transport Layer: Introduction



Why we need transport layer?

- Network layer is responsible for end to end (Host to Host) communication (IP address).
- There are several network application running in OS.
- How did NIC knows which packet belongs to which process/application?

Types of data deliveries: Internet Stack




Continued...


- The transport layer is responsible for process-to-process delivery— the delivery of a packet, part of a message, from one process to another.
- It provides *logical communication* between app processes running on different hosts
- transport protocols run in end systems
 - send side: breaks app messages into segments, passes to network layer
 - rcv side: reassembles segments into messages, passes to app layer
- more than one transport protocol available to apps
 - Internet: TCP and UDP

How It delivers messages to specific process


- Using Port address (16 bit)
- Ranges from 0 to 65,535




IP addresses versus port numbers



IANA ranges




Socket address (IP address + Port Address)



What is the use of socket?


- The socket mechanism provides a means of inter-process communication (IPC).
- Socket is basically an API for enabling communication between two end points.
- A **socket** is one endpoint of a **two way** communication link between two programs running on the network.

Socket API





Multiplexing and demultiplexing



Multiplexing/demultiplexing

Demultiplexing at rcv host:

delivering received segments to correct socket

= socket = process

Multiplexing at send host: -

gathering data from multiple sockets, enveloping data with header (later used for demultiplexing)

