

Logical Instructions

- These instructions perform logical operations on data stored in registers, memory and status flags.
- The logical operations are:
 - AND
 - OR
 - XOR
 - Rotate
 - Compare
 - Complement

AND, OR, XOR

- Any 8-bit data, or the contents of register, or memory location can logically have
 - AND operation
 - OR operation
 - XOR operation
- with the contents of accumulator.
- The result is stored in accumulator.

Rotate

- Each bit in the accumulator can be shifted either left or right to the next position.

Compare

- Any 8-bit data, or the contents of register, or memory location can be compared for:

- Equality
- Greater Than
- Less Than

with the contents of accumulator.

- The result is reflected in status flags.

Complement

- The contents of accumulator can be complemented.
- Each 0 is replaced by 1 and each 1 is replaced by 0.

Logical Instructions

Opcode	Operand	Description
CMP	R M	Compare register or memory with accumulator

- The contents of the operand (register or memory) are compared with the contents of the accumulator.
- Both contents are preserved .
- The result of the comparison is shown by setting the flags of the PSW as follows:

Logical Instructions

Opcode	Operand	Description
CMP	R M	Compare register or memory with accumulator

- if $(A) < (\text{reg}/\text{mem})$: carry flag is set
- if $(A) = (\text{reg}/\text{mem})$: zero flag is set
- if $(A) > (\text{reg}/\text{mem})$: carry and zero flags are reset.
- **Example:** CMP B or CMP M

Logical Instructions

Opcode	Operand	Description
CPI	8-bit data	Compare immediate with accumulator

- The 8-bit data is compared with the contents of accumulator.
- The values being compared remain unchanged.
- The result of the comparison is shown by setting the flags of the PSW as follows:

Logical Instructions

Opcode	Operand	Description
CPI	8-bit data	Compare immediate with accumulator

- if $(A) < \text{data}$: carry flag is set
- if $(A) = \text{data}$: zero flag is set
- if $(A) > \text{data}$: carry and zero flags are reset
- **Example:** CPI 89H

Logical Instructions

Opcode	Operand	Description
ANA	R M	Logical AND register or memory with accumulator

- The contents of the accumulator are logically ANDed with the contents of register or memory.
- The result is placed in the accumulator.
- If the operand is a memory location, its address is specified by the contents of H-L pair.
- S, Z, P are modified to reflect the result of the operation.
- CY is reset and AC is set.
- **Example:** ANA B or ANA M.

Logical Instructions

Opcode	Operand	Description
ANI	8-bit data	Logical AND immediate with accumulator

- The contents of the accumulator are logically ANDed with the 8-bit data.
- The result is placed in the accumulator.
- S, Z, P are modified to reflect the result.
- CY is reset, AC is set.
- **Example:** ANI 86H.

Logical Instructions

Opcode	Operand	Description
ORA	R M	Logical OR register or memory with accumulator

- The contents of the accumulator are logically ORed with the contents of the register or memory.
- The result is placed in the accumulator.
- If the operand is a memory location, its address is specified by the contents of H-L pair.
- S, Z, P are modified to reflect the result.
- CY and AC are reset.
- **Example:** ORA B or ORA M.

Logical Instructions

Opcode	Operand	Description
ORI	8-bit data	Logical OR immediate with accumulator

- The contents of the accumulator are logically ORed with the 8-bit data.
- The result is placed in the accumulator.
- S, Z, P are modified to reflect the result.
- CY and AC are reset.
- **Example:** ORI 86H.

Logical Instructions

Opcode	Operand	Description
XRA	R M	Logical XOR register or memory with accumulator

- The contents of the accumulator are XORed with the contents of the register or memory.
- The result is placed in the accumulator.
- If the operand is a memory location, its address is specified by the contents of H-L pair.
- S, Z, P are modified to reflect the result of the operation.
- CY and AC are reset.
- **Example:** XRA B or XRA M.

Logical Instructions

Opcode	Operand	Description
XRI	8-bit data	XOR immediate with accumulator

- The contents of the accumulator are XORed with the 8-bit data.
- The result is placed in the accumulator.
- S, Z, P are modified to reflect the result.
- CY and AC are reset.
- **Example:** XRI 86H.

Opcode	Operand	Description
RAL	None	Rotate accumulator left through carry

- Each binary bit of the accumulator is rotated left by one position through the Carry flag.
- Bit D₇ is placed in the Carry flag, and the Carry flag is placed in the least significant position Do.
- CY is modified according to bit D₇.
- S, Z, P, AC are not affected.
- **Example:** RAL.

Opcode	Operand	Description
RAR	None	Rotate accumulator right through carry

- Each binary bit of the accumulator is rotated right by one position through the Carry flag.
- Bit D0 is placed in the Carry flag, and the Carry flag is placed in the most significant position D7.
- CY is modified according to bit D0.
- S, Z, P, AC are not affected.
- **Example:** RAR.

■ circular Left shift

Opcode	Operand	Description
RLC	None	Rotate accumulator left

- Each binary bit of the accumulator is rotated left by one position.
- Bit D₇ is placed in the position of D₀ as well as in the Carry flag.
- CY is modified according to bit D₇.
- S, Z, P, AC are not affected.
- **Example:** RLC.

■ circular right shift

Opcode	Operand	Description
RRC	None	Rotate accumulator right

- Each binary bit of the accumulator is rotated right by one position.
- Bit D0 is placed in the position of D7 as well as in the Carry flag.
- CY is modified according to bit D0.
- S, Z, P, AC are not affected.
- **Example:** RRC.

Logical Instructions

Opcode	Operand	Description
CMA	None	Complement accumulator

- The contents of the accumulator are complemented.
- No flags are affected.
- **Example:** CMA.

Logical Instructions

Opcode	Operand	Description
CMC	None	Complement carry

- The Carry flag is complemented.
- No other flags are affected.
- **Example:** CMC.

Logical Instructions

Opcode	Operand	Description
STC	None	Set carry

- The Carry flag is set to 1.
- No other flags are affected.
- **Example:** STC.