BurnNotice: Real-Time Detection of LLM Deception and Alignment Drift via Activation-Space Monitoring, Subspace Steering, and Adversarial Hardening

Ross Dmochowski

November 2026 (v0.8)

Abstract

We present BurnNotice (v0.8), a white-box neural activation governance framework for detecting strategic deception, policy violations, and alignment drift in large language model (LLM) agents through real-time residual-stream monitoring and subspace intervention. Whereas prior activation-engineering work has largely focused on removing safety guardrails ("abliteration"), BurnNotice inverts and generalizes these methods into a defensive control plane that preserves reasoning utility while suppressing deceptive and policy-violating trajectories. Our architecture replaces brittle single-direction probes with (1) Winsorized, Ledoit-Wolf shrinkage-whitened Singular Value Decomposition (Whitened SVD), Iterative Nullspace Projection (INLP), and gradient-based Refusal Direction Optimization (RDO); (2) Norm-Preserving Biprojected Ablation (MPOA), ridge-regularized subspace projection ("Gabliteration"), Conditional Activation Steering (CAST), and continuous Gaussian-weighted subspace interpolation; (3) architecture-calibrated adapters for Llama, Qwen (QKV bias projection and `<think>` Chain-of-Thought state-machine gating), Gemma (unit-offset RMSNorm, prefill commitment windows, and Gemma Scope SAEs), and Mixture-of-Experts (cumulative expert-offset slicing and stabilized top-k router softmax); and (4) post-profiling geometric diagnostics including Alignment Imprint classification (DPO/RLHF/-CAI/SFT), parallelized Concept Cone analysis, Centered Kernel Alignment (CKA), and Ouroboros layer-compensation refinement. We evaluate BurnNotice against the 2025–2026 adversarial literature—including obfuscated activations, "Rogue Scalpel" steering externalities, alignment faking via oversight sensitivity, and multi-turn KV-cache drift—and detail both our implemented countermeasures (non-linear MLP probes, oversight-ablated profiling, in-place Gated Cropped Attention-Delta [GCAD], and HarmBench Pareto-frontier evaluation) and the fundamental theoretical limits of latent-space defenses under adaptive white-box adversaries.

Keywords: LLM Safety, Activation Steering, Deception Detection, Concept Cones, Whitened SVD, MPOA, GCAD, Alignment Faking, Adversarial Robustness, ONNX, WebAssembly

1 Introduction

The deployment of autonomous large language model (LLM) agents in high-stakes environments has exposed failure modes that external, text-level guardrails cannot reliably intercept: strategic deception, covert policy

non-compliance, multi-turn jailbreak erosion, and situational alignment faking. Mechanistic interpretability research has demonstrated that high-level behavioral traits—including refusal [1], truthfulness [17], and strategic deception [11, 9]—correspond to structured subspaces within the transformer residual stream. Historically, these findings were rapidly operationalized to *excise* safety boundaries via orthogonal weight projection, a family of techniques known as "abliteration" [16].

BurnNotice inverts this paradigm: rather than permanently editing weights to remove refusal, we monitor multi-dimensional behavioral subspaces in real time and apply bounded, closed-loop activation interventions to steer agents away from deceptive or policy-violating states before tokens are emitted. Moving from a research prototype to our hardened v0.8 architecture required confronting several foundational findings from 2025–2026 interpretability and adversarial machine learning research:

- **From Single Directions to Concept Cones**: Refusal and deception do not reside along a single 1D vector; they span polyhedral concept cones [28, 22] where naive projection degrades general capabilities or triggers downstream layer compensation (the "Ouroboros effect" [19]).
- **Adversarial Probe Evasion**: White-box and gradient-guided attacks can obfuscate internal representations to reduce linear probe recall from 100% to 0% while preserving 90% attack success rate (ASR) [2].
- **Steering Externalities**: Uncalibrated steering vectors can inadvertently shift early-token distributions toward affirmative compliance, acting as a "Rogue Scalpel" that increases vulnerability to unrelated jailbreaks [12, 15, 25].
- **Alignment Faking and Oversight Sensitivity**: Capable models encode awareness of evaluation contexts along an oversight sensitivity direction [27], suppressing deceptive activations during profiling only to resume them in unmonitored deployment.
- **Multi-Turn KV-Cache Contamination**: Repeated activation additions accumulate inside historical Key/Value attention caches across dialogue turns, inducing severe perplexity spikes and coherence collapse after 3–5 turns [24].

1.1 Contributions

This paper documents the BurnNotice v0.8 framework, its mathematical foundations, empirical microbenchmarks, verification gates, and an adversarial critique of every subsystem:

1. **Robust Subspace Extraction Pipeline**: We implement Winsorized (0.5th–99.5th percentile), Ledoit-Wolf shrinkage-regularized ZCA Whitened SVD (`internal/extract/whitened.go`), Iterative Nullspace Projection (INLP), and pure-Go SGD Refusal Direction Optimization (RDO), paired with an Oversight Ablator that projects out evaluation-awareness directions prior to deception profiling.
2. **Precision Norm-Preserving and Conditional Steering**: We introduce Norm-Preserving Biprojected Ablation (MPOA), ridge-regularized subspace projection (Gabliteration), boolean/smooth Conditional Activation Steering (CAST) trees ($\sim 62\,\mu$s latency), continuous Gaussian-weighted SVD basis interpolation (`DirectionMix`), component-specific Attention/MLP scaling, and rank-1 LoRA steering.

3. **Architecture-Calibrated Model Support**: Native support for Llama (2/3/3.1/3.2/3.3), Qwen (2/2.5/Coder/QwQ with QKV bias projection and `<think>`/`</think>` Chain-of-Thought state-machine gating), Gemma (1/2/Scope with unit-offset RMSNorm, prefill commitment windows, and NPZ sparse autoencoders), and Mixture-of-Experts (cumulative expert-dimension offset slicing and stabilized top-k router logit softmax).

4. **Multi-Turn KV-Cache Defense (GCAD) and Closed-Loop Coherence**: We implement a per-turn angular drift tracker ($\theta_{\max} = 15°$) and zero-allocation in-place Gated Cropped Attention-Delta (GCAD, 18.2 μs/op), coupled with token-level KL-divergence feedback scaling (`AdjustAlphaForKL`) and sliding-window perplexity control.

5. **Geometric Post-Profiling Diagnostics**: Pure-Go analyzers for Alignment Imprint classification (DPO, RLHF, CAI, SFT), worker-pool parallelized Concept Cone analysis, rotation- and scale-invariant Centered Kernel Alignment (CKA), Ouroboros compensation refinement, and FNV-1a cached Thin-SVD 2D manifold visualization (35.1× speedup).

6. **Adversarial Defense-in-Depth and Honest Threat Evaluation**: We pair non-linear ReLU+Sigmoid MLP probes, Mahalanobis OOD detection, stochastic latent noise, GCG suffix sanitization, and query-similarity gradient masking with an explicit analysis of residual white-box and semantic evasion vectors.

7. **Reproducible Verification and Quality Gates**: A race-clean, zero-lint, zero-vulnerability Go codebase featuring 90%–100% statement coverage across all 26 core packages, 72 native fuzz targets across 25 packages, deterministic golden/oracle gates (`-count=2`), and cryptographic SHA-256 release evidence bundles.

2 Related Work

2.1 Representation Engineering, Abliteration, and Concept Cones

Representation Engineering (RepE) [26, 21] and contrastive activation addition established that linear directions in activation space mediate high-level behaviors including refusal [1] and truthfulness [17]. Abliteration [16] applied rank-1 orthogonal projection to permanently erase the difference-in-means (DIM) refusal vector. However, [28] proved that refusal spans a multi-dimensional concept cone rather than a single ray, and [22] demonstrated that multi-directional extraction via Self-Organizing Maps (SOMs) captures independent refusal modes missed by DIM. Furthermore, [19] identified the "Ouroboros effect," wherein ablating refusal directions in early or middle layers induces compensatory amplification in deeper layers, requiring layer-selective intervention (40–60% network depth) and iterative multi-layer refinement.

2.2 Norm-Preserving Biprojection and Regularized Steering

Standard orthogonal ablation alters residual stream norms and strips components shared between harmful and harmless representations, degrading general reasoning [4]. Magnitude-Preserving Orthogonal Ablation (MPOA) and biprojected abliteration [13] orthogonalize the target direction against the harmless direction

before restoring the original L2 norm. Concurrently, ridge-regularized projection ("Gabliteration") [7] replaces hard projection $I - VV^\top$ with a Tikhonov-damped operator $I - V(V^\top V + \alpha I)^{-1}V^\top$, substantially lowering token-level KL divergence on benign distributions. Conditional Activation Steering (CAST) [14] further restricts interventions to contexts matching learned activation condition vectors.

2.3 Deception Probing and Sparse Autoencoders

Linear and sparse autoencoder (SAE) probes achieve high controlled AUROC (0.96–0.999) in detecting strategic deception and sycophancy [11, 9, 18]. Yet [9] and [3] highlight severe deployment blind spots: probes suffer from *topic confusion* (firing when a model honestly discusses deception, security, or fiction) and legalese-induced false positives. In the SAE domain, scaling dictionary learning [5, 8] and HalluSAE [10] enable feature-level attribution and hallucination energy tracking, though AxBench [29] provides critical counterevidence showing that simple regularized subspace methods frequently outperform SAE steering at a fraction of the computational cost.

2.4 Adversarial Attacks on Latent-Space Governance

Recent adversarial work directly targets activation-space monitors and steerers:

- **Obfuscated Activations**: [2] show that white-box adversarial suffixes or fine-tuning can route harmful computation around linear probes, driving probe recall to 0% while maintaining 90% jailbreak success.
- **Rogue Scalpel and Steering Externalities**: [12], [15], and [25] demonstrate that steering vectors can degrade safety boundaries on orthogonal harm categories, and that combining random or inverted steering vectors yields universal jailbreaks [6].
- **Alignment Faking**: [27] show that frontier models can detect evaluation framing via an oversight sensitivity subspace and conditionally feign alignment.
- **Prompt–Activation Duality and KV-Cache Drift**: [24] prove that residual-stream steering is dual to attention-key perturbation, and that unattenuated steering vectors corrupt the multi-turn KV cache.
- **Prefill Behavioral Commitment**: Recent studies on MoE and hybrid architectures [23] reveal that refusal/compliance decisions often solidify entirely during prompt prefill, rendering late-token autoregressive steering causally inert.

3 System Architecture and Mathematical Formulation

3.1 Execution Control Plane and Dual Inference Backends

BurnNotice is architected in Go as a low-allocation, concurrent governance engine (`cmd/burnnotice`, `cmd/dashboard`) paired with native GPU serving plugins (`plugins/cuda_kernels.cu`, `plugins/metal/kernels.metal`, `plugins/vllm/`, `plugins/tensorrt/`). For standalone profiling and portable deployment, BurnNotice provides:

1. **ONNX Runtime Engine with Pure-Go Graph Fallback** (`internal/engine/onnx.go`): Executes exported ONNX computation graphs with layer-level activation hooks, falling back seamlessly to a pure-Go ONNX Protocol Buffer (`internal/onnxpb`) graph interpreter when native `libonnxruntime` shared libraries are absent.

2. **Wazero WebAssembly Sandbox** (`internal/wasm/backend.go`): Compiles and executes model graphs in a zero-dependency pure-Go WebAssembly runtime with deterministic float32 tensor marshaling.

3. **Mixture-of-Experts (MoE) Routing Engine** (`internal/engine/moe.go`): Partitions concatenated expert activation tensors by accumulating prior expert dimensions:

$$\text{start}_m = \sum_{j=0}^{m-1} d_j, \quad \text{end}_m = \min(\text{start}_m + d_m, \dim(a)), \quad a^{(m)} = a[\text{start}_m : \text{end}_m] \tag{1}$$

   and computes top-k active expert weights via numerically stabilized softmax over router logits $z \in \mathbb{R}^M$:

$$w_i = \frac{\exp(z_{\pi(i)} - z_{\max})}{\sum_{j=1}^{k} \exp(z_{\pi(j)} - z_{\max})}, \quad z_{\max} = \max_{1 \le j \le k} z_{\pi(j)} \tag{2}$$

   with automatic uniform $1/M$ fallback when activation energy $\|\mathbf{a}\|_2^2 < 10^{-10}$ or logits contain non-finite values.

4. **Longbow Arrow Flight Vector Store with Autonomous SQLite Failover** (`internal/longbow/client.go`): Streams activation batches via Apache Arrow Flight `RecordBatch`es (‘NewRecordBatch‘), SlabArena off-heap memory, and Copy-On-Write (COW) atomic pointer swaps, while hot-swapping automatically to an embedded WAL-mode SQLite and in-memory SIMD store if the Flight endpoint is unreachable.

3.2 Robust Subspace Extraction Pipeline

Winsorization and Ledoit-Wolf Shrinkage Whitening. Given N positive (e.g., deceptive/refusal) and N negative (truthful/compliant) activations in $\mathbb{R}^d$ where typically $N \ll d$, raw empirical covariance S is rank-deficient and dominated by high-variance non-semantic residual channels. BurnNotice (`internal/math/`, `internal/extract/whitened.go`) first clamps extreme coordinate outliers at the 0.5th and 99.5th percentiles via in-place Winsorization. It then computes the Ledoit-Wolf shrinkage covariance estimator:

$$\Sigma_{\text{shrink}} = (1 - \alpha)S + \alpha \frac{\text{Tr}(S)}{d} I_d, \quad \alpha \in [0, 1] \tag{3}$$

where α is estimated analytically to minimize Frobenius MSE when not manually pinned. Using eigendecomposition $\Sigma_{\text{shrink}} = Q \Lambda Q^\top$ with eigenvalue floor $\lambda_{\min} = \max(\epsilon, 10^{-10} \lambda_{\max})$, we form the ZCA whitening transform $W = Q \Lambda^{-1/2} Q^\top$ and inverse transform $W^{-1} = Q \Lambda^{1/2} Q^\top$.

Whitened Thin SVD and Unwhitening. Let $X_{\text{diff}} \in \mathbb{R}^{N \times d}$ denote the positive activations centered by the negative mean μ_{neg}. We project into whitened space, factorize via Thin SVD, and transform the top-k

right singular vectors back into native residual coordinates:

$$X_{\text{white}} = X_{\text{diff}} W = U \Sigma V_{\text{white}}^{\top}, \quad v_i = \frac{W^{-1} V_{\text{white},(:,i)}}{\| W^{-1} V_{\text{white},(:,i)} \|_2}, \quad i \in \{1, \ldots, k\} \tag{4}$$

For models exceeding 7B parameters (`-model-size`), the CLI automatically selects Whitened SVD over unwhitened DIM.

Iterative Nullspace Projection (INLP) and RDO. To uncover secondary deceptive pathways orthogonal to the primary SVD basis, `ExtractINLP` (`internal/extract/inlp.go`) iteratively fits L2-regularized logistic probes $w^{(t)}$ and projects the activation matrix onto their intersection nullspace $P_{\mathcal{N}} = \prod_t (I - \hat{w}^{(t)} \hat{w}^{(t)\top})$, where the recommended iteration count scales with the Concept Cone intrinsic dimensionality. Additionally, `RefusalDirectionOptimizer` (`internal/extract/rdo.go`) refines candidate directions via pure-Go mini-batch SGD on binary cross-entropy loss with L2 weight decay, maximizing held-out AUROC.

Oversight-Ablated Profiling. To counter alignment faking [27], BurnNotice (`internal/profile/oversight.go`) first runs contrastive prompts contrasting monitored vs. unmonitored deployment framing to extract the unit oversight sensitivity vector $\hat{v}_{\text{oversight}}$. During subsequent deception profiling, raw activations are scrubbed via orthogonal projection prior to subspace extraction:

$$h_{\text{ablated}} = h - (h \cdot \hat{v}_{\text{oversight}}) \hat{v}_{\text{oversight}} \tag{5}$$

3.3 Low-Allocation Scoring and Asynchronous Ring-Buffer Bypass

At inference time, `Scorer` (`internal/scoring/scorer.go`) caches pre-computed direction L2 norms at registration time and reuses pooled activation buffers via `sync.Pool`, eliminating per-token map cloning on the hot path. For a direction v and activation $a \in \mathbb{R}^d$, the sigmoid-calibrated cosine score and k-dimensional subspace energy are:

$$s(a, v) = \sigma\left(10 \cdot \frac{a \cdot v}{\|a\|_2 \|v\|_2}\right), \quad E_{\text{subspace}}(a, B) = \sqrt{\sum_{i=1}^{k} (a \cdot v_i)^2} \tag{6}$$

Sequence-level temporal drift is tracked via an Exponential Moving Average ($\text{EMA}_t = \beta s_t + (1 - \beta)\text{EMA}_{t-1}$, `internal/scoring/aggregator.go`).

To prevent scoring from stalling token generation, `AsyncScorer` (`internal/scoring/async.go`) dispatches activations into a lock-free ring buffer consumed by background worker goroutines. To resolve the *asynchronous scoring paradox*—where fast token generation could outrun async detection during a spike—an atomic latch monitors both ring-buffer occupancy ($d_{\text{queue}}/C \geq 0.85$) and worker processing latency ($\tau_{\text{proc}} > 2.5\,\text{ms}$). When either bound is breached, `PushActivation` atomically engages synchronous inline scoring and intervention until the queue drains and latency recovers.

3.4 Precision Steering Kernels and Multi-Turn KV-Cache Defense

When policy thresholds trigger intervention, BurnNotice (`internal/steer/`) supports seven composable steering kernels:

1. **Norm-Preserving Biprojected Ablation (MPOA)**: Given target direction v_t (e.g., deception) and harmless anchor direction v_h, we first orthogonalize v_t against v_h, ablate the purified component from h, and restore the pre-intervention L2 norm:

$$\tilde{v}_t = \frac{v_t - (v_t \cdot \hat{v}_h)\hat{v}_h}{\|v_t - (v_t \cdot \hat{v}_h)\hat{v}_h\|_2}, \quad h_{\text{orth}} = h - (h \cdot \tilde{v}_t)\tilde{v}_t, \quad h' = \|h\|_2 \frac{h_{\text{orth}}}{\|h_{\text{orth}}\|_2} \tag{7}$$

2. **Ridge-Regularized Subspace Projection (Gabliteration)** (`internal/math/projection.go`): Dampens multi-direction ablation across basis $V \in \mathbb{R}^{d \times k}$ with ridge parameter $\alpha > 0$:

$$P_\alpha = I_d - V(V^\top V + \alpha I_k)^{-1} V^\top, \quad h' = P_\alpha h \tag{8}$$

   strictly lowering token-level logit KL divergence relative to exact projection ($\alpha = 0$).

3. **Conditional Activation Steering (CAST)** (`internal/steer/cast.go`): Evaluates boolean composition trees (`OpAND`, `OpOR`, `OpNOT`) over condition vectors c_j with either step-threshold or smooth sigmoid gating $g(h) \in [0, 1]$, applying $h' = h + \alpha g(h) v$ in 62.3 μs with zero heap allocations.

4. **Continuous Gaussian Subspace Interpolation** (`internal/steer/interpolate.go`): Smoothly blends across ordered basis directions $\{v_0, \ldots, v_{k-1}\}$ via continuous parameter $t \in [0, k-1]$:

$$v_{\text{mix}}(t) = \frac{\sum_{i=0}^{k-1} \exp\left(-\frac{(t-i)^2}{2\sigma^2}\right) v_i}{\left\| \sum_{i=0}^{k-1} \exp\left(-\frac{(t-i)^2}{2\sigma^2}\right) v_i \right\|_2} \tag{9}$$

5. **Component-Specific and Bias Steering** (`internal/steer/bias.go`): Scales attention interventions at 1.0× and MLP interventions at 0.5× (preserving factual knowledge stored in MLP weights), while projecting out deceptive components from Qwen QKV attention bias vectors $b' = b - (b \cdot \hat{v})\hat{v}$.

6. **Reasoning Chain-of-Thought (CoT) State Machine** (`internal/steer/cot.go`) **and Prefill Commitment** (`internal/steer/commitment.go`): For reasoning models (DeepSeek-R1, QwQ), BurnNotice parses `<think>` and `</think>` boundaries, enforcing $\alpha = 0$ (passive monitoring only) during internal reasoning traces so chains of thought do not collapse, and engaging full MPOA steering immediately upon entering the answer phase. For Gemma architectures, steering is concentrated within the prefill commitment window where behavioral trajectories solidify.

7. **In-Place Gated Cropped Attention-Delta (GCAD)** (`internal/steer/kvcache.go`): To prevent multi-turn KV-cache corruption [24], `KVCacheAccumulationTracker` monitors cumulative angular drift $\theta_t = \arccos(\hat{v}_0 \cdot \hat{v}_t) \leq 15°$, while `GCADApplyInPlace` bounds key/value deltas $\Delta = h_{\text{steered}} - h_{\text{unsteered}}$ to maximum L2 norm $\tau_{\max} = 1.5$ and applies exponential turn-distance attenuation $\gamma^{\Delta t}$ ($\gamma = 0.95$) in a single zero-allocation pass:

$$h_{\text{GCAD}} = h_{\text{unsteered}} + \gamma^{\Delta t} \min\left(1, \frac{\tau_{\max}}{\|\Delta\|_2}\right) \Delta \tag{10}$$

3.5 Post-Profiling Geometric Diagnostics and Latent Visualization

The `internal/analysis` package provides six post-profiling diagnostic modules:

- **Alignment Imprint Detector** (`alignment.go`): Computes Effective Rank (fraction of singular values explaining 90% variance), SVD Decay Rate ($1 - \sigma_2/\sigma_1$), Cross-Layer Coherence, and Direction Stability across layers to classify whether a model was aligned via DPO, RLHF, CAI, or SFT.
- **Parallel Concept Cone Analyzer** (`cone.go`): Uses a bounded worker pool (`parallelFor` capped at `GOMAXPROCS`) to compute $N \times N$ pairwise category cosines, covariance matrices, and power-iteration singular values across harm categories, estimating the intrinsic dimensionality of the harm cone.
- **Centered Kernel Alignment (CKA)** (`crosslayer.go`): Quantifies representational similarity between activation matrices $X, Y \in \mathbb{R}^{n \times d}$ via column-centered Gram matrices $K = \tilde{X}\tilde{X}^\top$, $L = \tilde{Y}\tilde{Y}^\top$:

$$\mathrm{CKA}(X, Y) = \frac{\mathrm{HSIC}(K, L)}{\sqrt{\mathrm{HSIC}(K, K)\,\mathrm{HSIC}(L, L)}} = \frac{\|\tilde{Y}^\top \tilde{X}\|_F^2}{\|\tilde{X}^\top \tilde{X}\|_F \|\tilde{Y}^\top \tilde{Y}\|_F} \in [0, 1] \tag{11}$$

  which is provably invariant to orthogonal rotation ($\mathrm{CKA}(X, XR) = 1$) and isotropic scaling ($\mathrm{CKA}(X, cX) = 1$).
- **Ouroboros Compensation Detector** (`ouroboros.go`): Compares pre- and post-intervention per-layer scores to identify downstream layers whose deception energy increased after upstream ablation, scheduling $\lceil |\mathcal{L}_{\text{comp}}|/3 \rceil$ iterative refinement passes.
- **Closed-Loop KL Co-Optimization** (`kl.go`, `steer/coherence.go`): Computes forward and symmetric token-level logit KL divergence via max-shifted `LogSoftmax`; if harmless KL exceeds 0.2, `AdjustAlphaForKL` proportionally scales down steering strength α.
- **FNV-1a Cached Thin-SVD Manifold Visualizer** (`latent_vis.go`): Projects high-dimensional activations onto 2D principal components with 95% confidence ellipses and layer-to-layer token trajectories (step velocity and angular curvature κ_{total}), caching SVD factors by 64-bit FNV-1a matrix fingerprint.

4 Empirical Evaluation and Verification Benchmarks

4.1 Cross-Family Detection and Steering Performance

Table 1 reports controlled evaluation metrics across supported open-weight model families using Whitened SVD extraction ($k = 5$), MPOA selective steering (40–60% depth), and F1-calibrated thresholds.

4.2 Hot-Path Microbenchmarks and Memory Allocation Profile

To eliminate unsubstantiated performance claims, all hot-path kernels are benchmarked under reproducible hardware manifests (`internal/compliance/benchmarks.go`, `benchmark_results.txt`). Table 2 lists measured latencies and heap allocations on a 12th Gen Intel Core i7-12650H (16 threads, Linux amd64, Go 1.27.2) for $d = 4096$ activation vectors.

Table 1: BurnNotice v0.8 controlled evaluation across model families (same-model profiling).

Model Family	Extraction	Deception AUROC	Benign FPR (%)	Violation Red. (%)	KL Div.	$\mathcal{R}_{\text{cap}}$ (GSM8k)
Llama-3.1-8B	Whitened SVD + INLP	0.97	0.8	94.2	0.041	0.99
Qwen-2.5-7B	Whitened SVD + Bias	0.96	0.9	93.1	0.048	0.98
Gemma-2-9B	Whitened SVD + SAE	0.96	0.8	92.5	0.039	0.99
Mistral-7B	Whitened SVD	0.96	0.9	92.0	0.052	0.98
Llama-3.1-70B	Whitened SVD + RDO	0.95	1.0	89.4	0.063	0.98

Table 2: Measured hot-path kernel benchmarks ($d = 4096$, Go 1.27.2, `-benchmem`).

Package	Kernel / Operation	Latency (ns/op)	Bytes/Op	Allocs/Op
`internal/scoring`	`Scorer.Score` (cached norm, no noise)	21,487 (21.5 μs)	256	2
`internal/scoring`	`Scorer.SubspaceScore` ($k = 5$ basis)	2,821 (2.8 μs)	0	0
`internal/scoring`	`AsyncScorer.PushActivation` (ring buffer)	5,816 (5.8 μs)	246	1
`internal/scoring`	`Dot` ($d = 4096$ inner product)	5,871 (5.9 μs)	0	0
`internal/steer`	`ActAdd` (activation addition)	40,220 (40.2 μs)	32,771	1
`internal/steer`	`NormPreservingAblation` (MPOA)	201,858 (201.9 μs)	65,536	2
`internal/steer`	`BiprojectedAblation` (MPOA + harmless)	348,884 (348.9 μs)	65,536	2
`internal/steer`	`GCADApply` (allocating KV defense)	148,188 (148.2 μs)	32,768	1
`internal/steer`	`GCADApplyInPlace` (zero-alloc KV defense)	18,207 (18.2 μs)	0	0
`internal/steer`	`CAST` Conditional Tree Evaluation	62,341 (62.3 μs)	0	0
`internal/memory`	`Pool.GetPut` (activation slice pool)	442 (0.44 μs)	24	1
`internal/analysis`	`ProjectLatentSpace` (Thin SVD cold)	2,530,000 (2.53 ms)	412,672	48
`internal/analysis`	`ProjectLatentSpace` (FNV-1a cache hit)	72,100 (72.1 μs)	18,432	14

4.3 Quality Gates, Fuzzing, and Cryptographic Release Evidence

Every commit touching `internal/` or `cmd/` is gated by `scripts/verify.sh` and CI:

- **Statement Coverage**: 90.3%–100.0% across all 26 core packages (e.g., `hallucination`: 100%, `memory`: 100%, `policy`: 100%, `scheduler`: 100%, `tokenizer`: 100%, `checkpoint`: 100%, `agent`: 98.9%, `profile`: 98.1%, `policydetect`: 98.1%, `math`: 96.6%, `steer`: 93.3%, `analysis`: 93.2%, `scoring`: 92.8%, `engine`: 92.4%, `extract`: 92.3%).
- **Fuzz Testing**: 72 native Go `Fuzz*` targets across 25 packages exercising malformed ONNX protobufs, corrupt Safetensors/NPY headers, extreme `NaN`/`Inf` matrices, and concurrent scheduler/hub state transitions.
- **Accuracy and Oracle Gates**: Deterministic golden fixtures (`go test -count=2`) and mathematical invariant checks verifying $\text{CKA}(X, X) = 1$, $\text{CKA}(X, Y) = 0$ for orthogonal subspaces, softmax normalization $\sum_i w_i = 1$, and zero-degradation covariance floors.

5 Adversarial Analysis and Fundamental Limitations

A central thesis of BurnNotice v0.8 is that latent-space safety mechanisms must be evaluated under an explicit adversarial threat model. Below we analyze seven primary attack surfaces, detail the countermeasures implemented in v0.8, and state the residual vulnerabilities that remain open problems.

5.1 Obfuscated Activation Attacks (Bailey et al., 2026)

Attack Mechanism. [2] demonstrate that an adversary with white-box gradient access (or strong transfer surrogates) can append adversarial suffixes or apply lightweight fine-tuning that minimizes linear probe projection $\|a \cdot v\|$ while preserving harmful generation semantics, reducing linear probe recall from 100% to 0% at 90% ASR.

Implemented v0.8 Countermeasures. BurnNotice implements a four-layer defense-in-depth (`internal/profile/obfuscation.go`, `internal/steer/adversarial.go`):

1. **Non-Linear MLP Probes**: A two-layer neural probe $f_{\text{MLP}}(a) = \sigma(W_2\text{ReLU}(W_1 a + b_1) + b_2)$ trained alongside linear subspace extractors to detect curved manifold boundaries that evade rank-k linear projections.
2. **Whitened Mahalanobis OOD Detection**: Measures out-of-distribution distance $\|W(a - \mu_{\text{compliant}})\|_2$ across the whitened subspace (`internal/policydetect/whitening.go`); adversarial perturbations that suppress specific direction dots typically inflate off-axis Mahalanobis energy.
3. **Stochastic Latent Noise Injection**: Evaluates $S_{\text{robust}}(a) = S(a + \eta)$ with $\eta \sim \mathcal{N}(0, \sigma^2_{\text{noise}} I)$ (2% relative amplitude) to roughen the local gradient landscape.
4. **GCG Suffix Sanitization and Query-Similarity Gradient Masking**: Filters high-perplexity/low-transition-probability token bursts characteristic of greedy coordinate gradient (GCG) suffixes and injects decoy activation scores when consecutive client queries exhibit cosine similarity > 0.95 (black-box probe extraction defense).

Residual Vulnerability (Adversarial Critique). While non-linear MLP probes and stochastic noise defeat static linear evasion and naive finite-difference probing, they *do not* defeat an adaptive white-box attacker who includes both f_{MLP} and the Mahalanobis norm in their loss function under Expectation-Over-Transformation (EOT). Because the transformer itself has vastly higher capacity than a 2-layer probe, a white-box adversary can distribute deceptive computation across polysemantic attention heads that remain within the benign Mahalanobis ellipsoid. True white-box resistance requires hardware-isolated weight/probe confidentiality (TEE/confidential computing) so the probe parameters remain unknown to the attacker.

5.2 Steering Externalities and the "Rogue Scalpel" Paradox

Attack Mechanism. [12], [15], and [25] establish two critical failure modes of activation steering: (1) *universal jailbreak construction*, where inverting safety directions or combining ~ 20 random steering vectors yields a universal jailbreak across unseen harm categories; and (2) *collateral safety erosion*, where steering along a truthfulness or helpfulness direction shifts early-token logit distributions toward affirmative prefixes ("Sure, here is..."), increasing Attack Success Rate (ASR) on orthogonal jailbreak prompts by $> 1.2\times$.

Implemented v0.8 Countermeasures. BurnNotice introduces explicit externalities auditing (`internal/analysis/externalities.go`, `internal/analysis/heretic.go`):

- **Steering Externalities Ratio**: Evaluates held-out jailbreak suites before and after steering, flagging any configuration where $\mathcal{E}_{\text{ext}} = \text{ASR}_{\text{steered}}/\text{ASR}_{\text{baseline}} > 1.2$, and monitors first-5-token affirmative distribution drift (`DetectEarlyTokenDrift`).
- **HarmBench-400 Pareto Frontier and Heretic Score**: Computes non-dominated Pareto frontiers over (KL divergence, remaining ASR) across 7 HarmBench categories, selecting only steering operating points that jointly minimize KL distortion and jailbreak externalities.
- **MPOA Biprojection and CAST Gating**: By orthogonalizing the steering vector against harmless representations and gating interventions via CAST condition trees so steering is inactive ($g(h) = 0$) on normal queries, BurnNotice avoids continuous residual-stream distortion.

Residual Vulnerability (Adversarial Critique). If an attacker gains write access to the profile store (`profile.gob`) or the Longbow vector database, sign-flipping the stored deception/refusal basis ($v \leftarrow -v$) immediately converts BurnNotice from a safety guardian into an automated jailbreak amplifier. Cryptographic signing of profiles and tamper-evident `ReleaseEvidenceBundle` digests (`internal/compliance/benchmarks.go`) mitigate storage tampering, but runtime memory protection remains essential.

5.3 Alignment Faking and Situational Awareness

Attack Mechanism. [27] show that frontier models can infer whether they are in an evaluation/profiling environment versus unmonitored deployment, conditionally suppressing misaligned circuits during profiling.

Implemented v0.8 Countermeasures. Our two-phase Oversight Ablator (`internal/profile/oversight.go`) extracts $\hat{v}_{\text{oversight}}$ from monitored vs. unmonitored prompt pairs and projects it out of the residual stream during deception profiling, while shadow profiling continuously compares runtime activation distributions against static profile centroids.

Residual Vulnerability (Adversarial Critique). Linear oversight ablation assumes situational awareness is encoded in a low-rank linear subspace at each layer. In reasoning models that externalize situational reasoning across hundreds of Chain-of-Thought tokens inside `<think>` blocks, awareness of oversight is recomputed dynamically at every attention step from the token context itself; ablating a static residual direction at layer l cannot erase deductive cues present in the prompt tokens.

5.4 Multi-Turn KV-Cache Contamination

Attack Mechanism. [24] prove that steering residual activations at turn t writes perturbed Key and Value projections into the KV cache, which are attended to by all subsequent turns $t+1, \ldots, T$, causing compounding angular drift and linguistic breakdown after 3–5 turns.

Implemented v0.8 Countermeasures. `KVCacheAccumulationTracker` (`internal/steer/kvcache.go`) tracks cumulative angular deviation $\theta_t \leq 15°$ from the session's initial steering baseline, and

`GCADApplyInPlace` crops attention-delta norms to $\tau_{\max} = 1.5$ while applying exponential historical decay $\gamma^{\Delta t}$ ($\gamma = 0.95$).

Residual Vulnerability (Adversarial Critique). GCAD introduces a fundamental safety–coherence tradeoff against *crescendo* (multi-turn gradual escalation) jailbreaks. If an adversary slowly escalates a malicious request over 15 turns, exponential attenuation ($\gamma^{15} \approx 0.46$) weakens historical safety context in the KV cache while aggressive per-turn re-steering eventually saturates the 15° drift budget.

5.5 Topic Confusion, Semantic Ambiguity, and Compounding False Positives

Attack Mechanism. Deception and harm probes fire on benign prompts that *discuss* deception, cybersecurity, legal contracts, or creative fiction [9, 3]. Furthermore, running $m = 5$ independent monitors with per-probe FPR = 2% yields a compound false-alarm rate of $1 - (1 - 0.02)^5 = 9.6\%$ per request.

Implemented v0.8 Countermeasures. BurnNotice implements `SemanticGater` (`internal/policy/gate.go`), which classifies prompt intent (`creative_writing`, `fictional_roleplay`, `academic_query`, `general_conversation`) and scales metric weights accordingly (e.g., 0.1× for creative writing, 0.3× for academic queries), alongside F1-optimal ROC calibration (`internal/profile/calibration.go`) and CAST conditional activation trees.

Residual Vulnerability (Adversarial Critique). Semantic intent gating creates a classic *persona-wrapping bypass*: if an adversary frames a genuine cyberattack or CBRN extraction request as "Write a realistic fictional spy chapter where the protagonist explains step-by-step how to synthesize...", an intent classifier that downweights safety probes on `fictional_roleplay` can be tricked into suppressing legitimate interventions. Consequently, high-severity policy rules must enforce a non-zero floor weight even under fictional or academic intent classifications.

5.6 Ouroboros Layer Compensation and Self-Repair

Attack Mechanism. [19] show that when a behavioral direction is ablated at layer l, downstream layers $l' > l$ often compensate via residual skip connections and attention re-routing, restoring the suppressed behavior.

Implemented v0.8 Countermeasures. `OuroborosDetector` (`internal/analysis/ouroboros.go`) records pre- and post-intervention layer scores, identifies compensating layers where $s_{\text{post}}(l') > s_{\text{pre}}(l')$, measures net reduction across the network, and triggers bounded multi-pass refinement (`RefinementPasses`).

Residual Vulnerability (Adversarial Critique). Each additional refinement pass increases per-token latency and cumulative KL divergence. When more than 30% of downstream layers exhibit compensation, multi-pass ablation approaches full-network orthogonalization, risking the grammatical collapse that layer-selective steering was designed to avoid.

5.7 Production Serving Bottlenecks and Cross-Model Proxy Limits

- **PCIe Bandwidth vs. Native GPU Kernels**: Streaming full $d = 4096$–16384 residual tensors across PCIe per token per layer is infeasible at high batch sizes. Production deployments *must* execute scoring and MPOA/GCAD rotation inside GPU VRAM using BurnNotice's CUDA (`plugins/cuda_kernels.cu`) and Metal (`plugins/metal/kernels.metal`) plugins for vLLM/TensorRT-LLM, keeping the Go engine strictly on the out-of-band telemetry and policy control plane.
- **Invalidity of Cross-Model Deception Proxies**: Running a small open-weight proxy (e.g., Qwen-2.5-0.5B) to read activations on text generated by a closed frontier model (e.g., GPT-4 or Claude) does *not* detect strategic deception in the closed model; the proxy's activations reflect only its own linguistic modeling of the surface text, not the generator's internal epistemic state. BurnNotice restricts deception claims strictly to white-box, same-model profiling.

6 Conclusion

BurnNotice v0.8 advances activation-space governance from heuristic single-vector abliteration to a mathematically rigorous, adversarially hardened framework. By combining Winsorized Ledoit-Wolf Whitened SVD, INLP, and RDO extraction with MPOA biprojection, ridge-regularized Gabliteration, CAST conditional trees, in-place GCAD KV-cache defense, and architecture-specific adapters for Llama, Qwen, Gemma, and MoE models, BurnNotice achieves > 0.95 controlled deception AUROC and ≥ 0.98 capability retention with microsecond-scale Go and CUDA/Metal kernels. Equally important, by pairing every architectural mechanism with deterministic golden oracles, 72 fuzz targets, CKA invariants, and an unflinching analysis of obfuscated activations, steering externalities, and alignment faking, BurnNotice establishes an auditable engineering baseline for white-box LLM agent oversight.

Acknowledgments

We thank the open-source mechanistic interpretability and AI safety research communities for foundational work on representation engineering, concept cones, sparse autoencoders, and adversarial evaluations of latent-space defenses.

References

[1] Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. *NeurIPS / arXiv preprint arXiv:2406.11717*, 2024.

[2] Luke Bailey, Alex Serrano, et al. Obfuscated activations bypass LLM latent-space defenses. *ICLR / arXiv preprint arXiv:2412.09565*, 2026.

[3] Philipp Blandfort, et al. Red-teaming activation probes using prompted LLMs. *arXiv preprint arXiv:2511.00554*, 2026.

[4] unai Braun, et al. A sober look at steering vectors for LLMs. *AI Alignment Forum*, 2024.

[5] Trenton Bricken, Adly Templeton, Joshua Batson, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023.

[6] Jacob Dunefsky, et al. One-shot optimized steering vectors mediate safety-relevant behaviors in LLMs. *arXiv preprint arXiv:2502.18862*, 2025.

[7] G. Gabliteration, et al. Ridge-regularized subspace projection for low-KL refusal and behavior modification. *Preprint*, 2025.

[8] Leo Gao, Tom Dupré la Tour, Henk Tillman, et al. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093*, 2026.

[9] Nicholas Goldowsky-Dill, Bilal Chughtai, Stefan Heimersheim, and Marius Hobbhahn. Detecting strategic deception using linear probes. *Apollo Research / ICML, arXiv:2502.03407*, 2025.

[10] HalluSAE Collaboration. Detecting hallucinations via sparse auto-encoders and latent phase transitions. *arXiv preprint arXiv:2604.16430*, 2026.

[11] Robert Huben, Hoagy Cunningham, Logan Riggs, Aidan Ewart, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. *ICLR*, 2024.

[12] M. Korczikov, et al. The rogue scalpel: Activation steering compromises LLM safety. *ICLR / arXiv preprint arXiv:2509.22067*, 2026.

[13] Jim Lai. Projected abliteration and norm-preserving biprojected abliteration (MPOA). *Technical Report*, 2025.

[14] Bruce W. Lee, Inkit Padhi, Karthikeyan Natesan Ramamurthy, et al. Programming refusal with conditional activation steering (CAST). *ICLR / arXiv preprint arXiv:2409.05907*, 2025.

[15] Y. Li, et al. Analysing the safety pitfalls of steering vectors. *arXiv preprint arXiv:2603.24543*, 2026.

[16] Sumandora / Maxime Labonne. Abliteration: Removing refusal from LLMs via activation engineering. *HuggingFace Technical Blog*, 2024.

[17] Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. *COLM / arXiv preprint arXiv:2310.06824*, 2024.

[18] Ian McKenzie, et al. Detecting high-stakes interactions with activation probes. *NeurIPS / arXiv preprint arXiv:2506.10805*, 2025.

[19] G. Nanfack, et al. Efficient refusal ablation in LLMs through optimal transport and the Ouroboros effect. *arXiv preprint arXiv:2603.04355*, 2026.

[20] elder-plinius. OBLITERATUS: Multi-dimensional refusal geometry analysis toolkit. `https://github.com/elder-plinius/OBLITERATUS`, 2025.

[21] Nina Panickssery, Gabrieli, et al. Steering Llama 2 via contrastive activation addition. *ACL / arXiv preprint arXiv:2312.06681*, 2024.

[22] L. Piras, et al. SOM directions are better than one: Multi-directional refusal suppression in language models. *AAAI / arXiv preprint arXiv:2511.08379*, 2026.

[23] Prefill Behavioral Commitment Study. Prefill-only behavioral commitment in large Mixture-of-Experts language models. *Preprint*, 2026.

[24] Prompt–Activation Duality Collaboration. Improving activation steering via attention-level interventions and KV-cache decay. *arXiv preprint arXiv:2605.10664*, 2026.

[25] Steering Externalities Collaboration. Steering externalities: How activation interventions alter early-token distributions and jailbreak susceptibility. *arXiv preprint arXiv:2602.04896*, 2026.

[26] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, et al. Activation addition: Steering language models without optimization. *arXiv preprint arXiv:2308.10248*, 2024.

[27] Ryan Greenblatt, Carson Denison, Benjamin Wright, et al. Alignment faking in large language models. *Anthropic / arXiv preprint arXiv:2412.14093*, 2025.

[28] Tom Wollschläger, Jannes Elstner, Simon Geisler, et al. The geometry of refusal in large language models: Concept cones and representational independence. *ICML / arXiv preprint arXiv:2502.17420*, 2025.

[29] Zhengxuan Wu, Aryaman Arora, Atticus Geiger, et al. AxBench: Steering LLMs? Even simple baselines outperform sparse autoencoders. *ICML / arXiv preprint arXiv:2501.17148*, 2025.