ASSIGNMENT-17.5

HT.NO-2403A52L06

BATCH-50

TASK-1:

Loan Approval Dataset Cleaning

Use AI to generate preprocessing code for a loan dataset.

Instructions:

• Handle missing values in loan_amount, credit_score.

• Encode loan_status (Approved/Rejected).

• Scale numerical features using standard scaling.

• Split the dataset into training and testing sets.

Sample Code:

```
import pandas as pd

data = pd.read_csv("loadapproval.csv")

print(data.head())
```

Dataset link:

https://www.kaggle.com/datasets/amineipad/loan-approval-

dataset

Expected Output:

• A machine-learning-ready loan dataset.

CODE:

```
import pandas as pd

import numpy as np

from sklearn.model_selection import train_test_split

from sklearn.preprocessing import StandardScaler, LabelEncoder, MinMaxScaler,
OneHotEncoder


# --- TASK 1 – LOAN APPROVAL DATASET CLEANING ---

print("--- TASK 1: LOAN APPROVAL DATASET CLEANING ---")
```

```
# Load dataset
# Replace 'loan_approval_dataset.csv' with your actual file path
try:
    df_loan = pd.read_csv('loan_approval_dataset.csv')
    print("Loan Approval Dataset loaded successfully.")
    print("Initial shape:", df_loan.shape)
    print("Initial missing values:\n", df_loan.isnull().sum())
except FileNotFoundError:
    print("Error: 'loan_approval_dataset.csv' not found. Creating a dummy DataFrame for demonstration.")
    data = {
        'loan_amount': [10000, 20000, np.nan, 15000, 30000, 25000, np.nan, 12000],
        'credit_score': [700, 650, 720, np.nan, 750, 680, 690, np.nan],
        'loan_status': ['Approved', 'Rejected', 'Approved', 'Approved', 'Rejected', 'Approved', 'Rejected', 'Approved'],
        'age': [30, 45, 28, 35, 50, 40, 33, 29],
        'income': [50000, 60000, 55000, 70000, 80000, 65000, 52000, 58000]
    }
    df_loan = pd.DataFrame(data)

# Handle missing values
# Fill 'loan_amount' with its mean
if 'loan_amount' in df_loan.columns:
    mean_loan_amount = df_loan['loan_amount'].mean()
    df_loan['loan_amount'].fillna(mean_loan_amount, inplace=True)
    print(f"Filled missing 'loan_amount' with mean: {mean_loan_amount:.2f}")

# Fill 'credit_score' with its median
if 'credit_score' in df_loan.columns:
```

```
    median_credit_score = df_loan['credit_score'].median()
    df_loan['credit_score'].fillna(median_credit_score, inplace=True)
    print(f"Filled missing 'credit_score' with median: {median_credit_score:.2f}")

print("Missing values after handling:\n", df_loan.isnull().sum())

# Encode target column 'loan_status'
# Convert 'Approved' to 1 and 'Rejected' to 0
if 'loan_status' in df_loan.columns:
    df_loan['loan_status'] = df_loan['loan_status'].map({'Approved': 1, 'Rejected': 0})
    print("Encoded 'loan_status' column (Approved=1, Rejected=0).")
    print("Sample of encoded 'loan_status':\n", df_loan['loan_status'].value_counts())

# Identify numerical features for scaling (excluding the target column)
# Select only numerical columns for scaling, excluding 'loan_status' if it's already encoded as numerical
numerical_features_loan = df_loan.select_dtypes(include=np.number).columns.tolist()
if 'loan_status' in numerical_features_loan: # If loan_status was int/float and part of numerical columns
    numerical_features_loan.remove('loan_status')

if numerical_features_loan:
    # Scale numerical features using StandardScaler
    scaler_loan = StandardScaler()
    df_loan[numerical_features_loan] = scaler_loan.fit_transform(df_loan[numerical_features_loan])
    print("Scaled numerical features using StandardScaler.")
    print("Sample of scaled data:\n", df_loan[numerical_features_loan].head())
else:
    print("No numerical features found for scaling in Loan Approval Dataset.")
```

```
# Split dataset into training and testing sets (80/20)
if 'loan_status' in df_loan.columns and len(df_loan) > 1:
    X = df_loan.drop('loan_status', axis=1)
    y = df_loan['loan_status']
    X_train_loan, X_test_loan, y_train_loan, y_test_loan = train_test_split(X, y, test_size=0.2, random_state=42, stratify=y if y.nunique() > 1 else None)
    print(f"Dataset split into training (80%) and testing (20%) sets.")
    print(f"X_train shape: {X_train_loan.shape}, X_test shape: {X_test_loan.shape}")
    print(f"y_train shape: {y_train_loan.shape}, y_test shape: {y_test_loan.shape}")
else:
    print("Cannot split data: 'loan_status' column missing or dataset too small.")

print("\n" + "="*60 + "\n")
```

OUTPUT:

```
... --- TASK 1: LOAN APPROVAL DATASET CLEANING ---
    Error: 'loan_approval_dataset.csv' not found. Creating a dummy DataFrame for demonstration.
    Filled missing 'loan_amount' with mean: 18666.67
    Filled missing 'credit_score' with median: 695.00
    Missing values after handling:
     loan_amount     0
    credit_score    0
    loan_status     0
    age             0
    income          0
    dtype: int64
    Encoded 'loan_status' column (Approved=1, Rejected=0).
    Sample of encoded 'loan_status':
     loan_status
    1    5
    0    3
    Name: count, dtype: int64
    Scaled numerical features using StandardScaler.
    Sample of scaled data:
        loan_amount  credit_score       age    income
    0    -1.407463      0.092057 -0.831948 -1.197978
    1     0.216533     -1.749092  1.164727 -0.133109
    2     0.000000      0.828517 -1.098171 -0.665544
    3    -0.595465     -0.092057 -0.166390  0.931761
    4     1.840529      1.933207  1.830285  1.996631
    Dataset split into training (80%) and testing (20%) sets.
    X_train shape: (6, 4), X_test shape: (2, 4)
    y_train shape: (6,), y_test shape: (2,)
```

TASK-2:

Task 2 – Social Media Profiles

Preprocess a social media engagement dataset using AI

assistance.

Instructions:

• Remove duplicate user profiles.

• Handle missing values

• Encode categorical columns

Dataset link:

https://www.kaggle.com/datasets/medaxone/top-100-social-

media-profiles

Expected Output:

• A cleaned dataset for engagement prediction.

CODE:

```
# --- TASK 2 – SOCIAL MEDIA PROFILES DATASET ---
print("--- TASK 2: SOCIAL MEDIA PROFILES DATASET ---")

# Load dataset
# Replace 'social_media_profiles.csv' with your actual file path
try:
    df_social = pd.read_csv('social_media_profiles.csv')
    print("Social Media Profiles Dataset loaded successfully.")
    print("Initial shape:", df_social.shape)
    print("Initial missing values:\n", df_social.isnull().sum())
except FileNotFoundError:
    print("Error: 'social_media_profiles.csv' not found. Creating a dummy DataFrame for demonstration.")
    data = {
        'user_id': [1, 2, 3, 1, 4, 5, 6, 7],
        'username': ['userA', 'userB', 'userC', 'userA', 'userD', 'userE', 'userF', 'userG'],
        'age': [25, 30, np.nan, 25, 35, 28, 40, np.nan],
        'gender': ['Male', 'Female', 'Other', 'Male', 'Female', np.nan, 'Male', 'Female'],
        'country': ['USA', 'Canada', 'UK', 'USA', 'Germany', 'France', 'USA', 'Canada'],
```

```
        'followers': [100, 200, 150, 100, 300, 120, 250, 180]
    }
    df_social = pd.DataFrame(data)

# Remove duplicate user profiles based on a unique identifier like 'user_id' or 'username'
initial_rows_social = df_social.shape[0]
df_social.drop_duplicates(subset=['user_id'], inplace=True)
print(f"Removed {initial_rows_social - df_social.shape[0]} duplicate user profiles.")
print("Shape after removing duplicates:", df_social.shape)

# Handle missing values (using appropriate method: mean/median for numerical, mode for categorical)
for col in df_social.columns:
    if df_social[col].isnull().any():
        if df_social[col].dtype == 'object' or pd.api.types.is_categorical_dtype(df_social[col]): # Categorical
            mode_val = df_social[col].mode()[0] # mode() can return multiple values, take the first
            df_social[col].fillna(mode_val, inplace=True)
            print(f"Filled missing '{col}' with mode: {mode_val}")
        elif pd.api.types.is_numeric_dtype(df_social[col]): # Numerical
            if df_social[col].nunique() > 10: # Heuristic for continuous-like numbers, use mean
                mean_val = df_social[col].mean()
                df_social[col].fillna(mean_val, inplace=True)
                print(f"Filled missing '{col}' with mean: {mean_val:.2f}")
            else: # Discrete-like numbers, use median
                median_val = df_social[col].median()
                df_social[col].fillna(median_val, inplace=True)
                print(f"Filled missing '{col}' with median: {median_val:.2f}")
print("Missing values after handling:\n", df_social.isnull().sum())
```

```
# Encode categorical columns (using One-Hot Encoding for 'gender' and 'country', Label Encoding for 'username' if unique counts are high)

# Identify categorical columns

categorical_cols_social = df_social.select_dtypes(include='object').columns.tolist()


for col in categorical_cols_social:

    if df_social[col].nunique() > 5 and col != 'username': # Heuristic for high cardinality, might consider target encoding for more advanced cases

        # For demonstration, using OneHotEncoder for columns with more than 5 unique values but not too many unique values to avoid sparse matrices

        # For 'username', we might not want to encode it directly as it's an identifier

        if col not in ['user_id', 'username']:

            print(f"Applying One-Hot Encoding to '{col}'.")

            encoder = OneHotEncoder(handle_unknown='ignore', sparse_output=False)

            encoded_features = encoder.fit_transform(df_social[[col]])

            encoded_df = pd.DataFrame(encoded_features, columns=encoder.get_feature_names_out([col]), index=df_social.index)

            df_social = pd.concat([df_social.drop(columns=[col]), encoded_df], axis=1)

    elif col not in ['user_id', 'username']:

        print(f"Applying Label Encoding to '{col}'.")

        le = LabelEncoder()

        df_social[col] = le.fit_transform(df_social[col])

    else:

        print(f"Skipping encoding for '{col}' (identifier column). Example: {df_social[col].head(2).tolist()}")


print("Sample of processed Social Media data (first 5 rows):\n", df_social.head())


print("\n" + "="*60 + "\n")
```

OUTPUT:

```
...
    ============================================================

    --- TASK 2: SOCIAL MEDIA PROFILES DATASET ---
    Error: 'social_media_profiles.csv' not found. Creating a dummy DataFrame for demonstration.
    Removed 1 duplicate user profiles.
    Shape after removing duplicates: (7, 6)
    Filled missing 'age' with median: 30.00
    Filled missing 'gender' with mode: Female
    Missing values after handling:
     user_id      0
    username     0
    age          0
    gender       0
    country      0
    followers    0
    dtype: int64
    Skipping encoding for 'username' (identifier column). Example: ['userA', 'userB']
    Applying Label Encoding to 'gender'.
    Applying Label Encoding to 'country'.
    Sample of processed Social Media data (first 5 rows):
        user_id username   age  gender  country  followers
    0        1    userA  25.0       1        4        100
    1        2    userB  30.0       0        0        200
    2        3    userC  30.0       2        3        150
    4        4    userD  35.0       0        2        300
    5        5    userE  28.0       0        1        120

    ============================================================
```

TASK-3:

Task 3 – Weather Dataset Feature Engineering

Task:

Use AI to preprocess a weather dataset for forecasting.

Instructions:

• Convert date column into datetime format.

• Handle missing values in temperature, humidity.

• Create new features (season, week_number).

• Normalize rainfall values.

Dataset link:

https://www.kaggle.com/code/alsamaualalhinai/weather-

dataset/input

Expected Output:

• A processed dataset ready for forecasting models.

CODE:

--- TASK 3 – WEATHER DATASET FEATURE ENGINEERING ---

```
print("--- TASK 3: WEATHER DATASET FEATURE ENGINEERING ---")


# Load dataset
# Replace 'weather_dataset.csv' with your actual file path
try:
    df_weather = pd.read_csv('weather_dataset.csv')
    print("Weather Dataset loaded successfully.")
    print("Initial shape:", df_weather.shape)
    print("Initial missing values:\n", df_weather.isnull().sum())
except FileNotFoundError:
    print("Error: 'weather_dataset.csv' not found. Creating a dummy DataFrame for demonstration.")
    data = {
        'date': ['2023-01-01', '2023-01-02', '2023-02-15', '2023-03-10', '2023-04-20', '2023-05-05', '2023-06-01', '2023-07-10', '2023-08-25', '2023-09-15', '2023-10-01', '2023-11-11', '2023-12-20', '2024-01-05'],
        'temperature': [10.5, 11.2, np.nan, 15.1, 18.0, 22.5, 25.0, np.nan, 28.1, 20.3, 14.5, 8.9, 3.1, 5.0],
        'humidity': [80, np.nan, 75, 70, 65, np.nan, 60, 85, 78, 82, 90, 92, 88, 85],
        'rainfall': [5.0, 2.1, 0.0, 1.5, 0.0, 10.2, 3.5, 0.0, 0.0, 6.7, 12.0, 8.1, 4.0, 1.0]
    }
    df_weather = pd.DataFrame(data)


# Convert 'date' column to datetime format
if 'date' in df_weather.columns:
    df_weather['date'] = pd.to_datetime(df_weather['date'])
    print("Converted 'date' column to datetime format.")
    print("Sample dates:\n", df_weather['date'].head())
else:
    print("Warning: 'date' column not found in Weather Dataset.")
```

```
# Handle missing values
# Fill 'temperature' with its mean
if 'temperature' in df_weather.columns:
    mean_temperature = df_weather['temperature'].mean()
    df_weather['temperature'].fillna(mean_temperature, inplace=True)
    print(f"Filled missing 'temperature' with mean: {mean_temperature:.2f}")

# Fill 'humidity' with its median
if 'humidity' in df_weather.columns:
    median_humidity = df_weather['humidity'].median()
    df_weather['humidity'].fillna(median_humidity, inplace=True)
    print(f"Filled missing 'humidity' with median: {median_humidity:.2f}")

print("Missing values after handling:\n", df_weather.isnull().sum())

# Create new features
# Create 'season' based on month
# Assuming Northern Hemisphere seasons: Dec-Feb (Winter), Mar-May (Spring), Jun-Aug (Summer), Sep-Nov (Autumn)
if 'date' in df_weather.columns:
    df_weather['month'] = df_weather['date'].dt.month
    def get_season(month):
        if month in [12, 1, 2]:
            return 'Winter'
        elif month in [3, 4, 5]:
            return 'Spring'
        elif month in [6, 7, 8]:
            return 'Summer'
```

```
        else:
            return 'Autumn'
    df_weather['season'] = df_weather['month'].apply(get_season)
    print("Created 'season' feature based on month.")
    print("Sample 'season' values:\n", df_weather[['date', 'month', 'season']].head())
    df_weather.drop('month', axis=1, inplace=True) # Drop auxiliary month column

    # Create 'week_number' from date
    df_weather['week_number'] = df_weather['date'].dt.isocalendar().week.astype(int) # .isocalendar() returns a DataFrame, .week extracts the series
    print("Created 'week_number' feature from date.")
    print("Sample 'week_number' values:\n", df_weather[['date', 'week_number']].head())
else:
    print("Cannot create 'season' and 'week_number' features as 'date' column is missing or not in datetime format.")

# Normalize 'rainfall' using MinMaxScaler
if 'rainfall' in df_weather.columns and df_weather['rainfall'].nunique() > 1:
    scaler_rainfall = MinMaxScaler()
    df_weather['rainfall_normalized'] = scaler_rainfall.fit_transform(df_weather[['rainfall']])
    print("Normalized 'rainfall' using MinMaxScaler.")
    print("Sample of normalized 'rainfall':\n", df_weather[['rainfall', 'rainfall_normalized']].head())
else:
    print("Cannot normalize 'rainfall': column missing or all values are the same.")

print("Sample of processed Weather data (first 5 rows):\n", df_weather.head())

print("\n" + "="*60 + "\n")
```

OUTPUT:

```
... --- TASK 3: WEATHER DATASET FEATURE ENGINEERING ---
    Error: 'weather_dataset.csv' not found. Creating a dummy DataFrame for demonstration.
    Converted 'date' column to datetime format.
    Sample dates:
     0   2023-01-01
    1   2023-01-02
    2   2023-02-15
    3   2023-03-10
    4   2023-04-20
    Name: date, dtype: datetime64[ns]
    Filled missing 'temperature' with mean: 15.18
    Filled missing 'humidity' with median: 81.00
    Missing values after handling:
     date           0
    temperature    0
    humidity       0
    rainfall       0
    dtype: int64
    Created 'season' feature based on month.
    Sample 'season' values:
             date  month  season
    0 2023-01-01      1  Winter
    1 2023-01-02      1  Winter
    2 2023-02-15      2  Winter
    3 2023-03-10      3  Spring
    4 2023-04-20      4  Spring
    Created 'week_number' feature from date.
    Sample 'week_number' values:
             date  week_number
```

TASK-4:

Task 4 – Movie Ratings Dataset Preparation

Task:

Clean and preprocess a movie ratings dataset using AI-

generated scripts.

Instructions:

• Handle missing values in rating, genre.

• Encode categorical variables like genre, language.

• Remove duplicate movie entries.

• Scale rating values between 0 and 1.

Dataset link:

https://www.kaggle.com/datasets/PromptCloudHQ/imdb-

data

Expected Output:

• A dataset suitable for recommendation systems.

CODE:

```
# --- TASK 4 – MOVIE RATINGS DATASET PREPROCESSING ---
print("--- TASK 4: MOVIE RATINGS DATASET PREPROCESSING ---")

# Load dataset
# Replace 'imdb_movie_dataset.csv' with your actual file path
try:
    df_movie = pd.read_csv('imdb_movie_dataset.csv')
    print("IMDB Movie Dataset loaded successfully.")
    print("Initial shape:", df_movie.shape)
    print("Initial missing values:\n", df_movie.isnull().sum())
except FileNotFoundError:
    print("Error: 'imdb_movie_dataset.csv' not found. Creating a dummy DataFrame for
demonstration.")
    data = {
        'movie_id': [1, 2, 3, 4, 1, 5, 6, 7],
        'title': ['Movie A', 'Movie B', 'Movie C', 'Movie D', 'Movie A', 'Movie E', 'Movie F',
'Movie G'],
        'rating': [8.5, 7.2, np.nan, 9.0, 8.5, 6.8, np.nan, 7.5],
        'genre': ['Action', 'Comedy', 'Drama', 'Action', 'Action', 'Sci-Fi', 'Comedy', np.nan],
        'language': ['English', 'Spanish', 'English', 'French', 'English', 'English', np.nan, 'German'],
        'year': [2020, 2021, 2022, 2020, 2020, 2023, 2021, 2022]
    }
    df_movie = pd.DataFrame(data)

# Handle missing values
# Fill 'rating' with its mean
if 'rating' in df_movie.columns:
    mean_rating = df_movie['rating'].mean()
    df_movie['rating'].fillna(mean_rating, inplace=True)
```

```
    print(f"Filled missing 'rating' with mean: {mean_rating:.2f}")

# Fill 'genre' with its mode
if 'genre' in df_movie.columns:
    mode_genre = df_movie['genre'].mode()[0]
    df_movie['genre'].fillna(mode_genre, inplace=True)
    print(f"Filled missing 'genre' with mode: {mode_genre}")

print("Missing values after handling:\n", df_movie.isnull().sum())

# Encode categorical columns 'genre' and 'language'
categorical_cols_movie = ['genre', 'language']

for col in categorical_cols_movie:
    if col in df_movie.columns and df_movie[col].dtype == 'object':
        if df_movie[col].nunique() < 10: # Use OneHotEncoder for columns with fewer unique categories
            print(f"Applying One-Hot Encoding to '{col}'.")
            encoder = OneHotEncoder(handle_unknown='ignore', sparse_output=False)
            encoded_features = encoder.fit_transform(df_movie[[col]])
            encoded_df = pd.DataFrame(encoded_features, columns=encoder.get_feature_names_out([col]), index=df_movie.index)
            df_movie = pd.concat([df_movie.drop(columns=[col]), encoded_df], axis=1)
        else: # For higher cardinality, LabelEncoder is an option, but OneHot is often preferred if cardinality is not excessive
            print(f"Applying Label Encoding to '{col}' (high cardinality or many unique values). Generally One-Hot is preferred if not too many categories.")
            le = LabelEncoder()
            df_movie[col] = le.fit_transform(df_movie[col])
    elif col not in df_movie.columns:
```

```
        print(f"Warning: Column '{col}' not found in Movie Ratings Dataset.")

# Remove duplicate movie entries based on 'movie_id' or 'title'
initial_rows_movie = df_movie.shape[0]
df_movie.drop_duplicates(subset=['movie_id'], inplace=True)
print(f"Removed {initial_rows_movie - df_movie.shape[0]} duplicate movie entries.")
print("Shape after removing duplicates:", df_movie.shape)

# Scale rating values between 0 and 1 using MinMaxScaler
if 'rating' in df_movie.columns and df_movie['rating'].nunique() > 1:
    scaler_movie_rating = MinMaxScaler()
    df_movie['rating_scaled'] = scaler_movie_rating.fit_transform(df_movie[['rating']])
    print("Scaled 'rating' values between 0 and 1 using MinMaxScaler.")
    print("Sample of scaled 'rating':\n", df_movie[['rating', 'rating_scaled']].head())
else:
    print("Cannot scale 'rating': column missing or all values are the same.")

print("Sample of processed Movie Ratings data (first 5 rows):\n", df_movie.head())

print("\n" + "="*60 + "\n")
print("All tasks completed. Please ensure you replace dummy file paths with your actual dataset paths.")
```

OUTPUT:

```
...
--- TASK 4: MOVIE RATINGS DATASET PREPROCESSING ---
Error: 'imdb_movie_dataset.csv' not found. Creating a dummy DataFrame for demonstration.
Filled missing 'rating' with mean: 7.92
Filled missing 'genre' with mode: Action
Missing values after handling:
 movie_id    0
title       0
rating      0
genre       0
language    1
year        0
dtype: int64
Applying One-Hot Encoding to 'genre'.
Applying One-Hot Encoding to 'language'.
Removed 1 duplicate movie entries.
Shape after removing duplicates: (7, 13)
Scaled 'rating' values between 0 and 1 using MinMaxScaler.
Sample of scaled 'rating':
      rating  rating_scaled
0  8.500000       0.772727
1  7.200000       0.181818
2  7.916667       0.507576
3  9.000000       1.000000
5  6.800000       0.000000
Sample of processed Movie Ratings data (first 5 rows):
    movie_id    title    rating  year  genre_Action  genre_Comedy  genre_Drama  \
0         1  Movie A  8.500000  2020           1.0           0.0          0.0
1         2  Movie B  7.200000  2021           0.0           1.0          0.0
```