

AI ASSISTED CODING

LAB TEST – 02

NAME : Neha Shazneen

ROLL NO : 2403A510A1

BATCH : 05

DEPARTMENT : CSE

SET A

A.1 - Compute per-player average from logs (AI completion)

Prompt :

You are integrating a sports analytics telemetry service where each player emits periodic measures as CSV lines: id,timestamp,velocity. Due to flaky connectivity, some lines may be truncated or contain non-numeric values. Ops needs a quick aggregation for dashboards and alert thresholds.

Task :

Write a Python function to parse the raw text (multiple lines) and compute per-player averages of velocity. Return a dict {id: avg} and separately compute an overall average.

Data & Edge Cases:

- Input contains newlines, optional leading/trailing spaces, and may include malformed rows.
- Timestamps are ISO-8601 but not needed for math.

Constraints & Notes:

- Prefer $O(n)$ pass; ignore lines that cannot be split into three fields or have non-numeric metric.
- Round averages to 2 decimals.

Code Generated :

```
1 def compute_player_averages(raw_text):
2     player_sums = {}
3     player_counts = {}
4     total_sum = 0.0
5     total_count = 0
6
7     for line in raw_text.strip().split('\n'):
8         line = line.strip()
9         if not line:
10            continue
11        parts = line.split(',')
12        if len(parts) != 3:
13            continue
14        player_id, _, velocity_str = parts
15        try:
16            velocity = float(velocity_str)
17        except ValueError:
18            continue
19        if player_id not in player_sums:
20            player_sums[player_id] = 0.0
21            player_counts[player_id] = 0
22        player_sums[player_id] += velocity
23        player_counts[player_id] += 1
24
25    total_sum += velocity
26    total_count += 1
27
28    player_averages = {}
29    for pid in player_sums:
30        avg = round(player_sums[pid] / player_counts[pid], 2)
31        player_averages[pid] = avg
32
33    overall_avg = round(total_sum / total_count, 2) if total_count else 0.0
34    return player_averages, overall_avg
35
36 if __name__ == "__main__":
37     sample_input = """
38     p191,2025-01-01T08:00,28.7
39     p192,2025-01-02T09:00,30.2
40     p193,2025-01-03T10:00,31.7
41     """
42     per_player, overall = compute_player_averages(sample_input)
43     print(per_player, "and overall_avg=", overall)
```

Output :

```
PS C:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding> & 'c:\Users\Summya Mehveen\AppData
a\Local\Programs\Python\Python313\python.exe' 'c:\Users\Summya Mehveen\.vscode\extensions\ms-python.
debugpy-2025.10.0-win32-x64\bundle\libs\debugpy\launcher' '51658' '--' 'c:\Users\Summya Mehveen\One
Drive\Desktop\AI associated coding\lab test 2.1.py'
{'p191': 28.7, 'p192': 30.2, 'p193': 31.7} and overall_avg= 30.2
PS C:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding>
```

Observation :

The provided Python function [compute_player_averages](#) correctly parses multiline CSV telemetry data, computes per-player average velocities, and calculates the overall average velocity. It robustly skips malformed or non-numeric lines, ensuring only valid data is aggregated. The output matches the expected format: a dictionary of player averages (rounded to 2 decimals) and an overall average. The sample input produces the correct result, demonstrating the function handles edge cases as required.

A.2 - Implement MatchStats with add/remove/summary (AI completion)

Prompt :

A microservice in the sports analytics platform maintains a small in-memory structure to track values keyed by identifier (e.g., order IDs, sensor IDs). Engineers want a minimal class to add, remove, and summarize current values for quick health checks.

Task :

Implement a MatchStats class with methods add(id: str, value: float), remove(id: str), and summary() -> tuple[int, float|None] returning (count, average).

Data & Edge Cases:

- IDs are unique keys.
- Re-adding the same ID overwrites its value.
- Removing a missing ID should be safe (no exception).
- For an empty store, average is None.

Constraints & Notes:

- Keep state in a dict; O(1) per operation; return rounded average to 2 decimals (when non-empty).

Code Generated :

```
1  from typing import Dict, Tuple, Optional
2
3  class MatchStats:
4      """
5      Minimal in-memory stats tracker for unique IDs and their float values.
6      Supports add, remove, and summary operations.
7      """
8      def __init__(self):
9          self._data: Dict[str, float] = {}
10
11     def add(self, id: str, value: float) -> None:
12         """
13         Add or update the value for the given ID.
14         """
15         self._data[id] = value
16
17     def remove(self, id: str) -> None:
18         """
19         Remove the value for the given ID if it exists.
20         Safe if ID is missing.
21         """
22         self._data.pop(id, None)
```

```
23
24     def summary(self) -> Tuple[int, Optional[float]]:
25         """
26         Returns a tuple of (count, average of values rounded to 2 decimals).
27         If empty, average is None.
28         """
29         count = len(self._data)
30         if count == 0:
31             return 0, None
32         avg = round(sum(self._data.values()) / count, 2)
33         return count, avg
34
35     # Example usage:
36     if __name__ == "__main__":
37         stats = MatchStats()
38         ops = [
39             {'op': 'add', 'id': 'a1', 'value': 18},
40             {'op': 'add', 'id': 'b2', 'value': 17},
41             {'op': 'remove', 'id': 'a1'},
42             {'op': 'add', 'id': 'c3', 'value': 15}
43         ]
```

```

44     for op in ops:
45         if op['op'] == 'add':
46             stats.add(op['id'], op['value'])
47         elif op['op'] == 'remove':
48             stats.remove(op['id'])
49     count, avg = stats.summary()
50     print(f"count={count}, avg={avg}")

```

Output :

```

PS C:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding> c:; cd 'c:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding'; & 'c:\Users\Summya Mehveen\AppData\Local\Programs\Python\Python313\python.exe' 'c:\Users\Summya Mehveen\.vscode\extensions\ms-python.debugpy-2025.10.0-win32-x64\bundled\libs\debugpy\launcher' '52293' '--' 'c:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding\lab test 2.2.py'
count=2, avg=16.0
PS C:\Users\Summya Mehveen\OneDrive\Desktop\AI associated coding>

```

Observation :

The [MatchStats](#) class efficiently manages a dictionary of unique IDs and their float values, supporting $O(1)$ add, remove, and summary operations.

- Adding an ID overwrites its value if it already exists.
- Removing a missing ID is safe and does not raise an exception.
- The [summary\(\)](#) method returns the correct count and the average (rounded to 2 decimals), or None for the average if the store is empty.

The provided example demonstrates correct behavior: after the sequence of operations, the count is 2 and the average is 16.0, matching the sample output and requirements.