

AI assisted coding

## ASSIGNMENT-10.3

2403A51266

Yashwanth

B-12

### TASK-1:

Provide AI with the following nested conditional code and ask it to simplify and refactor for readability

### PROMPT

# write the following nested conditional code and ask it to simplify and refactor for readability.

Nested code:

```
ai.py > ...
1  # write the following nested conditional code and ask it to simplify and refactor for readability.
2  def discount(price, category):
3      if category == "student":
4          if price > 1000:
5              return price * 0.9
6          else:
7              return price * 0.95
8      else:
9          if price > 2000:
10             return price * 0.85
11          else:
12             return price * 0.9
13  discount(1200, "student")
14
```

Output code:

```
ai.py > ...
1 # write the following nested conditional code and ask it to simplify and refactor for readability.
2 def student_discount(price):
3     return price * 0.9 if price > 1000 else price * 0.95
4
5 def regular_discount(price):
6     return price * 0.85 if price > 2000 else price
7
8 discount_rules = {
9     "student": student_discount,
10    "regular": regular_discount
11 }
12
13 def discount(price, category):
14     apply_discount = discount_rules.get(category, regular_discount)
15     return apply_discount(price)
16 print(discount(1200, "student"))
17 print(discount(800, "student"))
18 print(discount(2500, "regular"))
19 print(discount(1500, "regular"))
20 print(discount(1800, "unknown"))
21
```

TASK-2 :

Give AI this messy loop and ask it to refactor and optimize.

PROMPT

#write this messy loop and ask it to refactor and optimize.

Messy code:

```
ai.py > ...
1 #write this messy loop and ask it to refactor and optimize.
2 def find_common(a, b):
3     res = []
4     for i in a:
5         for j in b:
6             if i == j:
7                 res.append(i)
8     return res
9 find_common([1,2,3,4],[3,4,5,6])
```

Output code :

```
#write this messy loop and ask it to refactor and optimize.  
def find_common(a, b):  
    return list(set(a) & set(b))  
print(find_common([1,2,3,4],[3,4,5,6]))
```

TASK-3:

Provide this class with poor readability and ask AI to improve:

- Naming conventions
- Encapsulation
- Readability & maintainability

PROMPT

#Write this class with poor readability and ask AI to improve

# Naming conventions

# Encapsulation

# Readability & maintainability

## Poor readability code:

```
ai.py > ...
1  #Write this class with poor readability and ask AI to improve
2  # Naming conventions
3  # Encapsulation
4  # Readability & maintainability Python Script
5  class emp:
6      def __init__(self,n,s):
7          self.n=n
8          self.s=s
9      def inc(self,p):
10         self.s=self.s+(self.s*p/100)
11     def pr(self):
12         print("emp:",self.n,"salary:",self.s)
13 e1=emp("ajay",10000)
14 e1.inc(10)
15 e1.pr()
```

## Output code :

```
ai.py > ...
1  #Write this class with poor readability and ask AI to improve
2  # Naming conventions
3  # Encapsulation
4  # Readability & maintainability Python Script
5  class Employee:
6      def __init__(self, name: str, salary: float):
7          self._name = name
8          self._salary = salary
9
10     def increase_salary(self, percent: float):
11         self._salary += self._salary * (percent / 100)
12
13     def display_info(self):
14         print(f"Employee: {self._name}, Salary: ${self._salary:,.2f}")
15
16     def get_name(self) -> str:
17         return self._name
18
19     def get_salary(self) -> float:
20         return self._salary
21 emp1 = Employee("Alice Johnson", 50000)
22 emp1.display_info()
23 emp1.increase_salary(10)
24 emp1.display_info()
25
26
```

## TASK-4 :

Give AI this long unstructured function and let it modularize into smaller helper functions

Prompt

# Write the long unstructured function and let it modularize into smaller helper functions

Unstructured function :

```
#Write the long unstructured function and let it modularize into smaller helper functions
def process_scores(scores):
    total = 0
    for s in scores:
        total += s
    avg = total / len(scores)

    highest = scores[0]
    for s in scores:
        if s > highest:
            highest = s

    lowest = scores[0]
    for s in scores:
        if s < lowest:
            lowest = s

    print("Average:", avg)
    print("Highest:", highest)
    print("Lowest:", lowest)
    process_scores([10, 20, 30, 40, 50])
```

Output code :

```
py / ...  
#Write the long unstructured function and let it modularize into smaller helper functions  
def calculate_average(scores):  
    return sum(scores) / len(scores) if scores else 0  
  
def find_highest(scores):  
    return max(scores) if scores else None  
  
def find_lowest(scores):  
    return min(scores) if scores else None  
  
def process_scores(scores):  
    if not scores:  
        print("No scores provided.")  
        return  
  
    avg = calculate_average(scores)  
    highest = find_highest(scores)  
    lowest = find_lowest(scores)  
  
    print(f"Average: {avg:.2f}")  
    print(f"Highest: {highest}")  
  
    print(f"Lowest: {lowest}")  
    scores = [85, 90, 78, 92, 88]  
    process_scores(scores)
```

TASK-5 :

Provide AI with this faulty code and ask it to improve error handling, naming, and readability

PROMPT

#Write this faulty code and ask it to improve error handling, naming, and readability

Faulty code :

```
ai.py > ...
1 #Write this faulty code and ask it to improve error handling, naming, and readability|
2 def div(a,b):
3     return a/b
4
5 print(div(10,0)) # ZeroDivisionError
6
```

Output code :

```
ai.py > divide_numbers
1 #Write this faulty code and ask it to improve error handling, naming, and readability
2 def divide_numbers(numerator, denominator):|
3     try:
4         return numerator / denominator
5     except ZeroDivisionError:
6         return "Error: Cannot divide by zero."
7
8 result = divide_numbers(10, 0)
9 print(result)
10
```

TASK-6:

Use AI to simplify overly complex logic.

Sample Input Code

PROMPT

# write a python program to simplify overly complex logic.

Sample Input Code

#Example : grade = 85

Complex logic :

```
#write a python program to simplify overly complex logic.
#Example : grade = 85
def grade(score):
    if score >= 90:
        return "A"
    else:
        if score >= 80:
            return "B"
        else:
            if score >= 70:
                return "C"
            else:
                if score >= 60:
                    return "D"
                else:
                    return "F"
grade(85)
```

Output code :

```
ai.py > ...
1  #write a python program to simplify overly complex logic.
2  #Example : grade = 85
3  def grade(score):
4      if not (0 <= score <= 100):
5          return "Invalid score"
6      return (
7          "A" if score >= 90 else
8          "B" if score >= 80 else
9          "C" if score >= 70 else
10         "D" if score >= 60 else
11         "F"
12     )
13  print(grade(85))
14
15
16
```



