

**PROGRAM** : B.TECH/CSE

**SPECIALIZATION** : AIML

**COURSE TITLE** : AI ASSISTED CODING

**COURSE CODE** : 24CS101PC214

**SEMESTER** : 3RD

**NAME OF THE STUDENT** : KARNAKANTI GODADEVI

**ENROLLMENT NO** : 2403A52003

**BATCH NO** : 01


### Task Description #1 – Stack class implementation

Task: Ask AI to implement a stack class with push(), pop(), peek() and is\_empty() methods.

#### Prompt:

*generate a python code to implement a stack class with push(), pop(), peek() and is\_empty() methods.*

#### Code &Output:



The screenshot shows a Google Colab notebook titled 'Untitled10.ipynb'. The code defines a Stack class with the following methods:

```
[6] ✓ 0s
class Stack:
    def __init__(self):
        self.items = []


    def push(self, item):
        """Adds an item to the top of the stack."""
        self.items.append(item)

    def pop(self):
        """Removes and returns the item from the top of the stack.
        Returns None if the stack is empty.
        """
        if not self.is_empty():
            return self.items.pop()
        return None

    def peek(self):
        """Returns the item at the top of the stack without removing it.
        Returns None if the stack is empty.
        """
        if not self.is_empty():
            return self.items[-1]
        return None

    def is_empty(self):
        """Returns True if the stack is empty. False otherwise."""
```

The bottom of the image shows the Windows taskbar with the time 1:53 PM and date 08-10-2025.



```
[6] ✓ Os
Returns the item at the top of the stack without removing it.
Returns None if the stack is empty.
"""
if not self.is_empty():
    return self.items[-1]
return None

def is_empty(self):
    """Returns True if the stack is empty, False otherwise."""
    return len(self.items) == 0

# Example usage of the Stack class:
stack = Stack()
stack.push(10)
stack.push(20)
print("Top of the stack:", stack.peek())
print("Popping from the stack:", stack.pop())
print("Is the stack empty?", stack.is_empty())
print("Popping from the stack:", stack.pop())
print("Is the stack empty?", stack.is_empty())
print("Popping from an empty stack:", stack.pop()) # Demonstrate popping from empty stack

Top of the stack: 20
Popping from the stack: 20
Is the stack empty? False
Popping from the stack: 10
Is the stack empty? True
Popping from an empty stack: None
```

### Observation:

The code defines a Stack class with standard stack operations: push, pop, peek, and is\_empty.

The example usage demonstrates these operations:

- Items 10 and 20 are pushed onto the stack.
- peek() shows 20 is at the top.
- pop() removes and returns 20, then 10.
- is\_empty() correctly reports the stack's state after each pop.
- Attempting to pop() from an empty stack returns None.


### Task Description #2 – Queue Implementation

Task: Use AI to generate a Queue class with enqueue(), dequeue(), and is\_empty().

## Prompt:

generate a python code of Queue class with enqueue(), dequeue(), and is\_empty().

## Code&Output:



The screenshot shows a Google Colab notebook titled 'Untitled10.ipynb'. The code defines a Queue class with three methods: enqueue, dequeue, and is\_empty. The enqueue method appends an item to the queue. The dequeue method removes and returns the item from the front of the queue, returning None if the queue is empty. The is\_empty method returns True if the queue is empty, False otherwise. An example usage is provided, showing the queue being initialized, enqueued with 10 and 20, dequeued (returning 10), and then checked for emptiness (returning False).


```
[10] class Queue:
def __init__(self):
    self.items = []

def enqueue(self, item):
    """Adds an item to the end of the queue."""
    self.items.append(item)

def dequeue(self):
    """Removes and returns the item from the front of the queue.
    Returns None if the queue is empty.
    """
    if not self.is_empty():
        return self.items.pop(0)
    return None

def is_empty(self):
    """Returns True if the queue is empty, False otherwise."""
    return len(self.items) == 0

# Example usage (optional - can be added in a separate cell):
queue = Queue()
queue.enqueue(10)
queue.enqueue(20)
print("Dequeue:", queue.dequeue()) # Output: 10
print("Is queue empty?", queue.is_empty()) # Output: False
print("Dequeue:", queue.dequeue()) # Output: 20
```



The screenshot shows the same Google Colab notebook, but now with the output of the code execution. The output shows the results of the example usage: Dequeue: 10, Is queue empty? False, Dequeue: 20, Is queue empty? True, and Dequeue from empty queue: None.

```
[10] return None

def is_empty(self):
    """Returns True if the queue is empty, False otherwise."""
    return len(self.items) == 0

# Example usage (optional - can be added in a separate cell):
queue = Queue()
queue.enqueue(10)
queue.enqueue(20)
print("Dequeue:", queue.dequeue()) # Output: 10
print("Is queue empty?", queue.is_empty()) # Output: False
print("Dequeue:", queue.dequeue()) # Output: 20
print("Is queue empty?", queue.is_empty()) # Output: True
print("Dequeue from empty queue:", queue.dequeue()) # Output: None

Dequeue: 10
Is queue empty? False
Dequeue: 20
Is queue empty? True
Dequeue from empty queue: None
```

### Observation:

The code defines a Queue class with standard queue operations: enqueue, dequeue, and is\_empty.

The example usage demonstrates these operations:

- Items 10 and 20 are enqueued into the queue.
- dequeue() removes and returns 10, then 20 from the front.
- is\_empty() correctly reports the queue's state after each dequeue.
- Attempting to dequeue() from an empty queue returns None.


### Task Description #3 – Linked List Implementation

Task: Ask AI to create a singly linked list with insert\_at\_end(), insert\_at\_beginning(), and display().

### Prompt:

generate a python code to create a singly linked list with insert\_at\_end(), insert\_at\_beginning(), and display().

### Code&Output:



The screenshot shows a Google Colab notebook titled 'Untitled10.ipynb'. The code defines a Node class and a SinglyLinkedList class. The SinglyLinkedList class has methods for inserting at the end, inserting at the beginning, and displaying the list.

```
[13] ✓ 0s
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None


class SinglyLinkedList:
    def __init__(self):
        self.head = None

    def insert_at_end(self, data):
        """Inserts a new node with the given data at the end of the linked list."""
        new_node = Node(data)
        if self.head is None:
            self.head = new_node
            return
        current = self.head
        while current.next:
            current = current.next
        current.next = new_node

    def insert_at_beginning(self, data):
        """Inserts a new node with the given data at the beginning of the linked list."""
        new_node = Node(data)
        new_node.next = self.head
        self.head = new_node

    def display(self):
```

The bottom of the image shows a Windows taskbar with various application icons and a system clock indicating 14:11 on 08-10-2025.




```
[13] ✓ Os
new_node = Node(data)
new_node.next = self.head
self.head = new_node

def display(self):
    """Prints the data of each node in the linked list."""
    if self.head is None:
        print("Linked list is empty.")
        return
    current = self.head
    while current:
        print(current.data, end=" -> ")
        current = current.next
    print("None")

# Example usage of the SinglyLinkedList class:
l1 = SinglyLinkedList()
l1.insert_at_end(10)
l1.insert_at_beginning(5)
l1.insert_at_end(15)
print("Linked List after insertions:")
l1.display() # Expected Output: 5 -> 10 -> 15 -> None

print("\nInserting at beginning:")
l1.insert_at_beginning(2)
l1.display() # Expected Output: 2 -> 5 -> 10 -> 15 -> None
```



```
[13] ✓ Os
l1.insert_at_beginning(5)
l1.insert_at_end(15)
print("Linked List after insertions:")
l1.display() # Expected Output: 5 -> 10 -> 15 -> None

print("\nInserting at beginning:")
l1.insert_at_beginning(2)
l1.display() # Expected Output: 2 -> 5 -> 10 -> 15 -> None

print("\nInserting at end:")
l1.insert_at_end(20)
l1.display() # Expected Output: 2 -> 5 -> 10 -> 15 -> 20 -> None

print("\nDisplaying an empty list:")
empty_l1 = SinglyLinkedList()
empty_l1.display() # Expected Output: Linked list is empty.

Linked List after insertions:
5 -> 10 -> 15 -> None

Inserting at beginning:
2 -> 5 -> 10 -> 15 -> None

Inserting at end:
2 -> 5 -> 10 -> 15 -> 20 -> None

Displaying an empty list:
Linked list is empty.
```

## Observation:

The code defines a SinglyLinkedList class with methods to insert nodes at the beginning (insert\_at\_beginning), insert at the end (insert\_at\_end), and display the list (display).

The example usage demonstrates these operations:

- Nodes with data 10, 5, and 15 are inserted, resulting in the list 5 -> 10 -> 15.

- Inserting 2 at the beginning changes the list to 2 -> 5 -> 10 -> 15.
- Inserting 20 at the end changes the list to 2 -> 5 -> 10 -> 15 -> 20.
- Displaying an empty list correctly outputs "Linked list is empty."


#### Task Description #4 – Binary Search Tree (BST)

Task: Ask AI to generate a simple BST with insert() and inorder\_traversal().

#### Prompt:

generate a python code of simple BST with insert() and inorder\_traversal().

#### Code&Output:



```


class Node:
    def __init__(self, key):
        self.left = None
        self.right = None
        self.val = key

class BST:
    def __init__(self):
        self.root = None

    def insert(self, key):
        """Inserts a new node with the given key into the BST."""
        if self.root is None:
            self.root = Node(key)
        else:
            self._insert(self.root, key)

    def _insert(self, root, key):
        if key < root.val:
            if root.left is None:
                root.left = Node(key)
            else:
                self._insert(root.left, key)
        else:
            if root.right is None:
                root.right = Node(key)

```



```
class BST:
    def __init__(self):
        self.root = None


    def insert(self, key):
        if self.root is None:
            self.root = Node(key)
        else:
            self._insert(self.root, key)

    def _insert(self, root, key):
        if root is None:
            root = Node(key)
        else:
            self._insert(root.left, key)
        return root

    def inorder_traversal(self):
        """Performs an inorder traversal of the BST and prints the node values."""
        result = []
        self._inorder_traversal(self.root, result)
        return result

    def _inorder_traversal(self, root, result):
        if root:
            self._inorder_traversal(root.left, result)
            result.append(root.val)
            self._inorder_traversal(root.right, result)

# Example usage of the BST class:
bst = BST()
bst.insert(50)
bst.insert(30)
bst.insert(20)
bst.insert(40)
bst.insert(70)
bst.insert(60)
bst.insert(80)
```



```
"""Performs an inorder traversal of the BST and prints the node values."""
result = []
self._inorder_traversal(self.root, result)
return result

def _inorder_traversal(self, root, result):
    if root:
        self._inorder_traversal(root.left, result)
        result.append(root.val)
        self._inorder_traversal(root.right, result)

# Example usage of the BST class:
bst = BST()
bst.insert(50)
bst.insert(30)
bst.insert(20)
bst.insert(40)
bst.insert(70)
bst.insert(60)
bst.insert(80)

print("Inorder traversal of the BST:")
print(bst.inorder_traversal()) # Expected Output: [20, 30, 40, 50, 60, 70, 80]
```

Inorder traversal of the BST:  
[20, 30, 40, 50, 60, 70, 80]

## Observation:

The code defines a BST class with methods to insert nodes (insert) and perform an inorder traversal (inorder\_traversal).

The example usage demonstrates inserting several values into the BST.

The `inorder_traversal()` method visits the nodes in ascending order, resulting in the output `[20, 30, 40, 50, 60, 70, 80]`, which confirms the property of a Binary Search Tree where an inorder traversal yields a sorted sequence.