

```
import zipfile
import os

zip_path = "/content/UCI_Credit_Card.csv.zip"
extract_path = "/mnt/data/credit_data"

with zipfile.ZipFile(zip_path, 'r') as zip_ref:
    zip_ref.extractall(extract_path)

os.listdir(extract_path)

['UCI_Credit_Card.csv']
```

```
import pandas as pd

df = pd.read_csv("/mnt/data/credit_data/UCI_Credit_Card.csv")
df.head()
```

	ID	LIMIT_BAL	SEX	EDUCATION	MARRIAGE	AGE	PAY_0	PAY_2	PAY_3	PAY_4	...	BILL_AMT4	BILL_AMT5	BILL_AMT6	PAY_AMT1	PAY_AMT2	PAY_AMT3	PAY_AMT4	PAY_AMT5	PAY_AMT6	
0	1	20000.0	2	2	1	24	2	2	-1	-1	...	0.0	0.0	0.0	0.0	689.0	0.0	0.0	0.0	0.0	0.0
1	2	120000.0	2	2	2	26	-1	2	0	0	...	3272.0	3455.0	3261.0	0.0	1000.0	1000.0	1000.0	0.0	2000.0	2000.0
2	3	90000.0	2	2	2	34	0	0	0	0	...	14331.0	14948.0	15549.0	1518.0	1500.0	1000.0	1000.0	1000.0	5000.0	5000.0
3	4	50000.0	2	2	1	37	0	0	0	0	...	28314.0	28959.0	29547.0	2000.0	2019.0	1200.0	1100.0	1069.0	1000.0	1000.0
4	5	50000.0	1	2	1	57	-1	0	-1	0	...	20940.0	19146.0	19131.0	2000.0	36681.0	10000.0	9000.0	689.0	679.0	679.0

5 rows × 25 columns

```
# Drop ID column
df = df.drop("ID", axis=1)

# Target variable
y = df["default.payment.next.month"]

# Features
X = df.drop("default.payment.next.month", axis=1)
```

```
from sklearn.model_selection import train_test_split

X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42
)
```

```
from sklearn.tree import DecisionTreeClassifier

dt = DecisionTreeClassifier(random_state=42)

dt.fit(X_train, y_train)
```

```
y_pred_dt = dt.predict(X_test)
y_prob_dt = dt.predict_proba(X_test)[: ,1]
```

```
from sklearn.ensemble import AdaBoostClassifier

ada = AdaBoostClassifier(random_state=42)

ada.fit(X_train, y_train)

y_pred_ada = ada.predict(X_test)
y_prob_ada = ada.predict_proba(X_test)[: ,1]
```

```
from sklearn.ensemble import RandomForestClassifier

rf_models = {}

params = [(50,5),(100,10),(200,15)]

for n, depth in params:

    rf = RandomForestClassifier(
        n_estimators=n,
        max_depth=depth,
        random_state=42
    )

    rf.fit(X_train, y_train)

    rf_models[(n,depth)] = (
        rf.predict(X_test),
        rf.predict_proba(X_test)[: ,1]
    )
```

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, roc_auc_score
```

```
results = []

results.append([
    "Decision Tree",
    accuracy_score(y_test, y_pred_dt),
    precision_score(y_test, y_pred_dt),
    recall_score(y_test, y_pred_dt),
    roc_auc_score(y_test, y_prob_dt)
])

results.append([
    "AdaBoost",
    accuracy_score(y_test, y_pred_ada),
    precision_score(y_test, y_pred_ada),
    recall_score(y_test, y_pred_ada),
    roc_auc_score(y_test, y_prob_ada)
])
```

```
for (n,depth),(pred,prob) in rf_models.items():

    results.append([
        f"RandomForest n={n}, depth={depth}",
        accuracy_score(y_test, pred),
        precision_score(y_test, pred),
        recall_score(y_test, pred),
        roc_auc_score(y_test, prob)
    ])

```

```
results_df = pd.DataFrame(
    results,
    columns=["Model", "Accuracy", "Precision", "Recall", "ROC-AUC"]
)

results_df

```

	Model	Accuracy	Precision	Recall	ROC-AUC
0	Decision Tree	0.725500	0.381054	0.407464	0.611086
1	AdaBoost	0.816667	0.677796	0.309216	0.770105
2	RandomForest n=50, depth=5	0.816667	0.690519	0.293983	0.770942
3	RandomForest n=100, depth=10	0.819333	0.663805	0.353389	0.777112
4	RandomForest n=200, depth=15	0.819500	0.659280	0.362529	0.775483

```
import matplotlib.pyplot as plt
from sklearn.metrics import roc_curve

plt.figure()

# Decision Tree
fpr, tpr, _ = roc_curve(y_test, y_prob_dt)
plt.plot(fpr, tpr, label="Decision Tree")


# AdaBoost
fpr, tpr, _ = roc_curve(y_test, y_prob_ada)
plt.plot(fpr, tpr, label="AdaBoost")

plt.plot([0,1],[0,1], '--')

plt.xlabel("False Positive Rate")
plt.ylabel("True Positive Rate")
plt.title("ROC Curve Comparison")

plt.legend()
plt.show()

```



Decision Tree, AdaBoost, and Random Forest models were trained on the credit card default dataset.

Random Forest models were tested with different estimators and max_depth values.

Models were compared using Accuracy, Precision, Recall, and ROC-AUC.

Random Forest generally performs better because it combines multiple decision trees and reduces overfitting.

The model with highest ROC-AUC and Accuracy is considered the best model.