

AI ASSISTED CODING

ASSIGNMENT – 11

NAME: R.SURYANARAYANA

HT.NO: 2403A52038

BATCH: 03

Task-1

Task: Use AI to generate a Stack class with push, pop, peek, and is_empty methods.

Sample Input Code:

```
class Stack:
```

```
    pass
```

Expected Output:

- A functional stack implementation with all required methods and docstrings

Prompt: generate a Stack class with push, pop, peek, and is_empty methods.

Code:

AI ASSISTED CODING

The screenshot shows the VS Code AI Coding interface. The Explorer pane on the left lists several files, including task(1).py through task(5).py. The main editor displays the code for task(1).py, which defines a Stack class. The class has methods: push(item), pop(), peek(), and is_empty(). The push method adds an item to the stack, pop removes and returns the top item, peek returns the top item without removing it, and is_empty checks if the stack is empty. The __init__ method initializes an empty stack. The terminal at the bottom shows the command 'Is stack empty? False' and the output 'PS C:\Users\tharu\OneDrive\Desktop\AI CODING>'. The status bar at the bottom indicates the file is task(1).py, line 17, column 46, in UTF-8 encoding, with 4 spaces and CRLF line endings. The system tray at the very bottom shows the date and time as 3:48 PM on 9/16/2025.


```
1 class Stack:
2     """
3     A class to represent a stack data structure.
4     Methods:
5     push(item): Adds an item to the top of the stack.
6     pop(): Removes and returns the top item from the stack.
7     peek(): Returns the top item of the stack without removing it.
8     is_empty(): Checks if the stack is empty.
9     """
10
11 def __init__(self):
12     """
13     Initializes an empty stack.
14     """
15     self.items = []
16
17 def push(self, item):
18     """
19     Adds an item to the top of the stack.
20     Args:
21     item: The item to be added to the stack.
22     """
23     self.items.append(item)
24
25 def pop(self):
26     """
27     Removes and returns the top item from the stack.
28     Returns:
29     The top item of the stack.
30     Raises:
31     IndexError: If the stack is empty.
32     """
33     if self.is_empty():
34         raise IndexError("Pop from an empty stack.")
35     return self.items.pop()
36
37 def peek(self):
38     """
39     Returns the top item of the stack without removing it.
40     Returns:
41     The top item of the stack.
42     Raises:
43     IndexError: If the stack is empty.
44     """
45     if self.is_empty():
46         raise IndexError("Peek from an empty stack.")
47     return self.items[-1]
48
49 def is_empty(self):
50     """
51     Checks if the stack is empty.
52     Returns:
53     bool: True if the stack is empty, False otherwise.
54     """
55     return len(self.items) == 0
56
57 # Test the Stack class
58 if __name__ == "__main__":
59     stack = Stack()
60     print("Is stack empty?", stack.is_empty()) # Expected: True
61     stack.push(10)
62     stack.push(20)
63     stack.push(30)
64     print("Top of the stack:", stack.peek()) # Expected: 30
65     print("Popped item:", stack.pop()) # Expected: 30
66     print("Top of the stack after pop:", stack.peek()) # Expected: 20
67     print("Is stack empty?", stack.is_empty()) # Expected: False
```

This screenshot shows the same VS Code AI Coding interface as the first one, but with the completed implementation of the Stack class. The code now includes a test section at the bottom, which creates a Stack object, pushes three items (10, 20, 30), and tests the push, pop, peek, and is_empty methods. The terminal output shows the results of these tests, confirming that the stack is empty initially, the top item is 30, the top item is 20 after popping 30, and the stack is not empty after pushing 10, 20, and 30. The status bar at the bottom indicates the file is task(1).py, line 64, column 66, in UTF-8 encoding, with 4 spaces and CRLF line endings. The system tray at the very bottom shows the date and time as 3:48 PM on 9/16/2025.

```
1 class Stack:
2     """
3     A class to represent a stack data structure.
4     Methods:
5     push(item): Adds an item to the top of the stack.
6     pop(): Removes and returns the top item from the stack.
7     peek(): Returns the top item of the stack without removing it.
8     is_empty(): Checks if the stack is empty.
9     """
10
11 def __init__(self):
12     """
13     Initializes an empty stack.
14     """
15     self.items = []
16
17 def push(self, item):
18     """
19     Adds an item to the top of the stack.
20     Args:
21     item: The item to be added to the stack.
22     """
23     self.items.append(item)
24
25 def pop(self):
26     """
27     Removes and returns the top item from the stack.
28     Returns:
29     The top item of the stack.
30     Raises:
31     IndexError: If the stack is empty.
32     """
33     if self.is_empty():
34         raise IndexError("Pop from an empty stack.")
35     return self.items.pop()
36
37 def peek(self):
38     """
39     Returns the top item of the stack without removing it.
40     Returns:
41     The top item of the stack.
42     Raises:
43     IndexError: If the stack is empty.
44     """
45     if self.is_empty():
46         raise IndexError("Peek from an empty stack.")
47     return self.items[-1]
48
49 def is_empty(self):
50     """
51     Checks if the stack is empty.
52     Returns:
53     bool: True if the stack is empty, False otherwise.
54     """
55     return len(self.items) == 0
56
57 # Test the Stack class
58 if __name__ == "__main__":
59     stack = Stack()
60     print("Is stack empty?", stack.is_empty()) # Expected: True
61     stack.push(10)
62     stack.push(20)
63     stack.push(30)
64     print("Top of the stack:", stack.peek()) # Expected: 30
65     print("Popped item:", stack.pop()) # Expected: 30
66     print("Top of the stack after pop:", stack.peek()) # Expected: 20
67     print("Is stack empty?", stack.is_empty()) # Expected: False
```

OP:

AI ASSISTED CODING



Observation:

This program works like a collection where things are arranged one on top of another. At the beginning, the collection is empty. Whenever something new is added, it goes on the top, and if something needs to be removed, the latest one added comes out first. It also allows me to just see what is on top without removing it. There is even a way to check if the collection has nothing inside.

Task-2

Task: Use AI to implement a Queue using Python lists.

Sample Input Code:

```
class Queue:
```

```
pass
```


Expected Output:

- FIFO-based queue class with enqueue, dequeue, peek, and size methods

Prompt: implement a Queue using Python lists.


Code:

AI ASSISTED CODING



OP:

AI ASSISTED CODING



```
... 'C:\Users\tharu\OneDrive\Desktop\AI CODING\11_lab\task(2).py'
Is queue empty? True
Queue size: 3
Front of the queue: 10
Dequeued item: 10
Front of the queue after dequeue: 20
Queue size after dequeue: 2
Is queue empty? False
PS C:\Users\tharu\OneDrive\Desktop\AI CODING>
```

Observation:

This program works like a line where people stand one after another. In the beginning, the line is empty. Whenever something new comes, it joins at the end of the line, and when something leaves, it is always the first one that came in. You can also just look at who is at the front without removing them. There's a way to count how many are currently in the line, and also to check if the line is completely empty.

Task-3:

Task: Use AI to generate a Singly Linked List with insert and display methods.

Sample Input Code:

```
class Node:
    pass

class LinkedList:
    pass
```


Expected Output:

- A working linked list implementation with clear method documentation

Prompt: generate a Singly Linked List with insert and display methods. A working linked list implementation with clear method documentation

AI ASSISTED CODING

Code:




```
1 class Node:
2     """
3     A class to represent a node in a singly linked list.
4     Attributes:
5         data: The data stored in the node.
6         next: A reference to the next node in the linked list.
7     """
8     def __init__(self, data):
9         """
10        Initializes a new node with the given data.
11
12        Args:
13            data: The data to store in the node.
14        """
15        self.data = data
16        self.next = None
17
18 class LinkedList:
19     """
20     A class to represent a singly linked list.
21     Methods:
22         insert(data): Inserts a new node with the given data at the end of the list.
23         display(): Displays all the elements in the linked list.
24     """
25     def __init__(self):
26         """
27        Initializes an empty linked list.
28
29        """
30        self.head = None
31
32     def insert(self, data):
33         """
34        Inserts a new node with the given data at the end of the linked list.
35
36        Args:
37            data: The data to insert into the linked list.
38        """
39        new_node = Node(data)
40        if self.head is None:
41            self.head = new_node
```

class LinkedList:
pass
Expected Output:
• A working linked list
implementation with clear
method
documentation

Here's the implementation of a Singly
Linked List with `insert` and
`display` methods, along with
Google-style docstrings:

```
class Node:
    """
    A class to represent a
    ...
    Attributes:
        data: The data sto
        next: A reference
    ...
    def __init__(self, dat
    """
    Initializes a new
    ...
    Args:
        data: The data
    ...
    self.data = data
```

Add Context... task(3.py) +
Add context (#), extensions (@), cor
Ask v GPT-4o v ▶



```
17 class LinkedList:
18     def insert(self, data):
19         """
20         Inserts a new node with the given data at the end of the linked list.
21
22         Args:
23             data: The data to insert into the linked list.
24         """
25         new_node = Node(data)
26         if self.head is None:
27             self.head = new_node
28         else:
29             current = self.head
30             while current.next:
31                 current = current.next
32             current.next = new_node
33
34     def display(self):
35         """
36         Displays all the elements in the linked list.
37         Returns:
38             None
39         """
40         if self.head is None:
41             print("The linked list is empty.")
42         else:
43             current = self.head
44             while current:
45                 print(current.data, end=" -> ")
46                 current = current.next
47             print("None")
48
49 # Test the LinkedList class
50 if __name__ == "__main__":
51     linked_list = LinkedList()
52     linked_list.insert(10)
53     linked_list.insert(20)
54     linked_list.insert(30)
55     print("Elements in the linked list:")
56     linked_list.display()
```

class LinkedList:
pass
Expected Output:
• A working linked list
implementation with clear
method
documentation


Here's the implementation of a Singly
Linked List with `insert` and
`display` methods, along with
Google-style docstrings:

```
class Node:
    """
    A class to represent a
    ...
    Attributes:
        data: The data sto
        next: A reference
    ...
    def __init__(self, dat
    """
    Initializes a new
    ...
    Args:
        data: The data
    ...
    self.data = data
```

Add Context... task(3.py) +
Add context (#), extensions (@), cor
Ask v GPT-4o v ▶

OP:

AI ASSISTED CODING



Observation:

This program works like a line where people stand one after another. In the beginning, the line is empty. Whenever something new comes, it joins at the end of the line, and when something leaves, it is always the first one that came in. You can also just look at who is at the front without removing them. There's a way to count how many are currently in the line, and also to check if the line is completely empty.

Task-4:

Task: Use AI to create a BST with insert and in-order traversal methods.

Sample Input Code:

```
class BST:
```

```
pass
```



Expected Output:

- BST implementation with recursive insert and traversal method

Prompt: create a BST with insert and in-order traversal methods.


Code:

AI ASSISTED CODING



OP:

AI ASSISTED CODING



Observation:

This program is about creating and organizing a tree-like structure where each piece of data is stored in special boxes called nodes. Every node has a value, along with links that can connect to smaller nodes on the left and larger nodes on the right. When a new value is added, it is placed in the proper position by comparing it with existing values until it finds its correct spot. There is also a way to go through the tree in order, which means visiting the left side first, then the main value, and finally the right side, so all the values come out sorted.

Task-5:

Task: Use AI to implement a hash table with basic insert, search, and delete

methods.

Sample Input Code:

```
class HashTable:
```

```
pass
```

Expected Output:

- Collision handling using chaining, with well-commented methods

Prompt: implement a hash table with basic insert, search, and delete.

Collision handling using chaining, with well-commented methods

AI ASSISTED CODING

Code:


The screenshot shows the VS Code editor with the 'task(5).py' file open. The code defines a `HashTable` class with methods `__init__`, `_hash`, and `insert`. The `insert` method uses chaining for collision handling. The right-hand 'CHAT' panel displays an AI-generated explanation of the code, stating: 'Here's the implementation of a HashTable class with insert, search, and delete methods, using chaining for collision handling. The code includes detailed comments for clarity.'

```
class HashTable:
    """
    A class to represent a hash table with basic insert, search, and delete methods.
    Collision handling is implemented using chaining (linked lists).
    """
    def __init__(self, size=10):
        """
        Initializes the hash table with a given size.
        Args:
            size (int): The size of the hash table (number of buckets). Default is 10.
        """
        self.size = size
        self.table = [[] for _ in range(size)] # Create a list of empty lists (buckets)
    def _hash(self, key):
        """
        Generates a hash value for a given key.
        Args:
            key (str): The key to hash.
        Returns:
            int: The index of the bucket for the given key.
        """
        return hash(key) % self.size
    def insert(self, key, value):
        """
        Inserts a key-value pair into the hash table.
        Args:
            key (str): The key to insert.
            value: The value associated with the key.
        """
        index = self._hash(key) # Get the bucket index
        bucket = self.table[index]
        # Check if the key already exists in the bucket
        for pair in bucket:
            if pair[0] == key:
                pair[1] = value # Update the value if the key exists
                return
        # If the key does not exist, append the new key-value pair
        bucket.append((key, value))
```


This screenshot shows the same VS Code editor with the `HashTable` class extended. The `search`, `delete`, and `display` methods have been added. The `search` method returns the value for a given key or `None`. The `delete` method removes a key-value pair and returns a boolean. The `display` method is a placeholder for displaying the table's contents. The 'CHAT' panel on the right remains the same as in the first screenshot.

```
class HashTable:
    """
    A class to represent a hash table with basic insert, search, and delete methods.
    Collision handling is implemented using chaining (linked lists).
    """
    def __init__(self, size=10):
        """
        Initializes the hash table with a given size.
        Args:
            size (int): The size of the hash table (number of buckets). Default is 10.
        """
        self.size = size
        self.table = [[] for _ in range(size)] # Create a list of empty lists (buckets)
    def _hash(self, key):
        """
        Generates a hash value for a given key.
        Args:
            key (str): The key to hash.
        Returns:
            int: The index of the bucket for the given key.
        """
        return hash(key) % self.size
    def insert(self, key, value):
        """
        Inserts a key-value pair into the hash table.
        Args:
            key (str): The key to insert.
            value: The value associated with the key.
        """
        index = self._hash(key) # Get the bucket index
        bucket = self.table[index]
        # Check if the key already exists in the bucket
        for pair in bucket:
            if pair[0] == key:
                pair[1] = value # Update the value if the key exists
                return
        # If the key does not exist, append the new key-value pair
        bucket.append((key, value))
    def search(self, key):
        """
        Searches for a key in the hash table and returns its value.
        Args:
            key (str): The key to search for.
        Returns:
            The value associated with the key, or None if the key is not found.
        """
        index = self._hash(key) # Get the bucket index
        bucket = self.table[index]
        # Search for the key in the bucket
        for pair in bucket:
            if pair[0] == key:
                return pair[1] # Return the value if the key is found
        return None # Return None if the key is not found
    def delete(self, key):
        """
        Deletes a key-value pair from the hash table.
        Args:
            key (str): The key to delete.
        Returns:
            bool: True if the key was deleted, False if the key was not found.
        """
        index = self._hash(key) # Get the bucket index
        bucket = self.table[index]
        # Search for the key in the bucket
        for pair in bucket:
            if pair[0] == key:
                bucket.remove(pair) # Remove the key-value pair
                return True
        return False # Return False if the key was not found
    def display(self):
        """
        Displays the contents of the hash table.
        """
```

AI ASSISTED CODING



OP:



Observation:

AI ASSISTED CODING

This program is about storing data in a special table where each piece of information is placed in a specific spot calculated from its key.

Sometimes, more than one key can end up in the same spot, and in that case, they are simply kept together in a small list at that position. When adding something new, if the key already exists, its value gets updated; if not, the new pair is added. To look up information, it searches the correct spot and returns the value if the key is found, or nothing if it isn't. You can also remove a key from the table, and there's a way to display everything stored inside.

Task 6:

Use AI to implement a graph using an adjacency list.

Sample Input Code:

```
class Graph:  
    pass
```



Expected Output:

- Graph with methods to add vertices, add edges, and display connections

Prompt: implement a graph using an adjacency list.


Code:

AI ASSISTED CODING



OP:

AI ASSISTED CODING



Observation:

This setup treats a network like a map where each point keeps a small list of its neighboring points it directly connects to. New points can be added by creating an empty spot for their connections, and links between two points are recorded on both sides so each knows about the other. If a link is requested between points that don't exist, it's considered a mistake and the process is stopped with an error message. There's also a simple way to go through every point and show which other points it's connected to, making the whole map easy to read.

Task 7:

ask: Use AI to implement a priority queue using Python's `heapq` module.

Sample Input Code:

```
class PriorityQueue:
```

```
pass
```

AI ASSISTED CODING

Expected Output:

- Implementation with enqueue (priority), dequeue (highest priority), and display methods

Prompt:

Code:

OP:

Observation:

Task 8:

Use AI to implement a double-ended queue using collections.deque.

Sample Input Code:

```
class DequeDS:
```

```
pass
```

Expected Output:

- Insert and remove from both ends with docstrings.

Prompt:

Code:

OP:

Observation:

Task 9:

Task: Use AI to generate a comparison table of different data structures (stack, queue, linked list, etc.) including time complexities.

Sample Input Code:

```
# No code, prompt AI for a data structure comparison table
```


AI ASSISTED CODING

Expected Output:

- A markdown table with structure names, operations, and complexities

Prompt:

Code:

OP:

Observation:

Task 10

Your college wants to develop a Campus Resource Management System that

handles:

1. Student Attendance Tracking – Daily log of students entering/exiting the campus.
2. Event Registration System – Manage participants in events with quick search and removal.
3. Library Book Borrowing – Keep track of available books and their due dates.
4. Bus Scheduling System – Maintain bus routes and stop connections.
5. Cafeteria Order Queue – Serve students in the order they arrive.

Student Task:

- For each feature, select the most appropriate data structure from the list

below:

- o Stack
- o Queue
- o Priority Queue
- o Linked List

AI ASSISTED CODING

- o Binary Search Tree (BST)
- o Graph
- o Hash Table
- o Deque
- Justify your choice in 2–3 sentences per feature.
- Implement one selected feature as a working Python program with AI-assisted code generation.

Expected Output:

- A table mapping feature → chosen data structure → justification.
- A functional Python program implementing the chosen feature with comments and docstrings.

Prompt:

Code:

OP:

Observation: