

# AI ASSISTED CODING

**Program** :B.tech(CSE)  
**Name** :ANANTHA MANIDEEP  
**En No.** :2403A52078  
**Batch No.** :02

## LAB ASSIGNMENT-02

---


### Task Description -1:

Use Gemini and Colab to write a function that filters out all negative numbers from a give list.

### PROMPT:

Write a python code for a function, out of all negative numbers from the list.

### Question:




### Code:



The screenshot shows a Google Colab notebook interface. The browser address bar displays the URL: `colab.research.google.com/drive/1OLayK_n1QshnywiiXd0OrBrscL3wa1Mq`. The notebook is titled "Untitled1.ipynb". The code editor contains the following Python code:

```
[ ] def filter_negative_numbers(input_list):  
    """  
    Filters out negative numbers from a list.  
  
    Args:  
        input_list: A list of numbers.  
  
    Returns:  
        A new list containing only the non-negative numbers from the input list.  
    """  
    return [number for number in input_list if number >= 0]  
  
# Example usage:  
my_list = [1, -2, 3, -4, 5, -6, 0]  
filtered_list = filter_negative_numbers(my_list)  
print(filtered_list)
```

Output:



The screenshot shows a Google Colab notebook interface. The code editor contains the following Python code:

```
[2] def remove_negative_numbers(numbers):  
    """  
    Removes negative numbers from a list.  
  
    Args:  
        numbers: A list of numbers.  
  
    Returns:  
        A new list containing only the non-negative numbers from the input list.  
    """  
    non_negative_numbers = [num for num in numbers if num >= 0]  
    return non_negative_numbers  
  
# Example usage:  
my_list = [1, -2, 3, -4, 5, -6]  
non_negative_list = remove_negative_numbers(my_list)  
print(non_negative_list)
```

Below the code editor, the output of the code is displayed:

```
[1, 3, 5]
```

## TASK Description-2:

Ask Gemini to generate code that reads a text file and counts the frequency of each word. Then ask it to explain the code.

### Prompt-2:

Write a python code that reads a text file and count the frequency of each word and explain the code.

### Question-2:

Write a python code for that reads a text file and count the frequency of each word and explain the code

Happy to help! I can generate Python code to read a text file, count the frequency of each word, and then explain how the code works.

Here is a plan to accomplish this:

- **Generate code to read the text file:** Create a code cell that reads the content of a specified text file.
- **Generate code to count word frequencies:** Create a code cell that processes the text from the file, counts the occurrences of each word, and stores the frequencies (e.g., in a dictionary).
- **Generate code to display word frequencies:** Create

► What can I help you build?



### Code:

File Edit View Insert Help

Commands + Code + Text ▶ Run all ▼

↑ ↓ ↻ 🔗 🗨 ⚙ 📄 🗑 ⋮

Task

Write a python code that reads a text file and count the frequency of each word and explain the code.

Generate code to read the text file

Subtask:

Create a code cell that reads the content of a specified text file.

**Reasoning:** The subtask is to read the content of a text file. I will create a code cell to open, read, and close the file.

```
[6] file_path = 'example.txt'
    try:
        with open(file_path, 'r') as file:
            file_content = file.read()
```

🔍 Commands + Code + Text ▶ Run all ▼

☰ 📄 > ⚙ 📄 🗑 ⋮

```
[7] file_path = 'example.txt'
    file_content_to_write = "This is an example text file.\nIt contains some sample content fo

    try:
        with open(file_path, 'w') as file:
            file.write(file_content_to_write)
            print(f"File '{file_path}' created successfully.")
    except Exception as e:
        print(f"An error occurred while creating the file: {e}")
```

🔄 File 'example.txt' created successfully.

**Reasoning:** I have now created the text file. I will attempt to read its content again using the same code as before.

```
[8] file_path = 'example.txt'
    try:
        with open(file_path, 'r') as file:
            file_content = file.read()
```



0s



```
[8] file_path = 'example.txt'
    try:
        with open(file_path, 'r') as file:
            file_content = file.read()
            print(file_content)
    except FileNotFoundError:
        print(f"Error: The file '{file_path}' was not found.")
    except Exception as e:
        print(f"An error occurred: {e}")
```

↗ This is an example text file.  
It contains some sample content for testing.

## ▼ Generate code to count word frequencies

### Subtask:

Create a code cell that processes the text from the file, counts the occurrences of each word, and stores the frequencies (e.g., in a dictionary).



**Reasoning:** Process the text from the file, count word occurrences, and store frequencies using Counter.

```
[9] import re
    from collections import Counter

    lowercase_content = file_content.lower()
    words = re.findall(r'\b\w+\b', lowercase_content)
    word_frequencies = Counter(words)

    print(word_frequencies)

Counter({'this': 1, 'is': 1, 'an': 1, 'example': 1, 'text': 1, 'file': 1, 'it': 1, 'contain'
```

## Generate code to display word frequencies

Subtask:

Create a code cell to display the calculated word frequencies in a readable format.



## Generate code to display word frequencies

Subtask:




Create a code cell to display the calculated word frequencies in a readable format.

**Reasoning:** Iterate through the word frequencies and print them in a readable format. Sorting by frequency will make it easier to see the most common words.

```
[10] # Sort the word frequencies by count in descending order
    sorted_word_frequencies = sorted(word_frequencies.items(), key=lambda item: item[1], reverse=True)






    # Display the sorted word frequencies
    print("Word Frequencies:")
    for word, count in sorted_word_frequencies:
        print(f"{word}: {count}")


Word Frequencies:
this: 1
is: 1
```

 Untitled1.ipynb  

File Edit View Insert Runtime Tools Help

Q Commands + Code + Text ▶ Run all ▼





```
an: 1
example: 1
text: 1
file: 1
it: 1
contains: 1
some: 1
sample: 1
content: 1
for: 1
testing: 1
```


▼ Explain the generated code

Subtask:

Provide a natural language explanation of the code generated in the previous steps.

**Reasoning:** Provide a natural language explanation of the code generated in the previous steps, covering how the file is read, how word frequencies are counted using regular expressions and Counter, and how the results are sorted and displayed.





Untitled1.ipynb


File Edit View Insert Runtime Tools Help

Commands + Code + Text Run all

```
[11] # Explanation of the code:

# Step 1: Reading the Text File
# The first code cell is responsible for reading the content of the text file.
# It specifies the file path as 'example.txt'.
# It uses a 'try...except' block to handle potential errors during file operations.
# The 'with open(file_path, 'r') as file:' statement opens the file in read mode ('r').
# The 'with' statement ensures that the file is automatically closed even if errors occur.
# file.read() reads the entire content of the file into the 'file_content' variable.
# The content is then printed to the console.
# If the file is not found, a FileNotFoundError is caught, and an informative error message is printed.
# A general Exception is also caught to handle any other potential errors during file reading.

# Step 2: Counting Word Frequencies
# The second code cell processes the text to count the frequency of each word.
# It imports the 're' module for regular expressions and the 'Counter' class from the 'collections' module.
# file_content is converted to lowercase using .lower() to ensure that words like "The" and "the" are counted together.
# re.findall(r'\b\w+\b', lowercase_content) uses a regular expression to find all words in the text.
# The resulting list of words is passed to Counter(words), which creates a dictionary-like object to count the frequency of each word.
# The word_frequencies Counter object is then printed, showing the word counts.
```



Commands + Code + Text Run all

```
[11] # The word_frequencies Counter object is then printed, showing the word counts.

# Step 3: Displaying Word Frequencies
# The third code cell displays the calculated word frequencies in a readable format.
# It first sorts the word frequencies using the sorted() function.
# word_frequencies.items() returns a list of (word, count) tuples.
# key=lambda item: item[1] specifies that the sorting should be based on the second element (count).
# reverse=True sorts the results in descending order, so the most frequent words appear first.
# The code then prints a header "Word Frequencies:".
# It iterates through the sorted_word_frequencies list.
# For each (word, count) tuple, it prints the word and its count in the format "word: count".
```

### Task Description-3:

Use Cursor AI to generate a python class called book with attributes title, author, and a method Summery() that prints the details.

### Prompt-3:

Give me a code for python class Book with attributes title, author and a method summery() that prints the details

### QUESTION:



Untitled1.ipynb ☆ ☁

File Edit View Insert Runtime Tools Help

Commands + Code + Text ▶ Run all ▼

RAM — Disk —

Gemini ✕

Give a me code for python class called Book with attrit title, author and a method summy () that prints the d

Working...

What can I help you build?

CODE:

Untitled1.ipynb ☆ ☁

File Edit View Insert Runtime Tools Help

Commands + Code + Text ▶ Run all ▼

```
[19] class Book:
    """
    Represents a book with a title and author.
    """
    def __init__(self, title, author):
        """
        Initializes a new Book instance.

        Args:
            title: The title of the book.
            author: The author of the book.
        """
        self.title = title
        self.author = author

    def summary(self):
        """
        Prints the summary details of the book.
        """
        print(f"Title: {self.title}")
        print(f"Author: {self.author}")
```



The screenshot shows a Jupyter Notebook window titled "Untitled1.ipynb". The menu bar includes File, Edit, View, Insert, Runtime, Tools, and Help. Below the menu bar are tabs for "Commands", "+ Code", "+ Text", and "Run all". The code cell [19] contains the following Python code:

```
# Example usage:  
my_book = Book("The Hitchhiker's Guide to the Galaxy", "Douglas Adams")  
my_book.summary()
```

The output of the code cell is:

```
Title: The Hitchhiker's Guide to the Galaxy  
Author: Douglas Adams
```


#### Task Description-4 :

Ask Gemini to write a program that checks whether Number is an Armstrong number ,and then modify using cursor Ai to improve performance or structure.

#### Prompt-4:

Write a python to check whether the given number is Armstrong Number, and improve the Structure.

#### QUESTION:




The screenshot shows a Gemini chat interface. At the top, there is a status bar with a green checkmark, RAM usage, and Disk usage. Below this is a search bar with the text " Gemini X". The main chat area contains a prompt and a response.

**Prompt:** Write a python program ton check whether the given number is Armstrong Number, and improve the structure

**Response:** Okay, I can help you with that. Here is a Python program tha includes a function to check if a number is an Armstrong number, with improved structure and comments.


At the bottom of the chat area, there are icons for a thumbs up and a thumbs down. Below the chat area, there are three buttons: "Accept & Run", "Accept", and "Cancel".

## CODE:



The screenshot shows a Jupyter Notebook titled 'Untitled1.ipynb'. The interface includes a top bar with 'File', 'Edit', 'View', 'Insert', 'Runtime', 'Tools', and 'Help' menus. Below the menu bar is a toolbar with 'Commands', '+ Code', '+ Text', and 'Run all' buttons. The left sidebar contains icons for file management and a 'Gemini' tab. The main code area contains the following Python code:


```
[ ] def is_armstrong_number(number):  
    """  
    Checks if a given number is an Armstrong number.  
  
    An Armstrong number (or narcissistic number) is a number that is the sum  
    of its own digits each raised to the power of the number of digits.  
  
    Args:  
        number: An integer.  
  
    Returns:  
        True if the number is an Armstrong number, False otherwise.  
    """  
    # Convert the number to a string to easily access its digits  
    num_str = str(number)  
    # Get the number of digits  
    num_digits = len(num_str)  
    # Initialize the sum of the powers of the digits  
    armstrong_sum = 0  
  
    # Iterate through each digit in the number string  
    for digit in num_str:
```



The screenshot shows the same Jupyter Notebook interface, but with the completion of the function and example usage. The code continues from the previous block:

```
        for digit in num_str:  
            # Convert the digit back to an integer and raise it to the power of the number of digits  
            armstrong_sum += int(digit) ** num_digits  
  
    # Check if the calculated sum is equal to the original number  
    return armstrong_sum == number  
  
# Example usage:  
num_to_check = 153  
if is_armstrong_number(num_to_check):  
    print(f"{num_to_check} is an Armstrong number.")  
else:  
    print(f"{num_to_check} is not an Armstrong number.")  
  
num_to_check = 123  
if is_armstrong_number(num_to_check):  
    print(f"{num_to_check} is an Armstrong number.")  
else:  
    print(f"{num_to_check} is not an Armstrong number.")
```

## OUTPUT:



The screenshot shows a Jupyter Notebook window titled 'Untitled1.ipynb'. The interface includes a menu bar (File, Edit, View, Insert, Runtime, Tools, Help) and a toolbar with 'Commands', '+ Code', '+ Text', and 'Run all'. The code cell contains the following Python code:

```
[20] # Example usage:
num_to_check = 153
if is_armstrong_number(num_to_check):
    print(f"{num_to_check} is an Armstrong number.")
else:
    print(f"{num_to_check} is not an Armstrong number.")

num_to_check = 123
if is_armstrong_number(num_to_check):
    print(f"{num_to_check} is an Armstrong number.")
else:
    print(f"{num_to_check} is not an Armstrong number.")
```

The output of the code is displayed below the cell:

```
153 is an Armstrong number.
123 is not an Armstrong number.
```

Summary:




Here's a summary of the key parts and structure:

- **Function Definition:** I defined a function `is_armstrong_number(number)` that takes an integer `number` as input.
- **Docstring:** I included a clear docstring within triple quotes ( `"""..."""` ) to explain what the function does, its arguments, and what it returns. This improves readability and helps others (or your future self) understand the code.
- **Conversion to String:** Inside the function, I convert the input `number` to a string ( `num_str` ) to easily access each digit.
- **Getting Number of Digits:** I calculate the number of digits using `len(num_str)` .

- **Calculating Armstrong Sum:** I iterate through each `digit` in the `num_str`. For each digit, I convert it back to an integer ( `int(digit)` ) and raise it to the power of the total number of digits ( `num_digits` ). This result is added to `armstrong_sum`.
- **Checking the Condition:** Finally, I compare the calculated `armstrong_sum` with the original `number`. If they are equal, the function returns `True` (indicating it's an Armstrong number); otherwise, it returns `False`.
- **Example Usage:** Below the function definition, I included example calls to the function with different numbers ( `153` and `123` ) and printed whether each number is an Armstrong number or not. This demonstrates how to use the function and shows the

#### Task Description-6:

 Use both Gemini and Cursor AI to generate code for sorting a list of dictionaries by a specific key (e.g., age).

#### Prompt-6:

Write a Python code for sorting a list of dictionaries by a specific key example:age.

#### QUESTION:

Write a python code for sorting a list of dictionaries by a specific key example:age

Okay, I can provide you with Python code to sort a list of dictionaries by a specific key.

Here's an example using a list of dictionaries representing people, which will be sorted by their 'age':



#### CODE:



Untitled1.ipynb ☆ ☁

File Edit View Insert Runtime Tools Help

Commands + Code + Text ▶ Run all ▼



```
[ ] # Example list of dictionaries
people = [
    {'name': 'Alice', 'age': 30, 'city': 'New York'},
    {'name': 'Bob', 'age': 22, 'city': 'London'},
    {'name': 'Charlie', 'age': 35, 'city': 'Paris'},
    {'name': 'David', 'age': 22, 'city': 'Tokyo'},
]

# Sort the list of dictionaries by the 'age' key
# We use a lambda function as the 'key' to specify that we want to sort based on the 'age'
sorted_people = sorted(people, key=lambda person: person['age'])

# Print the sorted list
print("Sorted by age:")
print(sorted_people)

# You can also sort by other keys, for example, by 'name':
sorted_people_by_name = sorted(people, key=lambda person: person['name'])
print("\nSorted by name:")
print(sorted_people_by_name)
```

**OUTPUT:**



```
# You can also sort by other keys, for example, by 'name':
sorted_people_by_name = sorted(people, key=lambda person: person['name'])
print("\nSorted by name:")
print(sorted_people_by_name)
```

Sorted by age:

```
[{'name': 'Bob', 'age': 22, 'city': 'London'}, {'name': 'David', 'age': 22, 'city': 'Tokyo'}, {'name': 'Charlie', 'age': 35, 'city': 'Paris'}, {'name': 'Alice', 'age': 30, 'city': 'New York'}]
```

Sorted by name:

```
[{'name': 'Alice', 'age': 30, 'city': 'New York'}, {'name': 'Bob', 'age': 22, 'city': 'London'}, {'name': 'Charlie', 'age': 35, 'city': 'Paris'}, {'name': 'David', 'age': 22, 'city': 'Tokyo'}]
```

```
# You can also sort by other keys, for example, by 'name':
sorted_people_by_name = sorted(people, key=lambda person: person['name'])
print("\nSorted by name:")
print(sorted_people_by_name)
```

```
[{'name': 'Alice', 'age': 30, 'city': 'New York'}, {'name': 'Charlie', 'age': 35, 'city': 'Paris'}, {'name': 'David', 'age': 22, 'city': 'Tokyo'}, {'name': 'Bob', 'age': 22, 'city': 'London'}]
```

```
[{'name': 'Alice', 'age': 30, 'city': 'New York'}, {'name': 'Charlie', 'age': 35, 'city': 'Paris'}, {'name': 'David', 'age': 22, 'city': 'Tokyo'}, {'name': 'Bob', 'age': 22, 'city': 'London'}]
```

```
ample, by 'name':
y=lambda person: person['name'])
```

```
[{'name': 'Charlie', 'age': 35, 'city': 'Paris'}]
```

```
[{'name': 'David', 'age': 22, 'city': 'Tokyo'}]
```

---END---