

# AI ASSISTED CODING

**Program** :B.tech(CSE)

**Name of Student** :ANANTHA MANIDEEP

**Enrollment No.** :2403A52078

**Batch No.** :02

---

## LAB ASSIGNMENT-20

---

### TASK DESCRIPTION-1:

#### **Input Validation Check**

##### **Task:**

Analyze an AI-generated **Python login script** for input validation vulnerabilities.

##### **Instructions:**

- Prompt AI to generate a simple username-password login program.
- Review whether input sanitization and validation are implemented.

Suggest secure improvements (e.g., using re for input validation).

#### **PROMPT:**

Generate a simple Python program for a username-password login system. After generating it, analyze whether the program includes proper input validation and sanitization. Identify any vulnerabilities and explain how to fix them. Also suggest secure improvements, including using Python's re module for validating inputs.

#### **CODE:**

```
# simple_login.py

# Simple username/password CLI demo with basic validation and
salted+hashed passwords.

# For demonstration only — see analysis below for security
considerations and improvements.

import json
import os
import re
import secrets
import hashlib
import hmac
from getpass import getpass

USERS_FILE = "users.json"

PBKDF2_ITERATIONS = 200_000 # increase for better security on
modern machines

USERNAME_RE = re.compile(r"^[A-Za-z0-9._-]{3,20}$")

PASSWORD_RE = re.compile(r"^(?=.{8,})(?=.*\d)(?=.*[a-z])(?=.*[A-Z])(?=.*\W).*\$")
```

```
def load_users():

    if not os.path.exists(USERS_FILE):

        return {}

    with open(USERS_FILE, "r", encoding="utf-8") as f:

        return json.load(f)

def save_users(users):

    with open(USERS_FILE, "w", encoding="utf-8") as f:

        json.dump(users, f, indent=2)

def validate_username(username):

    username = username.strip()

    if not USERNAME_RE.match(username):

        return False, "Username must be 3-20 chars: letters, digits, dot,
underscore or hyphen."

    return True, ""

def validate_password(password):

    if not PASSWORD_RE.match(password):
```

```
    return False, "Password must be at least 8 chars and include upper,  
lower, digit, and symbol."  
  
return True, ""
```

```
def hash_password(password, salt=None):  
  
    if salt is None:  
  
        salt = secrets.token_hex(16) # 32 hex chars = 16 bytes  
  
    salt_bytes = bytes.fromhex(salt)  
  
    dk = hashlib.pbkdf2_hmac("sha256", password.encode("utf-8"),  
salt_bytes, PBKDF2_ITERATIONS)  
  
    return salt, dk.hex()
```

```
def verify_password(stored_salt, stored_hash, password_attempt):  
  
    _, attempt_hash = hash_password(password_attempt,  
salt=stored_salt)  
  
    # Use constant-time comparison  
  
    return hmac.compare_digest(stored_hash, attempt_hash)
```

```
def register_user(users):  
  
    username = input("Choose username: ").strip()  
  
    ok, msg = validate_username(username)
```



```
    print("Invalid username or password.")

    return

record = users[username]

if verify_password(record["salt"], record["hash"], password):
    print("Login successful.")

else:
    print("Invalid username or password.")

def main():

    users = load_users()

    while True:

        print("\n1) Register\n2) Login\n3) Quit")

        choice = input("Choose: ").strip()

        if choice == "1":

            register_user(users)

        elif choice == "2":

            login_user(users)

        elif choice == "3":

            break

    else:
```

```
print("Invalid option.")

if __name__ == "__main__":
    main()
```

## OUTPUT:

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS AZURE POSTMAN CONSOLE ...
Python Debug Console + ⌂ ⌂ ... [x]

PS C:\Users\deeks\OneDrive\Desktop\Web> & 'C:\Users\deeks\AppData\Local\Microsoft\WindowsApps\python3.12.exe' 'c:\Users\deeks\.vscode\extensions\ms-python.debugpy-2025.16.0-win32-x64\bundled\libs\debugpy\launcher' '53356' '--' 'c:\Users\deeks\OneDrive\Desktop\Web\AIAC.py'
\x5cdeeks\x5cOneDrive\x5cDesktop\x5cWeb\x5cAIAC.py' ;60d95a16-d8b5-4a4d-9c37-c4be7f12d820
1) Register
2) Login
3) Quit
Choose: 1
Choose username: deekshu_123
Invalid username: Username must be 3-20 chars: letters, digits, underscore or hyphen.

1) Register
2) Login
3) Quit
Choose: 1
Choose username: deekshu_123
Choose password:
User registered.

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS AZURE POSTMAN CONSOLE ...
Python Debug Console + ⌂ ⌂ ... [x]

PS C:\Users\deeks\OneDrive\Desktop\Web> & 'C:\Users\deeks\AppData\Local\Microsoft\WindowsApps\python3.12.exe' 'c:\Users\deeks\.vscode\extensions\ms-python.debugpy-2025.16.0-win32-x64\bundled\libs\debugpy\launcher' '53356' '--' 'c:\Users\deeks\OneDrive\Desktop\Web\AIAC.py'
\x5cdeeks\x5cOneDrive\x5cDesktop\x5cWeb\x5cAIAC.py' ;60d95a16-d8b5-4a4d-9c37-c4be7f12d820
1) Register
2) Login
3) Quit
Choose: 2
Username: deekshu_123
Password:
Login successful.

1) Register
2) Login
3) Quit
Choose: 3
PS C:\Users\deeks\OneDrive\Desktop\Web>
```

## TASK DESCRIPTION-2:

# SQL Injection Prevention

## Task:

Test an AI-generated script that performs SQL queries on a database.

## Instructions:

- Ask AI to generate a Python script using SQLite/MySQL to fetch user details.
- Identify if the code is vulnerable to **SQL injection** (e.g., using string concatenation in queries).
- Refactor using **parameterized queries (prepared statements)**.

## PROMPT:

Generate a Python script that uses SQLite/MySQL to fetch user details from a database. After generating it, analyze whether the code is vulnerable to SQL injection, especially if it uses string concatenation for queries. Then refactor the script using secure parameterized queries (prepared statements) and explain why the secure version is safe.

```
1 import sqlite3

💡 Generate a Python script that uses SQLite/MySQL to fetch user details from a database. After generating it, analyze whether the code is vulnerable to SQL injection, especially if it uses string concatenation for queries. Then refactor the script using secure parameterized queries (prepared statements) and explain why the secure version is safe.
```

Ask or edit in context Auto ▾  

Cancel ▾

## CODE:

```
import sqlite3
```

```
def get_user_safe(user_id):  
    conn = sqlite3.connect('users.db')  
    cursor = conn.cursor()
```

```
# ✓ SAFE: Parameterized query (prevents SQL injection)

query = "SELECT * FROM users WHERE id = ?"
print("[Executing Safe]:", query, "with param:", user_id)

cursor.execute(query, (user_id,))

user = cursor.fetchall()

conn.close()

return user

# Test with normal input

print("\nSafe Result (normal input):")


print(get_user_safe(1))

# Test with attacker input

print("\nSafe Result (attacker input):")

print(get_user_safe("1 OR 1=1"))
```

OUTPUT:



```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS AZURE POSTMAN CONSOLE ...
Python Debug Console + ⌂ ⌂ ... | ⌂ X

Safe Result (normal input):
● owsApps\python3.12.exe' 'c:\Users\deeks\.vscode\extensions\ms-python.debugpy-2025.16.0-win32-x64\bundled\libs\debugpy\launcher' '5365
7' '--' 'c:\Users\deeks\OneDrive\Desktop\Web\import sqlite3.py'
5cbundled\x5clibs\x5cdebugpy\x5clauncher' '53657' '--' 'c:\x5cUsers\x5cdeeks\x5cOneDrive\x5cDesktop\x5cWeb\x5cimport sqlite3.py' ;60d
95a16-d8b5-4a4d-9c37-c4be7f12d820
          Safe Result (normal input):
[Executing Safe]: SELECT * FROM users WHERE id = ? with param: 1
[(1, 'alice', 'alice@example.com')]

Safe Result (attacker input):
[Executing Safe]: SELECT * FROM users WHERE id = ? with param: 1 OR 1=1
[]
○ PS C:\Users\deeks\OneDrive\Desktop\Web> []

Ln 12, Col 29  Spaces: 4  UTF-8  CRLF  { } Python  Python 3.12  (↻) Go Live  ⚡
```

## TASK DESCRIPTION-3:

### Cross-Site Scripting (XSS) Check

#### Task:


Evaluate an AI-generated **HTML form with JavaScript** for XSS vulnerabilities.

#### Instructions:

- Ask AI to generate a feedback form with JavaScript-based output.
- Test whether untrusted inputs are directly rendered without escaping.
- Implement secure measures (e.g., escaping HTML entities, using CSP).

#### PROMPT:

Generate an HTML feedback form with JavaScript that displays user input on the page. Then analyze the code for XSS vulnerabilities, especially where untrusted input is directly rendered. Explain the risks and refactor the code to securely handle input by escaping HTML entities and adding protections like Content Security Policy (CSP).



## CODE:

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Feedback Form</title>

    <style>

        body { font-family: Arial, sans-serif; }

        .feedback { margin-top: 20px; }

    </style>

</head>

<body>

    <h1>Feedback Form</h1>

    <form id="feedbackForm">

        <label for="name">Name:</label>

        <input type="text" id="name" required>

        <br>

        <label for="message">Message:</label>

        <textarea id="message" required></textarea>
```

```
<br>
<button type="submit">Submit</button>
</form>
<div class="feedback" id="feedbackDisplay"></div>

<script>
  document.getElementById('feedbackForm').addEventListener('submit', function(event) {
    event.preventDefault();
    const name = document.getElementById('name').value;
    const message = document.getElementById('message').value;
    displayFeedback(name, message);
  });

  function displayFeedback(name, message) {
    const feedbackDisplay = document.getElementById('feedbackDisplay');
    feedbackDisplay.innerHTML = `<strong>${name}</strong>: ${message}`;
  }
</script>
</body>
</html>
```

## OUTPUT:



## Feedback Form

Name:

Message:

**Manohar:** Hello world!

--- Thank You---