

AI ASSISTED CODING

LAB ASSIGNMENT – 7.3:


TASK-1:


- Paste a function with a missing colon (add(a, b)), and let AI fix the syntax error.

python

```
def add(a, b)
    return a + b
```

CODE SCREENSHOTS BY USING GEMINI:





CODE EXPLANATION:

Gemini ✕

J GIVE ME THE EXPLANATION FOR ABOVE CODE

✦ Certainly! The code you provided defines a simple Python function named `add`.


Here's a breakdown of the code:

- `def add(a, b):`: This line defines a function named `add` that takes two arguments, `a` and `b`. The `def` keyword is used to define a function in Python, and the colon signifies the end of the function definition line.
- `return a + b`: This line is the body of the function. It calculates the sum of the two input arguments, `a` and `b`, and then uses the `return` keyword to send that sum back as the output of the function.


In essence, this function takes two values as input and returns their sum.

👍 💬

Code output with explanation:




Code output screenshots in copilot with code explanation:



TASK-2:

- Identify and fix a logic error in a loop that causes infinite iteration.

```
def count_down(n):  
    while n >= 0:  
        print(n)  
        n += 1 # Should be n -= 1
```



J explain the above code

★ Sure! I can explain the code above.

The code defines a function called `count_down` that takes one argument, `n`.

- **Original (infinite loop) version:**

```
def count_down(n):  
    while n > 0:  
        print(n)
```

In this version, the `while n > 0:` loop continues as long as `n` is greater than 0. However, since `n` is never changed inside the loop, if you call `count_down` with a positive value for `n` (like `count_down(5)`), `n` will always be greater than 0, and the loop will run forever, printing the same value of `n` repeatedly. This is an infinite loop.

- **Corrected version:**


```
def count_down(n):  
    while n > 0:  
        print(n)  
        n -= 1
```

In this corrected version, the line `n -= 1` is added inside the `while` loop. This line subtracts 1 from the value of `n` in each iteration. Now, with each pass through the loop, `n` gets smaller. Eventually, `n` will become 0 or less, and the condition `n > 0` will become false, causing the loop to terminate. This allows the function to count down from the initial value of `n` to 1.

The example usage `count_down(5)` demonstrates how the corrected function works, printing the numbers 5, 4, 3, 2, and 1.



Code output screenshots in copilot with code explanation:



TASK-3:

- Debug a runtime error caused by division by zero. Let AI insert try-except.

```
# Debug the following code
def divide(a, b):
    return a / b

print(divide(10, 0))
```

CODE SCREENSHOTS:

The screenshot shows a Google Colab notebook interface. The main editor displays a Python function `divide(a, b)` that attempts to divide `a` by `b`. A comment indicates that dividing by zero will cause a `ZeroDivisionError`. Below this, a `try-except` block is shown, which catches the `ZeroDivisionError` and prints an error message. The output of the code shows a successful division of 10 by 2 resulting in 5.0, and an error message for division by zero.

The right sidebar features the Gemini chat interface. It contains the following text:

block in the `divide` function.
Do you have any other code you would like to debug or any other questions about error handling in Python?

explain the above code

Certainly! Let me explain the code I provided to handle the division by zero error.
The code defines a function called `divide` that takes two arguments, `a` and `b`. Its purpose is to divide `a` by `b`.
Here's a breakdown of the corrected code with the `try-except` block:

```
def divide(a, b):  
    try:  
        return a / b  
    except ZeroDivisionError:  
        print("Error: Cannot divide by zero!")  
        return None # Or you could return a specific value like float('inf') or a message
```

- def divide(a, b):** This line defines the function named `divide` that accepts two parameters, `a` and `b`.
- try:** This keyword starts a `try` block. The code inside this block is what the program will attempt to execute. It's where you put the code that might cause an error. In this case, the division `a / b` is the operation that could potentially raise a `ZeroDivisionError`.
- return a / b:** If the division `a / b` is successful (i.e., `b` is not zero), the result of the division is returned by the function.
- except ZeroDivisionError:** This keyword starts an `except` block. This block is executed only if a `ZeroDivisionError` occurs within the preceding `try` block. It

What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

Code explanation:

J explain the above code

✦ Certainly! Let me explain the code I provided to handle the division by zero error.

The code defines a function called `divide` that takes two arguments, `a` and `b`. Its purpose is to divide `a` by `b`.

Here's a breakdown of the corrected code with the `try-except` block:

```
def divide(a, b):  
    try:  
        return a / b  
    except ZeroDivisionError:  
        print("Error: Cannot divide by zero!")  
        return None # Or you could return a specific value like float('inf') or a me
```

- `def divide(a, b):`: This line defines the function named `divide` that accepts two parameters, `a` and `b`.
- `try:`: This keyword starts a `try` block. The code inside this block is what the program will attempt to execute. It's where you put the code that *might* cause an error. In this case, the division `a / b` is the operation that could potentially raise a `ZeroDivisionError`.
- `return a / b`: If the division `a / b` is successful (i.e., `b` is not zero), the result of the division is returned by the function.
- `except ZeroDivisionError:`: This keyword starts an `except` block. This block is executed *only* if a `ZeroDivisionError` occurs within the preceding `try` block. It specifically catches the `ZeroDivisionError`.
- `print("Error: Cannot divide by zero!")`: If a `ZeroDivisionError` is caught, this line prints an informative error message to the console.
- `return None`: After printing the error message, this line returns `None` from the function. This is one way to indicate that the division was not successful due to the error. You could

✦ What can I help you build?



Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

Gemini X

executed *only* if a `ZeroDivisionError` occurs within the preceding `try` block. It specifically catches the `ZeroDivisionError`.

- `print("Error: Cannot divide by zero!")`: If a `ZeroDivisionError` is caught, this line prints an informative error message to the console.
- `return None`: After printing the error message, this line returns `None` from the function. This is one way to indicate that the division was not successful due to the error. You could choose to return a different value or handle the error in another way depending on your program's needs (e.g., return `float('inf')` for positive infinity or raise a different exception).

The example usage shows how the function behaves:

```
# Example usage:
result1 = divide(10, 2)
print(f"10 / 2 = {result1}")

result2 = divide(10, 0)
print(f"10 / 0 = {result2}")
```

When `divide(10, 2)` is called, the `try` block executes successfully, and the result `5.0` is returned and printed.

When `divide(10, 0)` is called, the division `10 / 0` inside the `try` block raises a `ZeroDivisionError`. The program then jumps to the `except ZeroDivisionError:` block, prints "Error: Cannot divide by zero!", and returns `None`, which is then printed.

This `try-except` block allows the program to handle the potential error gracefully instead of crashing.


Let me know if you have any more questions!



◆ What can I help you build?



Code output screenshots in copilot with code explanation:



TASK-4:

- Provide a faulty class definition (missing self in parameters). Let AI fix it

```
python

class Rectangle:
    def __init__(length, width):
        self.length = length
        self.width = width
```

Code screenshots:

The screenshot displays a Google Colab notebook titled 'Untitled9.ipynb'. The notebook contains three code cells. The first cell defines a `rectangle` class with an `__init__` method that initializes `self.length` and `self.width`, and a `rect` instance. The second and third cells create a `my_rectangle` object, print its length and width, and show the output: 'The length of the rectangle is: 10' and 'The width of the rectangle is: 5'. The right sidebar features the Gemini chat interface, which responds to the prompt 'give in one cell' with an example usage of the `rectangle` class. The bottom status bar shows the system clock at 10:42 AM on 02-09-2025, along with weather and network icons.

```
class rectangle:
    def __init__(self, length, width): # Corrected __init__ and added self
        self.length = length # Corrected capitalization of self
        self.width = width

rect = rectangle(5, 3) # Corrected indentation and placed outside the class definition

# Create a rectangle object with length 10 and width 5
my_rectangle = rectangle(10, 5)

# Access and print the length and width
print(f"The length of the rectangle is: {my_rectangle.length}")
print(f"The width of the rectangle is: {my_rectangle.width}")

The length of the rectangle is: 10
The width of the rectangle is: 5

# Create a rectangle object with length 10 and width 5
my_rectangle = rectangle(10, 5)

# Access and print the length and width
print(f"The length of the rectangle is: {my_rectangle.length}")
print(f"The width of the rectangle is: {my_rectangle.width}")

The length of the rectangle is: 10
The width of the rectangle is: 5

class rectangle:
    def __init__(self, length, width): # Corrected __init__ and added self
        self.length = length # Corrected capitalization of self
        self.width = width

    my_rectangle = rectangle(10, 5)

    print(f"The length of the rectangle is: {my_rectangle.length}")
    print(f"The width of the rectangle is: {my_rectangle.width}")

The length of the rectangle is: 10
The width of the rectangle is: 5
```

give in one cell

Certainly! Here is the example usage of the `rectangle` class in a single cell:

I have provided the example usage of the `rectangle` class in a single cell, as you requested. Is there anything else you would like to do or learn about Python classes or objects?

What can I help you build?

Rainy days ahead
26°C

10:42 AM Python 3
02-09-2025

Code explanation:

✓

RAM

Disk

▼

^

Gemini ✕

```
# Create a rectangle object with length 10 and width 5
my_rectangle = rectangle(10, 5)

# Access and print the length and width
print(f"The length of the rectangle is: {my_rectangle.length}")
print(f"The width of the rectangle is: {my_rectangle.width}")
```

Here's what each part does:


- `my_rectangle = rectangle(10, 5):`
 - This line creates a new instance (or object) of the `rectangle` class.
 - When you call the class name followed by parentheses (`rectangle(10, 5)`), you are actually calling the `__init__` method of the class.
 - The values `10` and `5` are passed as arguments to the `__init__` method. Inside `__init__`, these values are assigned to the `length` and `width` attributes of the newly created `my_rectangle` object.
 - The resulting `rectangle` object is then assigned to the variable `my_rectangle`.
- `print(f"The length of the rectangle is: {my_rectangle.length}"):`
 - This line accesses the `length` attribute of the `my_rectangle` object using dot notation (`my_rectangle.length`).
 - Since we created the object with a length of 10, this will retrieve the value 10.
 - The `f""` syntax is a f-string, which allows you to embed the value of a variable directly within a string. The output will be "The length of the rectangle is: 10".
- `print(f"The width of the rectangle is: {my_rectangle.width}"):`
 - Similar to the previous line, this accesses the `width` attribute of the `my_rectangle` object using `my_rectangle.width`.
 - Since we created the object with a width of 5, this will retrieve the value 5.
 - Using the f-string, the output will be "The width of the rectangle is: 5".

◆

What can I help you build?

⊕ ▶

Code output screenshots in copilot with code explanation:



TASK-5:

- Access an invalid list index and use AI to resolve the Index Error.

```
python

numbers = [1, 2, 3]
print(numbers[5])
```

Code screenshots by using gemini:

The screenshot shows a Google Colab notebook interface. The top bar indicates the notebook is named 'Untitled13.ipynb' and is located at 'colab.research.google.com/drive/1O_FHY5KH8dDggPrVD88u2WxPVfg6A8Mm'. The notebook has tabs for 'File', 'Edit', 'View', 'Insert', 'Runtime', 'Tools', and 'Help'. The 'Code' tab is active, showing a Python code snippet:

```
[5] # Create a list
my_list = [1, 2, 3]

# Access a valid index (e.g., index 0)
print(my_list[0])
```

The output of the code is '1'. To the right of the code editor is a 'Gemini X' chat window. It contains the following text:

the example usage

✦ The error in the code is an `IndexError` because you are trying to access an index (5) that is outside the valid range of the list `my_list` (which has indices 0, 1, and 2). To fix this, you need to access an index within the valid range. Here is the corrected code accessing a valid index (0) and its output:

I have identified and corrected the `IndexError` for you.

Would you like to explore other types of Python errors or work with different data structures like dictionaries or tuples?

explain the above code

✦ Certainly! The code you provided is a simple Python example that demonstrates how to create a list and access its elements.

Here's a breakdown:

```
# Create a list
my_list = [1, 2, 3]
```

This line creates a list named `my_list` and initializes it with three integer values: 1, 2, and 3. Lists in Python are ordered collections of items, and each item has an index.

```
# Access a valid index (e.g., index 0)
print(my_list[0])
```

This line accesses the element at index 0 of the `my_list`. In Python, list indices start from 0. So, `my_list[0]` refers to the first element in the list, which is the number 1. The `print()` function then displays this value to the console.

In summary: the code creates a list and prints the first element.

✦ What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

The bottom of the screen shows a Windows taskbar with the date '10:44' and time '07-09-2025'.

Code explanation by using gemini:

- ◆ The error in the code is an `IndexError` because you are trying to access an index (5) that is outside the valid range of the list `my_list` (which has indices 0, 1, and 2).

To fix this, you need to access an index within the valid range. Here is the corrected code accessing a valid index (0) and its output:

I have identified and corrected the `IndexError` for you.

Would you like to explore other types of Python errors or work with different data structures like dictionaries or tuples?



- J explain the above code

- ◆ Certainly! The code you provided is a simple Python example that demonstrates how to create a list and access its elements.

Here's a breakdown:

```
# Create a list
my_list = [1, 2, 3]
```

This line creates a list named `my_list` and initializes it with three integer values: 1, 2, and 3. Lists in Python are ordered collections of items, and each item has an index.

```
# Access a valid index (e.g., index 0)
print(my_list[0])
```

This line accesses the element at index 0 of the `my_list`. In Python, list indices start from 0. So, `my_list[0]` refers to the first element in the list, which is the number 1. The `print()` function then displays this value to the console.

Code output screenshots in copilot with code explanation:

File Edit Selection View Go Run Terminal Help

temp1.html ai.py temp11.js

EXPLORER

temp1.html
ai.py
temp11.js

WTMP

ai.py
html.py
temp1.html
temp11.js

OUTLINE
TIMELINE

1
2
3
4
5
6
7
8

my_list = [1, 2, 3]
try:
 print(my_list[5]) # This will cause an IndexError
except IndexError:
 print("Error: List index out of range.")

Example usage with a valid index
print(my_list[1]) # Output: 2

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

hon.exe c:/Users/HP/OneDrive/Desktop/WTMP/ai.py
Error: List index out of range.
PS c:\Users\HP\OneDrive\Desktop\WTMP> & c:\Users\HP\AppData\Local\Programs\Python\Python313\pyth
hon.exe c:/Users/HP/OneDrive/Desktop/WTMP/ai.py
Error: List index out of range.
2
Error: List index out of range.
PS c:\Users\HP\OneDrive\Desktop\WTMP>

CHAT

give me the explanation for the above code

Here's the explanation for your code in ai.py :

- my_list = [1, 2, 3] creates a list with three elements.
- The try block attempts to print my_list[5]. Since there is no index 5 in the list (Python lists are zero-indexed and this list only has indices 0, 1, and 2), this line raises an IndexError.
- The except IndexError block catches this error and prints "Error: List index out of range." instead of letting the program crash.
- After the try-except block, print(my_list[1]) prints the element at index 1, which is 2.

So, the output will be:

Error: List index out of range.
2

This code demonstrates how to safely handle invalid list index access and how to access a valid index.

2 files changed
ai.py
html.py
Add Context...
Add context (#), extensions (@), commands (/)
Agent GPT-4.1

Ln 8, Col 31 Spaces: 4 UTF-8 CRLF Python Python 3.13 (64-bit) Go Live

Rainy days ahead 27°C

Search

10:53 07-09-2025