

LAB ASSIGNMENT – 4.1

NAME : M.Shiva
HALL.NO : 2403A52377
BATCH.NO : AI 14
ASSIGNMENT : 4.1

PROMPT 01 :

i need a python code function that validates an Indian mobile number.

Requirements

The function must ensure the mobile number:

Starts with 6, 7, 8, or 9

Contains exactly 10 digits

CODE :

```
[1] import re

def validate_indian_mobile(number):
    """
    Validates if a given number is a valid Indian mobile number.

    Args:
        number: The mobile number as a string.

    Returns:
        True if the number is a valid Indian mobile number, False otherwise.
    """
    # Remove any non-digit characters
    number = re.sub(r'\D', '', number)

    # Check if the number starts with 6, 7, 8, or 9 and has exactly 10 digits
    if re.match(r'^[6-9]\d{9}$', number):
        return True
    else:
        return False

# Example usage:
print(validate_indian_mobile("9876543210"))
print(validate_indian_mobile("5123456789"))
print(validate_indian_mobile("987654321"))
print(validate_indian_mobile("98765432101"))
print(validate_indian_mobile("+91 98765 43210"))
```

OUTPUT :

```
True
False
False
False
False
```

• CODE EXPLANATION :

- import re:** This line imports the re module, which provides support for regular expressions in Python. Regular expressions are used here to define a pattern for matching valid mobile numbers.
- def validate_indian_mobile(number):**: This defines a function named `validate_indian_mobile` that takes one argument, `number`, which is expected to be the mobile number string you want to validate.
- number = re.sub(r'\D', '', number):** This line uses a regular expression `\D` to find and remove any non-digit characters from the input number string. This cleans the input so that only digits remain for validation.
- if re.match(r'^[6-9]\d{9}\$', number):**: This is the core validation step.
 - `re.match()` attempts to match the regular expression pattern from the *beginning* of the cleaned number string.

- `^[6-9]` matches the start of the string (^) followed by a single digit that is either 6, 7, 8, or 9.
- `\d{9}` matches exactly 9 digits (\d matches any digit).
- `$` matches the end of the string.
- So, the entire pattern `^[6-9]\d{9}$` ensures the number starts with 6, 7, 8, or 9 and is exactly 10 digits long.
- **return True:** If the regular expression matches the cleaned number string, the function returns True, indicating a valid Indian mobile number.
- **else: return False:** If the regular expression does not match, the function returns False, indicating an invalid Indian mobile number.
- **print(...):** These lines demonstrate how to call the `validate_indian_mobile` function with different example numbers and print the returned boolean result (True or False).

PROMPT 02 :

i need a python code function that calculates the factorial of a number. Requirements • Provide one sample input-output pair in the prompt to guide the AI. • The function should handle: o 0! correctly o Negative input by returning an appropriate message

CODE :

```

def calculate_factorial(number):
    """
    Calculates the factorial of a non-negative integer.

    Args:
        number: An integer.

    Returns:
        The factorial of the number if it's a non-negative integer,
        otherwise an appropriate message for negative input.
    """
    if not isinstance(number, int):
        return "Input must be an integer."
    elif number < 0:
        return "Factorial is not defined for negative numbers."
    elif number == 0:
        return 1
    else:
        factorial = 1
        for i in range(1, number + 1):
            factorial *= i
        return factorial

# Example usage:
print(f"Factorial of 5: {calculate_factorial(5)}")
print(f"Factorial of 0: {calculate_factorial(0)}")
print(f"Factorial of -5: {calculate_factorial(-5)}")
print(f"Factorial of 3.5: {calculate_factorial(3.5)}")

```

OUTPUT :

```

Factorial of 5: 120
Factorial of 0: 1
Factorial of -5: Factorial is not defined for negative numbers.
Factorial of 3.5: Input must be an integer.

```

CODE EXPLANATION :

- `def calculate_factorial(number):`:: This defines a function named `calculate_factorial` that takes one argument, `number`, which is the integer for which you want to calculate the factorial.
- `if not isinstance(number, int):`:: This checks if the input number is not an integer. If it's not an integer, it returns the message "Input must be an integer."
- `elif number < 0:` If the number is an integer but is less than 0, this condition is met, and the function returns the message "Factorial is not defined for negative numbers."
- `elif number == 0:` If the number is an integer and is 0, this condition is met, and the function returns 1, because the factorial of 0 is defined as 1.
- `else:` If the number is a non-negative integer (greater than 0), this block of code is executed.
 - `factorial = 1:` Initializes a variable `factorial` to 1. This is the starting point for the calculation.

- for i in range(1, number + 1):: This loop iterates from 1 up to and including the input number.
 - factorial *= i: In each iteration, the current value of factorial is multiplied by the loop variable i. This performs the cumulative multiplication for the factorial.
 - return factorial: After the loop finishes, the final calculated factorial value is returned.
- print(f"Factorial of...: These lines are examples of how to call the calculate_factorial function with different inputs (5, 0, -5, and 3.5) and print the results, including the informative messages for invalid inputs.

PROMPT 03 :

i need a python code with 2 to 3 examples function that parses a nested dictionary representing student information. Requirements • The function should extract and return: o Full Name o Branch o SGPA

CODE :

```
def parse_student_info(student_data):
    """
    Parses a nested dictionary of student information to extract Full Name, Branch, and SGPA.

    Args:
        student_data: A dictionary containing student information.

    Returns:
        A dictionary containing 'Full Name', 'Branch', and 'SGPA' if found,
        otherwise returns a dictionary with missing information noted.
    """
    parsed_info = {}

    # Extract Full Name (assuming it's under 'personal_info' -> 'name')
    name = student_data.get('personal_info', {}).get('name')
    if name:
        parsed_info['Full Name'] = name
    else:
        parsed_info['Full Name'] = 'Not available'

    # Extract Branch (assuming it's under 'academic_info' -> 'branch')
    branch = student_data.get('academic_info', {}).get('branch')
    if branch:
        parsed_info['Branch'] = branch
    else:
        parsed_info['Branch'] = 'Not available'

    # Extract SGPA (assuming it's under 'academic_info' -> 'sgpa')
    sgpa = student_data.get('academic_info', {}).get('sgpa')
    if sgpa is not None: # Check for None as SGPA could be 0 or other valid falsy values
        parsed_info['SGPA'] = sgpa
    else:
        parsed_info['SGPA'] = 'Not available'

    return parsed_info

# Example 1: Complete student data
```

```

# Example 1: Complete student data
student1_data = {
    'student_id': '101',
    'personal_info': {
        'name': 'Alice Smith',
        'age': 20,
        'address': '123 Main St'
    },
    'academic_info': {
        'branch': 'Computer Science',
        'roll_no': 'CS101',
        'sgpa': 8.5
    }
}

# Example 2: Missing some information
student2_data = {
    'student_id': '102',
    'personal_info': {
        'name': 'Bob Johnson',
        'age': 21
    },
    'academic_info': {
        'roll_no': 'EC205',
        'sgpa': 7.8
    }
}

# Example 3: Different structure and missing info
student3_data = {
    'id': '103',
    'details': {
        'full_name': 'Charlie Brown',
        'major': 'Electrical Engineering'
    },
    'results': {
        'gpa': 9.1
    }
}

```

```

        'gpa': 9.1
    }
}

print("Student 1 Info:", parse_student_info(student1_data))
print("Student 2 Info:", parse_student_info(student2_data))
print("Student 3 Info:", parse_student_info(student3_data))

```

OUT PUT :

```

Student 1 Info: {'Full Name': 'Alice Smith', 'Branch': 'Computer Science', 'SGPA': 8.5}
Student 2 Info: {'Full Name': 'Bob Johnson', 'Branch': 'Not available', 'SGPA': 7.8}
Student 3 Info: {'Full Name': 'Not available', 'Branch': 'Not available', 'SGPA': 'Not available'}

```

CODE EXPLANATION :

- `def parse_student_info(student_data)::` This defines a function named `parse_student_info` that takes one argument, `student_data`, which is the nested dictionary containing the student's information.
- `parsed_info = {}:` Initializes an empty dictionary called `parsed_info`. This dictionary will store the extracted 'Full Name', 'Branch', and 'SGPA'.
- `name = student_data.get('personal_info', {}).get('name'):` This line attempts to extract the student's name.
 - `student_data.get('personal_info', {})` safely tries to access the 'personal_info' key from the `student_data` dictionary. If 'personal_info' doesn't exist, it returns an empty dictionary `{}` to prevent an error.
 - `.get('name')` then safely tries to access the 'name' key from the result of the previous step. If 'name' doesn't exist (either because 'personal_info' was missing or 'name' was missing within it), it returns `None`.
- `if name::` This checks if the extracted name is not `None` and is a truthy value (like a non-empty string).
- `parsed_info['Full Name'] = name:` If a name was found, it's added to the `parsed_info` dictionary with the key 'Full Name'.
- `else: parsed_info['Full Name'] = 'Not available':` If no name was found, 'Not available' is added to `parsed_info` for 'Full Name'.
- `branch = student_data.get('academic_info', {}).get('branch'):` Similar to extracting the name, this line safely attempts to extract the 'branch' from the 'academic_info' nested dictionary.
- `if branch::` Checks if a branch was found.
- `parsed_info['Branch'] = branch:` If a branch was found, it's added to `parsed_info`.
- `else: parsed_info['Branch'] = 'Not available':` If no branch was found, 'Not available' is added for 'Branch'.
- `sgpa = student_data.get('academic_info', {}).get('sgpa'):` Safely attempts to extract the 'sgpa' from the 'academic_info' nested dictionary.
- `if sgpa is not None::` This checks if the extracted sgpa is not `None`. It specifically checks for is not `None` because sgpa could be 0, which is a falsy value in Python, but a valid SGPA.
- `parsed_info['SGPA'] = sgpa:` If an SGPA (including 0) was found, it's added to `parsed_info`.
- `else: parsed_info['SGPA'] = 'Not available':` If no SGPA was found (i.e., it was `None`), 'Not available' is added for 'SGPA'.
- `return parsed_info:` The function returns the `parsed_info` dictionary containing the extracted (or 'Not available') information.
- `student1_data = {...}, student2_data = {...}, student3_data = {...}:` These are example dictionaries representing different student data structures and missing information.
- `print("Student 1 Info:", parse_student_info(student1_data)):` These lines demonstrate calling the `parse_student_info` function with the example data and printing the resulting dictionaries.

PROMPT 04:

i need a python code functions for CSV file analysis. Requirements • Each generated function should:
o Read a .csv file
o Return the total number of rows
o Count the number of empty rows
o Count the number of words across the file

CODE :

```
[12] import pandas as pd
import re

def analyze_csv_file(file_path):
    """
    Analyzes a CSV file to determine total rows, empty rows, and total word count.

    Args:
        file_path: The path to the CSV file.

    Returns:
        A tuple containing:
        - The total number of rows in the DataFrame.
        - The number of empty rows in the DataFrame.
        - The total number of words in the DataFrame.
        Returns error messages and 0 counts if the file is not found or an error occurs.
    """
    try:
        df = pd.read_csv(file_path)
        total_rows = len(df)

        # Calculate the number of empty rows (where all values are NaN)
        empty_rows_count = df.isnull().all(axis=1).sum()

        # Calculate the total number of words
        total_words = 0
        # Convert the entire DataFrame to string type to handle mixed data types
        df_str = df.astype(str)
        # Apply a function to each element to count words
        total_words = df_str.applymap(lambda x: len(str(x).split())).sum().sum()

        return total_rows, empty_rows_count, total_words

    except FileNotFoundError:
        return "Error: File not found", 0, 0
```



```

    return total_rows, empty_rows_count, total_words

except FileNotFoundError:
    return "Error: File not found", 0, 0
except Exception as e:
    return f"An error occurred: {e}", 0, 0

# Example usage:

# 1. Create a dummy CSV file for demonstration
csv_data = {'colA': ['apple', 'banana split', None, 'orange', 'grape'],
            'colB': [1, None, 3, 4, None],
            'colC': ['one two', 'three', 'four five six', None, None]}
sample_df = pd.DataFrame(csv_data)
sample_csv_path = 'sample_analysis.csv'
sample_df.to_csv(sample_csv_path, index=False)

print(f"Analyzing file: {sample_csv_path}")
total_rows, empty_rows_count, total_words = analyze_csv_file(sample_csv_path)

print(f"Total number of rows: {total_rows}")
print(f"Number of empty rows: {empty_rows_count}")
print(f"Total number of words: {total_words}")

print("\nAnalyzing a non-existent file:")
non_existent_file = 'non_existent.csv'
total_rows_err, empty_rows_count_err, total_words_err = analyze_csv_file(non_existent_file)
print(total_rows_err) # This will print the error message
print(f"Total rows: {total_rows_err}, Empty rows: {empty_rows_count_err}, Total words: {total_words_err}")

```

OUTPUT :

```

Analyzing file: sample_analysis.csv
Total number of rows: 5
Number of empty rows: 0
Total number of words: 19

Analyzing a non-existent file:
Error: File not found
Total rows: Error: File not found, Empty rows: 0, Total words: 0
/tmp/ipython-input-1294288315.py:30: FutureWarning: DataFrame.applymap has been deprecated. Use DataFrame.map instead.
  total_words = df_str.applymap(lambda x: len(str(x).split())).sum().sum()

```

• CODE EXPLANATION :

- import pandas as pd: This line imports the pandas library, which is essential for working with DataFrames and reading CSV files, and assigns it the alias pd.
- import re: This line imports the regular expression module, although it's not directly used in the final version of the analyze_csv_file function provided. It was likely included in an earlier iteration of combining code.
- def analyze_csv_file(file_path):: This defines a function named analyze_csv_file that takes one argument, file_path, which is the path to the CSV file you want to analyze.

- `try...except FileNotFoundError...except Exception as e::` This block handles potential errors during file processing.
 - It attempts to execute the code within the try block.
 - If a `FileNotFoundError` occurs (meaning the specified file doesn't exist), it returns an error message "Error: File not found" and 0 for the counts.
 - If any other `Exception` occurs during the process, it catches it and returns a generic error message including the exception details and 0 for the counts.
- `df = pd.read_csv(file_path):` Inside the try block, this line reads the CSV file specified by `file_path` into a pandas `DataFrame` named `df`.
- `total_rows = len(df):` This calculates the total number of rows in the `DataFrame` `df` using the `len()` function and stores it in the `total_rows` variable.
- `empty_rows_count = df.isnull().all(axis=1).sum():` This calculates the number of empty rows.
 - `df.isnull()` creates a boolean `DataFrame` where `True` indicates a missing value (`NaN`).
 - `.all(axis=1)` checks if *all* values across each row (`axis=1`) are `True` (i.e., if the entire row is null).
 - `.sum()` counts the number of `True` values, giving the count of empty rows.
- `total_words = df.astype(str).applymap(lambda x: len(str(x).split())).sum().sum():` This calculates the total number of words across all cells. Note: As mentioned in the previous response, `applymap` is deprecated and `map` is recommended for future use.
 - `df.astype(str)` converts all `DataFrame` elements to strings.
 - `.applymap(lambda x: len(str(x).split()))` applies a function to *each cell* (`applymap`). The function `lambda x: len(str(x).split())` splits the string in a cell by whitespace and counts the resulting words.
 - The first `.sum()` sums the word counts within each column.
 - The second `.sum()` sums the column totals to get the grand total word count for the `DataFrame`.
- `return total_rows, empty_rows_count, total_words:` The function returns a tuple containing the calculated total rows, empty rows count, and total words.
- **Example Usage Block:** This part of the code demonstrates calling the `analyze_csv_file` function with a created sample CSV file and a non-existent file to show the results and error handling.

PROPT 05 :

i need a python code function that processes text and analyzes word frequency.

Requirements The function must: • Accept a paragraph as input • Convert all text to lowercase • Remove punctuation • Return the most frequently used word

CODE :

```
import string
from collections import Counter

def most_frequent_word(paragraph):
    """
    Processes a paragraph of text to find the most frequently used word.

    Args:
        paragraph: A string containing the text paragraph.

    Returns:
        A tuple containing the most frequent word and its count, or None if the paragraph is empty.
    """
    if not paragraph:
        return None

    # Convert to lowercase
    paragraph = paragraph.lower()

    # Remove punctuation
    paragraph = paragraph.translate(str.maketrans('', '', string.punctuation))

    # Split into words and count frequency
    words = paragraph.split()
    if not words:
        return None

    word_counts = Counter(words)

    # Get the most frequent word
    most_common = word_counts.most_common(1)

    return most_common[0]

# Example usage:
text1 = "This is a sample paragraph. This paragraph is a sample."
print(f"Most frequent word in text1: {most_frequent_word(text1)}")

text2 = "Hello, world! Hello!"
print(f"Most frequent word in text2: {most_frequent_word(text2)}")

text3 = " " # Empty or whitespace only
print(f"Most frequent word in text3: {most_frequent_word(text3)}")

text4 = "A single word."
print(f"Most frequent word in text4: {most_frequent_word(text4)}")
```

CODE EXPLANATION :

- `import string`: This line imports the string module, which provides a collection of string constants, including `string.punctuation` which is used here to get a string of all punctuation characters.

- `from collections import Counter`: This line imports the Counter class from the collections module. Counter is a specialized dictionary subclass for counting hashable objects (like words).
- `def most_frequent_word(paragraph)::` This defines a function named `most_frequent_word` that takes one argument, `paragraph`, which is the text string you want to analyze.
- `if not paragraph::` This checks if the input `paragraph` is empty or None. If it is, the function returns None.
- `paragraph = paragraph.lower():` This line converts the entire `paragraph` string to lowercase. This ensures that words like "The" and "the" are treated as the same word.
- `paragraph = paragraph.translate(str.maketrans("", "", string.punctuation)):` This line removes punctuation from the `paragraph`.
 - `str.maketrans("", "", string.punctuation)` creates a translation table that maps each punctuation character to None, effectively telling `translate` to remove them.
 - `.translate(...)` applies this translation table to the `paragraph` string.
- `words = paragraph.split():` This line splits the cleaned `paragraph` string into a list of individual words using whitespace as the delimiter.
- `if not words::` This checks if the `words` list is empty after splitting (which could happen if the input was just punctuation or whitespace). If it's empty, the function returns None.
- `word_counts = Counter(words):` This creates a Counter object named `word_counts` from the list of words. The Counter automatically counts the occurrences of each word.
- `most_common = word_counts.most_common(1):` This calls the `most_common()` method on the `word_counts` Counter. `most_common(1)` returns a list containing a single tuple, where the tuple contains the most frequent word and its count.
- `return most_common[0]:` The function returns the first (and only) element of the `most_common` list, which is the tuple containing the most frequent word and its count.
- `text1 = "...", text2 = "...", etc.:` These lines define example `paragraph` strings.
- `print(f"Most frequent word in...:)` These lines demonstrate calling the `most_frequent_word` function with the example texts and printing the results.