

Ex.no : 57

Date : 20.11.2024

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Function Description

Complete the function balancedSum in the editor below.

balancedSum has the following parameter(s):

int arr[n]: an array of integers

Returns:

int: an integer representing the index of the pivot

PROGRAM:

reset answer

```

1  /*
2  * Complete the 'balancedSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY arr as parameter.
6  */
7
8  int balancedSum(int n, int* x)
9  {
10     int a=0,b=0;
11     for(int i = 0;i < n;i++) {
12         b+=x[i];
13     }
14     for(int i = 0;i < n;i++) {
15         if(a==b-x[i]) {
16             return i;
17         }
18         a+=x[i];
19         b-=x[i];
20     }
21     return 1;
22 }
23
24

```

WEEK 13

OUTPUT:

	Test	Expected	Got	
✓	<pre>int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))</pre>	2	2	✓

Passed all tests! ✓

Ex.no : 58

Date : 20.11.2024

Calculate the sum of an array of integers.

Example

numbers = [3, 13, 4, 11, 9]

The sum is $3 + 13 + 4 + 11 + 9 = 40$.

Function Description

Complete the function arraySum in the editor below.

arraySum has the following parameter(s):

int numbers[n]: an array of integers

Returns

int: integer sum of the numbers array

Constraints

PROGRAM:

```
1  /*  
2  * Complete the 'arraySum' function below.  
3  *  
4  * The function is expected to return an INTEGER.  
5  * The function accepts INTEGER_ARRAY numbers as parameter.  
6  */  
7  
8  int arraySum(int n, int *a)  
9  {  
10     int s = 0;  
11     for(int i = 0; i < n; i++) {  
12         s+=a[i];  
13     }  
14     return s;  
15  
16 }  
17
```

WEEK 13

OUTPUT:

	Test	Expected	Got	
✓	<pre>int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))</pre>	15	15	✓

Passed all tests! ✓

Ex.no : 59

Date : 20.11.2024

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example $n = 5$ $arr = [1, 3, 3, 2, 4]$ If the list is rearranged as $arr' = [1, 2, 3, 3, 4]$, the absolute differences are $|1 - 2| = 1$, $|2 - 3| = 1$, $|3 - 3| = 0$, $|3 - 4| = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$. Function Description Complete the function `minDiff` in the editor below. `minDiff` has the following parameter: `arr`: an integer array Returns: `int`: the sum of the absolute differences of adjacent elements Constraints $2 \leq n \leq 105$ $0 \leq arr[i] \leq 109$, where $0 \leq i < n$ Input Format For Custom Testing The first line of input contains an integer, n , the size of `arr`. Each of the following n lines contains an integer that describes `arr[i]` (where $0 \leq i < n$). Sample Case 0 Sample Input For Custom Testing STDIN Function ----- $5 \rightarrow arr[]$ size $n = 5$ $5 \rightarrow arr[] = [5, 1, 3, 7, 3]$ 1 3 7 3 Sample Output 6 Explanation $n = 5$ $arr = [5, 1, 3, 7, 3]$ If `arr` is rearranged as $arr' = [1, 3, 3, 5, 7]$, the differences are minimized. The final answer is $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$. Sample Case 1 Sample Input For Custom Testing STDIN Function ----- $-2 \rightarrow arr[]$ size $n = 2$ 3 $\rightarrow arr[] = [3, 2]$ 2 Sample Output 1 Explanation $n = 2$ $arr = [3, 2]$ There is no need to rearrange because there are only two elements. The final answer is $|3 - 2| = 1$.

PROGRAM:

```

1  /*
2  * Complete the 'minDiff' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY arr as parameter.
6  */
7  #include<stdlib.h>
8  int cmp(const void* a, const void* b) {
9      return (*(int*)a - *(int*)b);
10 }
11 int minDiff(int n, int* a)
12 {
13     qsort(a, n, sizeof(int), cmp);
14     int s = 0;
15     for(int i = 0; i < (n-1); i++) {
16         int c = a[i] - a[i+1];
17         if(c < 0)
18             s -= c;
19         else
20             s += c;
21     }
22     return s;
23 }
24 }
25

```

OUTPUT:

	Test	Expected	Got	
✓	int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))	6	6	✓

Passed all tests! ✓