

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_MCQ_Updated

Attempt : 1
Total Mark : 20
Marks Obtained : 15

Section 1 : MCQ

1. How many pointers does a node in a doubly linked list have?

Answer

2

Status : Correct

Marks : 1/1

2. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

Answer

The node will become the new head

Status : Correct

Marks : 1/1

3. What is a memory-efficient double-linked list?

Answer

A doubly linked list that uses bitwise AND operator for storing addresses

Status : Correct

Marks : 1/1

4. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
newNode->data = value;  
newNode->next = NULL;  
newNode->prev = NULL;
```

Answer

Creates a new node and initializes its data to 'value'

Status : Correct

Marks : 1/1

5. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head_ref: Pointer to Pointer of node)

temp = NULL

current = *head_ref

While current is not NULL

temp = current->prev

current->prev = current->next

current->next = temp

current = current->prev

End While

```
If temp is not NULL
    *head_ref = temp->prev
End If
End Procedure
```

Answer

6 <--> 5 <--> 4 <--> 3 <--> 2 <--> 1.

Status : Correct

Marks : 1/1

6. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

```
Define Structure Node
    data: Integer
    prev: Pointer to Node
    next: Pointer to Node
End Define
```

```
Define Structure TwoWayLinkedList
    head: Pointer to Node
    tail: Pointer to Node
End Define
```

Answer

```
struct TwoWayLinkedList* list = malloc(sizeof(struct TwoWayLinkedList)); list-
&gt;head = NULL; list-&gt;tail = NULL;
```

Status : Correct

Marks : 1/1

7. What will be the output of the following program?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
```

```
};
```

```
int main() {  
    struct Node* head = NULL;  
    struct Node* tail = NULL;  
    for (int i = 0; i < 5; i++) {  
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));  
        temp->data = i + 1;  
        temp->prev = tail;  
        temp->next = NULL;  
        if (tail != NULL) {  
            tail->next = temp;  
        } else {  
            head = temp;  
        }  
        tail = temp;  
    }  
    struct Node* current = head;  
    while (current != NULL) {  
        printf("%d ", current->data);  
        current = current->next;  
    }  
    return 0;  
}
```

Answer

1 2 3 4 5

Status : Correct

Marks : 1/1

8. How do you reverse a doubly linked list?

Answer

By traversing the list in reverse order and creating a new reversed list

Status : Wrong

Marks : 0/1

9. Which pointer helps in traversing a doubly linked list in reverse order?

Answer

prev

Status : Correct

Marks : 1/1

10. What is the correct way to add a node at the beginning of a doubly linked list?

Answer

```
void addFirst(int data){&nbsp;Node* newNode = new  
Node(data);&nbsp;newNode-&gt;prev = head;&nbsp;head = newNode;}
```

Status : Wrong

Marks : 0/1

11. Which of the following is false about a doubly linked list?

Answer

Implementing a doubly linked list is easier than singly linked list

Status : Correct

Marks : 1/1

12. How do you delete a node from the middle of a doubly linked list?

Answer

All of the mentioned options

Status : Correct

Marks : 1/1

13. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;
```

```
struct Node *Fwd;  
struct Node *Bwd;  
);
```

Answer

X->Bwd->Fwd = X->Bwd ; X->Fwd->Bwd = X->Fwd;

Status : Wrong

Marks : 0/1

14. Which of the following is true about the last node in a doubly linked list?

Answer

Its next pointer is NULL

Status : Correct

Marks : 1/1

15. Which code snippet correctly deletes a node with a given value from a doubly linked list?

```
void deleteNode(Node** head_ref, Node* del_node) {  
    if (*head_ref == NULL || del_node == NULL) {  
        return;  
    }  
    if (*head_ref == del_node) {  
        *head_ref = del_node->next;  
    }  
    if (del_node->next != NULL) {  
        del_node->next->prev = del_node->prev;  
    }  
    if (del_node->prev != NULL) {  
        del_node->prev->next = del_node->next;  
    }  
    free(del_node);  
}
```

Answer

Deletes the node at a given position in a doubly linked list.

Status : Wrong

Marks : 0/1

16. What happens if we insert a node at the beginning of a doubly linked list?

Answer

The previous pointer of the head node is not updated

Status : Wrong

Marks : 0/1

17. What will be the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>

struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};

int main() {
    struct Node* head = NULL;
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
    temp->data = 2;
    temp->next = NULL;
    temp->prev = NULL;
    head = temp;
    printf("%d\n", head->data);
    free(temp);
    return 0;
}
```

Answer

2

Status : Correct

Marks : 1/1

18. Which of the following statements correctly creates a new node for a doubly linked list?

Answer

```
struct Node* newNode = (struct Node*) malloc(sizeof(struct Node));
```

Status : Correct

Marks : 1/1

19. Which of the following information is stored in a doubly-linked list's nodes?

Answer

All of the mentioned options

Status : Correct

Marks : 1/1

20. What is the main advantage of a two-way linked list over a one-way linked list?

Answer

Two-way linked lists allow for traversal in both directions.

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
# You are using Python
```

```
def insert_end(self, item):  
    new_node = Node(item)  
    if self.tail:  
        self.tail.next = new_node  
        new_node.prev = self.tail  
    else:  
        self.head = new_node  
        self.tail = new_node
```

```

def insert_front(self, item):
    new_node = Node(item)
    if self.head:
        self.head.prev = new_node
        new_node.next = self.head
    else:
        self.tail = new_node
    self.head = new_node

```

```

def display_forward(self):
    print("Forward Playlist: ", end="")
    temp = self.head
    while temp:
        print(temp.data, end=" " if temp.next else "")
        temp = temp.next
    print()

```

```

def display_backward(self):
    print("Backward Playlist: ", end="")
    temp = self.tail
    while temp:
        print(temp.data, end=" " if temp.prev else "")
        temp = temp.prev
    print()

```

```

int main() {
    struct Node* playlist = NULL;
    char item;

    while (1) {
        scanf("%c", &item);
        if (item == '-') {
            break;
        }
        insertAtEnd(&playlist, item);
    }

```

```

    struct Node* tail = playlist;
    while (tail->next != NULL) {
        tail = tail->next;
    }

```

```

    printf("Forward Playlist: ");

```

```
    displayForward(playlist);  
    printf("Backward Playlist: ");  
    displayBackward(tail);  
  
    freePlaylist(playlist);  
  
    return 0;  
}
```

Status : Wrong

Marks : 0/10

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

Input Format

The first line consists of an integer n , representing the number of participant IDs to be added.

The second line consists of n space-separated integers representing the participant IDs.

Output Format

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

163 137 155

Output: 163

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
typedef struct myNode

{

    int val;
    struct myNode * next;
    struct myNode * prev;
}
Node;
void append(Node ** head, int val)

{

    Node * tmp = (Node * ) malloc(sizeof(Node));
    tmp->val = val;
    tmp->prev = NULL;
    tmp->next = NULL;
    if (* head == NULL)
```

```
{
```

```
    * head = tmp;
```

```
    } else
```

```
    {
```

```
        Node * curr = * head;  
        while (curr -> next != NULL)
```

```
        {
```

```
            curr = curr -> next;
```

```
        }
```

```
        curr -> next = tmp;  
        tmp -> prev = curr;
```

```
    }
```

```
    }
```

```
    void printMax(Node * head)
```

```
    {
```

```
        if (head == NULL)
```

```
        {
```

```
            printf("Empty list!");  
            return;
```

```
        }
```

```
        Node * curr = head;  
        int max = curr -> val;  
        while (curr -> next != NULL)
```

```
{
    curr = curr -> next;
    max = curr -> val > max ? curr -> val : max;

}
printf("%d", max);

}
int main(void)

{
    int num_of_nodes, i;
    scanf("%d", & num_of_nodes);
    Node * myList = NULL;
    for (i = 0; i < num_of_nodes; i++)

    {

        int val;
        scanf("%d", & val);
        append( & myList, val);
    }
    printMax(myList);
    return 0;

}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

Bob is tasked with developing a company's employee record management system. The system needs to maintain a list of employee records using a doubly linked list. Each employee is represented by a unique integer ID.

Help Bob to complete a program that adds employee records at the front, traverses the list, and prints the same for each addition of employees to the list.

Input Format

The first line of input consists of an integer N, representing the number of employees.

The second line consists of N space-separated integers, representing the employee IDs.

Output Format

For each employee ID, the program prints "Node Inserted" followed by the current state of the doubly linked list in the next line, with the data values of each node separated by spaces.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

101 102 103 104

Output: Node Inserted

101

Node Inserted

102 101

Node Inserted

103 102 101

Node Inserted

104 103 102 101

Answer

-

Status : Skipped

Marks : 0/10

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

Answer

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node
```

```
{
```

```
    int num;
```

```
    struct node * preptr;
```

```
    struct node * nextptr;
```

```
}*stnode, *ennode;
```

```
void DListcreation(int n);
```

```
void displayDList();
```

```
int main()
```

```
{
```

```
    int n;
```

```
    stnode = NULL;
```

```
    ennode = NULL;
```

```
    scanf("%d", &n);
```

```
DListcreation(n);  
displayDList();  
return 0;
```

```
}  
void DListcreation(int n)
```

```
{
```

```
int i, num;  
struct node *fnNode;
```

```
if(n >= 1)
```

```
{
```

```
stnode = (struct node *)malloc(sizeof(struct node));
```

```
if(stnode != NULL)
```

```
{
```

```
scanf("%d", &num);
```

```
stnode->num = num;
```

```
stnode->preptr = NULL;
```

```
stnode->nextptr = NULL;
```

```
ennode = stnode;
```

```
// putting data for rest of the nodes
```

```
for(i=2; i<=n; i++)
```

```
{
```

```
fnNode = (struct node *)malloc(sizeof(struct node));
```



```
printf(" No data found in the List yet.");
```

```
}  
else
```

```
{
```

```
    tmp = stnode;  
    while(tmp != NULL)
```

```
    {
```

```
        printf("%d ",tmp->num);  
        n++;  
        tmp = tmp->nextptr; // current pointer moves to the next node
```

```
    }
```

```
}
```

```
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Ajay kumar p
Email: 240801016@rajalakshmi.edu.in
Roll no: 240801016
Phone: 9445788683
Branch: REC
Department: I ECE FA
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 2
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

1 2 3 4

5

Output: Data entered in the list:

node 1 : 1

node 2 : 2

node 3 : 3

node 4 : 4

Invalid position. Try again.

Answer

```
# You are using Python
```

```
class Node:
```

```
    def __init__(self, data):
```

```
self.data = data
self.next = None
self.prev = None
```

```
class DoublyLinkedList:
```

```
def __init__(self):
    self.head = None
```

```
def insert_at_end(self, data):
    new_node = Node(data)
    if not self.head:
        self.head = new_node
    return
```

```
    last = self.head
    while last.next:
        last = last.next
    last.next = new_node
    new_node.prev = last
```

```
def delete_at_position(self, position):
    if self.head is None or position <= 0:
        return False
```

```
    current = self.head
```

```
    # Traverse to the position
    for _ in range(position - 1):
        if current is None:
            return False
        current = current.next
```

```
    # If current is None, position is invalid
    if current is None:
        return False
```

```
    # If the node to be deleted is the head
    if current.prev is None:
        self.head = current.next
        if self.head:
            self.head.prev = None
    else:
        current.prev.next = current.next
```

```

        if current.next:
            current.next.prev = current.prev

    return True

def display(self):
    current = self.head
    nodes = []
    index = 1
    while current:
        nodes.append(f"node {index} : {current.data}")
        current = current.next
        index += 1
    return nodes

def main():
    # Input reading
    n = int(input())
    items = list(map(int, input().split()))
    p = int(input())

    # Create the doubly linked list
    dll = DoublyLinkedList()
    for item in items:
        dll.insert_at_end(item)

    # Display the list before deletion
    print("Data entered in the list:")
    print(" ".join(dll.display()))

    # Attempt to delete the item at position p
    if not dll.delete_at_position(p):
        print("Invalid position. Try again.")
    else:
        # Display the list after deletion
        print("After deletion the new list:")
        print(" ".join(dll.display()))

# Run the main function
if __name__ == "__main__":
    main()

```

Status : Correct

Marks : 10/10